



Wirewound Resistors, Industrial Power, Tubular, Ribwound (RB), Fixed (RBEF, RBSF)



FEATURES

- High temperature silicone or vitreous enamel coatings
- Excellent for pulsing applications
- All welded construction
- Designed to meet heavy-duty requirements where space is at a premium
- Hardware mounting options and enclosures available
- Wirewound
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912




RoHS COMPLIANT

| STANDARD ELECTRICAL SPECIFICATIONS | | | | | | |
|------------------------------------|--------------------|----------------|---------------------------|-------------|----------------|--------|
| GLOBAL MODEL | HISTORICAL MODEL | POWER RATING W | RESISTANCE RANGE Ω | TOLERANCE % | TERMINAL STYLE | |
| | | | | | STANDARD | OPTION |
| RBEF0040 ⁽¹⁾ | 9-32- Ω R | 40 | 0.010 to 10.6 | 10 | D | H |
| RBEF0050 ⁽¹⁾ | 12-32- Ω R | 50 | 0.020 to 8.2 | 10 | F | H |
| RBEF0075 ⁽¹⁾ | 12-48- Ω R | 75 | 0.010 to 19.3 | 10 | F | H |
| RBEF0090 ⁽¹⁾ | 9-64- Ω R | 90 | 0.015 to 28.3 | 10 | D | H |
| RBEF0100 ⁽¹⁾ | 12-56- Ω R | 100 | 0.012 to 24.5 | 10 | F | H |
| RBEF0110 ⁽¹⁾ | 12-64- Ω R | 110 | 0.015 to 30.6 | 10 | F | H |
| RBEF0120 ⁽¹⁾ | 12-72- Ω R | 120 | 0.018 to 36.8 | 10 | F | H |
| RBEF0135 ⁽¹⁾ | 12-80- Ω R | 135 | 0.021 to 42.9 | 10 | F | H |
| RBEF0150 ⁽¹⁾ | 18-64- Ω R | 150 | 0.019 to 44.8 | 10 | F | H |
| RBEF0160 ⁽¹⁾ | 12-96- Ω R | 160 | 0.027 to 55.0 | 10 | F | H |
| RBEF0175 ⁽¹⁾ | 18-72- Ω R | 175 | 0.023 to 53.7 | 10 | F | H |
| RBEF0180 ⁽¹⁾ | 12-104- Ω R | 180 | 0.030 to 61.3 | 10 | F | H |
| RBEF0220 ⁽¹⁾ | 18-96- Ω R | 220 | 0.035 to 80.6 | 10 | F | H |
| RBEF0225 ⁽¹⁾ | 18-98- Ω R | 225 | 0.036 to 82.8 | 10 | F | H |
| RBEF0240 ⁽¹⁾ | 18-104- Ω R | 240 | 0.038 to 89.5 | 10 | F | H |
| RBEF0300 ⁽¹⁾ | 18-136- Ω R | 300 | 0.054 to 125 | 10 | F | H |
| RBEF0375 ⁽¹⁾ | 18-168- Ω R | 375 | 0.069 to 161 | 10 | F | H |
| RBEF0400 ⁽¹⁾ | 26-136- Ω R | 400 | 0.061 to 159 | 10 | G | - |
| RBEF0420 ⁽¹⁾ | 18-188- Ω R | 420 | 0.079 to 184 | 10 | F | H |
| RBEF0500 ⁽¹⁾ | 26-168- Ω R | 500 | 0.081 to 210 | 10 | G | - |
| RBEF0550 ⁽¹⁾ | 26-188- Ω R | 550 | 0.093 to 242 | 10 | G | - |
| RBSF0750 | 40-192- Ω R | 750 | 0.128 to 166 | 10 | G | - |
| RBSF0850 | - | 850 | 0.160 to 400 | 10 | F | G, H |
| RBSF1000 | 40-240- Ω R | 1000 | 0.168 to 217 | 10 | G | - |
| RBSF1100 | - | 1100 | 0.180 to 525 | 10 | G | - |
| RBSF1500 | 40-320- Ω R | 1500 | 0.234 to 303 | 10 | G | - |
| RBSF1700 | - | 1700 | 0.270 to 350 | 10 | G | - |
| RBSF2000 | 52-320- Ω R | 2000 | 0.281 to 391 | 10 | G | - |


Note

⁽¹⁾ Vitreous enamel coating is standard (RBEF type), silicone coating is optional (RBSF type).

DIMENSIONS in inches (millimeters)


- For Terminal Data and Mounting Hardware, see www.vishay.com/doc?31811
- For Enclosures and Frames, see www.vishay.com/doc?31810

| GLOBAL MODEL | CORE DIMENSIONS (REF.) | | | A DISTANCE BETWEEN TERMINAL (REF.) | WEIGHT (TYP.) g |
|--------------|------------------------|---------------------|---------------------|---|-----------------------|
| | B LENGTH | C OUTER DIAMETER | D INNER DIAMETER | | |
| RBEF0040 | 2 (50.8) | 0.5625 (14.2875) | 0.3125 (7.9375) | 1.25 (31.75) | 20 |
| RBEF0050 | 2 (50.8) | 0.75 (19.05) | 0.5 (12.7) | 1.15 (29.21) | 30 |
| RBEF0075 | 3 (76.2) | 0.75 (19.05) | 0.5 (12.7) | 2.13 (53.975) | 50 |
| RBEF0090 | 4 (101.6) | 0.5625 (14.2875) | 0.3125 (7.9375) | 3.50 (88.9) | 65 |
| RBEF0100 | 3.5 (88.9) | 0.75 (19.05) | 0.5 (12.7) | 2.63 (66.675) | 58 |
| RBEF0110 | 4 (101.6) | 0.75 (19.05) | 0.5 (12.7) | 3.13 (79.375) | 62 |
| RBEF0120 | 4.5 (114.3) | 0.75 (19.05) | 0.5 (12.7) | 3.63 (92.075) | 68 |
| RBEF0135 | 5 (127) | 0.75 (19.05) | 0.5 (12.7) | 4.13 (104.775) | 75 |
| RBEF0150 | 4 (101.6) | 1.125 (28.575) | 0.75 (19.05) | 3.13 (79.375) | 127 |
| RBEF0160 | 6 (152.4) | 0.75 (19.05) | 0.5 (12.7) | 5.13 (130.175) | 95 |
| RBEF0175 | 4.5 (114.3) | 1.125 (28.575) | 0.75 (19.05) | 3.63 (92.075) | 140 |
| RBEF0180 | 6.5 (165.1) | 0.75 (19.05) | 0.5 (12.7) | 5.63 (142.875) | 100 |
| RBEF0220 | 6 (152.4) | 1.125 (28.575) | 0.75 (19.05) | 5.13 (130.175) | 165 |
| RBEF0225 | 6.125 (155.575) | 1.125 (28.575) | 0.75 (19.05) | 5.25 (133.35) | 175 |
| RBEF0240 | 6.5 (165.1) | 1.125 (28.575) | 0.75 (19.05) | 5.63 (142.875) | 200 |
| RBEF0300 | 8.5 (215.9) | 1.125 (28.575) | 0.75 (19.05) | 7.63 (193.675) | 265 |
| RBEF0375 | 10.5 (266.7) | 1.125 (28.575) | 0.75 (19.05) | 9.63 (244.475) | 300 |
| RBEF0400 | 8.5 (215.9) | 1.625 (41.275) | 1.125 (28.575) | 7.63 (193.675) | 410 |
| RBEF0420 | 11.75 (298.45) | 1.125 (28.575) | 0.75 (19.05) | 10.88 (276.225) | 336 |
| RBEF0500 | 10.5 (266.7) | 1.625 (41.275) | 1.125 (28.575) | 9.00 (228.6) | 525 |
| RBEF0550 | 11.75 (298.45) | 1.625 (41.275) | 1.125 (28.575) | 10.25 (260.35) | 535 |
| RBSF0750 | 12 (304.8) | 2.5 (63.5) | 1.75 (44.45) | 10.50 (266.7) | 1200 |
| RBSF0850 | 25 (635) | 1.125 (28.575) | 0.75 (19.05) | 23.75 (603.25) | 715 |
| RBSF1000 | 15 (381) | 2.5 (63.5) | 1.75 (44.45) | 13.50 (342.9) | 1500 |
| RBSF1100 | 25 (635) | 1.625 (41.275) | 1.125 (28.58) | 23 (584.2) | 1140 |
| RBSF1500 | 20 (508) | 2.5 (63.5) | 1.75 (44.45) | 18.50 (169.9) | 1900 |
| RBSF1700 | 25 (635) | 2.5 (63.5) | 1.75 (44.45) | 23 (584.2) | 2450 |
| RBSF2000 | 20 (508) | 3.25 (82.55) | 1.75 (44.45) | 18.50 (169.9) | 3900 |


TERMINAL STYLE in inches (millimeters)


| DIMENSIONS | D (1/4" LUG) | F (3/8" LUG) | G (1/2" LUG) | H (1/4" SQC) |
|---------------|--------------|----------------|------------------|----------------|
| Width (A) | 0.25 (6.35) | 0.375 (9.525) | 0.5 (12.7) | 0.25 (6.35) |
| Height (B) | 0.5 (12.7) | 0.625 (15.875) | 0.9375 (23.8125) | 0.625 (15.875) |
| Diameter (C) | 0.17 (4.318) | 0.2 (5.08) | 0.26 (6.604) | 0.065 (1.651) |
| Thickness (D) | 0.02 (0.508) | 0.035 (0.889) | 0.046 (1.1684) | 0.032 (0.8128) |



| METRIC OPTIONS AVAILABLE | |
|---|--|
| Metric Hardware on Terminal Lugs | Use terminal designation "1" example: RBEF03001R000K1B00 |
| Metric Mounting Hardware | Vertical mount: use special designation "VM" example: RBEF03001R000K1BVM 1 high bracket: use special designation "1A" example: RBEF03001R000K1B1M 2 high bracket: use special designation "2A" example: RBEF03001R000K1B2M 3 high bracket: use special designation "3A" example: RBEF03001R000K1B3M 4 high bracket: use special designation "4A" example: RBEF03001R000K1B4M |

| TECHNICAL SPECIFICATIONS | | |
|--|---------------------|---|
| PARAMETER | UNIT | RESISTOR CHARACTERISTICS |
| Power rating | W | 40 to 200 |
| Resistance range | Ω | 0.01 to 391 |
| Resistance tolerance | % | 10 |
| TCR | ppm/°C | $\pm 400, \pm 180, \pm 130, \pm 20$ (varies by wattage and resistance) |
| Operating temperature | °C | -55 to +415 |
| Temperature rise | °C | 375 above an ambient of 40 °C |
| Maximum altitude | f.a.s.l. (m.a.s.l.) | derate above 4921 f.a.s.l. (1500 m.a.s.l.) |
| Short-term overload (surge) | | 10 x rated power for 5 s |
| Surge windings | | available |
| Maximum working voltage | | $(P \times R)^{1/2}$ |
| Insulation resistance | Ω | 1M |
| Dielectric voltage | V _{RMS} | up to 1500 (upon request) |
| Creepage | inch (mm) | minimum 0.125 (3.175), typical (varies by wattage) |
| Terminal sleeves | | n/a |
| Inductance | μ H | 0.1 to 340 (varies by wattage and resistance) |
| Non-inductive winding | | consult factory: www.vishay.com/milwaukee/contact |
| Terminal strength | lb | 10 |
| Electrical or mechanical customization | | available: www.vishay.com/doc?31856 |




| MATERIAL SPECIFICATIONS | |
|-------------------------|--|
| Element | copper-nickel, nickel-chrome, iron-chrome-aluminum |
| Core | cordierite, steatite |
| Coating | special high temperature silicone or vitreous enamel |
| Standard terminals | nickel-iron |
| Part marking | value, date code, MRC |

| OPTIONS | EXAMPLE PHOTO | EXAMPLE: 300 W | OPTIONS | EXAMPLE PHOTO | EXAMPLE: 300 W |
|-------------------------------|---------------|---|---|---------------|--|
| Standard "00" option | | Part number ends with " 00 " example: RBEF0300xxxxxKGB 00 | Thru Bolt "VT" option | | Part number ends with " VT " example: RBEF0300xxxxxKGB VT |
| 1 High Bracket "1A" option | | Part number ends with " 1A " example: RBEF0300xxxxxKGB 1A | Clips "CP" option | | Part number ends with " CP " example: RBEF0300xxxxxKGB CP |
| 2 High Bracket "2A" option | | Part number ends with " 2A " example: RBEF0300xxxxxKGB 2A | Adjustable | | Part model starts with " RBEA " example: RBEA 0300xxxxxKFB00 |
| 3 High Bracket "3A" option | | Part number ends with " 3A " example: RBEF0300xxxxxKGB 3A | Enclosures | | Consult factory for options: vishaymilwaukeeeresistor@vishay.com |
| 4 High Bracket "4A" option | | Part number ends with " 4A " example: RBEF0300xxxxxKGB 4A | Electrical customizations (TCR, inductance, etc.) | | Consult factory for options: vishaymilwaukeeeresistor@vishay.com |

GLOBAL PART NUMBER INFORMATION

Global Part Numbering example: RBSF150015R00JGB1A (RBSF1500-1A 15 5 % 1/2L B)





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru