



ETA-USA

HIGH QUALITY SWITCHING POWER SUPPLIES

AC/DC SWITCHING ADAPTOR DESKTOP
SINGLE OUTPUT / UNIVERSAL RANGE INPUT
WITH ACTIVE PFC

80 WATTS



DTC80-xSX-F-W SERIES

3-pole IEC-C14 AC inlet, Class 1
Meets LEVEL V Efficiency requirements
2 year warranty



DIMENSION: L132×W69×H40mm

Input

Input Voltage Range: 90-264VAC (Full Range)
Input Current (rms): 2A @ 90VAC; 1A @ 264VAC MAX.


Frequency: 47 - 63Hz
Power factor: >0.9 (20%~100% Load)

Efficiency: >80% @ full load, 115VAC

Options

N/A

General Description



Features

1. High Reliability
2. 100% BURN-IN Tested
3. 100% Hi-Pot tested
4. Safety Approvals, EMC compliance



ETA USA
16170 Vineyard Blvd. Suite 180, Morgan Hill, CA 95037
Phone: 1-800-ETA-POWER, (408) 778-2793 Fax: (408) 779-2753

Visit us at: www.eta-usa.com
email at: sales@eta-usa.com



ETA-USA

HIGH QUALITY SWITCHING POWER SUPPLIES

Environmental Specification	
Operating Temperature	0°C TO +40°C
Storage Temperature	-10°C +70°C
MTBF	>80'000 Hours at full load and 25°C ambient temp.
Protection	
Over voltage protection, AC recycles; Short circuit protection, Auto recovery.	
Safety	UL 60950 Third Edition CSA C22.2-No.60950 TUV EN60950 CB IEC 60950
EMI STANDARDS	FCC Class B CISPR22 Class B EN 55022 Class B EN 61000-3-2 CE
Dimension	L132×W69×H40mm
AC Input Connector	IEC 320-C14 Inlet

Output Characteristic	Unit	DTC80-09SX-F-W	DTC80-12SX-F-W	DTC80-15SX-F-W	DTC80-18SX-F-W	DTC80-24SX-F-W
Output Voltage	Vdc	9	12	15	18	24
Output Current	A	8	6.67	5.33	4.45	3.34
Output Power	W	72	80	80	80	80
Ripple and Noise	mVp-p	90	120	150	180	240
Output Regulation	%	± 5%				
Hold up time	mS	10ms (typical at full load @ 115VAC)				

Efficiency	%	87% At Full Load@115Vac
-------------------	----------	--------------------------------

Note: 1. Peak to Peak with 20MHz bandwidth with a tantalum 10uF in parallel with a 0.1uF ceramic capacitor.






ETA-USA

HIGH QUALITY SWITCHING POWER SUPPLIES

Dimension Diagram






ETA-USA

HIGH QUALITY SWITCHING POWER SUPPLIES

Derating Curve



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru