



USB-TO-SERIAL  
CONVERTERS



# EDGEPORT®

Easy out-of-the-box solution for I/O expansion is available in a wide variety of configurations for maximum flexibility and scalability

Edgeport USB-to-serial converters offer instant I/O expansion for peripheral device connectivity. An out-of-the-box (external) alternative to PCI cards, Edgeport makes it easy to add serial and USB ports to a PC, server or thin client in minutes – without opening the chassis, reconfiguring or rebooting the system.

Edgeport is available in multiple configurations for maximum flexibility and scalability. Choose from compact form factors for space-prohibitive applications; single port “bump-in-the-cable” solutions for notebook expansion; software-selectable RS-232/422/485 models to connect any type of serial device to

one box; metal enclosures for rugged applications; models with galvanic isolated ports for extended electrical safety; and DB-9 or DB-25 connectors to meet cabling requirements.

Feature-rich design, reliability and unmatched operating system support make Edgeport USB-to-serial converters ideal for mission-critical enterprise applications.

## BENEFITS

- Add 1, 2, 4, 8 or 16 serial ports to a PC, thin client or server in minutes
- Designed for peripheral device connectivity in retail stations, self check-out systems, emergency vehicles, kiosks, ATMs and more
- Software selectable MEI, galvanic isolated, industrial, compact and metal ruggedized models
- Low total cost of ownership with external, user-installable solution

## RELATED PRODUCTS



## APPLICATION EXAMPLE

### POS CONNECTIVITY



SPECIFICATIONS	Edgeport® Serial   Edgeport® Extended Safety   Edgeport® Industrial		
<b>INTERFACES (VARIES BY MODEL)</b>			
<b>SERIAL PORTS</b>	1, 2, 4, 8 or 16	4 (separately isolated)	1, 2, 4 or 8
<b>SERIAL TYPE</b>	RS-232	RS-232/422/485	RS-422/485, software selectable RS-232/422/485
<b>SERIAL CONNECTOR</b>	DB-9, DB-25	DB-9	DB-9
<b>SERIAL DATA RATE</b>	230 Kbps per port simultaneously		
<b>DOWNSTREAM USB PORTS</b>	4 (16-port models only)	1 (separately isolated)	0
<b>FEATURES</b>			
<b>USB</b>	USB 1.0 and USB 1.1 compatible; backwards compatibility for USB 2.0 and USB 3.0; USB-IF certified; Plug and Play		
<b>LEDS</b>	Tri-state LED displays device status and COM port activity		
<b>OPERATING SYSTEMS</b>	Windows 10®, Windows 8, Windows 7, Windows Vista®, Windows Server 2012, Windows Server® 2008 R2, Windows XP®, Windows XP Embedded, Windows CE 5, Windows CE 6 (x86 only), Windows Server® 2003 R2, Windows 2000; Linux*, Sun Solaris (SPARC)**		
<b>CABLES</b>	1-meter USB cable		
<b>OTHER (GENERAL)</b>	Automatic port reacquisition; COM port assignments maintained across reboots; Full hardware and software flow control; No additional IRQ or memory address requirements; Low power consumption; Rack mountable; Hot-swappable		
<b>OTHER (MODEL-SPECIFIC)</b>	N/A	2.0 kV DC galvanic isolation on all ports	N/A
<b>POWER REQUIREMENTS</b>			
<b>POWER SUPPLY</b>	External power supply not required for models without USB ports (USB powered); Models with USB ports (Edgeport 416) ship with power supply: 100/240VAC 60/50 Hz at 5VDC @ 3 Amps max		
<b>ENVIRONMENTAL</b>			
<b>OPERATING TEMPERATURE</b>	0° C to 55° C (32° F to 131° F)		
<b>RELATIVE HUMIDITY</b>	0% to 95% (non-condensing)		
<b>REGULATORY APPROVALS</b>			
<b>SAFETY</b>	EN60950, UL 1950, CSA 2.2 No. 950, IEC 950		
<b>EMISSIONS/IMMUNITY</b>	CE, FCC Part 15 Class B, EN55022, EN55024		

\*Driver support provided by Linux USB maintainers.

\*\*Driver support provided by Sun.

SPECIFICATIONS		Edgeport® Compact	Edgeport® Metal
<b>INTERFACES (VARIES BY MODEL)</b>			
<b>SERIAL PORTS</b>	2		4
<b>SERIAL TYPE</b>	RS-232		RS-232
<b>SERIAL CONNECTOR</b>	DB-9		
<b>SERIAL DATA RATE</b>	230 Kbps per port simultaneously		
<b>DOWNSTREAM USB PORTS</b>	2		0
<b>OTHER PORTS</b>	N/A		N/A
<b>FEATURES</b>			
<b>USB</b>	USB 1.0 and USB 1.1 compatible; backwards compatibility for USB 2.0 and USB 3.0; USB-IF certified; Plug and Play		
<b>LEDS</b>	Tri-state LED displays device status and COM port activity		
<b>OPERATING SYSTEMS</b>	Windows® 10, Windows 8, Windows 7, Windows Vista®, Windows Server 2012, Windows Server® 2008 R2, Windows XP®, Windows XP Embedded, Windows CE 5, Windows CE 6 (x86 only), Windows Server® 2003 R2, Windows 2000; Linux*, Sun Solaris (SPARC)**		
<b>CABLES</b>	Captive 2-meter cable for secure connection in rugged environments (mobile computing)		1-meter USB cable
<b>OTHER (GENERAL)</b>	Automatic port reacquisition; COM port assignments maintained across reboots; Full hardware and software flow control; No additional IRQ or memory address requirements; Low power consumption; Rack mountable; Hot-swappable		
<b>OTHER (MODEL-SPECIFIC)</b>	N/A		Aluminum chassis; Designed for rugged environments (emergency vehicles, restaurant kitchens); Rack mount bracket for added security
<b>POWER REQUIREMENTS</b>			
<b>POWER SUPPLY</b>	USB powered		
<b>ENVIRONMENTAL</b>			
<b>OPERATING TEMPERATURE</b>	0° C to 55° C (32° F to 131° F)		
<b>RELATIVE HUMIDITY</b>	0% to 95% (non-condensing)		
<b>REGULATORY APPROVALS</b>			
<b>SAFETY</b>	EN60950, UL 1950, CSA 2.2 No. 950, IEC 950		
<b>EMISSIONS/IMMUNITY</b>	CE, FCC Part 15 Class B, EN55022, EN55024		

\*Driver support provided by Linux USB maintainers.

\*\*Driver support provided by Sun.

## SPECIFICATIONS

## Measurements



### EDGEPORT/1, 1I

Length: 3.15 in (8.00 cm)  
 Width: 1.75 in (4.40 cm)  
 Height: 0.80 in (2.03 cm)  
 Weight: 1.60 oz (45.36 g)



### EDGEPORT/4M

Length: 4.30 in (10.92 cm)  
 Width: 8.00 in (20.32 cm)  
 Height: 1.36 in (3.45 cm)  
 Weight: 10.00 oz (311.00 g)



### EDGEPORT/2C, 22C

Length: 2.38 in (6.04 cm)  
 Width: 3.94 in (10.00 cm)  
 Height: 1.00 in (2.54 cm)  
 Weight: 5.00 oz (141.75 g)



### EDGEPORT/416, 416/DB-25, 8/DB-25

Length: 5.00 in (12.70 cm)  
 Width: 17.00\* in (43.118 cm)  
 Height: 1.80 in (4.53 cm)  
 Weight: 41.30 oz (1170.84 g)



### EDGEPORT/4/DB-25, 8, 8S MEI

Length: 4.35 in (11.05 cm)  
 Width: 7.20 in (18.29 cm)  
 Height: 1.75 in (4.45 cm)  
 Weight: 16.00 oz (453.59 g)



### EDGEPORT/2, 2S, 4, 4S MEI, 4S MEI ISOLATED

Length: 4.35 in (11.05 cm)  
 Width: 7.20 in (18.29 cm)  
 Height: 1.03 in (2.61 cm)  
 Weight: 10.00 oz (311.00 g)

\* 19.0 in (48.26 cm) with optional rack mount ears



PART NUMBERS	DESCRIPTION
301-1003-10	Edgeport/2c - 2 RS-232 serial DB-9, captive 2-meter cable
301-1003-30	Edgeport/22c - 2 USB, 2 RS-232 serial DB-9, captive cable
301-1000-02	Edgeport/2 - 2 RS-232 serial DB-9
301-1000-03	Edgeport/2 - 2 RS-232 serial DB-9 (International)
301-1000-04	Edgeport/4 - 4 RS-232 serial DB-9
301-1000-10	Edgeport/416 DB-9 - 4 USB, 16 RS-232 serial DB-9, rack mountable
301-1001-11	Edgeport/1 - 1 RS-232 serial DB-9
301-1001-21	Edgeport/1 25 Unit Bulk Pack - 1 RS-232 serial DB-9 (25 each)
301-1001-15	Edgeport/1 with 2-Meter Captive Cable - 1 RS-232 serial DB-9, captive 2 meter cable
301-1002-08	Edgeport/8 DB-9 - 8 RS-232 serial DB-9
301-1016-08	Edgeport/8/DB-25 - 8 RS-232 serial DB-25, rack mountable
301-1016-16	Edgeport/416 DB-25 - 4 USB, 16 RS-232 serial DB-25, rack mountable
301-2000-10	Edgeport/416 DB-9 - 4 USB, 16 RS-232 serial DB-9, rack mountable (International)
301-2016-16	Edgeport/416 DB-25 - 4 USB, 16 RS-232 serial DB-25, rack mountable (International)
301-1000-95	Edgeport/4s MEI Isolated - 4 RS-232/422/485 serial DB-9 software selectable with galvanic isolation
301-1000-92	Edgeport/2s MEI - 2 RS-232/422/485 serial DB-9; software selectable
301-1000-94	Edgeport/4s MEI - 4 RS-232/422/485 serial DB-9; software selectable
301-1001-31	Edgeport/1i - 1 RS-422/485 serial DB-9
301-1002-98	Edgeport/8s MEI - 8 RS-232/422/485 serial DB-9; software selectable
301-1000-81	Edgeport/4m - 4 RS-232 serial DB-9, aluminum chassis

FOR MORE INFORMATION  
PLEASE VISIT [WWW.DIGI.COM](http://WWW.DIGI.COM)



**DIGI SERVICE AND SUPPORT** / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit [www.digi.com/support](http://www.digi.com/support).

© 1996-2015 Digi International Inc. All rights reserved.  
All trademarks are the property of their respective owners.

91001226  
F1/915

**DIGI INTERNATIONAL WORLDWIDE HQ**  
877-912-3444 / 952-912-3444 / [www.digi.com](http://www.digi.com)

**DIGI INTERNATIONAL FRANCE**  
+33-1-55-61-98-98 / [www.digi.fr](http://www.digi.fr)

**DIGI INTERNATIONAL JAPAN**  
+81-3-5428-0261 / [www.digi-intl.co.jp](http://www.digi-intl.co.jp)

**DIGI INTERNATIONAL SINGAPORE**  
+65-6213-5380

**DIGI INTERNATIONAL CHINA**  
+86-21-50492199 / [www.digi.com.cn](http://www.digi.com.cn)



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)