

# 89 Series

## Metal-Mite® Aluminum Housed Axial Terminal Wirewound, 1% Tolerance



The 89 Series is a high-performance axial type resistor. These molded-construction metal-housed resistors are available in higher power ratings than standard axial resistors and are better suited to withstanding vibration, shock and harsh environmental conditions.

The 89 Series Metal-Mite® resistors are aluminum housed to maintain high stability during operation and to permit secure mounting to chassis surfaces.

The metal housing also provides heat-sinking capabilities.

### FEATURES

- High Stability:  $\pm 0.5\% \Delta R$
- High power to size ratio
- Metal housing allows chassis mounting and provides heat sink capability

### SERIES SPECIFICATIONS

| Series | Wattage | Ohms       | Voltage |
|--------|---------|------------|---------|
| 805    | 5       | 0.10-25K   | 210     |
| 810    | 10      | 0.10-50K   | 320     |
| 825    | 25      | 0.010-75K  | 520     |
| 850    | 50      | 0.005-100K | 1170    |

Non-Inductive versions available. Insert "N" before tolerance code.  
Example: 850NF560

### CHARACTERISTICS

|  |  |
|--|--|
| <b>Housing</b>                         | Metal, anodized aluminum   |
| <b>Internal Coating</b>                | Silicone   |
| <b>Core</b>                            | Ceramic  |
| <b>Terminals</b>                       | Solder-coated axial  |
| <b>Derating</b>                        | Linearly from 100% @ +25°C to 0% @ +275°C.   |
| <b>Tolerance</b>                       | $\pm 1\%$ and $\pm 5\%$ (other tolerances available).  |
| <b>Power rating</b>                    | Rating is based on chassis mounting area and temperature stability. Proper heat sink as follows: 5W and 10W units, 4" x 6" x 2" x .040" Aluminum chassis; 25W units, 5" x 7" x 2" x .040" Aluminum chassis; 50W units, 12" x 12" x .059" Aluminum panel. |
| <b>Maximum ohmic values</b>            | See chart.   |
| <b>Overload</b>                        | 5 times rated wattage for 5 seconds.   |
| <b>Temperature coefficient</b>         | Under 1 $\Omega$ : $\pm 90$ ppm/°C; 1 to 9.99 $\Omega$ : $\pm 50$ ppm/°C; 10 $\Omega$ and over: $\pm 20$ ppm/°C.   |
| <b>Dielectric withstanding voltage</b> | 5W and 10W rating, 1000 VAC; 25 and 50W ratings, 2250 VAC.   |

(continued)

# 89 Series

## Metal-Mite® Aluminum Housed Axial Terminal Wirewound, 1% Tolerance

### DIMENSIONS

(in./mm)



Dimensions have changed as of August 2015

|     | A max.       | B max.       | C max.       | D max.       | E max.       | F ±.3mm      | G ±.3mm      | H max.      | J max.      | K max.      | L ±.25mm    |
|-----|--------------|--------------|--------------|--------------|--------------|--------------|--------------|-------------|-------------|-------------|-------------|
| 805 | 0.65" / 16.5 | 1.18" / 30.0 | 0.35" / 8.8  | 0.33" / 8.5  | 0.63" / 15.9 | 0.44" / 11.3 | 0.49" / 12.4 | 0.18" / 4.5 | 0.09" / 2.4 | 0.07" / 1.8 | 0.09" / 2.4 |
| 810 | 0.83" / 21.0 | 1.44" / 36.5 | 0.43" / 11.0 | 0.44" / 11.2 | 0.78" / 19.9 | 0.56" / 14.3 | 0.63" / 15.9 | 0.22" / 5.5 | 0.11" / 2.8 | 0.07" / 1.8 | 0.09" / 2.4 |
| 825 | 1.10" / 28.0 | 2.01" / 51.0 | 0.58" / 14.8 | 0.56" / 14.2 | 1.07" / 27.3 | 0.72" / 18.3 | 0.78" / 19.8 | 0.30" / 7.7 | 0.20" / 5.2 | 0.10" / 2.6 | 0.13" / 3.2 |
| 850 | 1.10" / 28.0 | 2.85" / 72.5 | 0.58" / 14.8 | 0.56" / 14.2 | 1.93" / 49.1 | 1.56" / 39.7 | 0.84" / 21.4 | 0.33" / 8.4 | 0.20" / 5.2 | 0.10" / 2.6 | 0.13" / 3.2 |

### ORDERING INFORMATION

| Ohmic value | Wattage         |   |    |    | Ohmic value | Wattage |                 |   |    | Ohmic value | Wattage |      |                 |   |    |    |
|-------------|-----------------|---|----|----|-------------|---------|-----------------|---|----|-------------|---------|------|-----------------|---|----|----|
|             | Part No. Prefix | 5 | 10 | 25 |             | 50      | Part No. Prefix | 5 | 10 |             | 25      | 50   | Part No. Prefix | 5 | 10 | 25 |
| 0.005       | R005            |   |    | ✓  | 20          | 20R     | ✓               | ✓ | ✓  | ✓           | 1,500   | 1K5  | ✓               | ✖ | ✖  | ✓  |
| 0.010       | R010            |   |    | ✓  | 25          | 25R     | ✓               | ✓ | ✓  | ✓           | 2,000   | 2K0  | ✓               | ✖ | ✖  | ✓  |
| 0.025       | R025            |   |    | ✓  | 30          | 30R     | ✖               | ✖ | ✓  | ✓           | 2,500   | 2K5  | ✓               | ✓ | ✓  | ✓  |
| 0.1         | R10             |   |    | ✓  | 40          | 40R     | ✖               | ✓ | ✓  | ✓           | 3,000   | 3K0  | ✖               | ✓ | ✓  | ✖  |
| 0.3         | R30             |   |    | ✓  | 50          | 50R     | ✓               | ✓ | ✓  | ✓           | 3,500   | 3K5  | ✖               | ✖ | ✓  | ✓  |
| 0.5         | R50             |   |    | ✓  | 75          | 75R     | ✓               | ✖ | ✓  | ✓           | 4,000   | 4K0  | ✓               | ✓ | ✓  | ✓  |
| 0.7         | R70             |   |    | ✓  | 100         | 100R    | ✓               | ✓ | ✓  | ✓           | 4,500   | 4K5  | ✓               | ✖ | ✓  | ✓  |
| 1.0         | 1R0             | ✓ | ✓  | ✓  | 150         | 150R    | ✓               | ✓ | ✓  | ✓           | 5,000   | 5K0  | ✓               | ✓ | ✓  | ✓  |
| 1.5         | 1R5             | ✖ | ✓  | ✓  | 200         | 200R    | ✖               | ✖ | ✓  | ✓           | 6,000   | 6K0  | ✖               | ✖ | ✓  | ✓  |
| 2.0         | 2R0             | ✖ | ✓  | ✓  | 250         | 250R    | ✓               | ✓ | ✓  | ✓           | 10,000  | 10K  | ✓               | ✖ | ✓  | ✓  |
| 3.0         | 3R0             | ✓ | ✓  | ✓  | 300         | 300R    | ✓               | ✖ | ✓  | ✓           | 15,000  | 15K  | ✓               | ✓ | ✖  | ✖  |
| 4.0         | 4R0             | ✖ | ✓  | ✓  | 400         | 400R    | ✖               | ✖ | ✓  | ✓           | 20,000  | 20K  | ✓               | ✖ | ✖  | ✖  |
| 5.0         | 5R0             | ✓ | ✓  | ✓  | 500         | 500R    | ✖               | ✖ | ✓  | ✓           | 25,000  | 25K  | ✓               | ✖ | ✖  | ✖  |
| 10.0        | 10R             | ✓ | ✓  | ✓  | 750         | 750R    | ✖               | ✖ | ✓  | ✓           | 50,000  | 50K  | ✖               | ✖ | ✖  | ✖  |
| 15.0        | 15R             | ✓ | ✓  | ✓  | 1,000       | 1K0     | ✖               | ✓ | ✓  | ✓           | 75,000  | 75K  | ✖               | ✖ | ✖  | ✖  |
|             |                 |   |    |    |             |         |                 |   |    |             | 100,000 | 100K | ✖               | ✖ | ✖  | ✖  |

Non-Inductive Winding  
Optional (blank = std. winding)    RoHS Compliant

|                  |           |               |
|------------------|-----------|---------------|
| <b>805NF5R0E</b> |           |               |
| Series           | Tolerance | Ohms          |
| 805 = 5 Watt     | F = 1%    | R005 = 0.005Ω |
| 810 = 10 watt    | J = 5%    | R10 = 0.1Ω    |
| 825 = 25 watt    |           | 1R0 = 1.0Ω    |
| 850 = 50 watt    |           | 250 = 250Ω    |
|                  |           | 1K0 = 1,000Ω  |
|                  |           | 1K5 = 1,500Ω  |
|                  |           | 25K = 25,000Ω |

✓ = Standard values  
✖ = Non-standard values subject to minimum handling charge per item

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

As of September 2006, the 89 Series is no longer offered as Mil. Spec.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)