

# CFSH-4

## SURFACE MOUNT SILICON SCHOTTKY DIODE



www.centrasemi.com



SOD-882L CASE

### DESCRIPTION:

The CENTRAL SEMICONDUCTOR CFSH-4 is a high quality Schottky diode designed for applications where ultra small size and power dissipation are prime requirements. Packaged in the space saving SOD-882L surface mount package, this component provides performance characteristics suitable for the most demanding size constrained applications.

### MARKING CODE: L

### FEATURES:

- Device is **Halogen Free** by design
- Current ( $I_O=200\text{mA}$ )
- Low forward voltage drop ( $V_F=0.35\text{V TYP @ } 1.0\text{mA}$ )
- Low reverse current ( $25\text{nA TYP @ } 30\text{V}$ )
- Extremely fast switching ( $5.0\text{ns MAX}$ )
- Small  $1\text{mm} \times 0.6\text{mm} \times 0.4\text{mm}$ , SOD-882L, ultra low profile, leadless surface mount package.

### APPLICATIONS:

- DC-DC converters
- Voltage clamping
- Protection circuits
- Battery powered applications including cell phones, digital cameras, pagers, PDAs, laptop computers, etc.

### MAXIMUM RATINGS: ( $T_A=25^\circ\text{C}$ )

Peak Repetitive Reverse Voltage  
 Average Forward Current  
 Peak Forward Surge Current,  $t_p=8.3\text{ms}$   
 Power Dissipation  
 Operating Junction Temperature  
 Storage Temperature  
 Thermal Resistance

### SYMBOL

SYMBOL		UNITS
$V_{RRM}$	40	V
$I_O$	200	mA
$I_{FSM}$	600	mA
$P_D$	100	mW
$T_J$	-65 to +125	$^\circ\text{C}$
$T_{stg}$	-65 to +150	$^\circ\text{C}$
$\theta_{JA}$	1000	$^\circ\text{C/W}$




### ELECTRICAL CHARACTERISTICS: ( $T_A=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
$I_R$	$V_R=30\text{V}$		25	200	nA
$BV_R$	$I_R=10\mu\text{A}$	40			V
$V_F$	$I_F=1.0\text{mA}$		0.35	0.38	V
$V_F$	$I_F=15\text{mA}$		0.55	0.65	V
$V_F$	$I_F=40\text{mA}$		0.77	1.00	V
$C_J$	$V_R=0, f=1.0\text{MHz}$			5.0	pF
$t_{rr}$	$I_F=I_R=10\text{mA}, I_{rr}=1.0\text{mA}, R_L=100\Omega$			5.0	ns

**CFSH-4**  
**SURFACE MOUNT SILICON**  
**SCHOTTKY DIODE**



**SOD-882L CASE - MECHANICAL OUTLINE**



\* Pin 1 chamfer may appear on any corner.

SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.037	0.041	0.95	1.05
B	0.022	0.026	0.55	0.65
C	0.026		0.65	
D	0.000	0.002	0.00	0.05
E	0.012	0.016	0.30	0.40
F	0.018	0.022	0.45	0.55
G	0.008	0.012	0.20	0.30

SOD-882L (REV:R2)

**LEAD CODE:**

- 1) Cathode
- 2) Anode

**MARKING CODE: L**





R2

R5 (3-August 2015)

**CFSH-4**  
**SURFACE MOUNT SILICON**  
**SCHOTTKY DIODE**



**TYPICAL ELECTRICAL CHARACTERISTICS**





R5 (3-August 2015)

**CFSH-4**  
**SURFACE MOUNT SILICON**  
**SCHOTTKY DIODE**



**TYPICAL ELECTRICAL CHARACTERISTICS**



R5 (3-August 2015)

**CFSH-4**  
**SURFACE MOUNT SILICON**  
**SCHOTTKY DIODE**



**SERVICES**

- Bonded Inventory
- Custom Electrical Screening
- Custom Electrical Characteristic Curves
- SPICE Models
- Custom Packaging
- Package Base Options
- Custom Device Development/ Multi Discrete Modules (MDM™)
- Bare Die Available for Hybrid Applications

---

**LIMITATIONS AND DAMAGES DISCLAIMER:** In no event shall Central be liable for any collateral, indirect, punitive, incidental, consequential, or exemplary damages in connection with or arising out of a purchase order or contract or the use of products provided hereunder, regardless of whether Central has been advised of the possibility of such damages. Excluded damages shall include, but not be restricted to: cost of removal or reinstallation, rework, ancillary costs to the procurement of substitute products, loss of profits, loss of savings, loss of use, loss of data, or business interruption. No claim, suit, or action shall be brought against Central more than two (2) years after the related cause of action has occurred.

In no event shall Central's aggregate liability from any warranty, indemnity, or other obligation arising out of or in connection with a purchase order or contract, or any use of any Central product provided hereunder, exceed the total amount paid to Central for the specific products sold under a purchase order or contract with respect to which losses or damages are claimed. The existence of more than one (1) claim against the specific products sold to Buyer under a purchase order or contract shall not enlarge or extend this limit.

Buyer understands and agrees that the foregoing liability limitations are essential elements of a purchase order or contract and that in the absence of such limitations, the material and economic terms of the purchase order or contract would be substantially different.

R5 (3-August 2015)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренеспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)