



Dimension A&B&C

DIM A	$(N+2) \times 9.5 + 2.0$
DIM B	$(N-1) \times 9.5$
DIM C	$N \times 9.5 + 2.0$

N=Number of contacts

Dimension A&B&C	Tolerance
>6-30	±0.30
>30-120	±0.40
>120-400	±0.60

SIGN	DATE	DESCRIPTION	APPROVER
△	10/14/08	將Body底部方槽改為φ3.0圓孔形	Kind
△	09/05/26	Voltage & Current changed from 300V,25A to 300V,30A	Eris
△	09/05/26	wire range changed from 22-14 AWG to 10-22 AWG	Eris
△	09/05/26	add Safety Approval	Eris
△	10/22'12	Change the screw plating specification	Jacky
△	10/22'12	Add the view	Jacky
△	10/22'12	Change the dimensional tolerance	Jacky
△	10/22'12	Change the electrical specification	Jacky
△	10/22'12	Add the dimensional label	Jacky

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- △ MATERIALS ELECTRICAL
- △ RATED VOLTAGE & CURRENT: 300 V, 25A
- WITHSTAND VOLTAGE: AC 2000 V/Min
- INSULATION RESISTANCE: 1000 MΩ OR MORE AT DC 500 V
- OPERATING TEMPERATURE RANG: -40 °C ~ +115 °C
- SCREW TORQUE VALUE: 8.8 Lb-In.
- △ WIRE RANGE: 14-22 AWG
- 1) MOLDED PARTS: Thermoplastic, UL 94 V-0 BLACK
- 2) TERMINAL: BRASS, 0.8t, Tin PLATED
- 3) TERMINAL SCREWS: STEEL, M3.5
- △ APPROVAL: (CNS) PENDING
- PART NO.:
- Critical dimension: ▽

YK 516 xx 3 x x 00G

- NO. OF POLES: 02: 2 POLES, 03: 3 POLES, 04: 4 POLES, 30: 30 POLES
- MARK: 0: "@ " MARK, 1: "ANY " MARK
- TERMINAL & SCREW PLATED: 0: TERMINAL & SCREW: G/F, 1: TERMINAL: G/F, SCREW: Zinc, 2: TERMINAL: Sn, SCREW: G/F, 3: TERMINAL: Sn, SCREW: Zinc
- G:RoHS compliant(lead<4%) in copper alloy

**ANYTEK**

**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		YK-516 W/Flange Series		
PART NO.	YK516xx3xx00G	DWG NO.	8YK0002-516	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.
		Jacky 2012.10.22	Jacky 2012.10.22	
SHEET: 01/01		Tolerance		
UNIT: mm		X. ±0.50		
SCALE: NONE		X.X ±0.30		
		X.XX ±0.10		
		X° ±1°		

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)