

Wet Tantalum Capacitors Surface Mount, Molded Case



FEATURES

- Molded surface mountable design
- Terminations: standard tin/lead (SnPb), 100 % tin (RoHS compliant) available
- Industry standard ratings
- Model M35 wet tantalum electrolytic chip capacitors incorporate the advantages of all the varieties of electrolytic capacitors and eliminate most of the disadvantages. These units have a 3 V reverse voltage capability at + 85 °C and a higher ripple current capability than any other electrolytic type with similar combinations of capacitance and case size.
- Compliant to RoHS Directive 2002/95/EC


RoHS*
COMPLIANT

Note

* Pb containing terminations are not RoHS compliant, exemptions may apply

PERFORMANCE CHARACTERISTICS

Operating Temperature: - 55 °C to + 85 °C
(to + 125 °C with voltage derating)

Capacitance Tolerance: At 120 Hz, + 25 °C. $\pm 20 \%$ standard. $\pm 10 \%$, $\pm 5 \%$ available as special.

DC Leakage Current (DCL Max.): At + 25 °C and above: Leakage current shall not exceed the values listed in the Standard Ratings Tables.

Life Test: Capacitors are capable of withstanding a 2000 h life test at a temperature of + 85 °C or + 125 °C at the applicable rated DC working voltage.

Following life test:

1. DCL, measured at + 85 °C rated voltage, shall not be in excess of the original requirement.
2. The equivalent series resistance shall not exceed 150 % of the initial requirement.
3. Change in capacitance shall not exceed 10 % from the initial measurement.


ORDERING INFORMATION

M35	C	826	M	125	B	Z	S	L
MODEL	CASE CODE	CAPACITANCE	CAPACITANCE TOLERANCE	DC VOLTAGE RATING AT + 85 °C	TERMINATION AND PACKAGING	RELIABILITY LEVEL	TEMP	ESR
	See Ratings and Case Codes table	This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow.	K = $\pm 10 \%$ M = $\pm 20 \%$	This is expressed in volts. To complete the three-digit block, zeros precede the voltage rating. A decimal point is indicated by an "R" (6R3 = 6.3 V)	A = 100 % tin (RoHS compliant), bulk B = Std, tin/lead, bulk	Z = Non-ER	S = Std	S = Std. L = Low


Note

- Packaging: The use of formed plastic tubes for packing bulk components is standard

DIMENSIONS in inches [millimeters]

						
CASE CODE	L (MAX.)	W	H	P (MIN.)	TW	TH (MIN.)
C	0.835 [21.2]	0.315 $\pm$ 0.012 [8 $\pm$ 0.3]	0.295 $\pm$ 0.012 [7.5 $\pm$ 0.3]	0.118 [3.0]	0.236 $\pm$ 0.012 [6.0 $\pm$ 0.3]	0.075 [1.9]

RECOMMENDED REFLOW PROFILES



T_p Lead (Pb)-free	T_p Sn/Pb	t_p	T_L Lead (Pb)-free	T_L Sn/Pb	T_s MIN. Lead (Pb)-free	T_s MIN. Sn/Pb	T_s MAX. Lead (Pb)-free	T_s MAX. Sn/Pb	t_s Lead (Pb)-free	t_s Sn/Pb	t_L
260 °C	240 °C	10	217 °C	183 °C	150 °C	100 °C	200 °C	150 °C	60 to 150	60 to 90	60

MOUNTING

Due to the size and weight of these capacitors, we recommend that a supplemental mounting restraint to be used in printed circuit board attachment in addition to the reflowed solder.

One recommendation is to use an adhesive such as defined in the J-STD-001DS.

This is the Space Application Electronic Hardware Addendum to J-STD-001 (Requirements for Solder Electrical and Electronic Assemblies).

STANDARD RATINGS

CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. ESR AT + 25 °C	MAX. ESR AT - 55 °C	MAX. DCL (μ A) AT		MAX. CAPACITANCE CHANGE (%) AT			MAX. RIPPLE 40 kHz RMS (mA)
					+ 25 °C	+ 85 °C + 125 °C	- 55 °C	+ 85 °C	+ 125 °C	
6 V _{DC} AT + 85 °C; 4 V _{DC} AT + 125 °C										
30	C	M35C306(1)006(2)ZS(3)	4.0	100	1.0	2.0	- 40	+ 10.5	+ 12	820
68	C	M35C686(1)006(2)ZS(3)	3.2	60	1.0	2.0	- 40	+ 14	+ 16	960
220	C	M35C227(1)006(2)ZS(3)	3.0	36	2.0	9.0	- 64	+ 13	+ 16	1000
8 V _{DC} AT + 85 °C; 5 V _{DC} AT + 125 °C										
25	C	M35C256(1)008(2)ZS(3)	4.0	100	1.0	2.0	- 40	+ 10.5	+ 12	820
56	C	M35C566(1)008(2)ZS(3)	3.3	59	1.0	2.0	- 40	+ 14	+ 16	900
180	C	M35C187(1)008(2)ZS(3)	3.0	45	2.0	9.0	- 60	+ 13	+ 16	1000
10 V _{DC} AT + 85 °C; 7 V _{DC} AT + 125 °C										
20	C	M35C206(1)010(2)ZS(3)	4.0	120	1.0	2.0	- 32	+ 10.5	+ 12	820
47	C	M35C476(1)010(2)ZS(3)	3.7	90	1.0	2.0	- 36	+ 14	+ 16	855
120	C	M35C127(1)010(2)ZS(3)	3.2	54	2.0	6.0	- 40	+ 14	+ 16	900
150	C	M35C157(1)010(2)ZS(3)	3.0	54	2.0	9.0	- 55	+ 13	+ 16	900

Note

- Part number definitions:
 - Capacitance tolerance: K, M
 - Termination/packaging: (see Ordering Information)
 - Reliability level: Z = Non-ER
 - Temperature: S = STD
 - ESR: S = STD, L = Low (1/2 standard ESR value)



STANDARD RATINGS

CAPACITANCE (μF)	CASE CODE	PART NUMBER	MAX. ESR AT + 25 °C	MAX. ESR AT - 55 °C	MAX. DCL (μA) AT		MAX. CAPACITANCE CHANGE (%) AT			MAX. RIPPLE 40 kHz RMS (mA)
					+ 25 °C	+ 85 °C + 125 °C	- 55 °C	+ 85 °C	+ 125 °C	
15 V _{DC} AT + 85 °C; 10 V _{DC} AT + 125 °C										
15	C	M35C156(1)015(2)ZS(3)	4.4	155	1.0	2.0	- 24	+ 10.5	+ 12	780
33	C	M35C336(1)015(2)ZS(3)	4.0	90	1.0	2.0	- 28	+ 14	+ 16	820
82	C	M35C826(1)015(2)ZS(3)	3.9	72	2.0	6.0	- 35	+ 12	+ 16	900
100	C	M35C107(1)015(2)ZS(3)	3.9	72	2.0	9.0	- 44	+ 13	+ 16	900
25 V _{DC} AT + 85 °C; 15 V _{DC} AT + 125 °C										
10	C	M35C106(1)025(2)ZS(3)	5.3	220	1.0	2.0	- 16	+ 8	+ 9	715
22	C	M35C226(1)025(2)ZS(3)	4.2	140	1.0	2.0	- 20	+ 10.5	+ 12	800
56	C	M35C566(1)025(2)ZS(5)	4.3	90	2.0	6.0	- 25	+ 12	+ 15	850
68	C	M35C686(1)025(2)ZS(5)	4.3	90	2.0	9.0	- 40	+ 12	+ 15	850
30 V _{DC} AT + 85 °C; 20 V _{DC} AT + 125 °C										
8	C	M35C805(1)030(2)ZS(3)	6.6	275	1.0	2.0	- 16	+ 8	+ 12	640
15	C	M35C156(1)030(2)ZS(3)	6.2	175	1.0	2.0	- 20	+ 10.5	+ 12	780
47	C	M35C476(1)030(2)ZS(3)	5.2	100	2.0	6.0	- 23	+ 12	+ 15	800
56	C	M35C566(1)030(2)ZS(3)	5.2	100	2.0	9.0	- 38	+ 12	+ 15	800
35 V _{DC} AT + 85 °C; 22 V _{DC} AT + 125 °C										
15	C	M35C156(1)035(2)ZS(3)	6.2	175	0.75	1.5	- 20	+ 10.5	+ 12	660
39	C	M35C396(1)035(2)ZS(3)	4.1	61	2.0	6.0	- 22	+ 12	+ 14	820
50 V _{DC} AT + 85 °C; 30 V _{DC} AT + 125 °C										
5	C	M35C505(1)050(2)ZS(3)	8.0	400	1.0	2.0	- 16	+ 5	+ 6	580
10	C	M35C106(1)050(2)ZS(3)	6.4	250	1.0	2.0	- 24	+ 8	+ 9	715
33	C	M35C336(1)050(2)ZS(3)	5.0	135	2.0	9.0	- 29	+ 10	+ 12	700
60 V _{DC} AT + 85 °C; 40 V _{DC} AT + 125 °C										
4	C	M35C405(1)060(2)ZS(3)	9.3	550	1.0	2.0	- 16	+ 5	+ 6	525
8.2	C	M35C825(1)060(2)ZS(3)	6.6	275	1.0	2.0	- 24	+ 8	+ 9	625
27	C	M35C276(1)060(2)ZS(3)	5.0	144	3.0	12	- 24	+ 10	+ 12	700
75 V _{DC} AT + 85 °C; 50 V _{DC} AT + 125 °C										
3.5	C	M35C355(1)075(2)ZS(3)	9.5	650	1.0	2.0	- 16	+ 5	+ 6	525
6.8	C	M35C685(1)075(2)ZS(3)	6.8	300	1.0	2.0	- 20	+ 8	+ 9	610
22	C	M35C226(1)075(2)ZS(3)	5.1	157	3.0	12	- 19	+ 10	+ 12	600
100 V _{DC} AT + 85 °C; 65 V _{DC} AT + 125 °C										
2.5	C	M35C255(1)100(2)ZS(3)	10.6	950	1.0	2.0	- 16	+ 7	+ 8	505
4.7	C	M35C475(1)100(2)ZS(3)	8.5	500	1.0	2.0	- 16	+ 7	+ 8	565
10	C	M35C106(1)100(2)ZS(3)	5.9	200	3.0	12	- 17	+ 10	+ 12	800
125 V _{DC} AT + 85 °C; 85 V _{DC} AT + 125 °C										
1.7	C	M35C175(1)125(2)ZS(3)	15.6	1250	1.0	2.0	- 16	+ 7	+ 8	415
3.6	C	M35C365(1)125(2)ZS(3)	10.0	600	1.0	2.0	- 16	+ 7	+ 8	520
6.8	C	M35C685(1)125(2)ZS(3)	11.7	300	3.0	12	- 14	+ 10	+ 12	700

Note

- Part number definitions:
 - Capacitance tolerance: K, M
 - Termination/packaging: (see Ordering Information)
 - Reliability level: Z = Non-ER
 - Temperature: S = STD
 - ESR: S = STD, L = Low (1/2 standard ESR value)

**PERFORMANCE CHARACTERISTICS OF M35 CAPACITORS**

ELECTRICAL CHARACTERISTICS	
ITEM	PERFORMANCE CHARACTERISTICS
Operating temperature range	- 55 °C to + 125 °C
Capacitor tolerance	± 20 %, ± 10 % at 120 Hz
Capacitance change (maximum)	Limits per Standard Ratings table. Measured per requirements of MIL-PRF-39006.
ESR	
AC ripple current	
DCL (maximum leakage current)	
Impedance (maximum)	
Reverse voltage	Reverse voltage shall be in accordance with MIL-PRF-39006/22. Units are capable of withstanding 3 V in reverse at + 85 °C for 125 h.
Surge voltage	Surge voltage shall be in accordance with MIL-PRF-39006. The DC rated surge voltage is the maximum voltage to which the capacitors should be subjected under any conditions. This includes transients and peak ripple at the highest line voltage. The surge voltage is 115 % of rated DC working voltage.
Life test	The capacitors shall be capable of withstanding a 2000 h life test at 85 °C at rated voltage.

ENVIRONMENTAL CHARACTERISTICS		
ITEM	CONDITION	COMMENTS
Hermeticity	MIL-PRF-39006	The internal component has been tested to be compliant to the hermeticity requirements of MIL-PRF-39006/22. The internal component has been tested to be compliant to the moisture resistance requirements of MIL-PRF-39006/22. The internal component has been tested to be compliant to the altitude or reduced barometric pressure requirements of MIL-PRF-39006/22 (150 000 feet).
Moisture resistance	MIL-PRF-39006	
Altitude/barometric pressure (reduced)	MIL-PRF-39006	

MECHANICAL CHARACTERISTICS		
ITEM	CONDITION	COMMENTS
Thermal shock	MIL-STD-202, Method 107, A	Per MIL-PRF-39006, 30 cycles
Shock	MIL-STD-202, Method 213	Per MIL-PRF-39006, 500 g
Vibration (high frequency)	MIL-STD-202, Method 204	Per MIL-PRF-39006, 80 g
Vibration (random)	MIL-STD-202, Method 214	Per MIL-PRF-39006, 53.79 g
Resistance to solder heat	MIL-STD-202, Method 210	The capacitor must withstand solder dipping of the terminals at 260 °C for 10 s. The capacitor must not be visibly damaged and the electrical characteristics must not be affected.
Solderability	ANSI J-STD-002	The terminations must be solderable per the requirements of MIL-PRF-55365 para. 4.10
Part markings	MIL-STD-1285	The part marking shall include Vishay name, trademark, capacitance, voltage, date code and lot symbol.
Weight (typical) in g	3.5	

PAD DIMENSIONS in millimeters				
CASE CODE	A (MIN.)	B (NOM.)	C (NOM.)	D (NOM.)
C	22.7	14.7	4.0	6.4

STANDARD PACKAGING QUANTITY		
SERIES	CASE CODE	BULK/TUBE
M35	C	10 pcs



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru