

# MC14022B

## Octal Counter

The MC14022B is a four-stage Johnson octal counter with built-in code converter. High-speed operation and spike-free outputs are obtained by use of a Johnson octal counter design. The eight decoded outputs are normally low, and go high only at their appropriate octal time period. The output changes occur on the positive-going edge of the clock pulse. This part can be used in frequency division applications as well as octal counter or octal decode display applications.

### Features

- Fully Static Operation
- DC Clock Input Circuit Allows Slow Rise Times
- Carry Out Output for Cascading
- Supply Voltage Range = 3.0 Vdc to 18 Vdc
- Capable of Driving Two Low-Power TTL Loads or One Low-Power Schottky TTL Load Over the Rated Temperature Range
- Pin-for-Pin Replacement for CD4022B
- Triple Diode Protection on All Inputs
- These Devices are Pb-Free and are RoHS Compliant

### MAXIMUM RATINGS (Voltages Referenced to $V_{SS}$ )

| Symbol            | Parameter   | Value                  | Unit        |
|-------------------|---|------------------------|-------------|
| $V_{DD}$          | DC Supply Voltage Range                           | -0.5 to +18.0          | V           |
| $V_{in}, V_{out}$ | Input or Output Voltage Range (DC or Transient)   | -0.5 to $V_{DD} + 0.5$ | V           |
| $I_{in}, I_{out}$ | Input or Output Current (DC or Transient) per Pin | $\pm 10$               | mA          |
| $P_D$             | Power Dissipation, per Package (Note 1)           | 500                    | mW          |
| $T_A$             | Ambient Temperature Range                         | -55 to +125            | $^{\circ}C$ |
| $T_{stg}$         | Storage Temperature Range                         | -65 to +150            | $^{\circ}C$ |
| $T_L$             | Lead Temperature (8-Second Soldering)             | 260                    | $^{\circ}C$ |

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

#### 1. Temperature Derating:

Plastic "P and D/DW" Packages: - 7.0 mW/ $^{\circ}C$  From 65 $^{\circ}C$  To 125 $^{\circ}C$

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation,  $V_{in}$  and  $V_{out}$  should be constrained to the range  $V_{SS} \leq (V_{in} \text{ or } V_{out}) \leq V_{DD}$ .


Unused inputs must always be tied to an appropriate logic voltage level (e.g., either  $V_{SS}$  or  $V_{DD}$ ). Unused outputs must be left open.





ON Semiconductor®

<http://onsemi.com>

### MARKING DIAGRAMS



PDIP-16  
P SUFFIX  
CASE 648



SOIC-16  
D SUFFIX  
CASE 751B




A = Assembly Location  
WL = Wafer Lot  
YY, Y = Year  
WW = Work Week  
G = Pb-Free Indicator

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.


# MC14022B

## PIN ASSIGNMENT



NC = NO CONNECTION

## BLOCK DIAGRAM




NC = PIN 6, 9

## FUNCTIONAL TRUTH TABLE (Positive Logic)

| Clock | Clock Enable | Reset | Output=n |
|-------|--------------|-------|----------|
| 0     | X            | 0     | n        |
| X     | 1            | 0     | n        |
| ↗     | 0            | 0     | n+1      |
| ↘     | X            | 0     | n        |
| 1     | ↘            | 0     | n+1      |
| X     | ↗            | 0     | n        |
| X     | X            | 1     | Q0       |

X = Don't Care. If n < 4 Carry = 1, Otherwise = 0.

## LOGIC DIAGRAM



# MC14022B

## ELECTRICAL CHARACTERISTICS (Voltages Referenced to V<sub>SS</sub>)

| Characteristic  | Symbol                       | V <sub>DD</sub><br>Vdc | - 55°C  |       | 25°C  |                 |       | 125°C |       | Unit |      |
|---|------------------------------|------------------------|---|-------|-------|-----------------|-------|-------|-------|------|------|
|   |                              |                        | Min   | Max   | Min   | Typ<br>(Note 2) | Max   | Min   | Max   |      |      |
| Output Voltage<br>V <sub>in</sub> = V <sub>DD</sub> or 0<br><br>V <sub>in</sub> = 0 or V <sub>DD</sub>  | "0" Level<br>V <sub>OL</sub> | 5.0                    | —   | 0.05  | —     | 0               | 0.05  | —     | 0.05  | Vdc  |      |
|   |                              | 10                     | —   | 0.05  | —     | 0               | 0.05  | —     | 0.05  |      |      |
|   |                              | 15                     | —   | 0.05  | —     | 0               | 0.05  | —     | 0.05  |      |      |
|   | "1" Level<br>V <sub>OH</sub> | 5.0                    | 4.95  | —     | 4.95  | 5.0             | —     | 4.95  | —     |      | Vdc  |
|   |                              | 10                     | 9.95  | —     | 9.95  | 10              | —     | 9.95  | —     |      |      |
|   |                              | 15                     | 14.95   | —     | 14.95 | 15              | —     | 14.95 | —     |      |      |
| Input Voltage<br>"0" Level<br>(V <sub>O</sub> = 4.5 or 0.5 Vdc)<br>(V <sub>O</sub> = 9.0 or 1.0 Vdc)<br>(V <sub>O</sub> = 13.5 or 1.5 Vdc)<br><br>"1" Level<br>(V <sub>O</sub> = 0.5 or 4.5 Vdc)<br>(V <sub>O</sub> = 1.0 or 9.0 Vdc)<br>(V <sub>O</sub> = 1.5 or 13.5 Vdc) | V <sub>IL</sub>              | 5.0                    | —   | 1.5   | —     | 2.25            | 1.5   | —     | 1.5   | Vdc  |      |
|   |                              | 10                     | —   | 3.0   | —     | 4.50            | 3.0   | —     | 3.0   |      |      |
|   |                              | 15                     | —   | 4.0   | —     | 6.75            | 4.0   | —     | 4.0   |      |      |
|   | V <sub>IH</sub>              | 5.0                    | 3.5   | —     | 3.5   | 2.75            | —     | 3.5   | —     |      | Vdc  |
|   |                              | 10                     | 7.0   | —     | 7.0   | 5.50            | —     | 7.0   | —     |      |      |
|   |                              | 15                     | 11  | —     | 11    | 8.25            | —     | 11    | —     |      |      |
| Output Drive Current<br>Source<br>(V <sub>OH</sub> = 2.5 Vdc)<br>(V <sub>OH</sub> = 4.6 Vdc)<br>(V <sub>OH</sub> = 9.5 Vdc)<br>(V <sub>OH</sub> = 13.5 Vdc)<br><br>Sink<br>(V <sub>OL</sub> = 0.4 Vdc)<br>(V <sub>OL</sub> = 0.5 Vdc)<br>(V <sub>OL</sub> = 1.5 Vdc)        | I <sub>OH</sub>              | 5.0                    | -3.0  | —     | -2.4  | -4.2            | —     | -1.7  | —     | mAdc |      |
|   |                              | 5.0                    | -0.64   | —     | -0.51 | -0.88           | —     | -0.36 | —     |      |      |
|   |                              | 10                     | -1.6  | —     | -1.3  | -2.25           | —     | -0.9  | —     |      |      |
|   |                              | 15                     | -4.2  | —     | -3.4  | -8.8            | —     | -2.4  | —     |      |      |
|   | I <sub>OL</sub>              | 5.0                    | 0.64  | —     | 0.51  | 0.88            | —     | 0.36  | —     |      | mAdc |
|   |                              | 10                     | 1.6   | —     | 1.3   | 2.25            | —     | 0.9   | —     |      |      |
| 15  |                              | 4.2                    | —   | 3.4   | 8.8   | —               | 2.4   | —     |       |      |      |
| Input Current   | I <sub>in</sub>              | 15                     | —   | ± 0.1 | —     | ± 0.00001       | ± 0.1 | —     | ± 1.0 | μAdc |      |
| Input Capacitance<br>(V <sub>in</sub> = 0)  | C <sub>in</sub>              | —                      | —   | —     | —     | 5.0             | 7.5   | —     | —     | pF   |      |
| Quiescent Current<br>(Per Package)  | I <sub>DD</sub>              | 5.0                    | —   | 5.0   | —     | 0.005           | 5.0   | —     | 150   | μAdc |      |
|   |                              | 10                     | —   | 10    | —     | 0.010           | 10    | —     | 300   |      |      |
|   |                              | 15                     | —   | 20    | —     | 0.015           | 20    | —     | 600   |      |      |
| Total Supply Current (Notes 3 & 4)<br>(Dynamic plus Quiescent,<br>Per Package)<br>(C <sub>L</sub> = 50 pF on all outputs, all<br>buffers switching)   | I <sub>T</sub>               | 5.0                    | I <sub>T</sub> = (0.28 μA/kHz)f + I <sub>DD</sub><br>I <sub>T</sub> = (0.56 μA/kHz)f + I <sub>DD</sub><br>I <sub>T</sub> = (0.85 μA/kHz)f + I <sub>DD</sub> |       |       |                 |       |       |       | μAdc |      |
|   |                              | 10                     |   |       |       |                 |       |       |       |      |      |
|   |                              | 15                     |   |       |       |                 |       |       |       |      |      |

2. Data labelled "Typ" is not to be used for design purposes but is intended as an indication of the IC's potential performance.

3. The formulas given are for the typical characteristics only at 25°C.

4. To calculate total supply current at loads other than 50 pF:

$$I_T(C_L) = I_T(50 \text{ pF}) + (C_L - 50) Vfk$$

where: I<sub>T</sub> is in μA (per package), C<sub>L</sub> in pF, V = (V<sub>DD</sub> - V<sub>SS</sub>) in volts, f in kHz is input frequency, and k = 0.00125.

# MC14022B

## SWITCHING CHARACTERISTICS (Note 5) ( $C_L = 50 \text{ pF}$ , $T_A = 25^\circ\text{C}$ )

| Characteristic  | Symbol                   | $V_{DD}$<br>Vdc | Min               | Typ<br>(Note 6)   | Max                | Unit |
|---|--------------------------|-----------------|-------------------|-------------------|--------------------|------|
| Output Rise and Fall Time<br>$t_{TLH}$ , $t_{THL} = (1.5 \text{ ns/pF}) C_L + 25 \text{ ns}$<br>$t_{TLH}$ , $t_{THL} = (0.75 \text{ ns/pF}) C_L + 12.5 \text{ ns}$<br>$t_{TLH}$ , $t_{THL} = (0.55 \text{ ns/pF}) C_L + 9.5 \text{ ns}$                       | $t_{TLH}$ ,<br>$t_{THL}$ | 5.0<br>10<br>15 | —<br>—<br>—       | 100<br>50<br>40   | 200<br>100<br>80   | ns   |
| Propagation Delay Time<br>Reset to Decode Output<br>$t_{PLH}$ , $t_{PHL} = (1.7 \text{ ns/pF}) C_L + 415 \text{ ns}$<br>$t_{PLH}$ , $t_{PHL} = (0.66 \text{ ns/pF}) C_L + 197 \text{ ns}$<br>$t_{PLH}$ , $t_{PHL} = (0.5 \text{ ns/pF}) C_L + 150 \text{ ns}$ | $t_{PLH}$ ,<br>$t_{PHL}$ | 5.0<br>10<br>15 | —<br>—<br>—       | 500<br>230<br>175 | 1000<br>460<br>350 | ns   |
| Propagation Delay Time<br>Clock to $C_{out}$<br>$t_{PLH}$ , $t_{PHL} = (1.7 \text{ ns/pF}) C_L + 315 \text{ ns}$<br>$t_{PLH}$ , $t_{PHL} = (0.66 \text{ ns/pF}) C_L + 142 \text{ ns}$<br>$t_{PLH}$ , $t_{PHL} = (0.5 \text{ ns/pF}) C_L + 100 \text{ ns}$     | $t_{PLH}$ ,<br>$t_{PHL}$ | 5.0<br>10<br>15 | —<br>—<br>—       | 400<br>175<br>125 | 800<br>350<br>250  | ns   |
| Propagation Delay Time<br>Clock to Decode Output<br>$t_{PLH}$ , $t_{PHL} = (1.7 \text{ ns/pF}) C_L + 415 \text{ ns}$<br>$t_{PLH}$ , $t_{PHL} = (0.66 \text{ ns/pF}) C_L + 197 \text{ ns}$<br>$t_{PLH}$ , $t_{PHL} = (0.5 \text{ ns/pF}) C_L + 150 \text{ ns}$ | $t_{PLH}$ ,<br>$t_{PHL}$ | 5.0<br>10<br>15 | —<br>—<br>—       | 275<br>125<br>95  | 1000<br>460<br>350 | ns   |
| Turn-Off Delay Time<br>Reset to $C_{out}$<br>$t_{PLH} = (1.7 \text{ ns/pF}) C_L + 315 \text{ ns}$<br>$t_{PLH} = (0.66 \text{ ns/pF}) C_L + 142 \text{ ns}$<br>$t_{PLH} = (0.5 \text{ ns/pF}) C_L + 100 \text{ ns}$  | $t_{PLH}$                | 5.0<br>10<br>15 | —<br>—<br>—       | 400<br>175<br>125 | 800<br>350<br>250  | ns   |
| Clock Pulse Width   | $t_{WH}$                 | 5.0<br>10<br>15 | 250<br>100<br>75  | 125<br>50<br>35   | —<br>—<br>—        | ns   |
| Clock Frequency   | $f_{cl}$                 | 5.0<br>10<br>15 | —<br>—<br>—       | 5.0<br>12<br>16   | 2.0<br>5.0<br>6.7  | MHz  |
| Reset Pulse Width   | $t_{WH}$                 | 5.0<br>10<br>15 | 500<br>250<br>190 | 250<br>125<br>95  | —<br>—<br>—        | ns   |
| Reset Removal Time  | $t_{rem}$                | 5.0<br>10<br>15 | 750<br>275<br>210 | 375<br>135<br>105 | —<br>—<br>—        | ns   |
| Clock Input Rise and Fall Time  | $t_{TLH}$ , $t_{THL}$    | 5.0<br>10<br>15 | No Limit          |                   |                    | —    |
| Clock Enable Setup Time   | $t_{su}$                 | 5.0<br>10<br>15 | 350<br>150<br>115 | 175<br>75<br>52   | —<br>—<br>—        | ns   |
| Clock Enable Removal Time   | $t_{rem}$                | 5.0<br>10<br>15 | 420<br>200<br>140 | 260<br>100<br>70  | —<br>—<br>—        | ns   |

5. The formulas given are for the typical characteristics only at  $25^\circ\text{C}$ .

6. Data labelled "Typ" is not to be used for design purposes but is intended as an indication of the IC's potential performance.

# MC14022B




Figure 1. Typical Output Source and Output Sink Characteristics Test Circuit




Figure 2. Typical Power Dissipation Test Circuit

## APPLICATIONS INFORMATION

Figure 3 shows a technique for extending the number of decoded output states for the MC14022B. Decoded outputs are sequential within each stage and from stage to stage, with no dead time (except propagation delay).




Figure 3. Counter Expansion

# MC14022B




Figure 4. AC Measurement Definition and Functional Waveforms

## ORDERING INFORMATION


| Device       | Package              | Shipping†                |
|--------------|----------------------|--------------------------|
| MC14022BCPG  | PDIP-16<br>(Pb-Free) | 500 Units / Rail         |
| MC14022BDG   | SOIC-16<br>(Pb-Free) | 48 Units / Rail          |
| MC14022BDR2G | SOIC-16<br>(Pb-Free) | 2500 Units / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MC14022B

## PACKAGE DIMENSIONS

PDIP-16  
P SUFFIX  
PLASTIC DIP PACKAGE  
CASE 648-08  
ISSUE T



NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
4. DIMENSION B DOES NOT INCLUDE MOLD FLASH.
5. ROUNDED CORNERS OPTIONAL.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.740     | 0.770 | 18.80       | 19.55 |
| B   | 0.250     | 0.270 | 6.35        | 6.85  |
| C   | 0.145     | 0.175 | 3.69        | 4.44  |
| D   | 0.015     | 0.021 | 0.39        | 0.53  |
| F   | 0.040     | 0.70  | 1.02        | 1.77  |
| G   | 0.100 BSC |       | 2.54 BSC    |       |
| H   | 0.050 BSC |       | 1.27 BSC    |       |
| J   | 0.008     | 0.015 | 0.21        | 0.38  |
| K   | 0.110     | 0.130 | 2.80        | 3.30  |
| L   | 0.295     | 0.305 | 7.50        | 7.74  |
| M   | 0°        | 10°   | 0°          | 10°   |
| S   | 0.020     | 0.040 | 0.51        | 1.01  |

# MC14022B

## PACKAGE DIMENSIONS

SOIC-16  
D SUFFIX  
PLASTIC SOIC PACKAGE  
CASE 751B-05  
ISSUE K




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

| DIM | MILLIMETERS |       | INCHES    |       |
|-----|-------------|-------|-----------|-------|
|     | MIN         | MAX   | MIN       | MAX   |
| A   | 9.80        | 10.00 | 0.386     | 0.393 |
| B   | 3.80        | 4.00  | 0.150     | 0.157 |
| C   | 1.35        | 1.75  | 0.054     | 0.068 |
| D   | 0.35        | 0.49  | 0.014     | 0.019 |
| F   | 0.40        | 1.25  | 0.016     | 0.049 |
| G   | 1.27 BSC    |       | 0.050 BSC |       |
| J   | 0.19        | 0.25  | 0.008     | 0.009 |
| K   | 0.10        | 0.25  | 0.004     | 0.009 |
| M   | 0°          | 7°    | 0°        | 7°    |
| P   | 5.80        | 6.20  | 0.229     | 0.244 |
| R   | 0.25        | 0.50  | 0.010     | 0.019 |

## SOLDERING FOOTPRINT



ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** orderlit@onsemi.com

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)