

Component Housings

Weidmüller DK 4 and DKT 4 modular terminals are suitable for the installation of electronic components with a maximum diameter or width of 4.5 mm. Four independent clamping yoke screw connections are available for this purpose. A snap-on contour frame expands the installation space in the DK 4 by 6 mm. Depending on type, these modular terminals are suitable for mounting on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails according to European Standards EN 50035 and EN 50022.

Weidmüller WDK 2.5 modular terminals are suitable for the installation of electronic components with a maximum width of 4 mm. Up to four independent clamping yoke screw connections or four 6.3 x 0.8 tab connections are available for this purpose. These modular terminals are suitable for mounting on TS 35 x 7.5 or TS 35 x 15 mounting rails.

Weidmüller EG 1 housings have four screw connections and, as accessories, up to four 0.8 x 2.8 or 0.8 x 4.8 mm solder/tab connections on a width of 18 mm. The screw clamp busbar ends with a solder ring inside the housing. Two end plates seal the module. Depending on type, the modules are mounted on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails.

Weidmüller EG 2 housings — The external shape of these housings corresponds to Type EG 1. Four screw connections or up to eight 0.8 x 6.3 mm / 0.8 x 2.8 mm tab connectors are connected with a printed circuit board in the housing. They can be mounted on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails.

Weidmüller EG 3 housings provide six screw connections or twelve 0.8 x 6.3 mm / 0.8 x 2.8 mm tab connections on a width of 22.5 mm. As an accessory, Weidmüller offers a speed printed circuit board with a 2.54 mm hole pitch or fully copper-coated. The engageable combination foot allows the terminals to be mounted on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails. The MPL mounting plate is used to mount the housing directly (without mounting rail). Due to the sliding foot construction, the EG 3 can be turned through 180° in all types of assembly (e.g. exchanging input and output).

Weidmüller EG 4 housing, like Type EG 3, offers a width of 22.5 mm. However, the greater installation depth (75 mm) and height (109 mm) allow the installation of more complex circuit configurations. The installed circuit can be connected via six screw connections.

The engageable combination foot allows the terminals to be mounted on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails. Due to the sliding foot construction, the EG 4 can be slid 6 mm forwards or backwards on the engaging foot and can be turned through 180° (e.g. exchanging input and output).

Weidmüller EG 5 housings — The external dimensions of these housings correspond to Type EG 4. The EG 5 has twelve screw connections which can be wired with solder lugs inside the housing. The engageable combination foot allows the terminals to be mounted on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails. Due to the sliding foot construction, the EG 4 can be slid 6 mm forwards or backwards on the engaging foot and can be turned through 180° (e.g. exchanging input and output).

Weidmüller RS 70 individual parts for rail mounting — The end sections can be engaged to form units up to 20 mm wide. Any desired intermediate spacers or feet can be connected between two side pieces (fixing feet) at intervals of 5 mm. In this way, a carrier module is constructed for a printed circuit board on which various components can be soldered. The module snaps onto TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails.

Weidmüller rail-mounted profiles — The RS 45, RS 80 and RS 100 profiles are available as 2 m long strips. The extruded profiles can be easily cut to any length with a saw. In this way, a carrier module is constructed for a printed circuit board on which various components can be soldered. The fixing feet can be slid into these profiles for mounting on TS 32, TS 35 x 7.5 or TS 35 x 15 mounting rails. The sliding foot construction of the RS 80 also allows the fixing foot to be turned through 180°.


The Wavebox is characterized by:

- Optimal width for any application (12.5 mm, 17.5 mm, 22.5 mm, 45 mm)
- Large component assembly
- UL94 Flammability class V2
- No tools required for assembly
- Plug-in printed circuit board
- Plug-in cross-connection via ZQV 2.5 N
- Hinged, transparent cover
- BLZ 5.08 screw/plug and socket connector
- BLZF 5.08 optional tension clamp/plug and socket connector
- Marking option with WS tags
- Suitable for snap-fitting on TS 35

Modular Terminals

Dimensions			
Terminal width (+ 0.2 assembly tolerance)			
Insulation stripping length			
Connection Data			
Screw connection, solid strand			
Screw connection, flexible strand			
Conductor cross-section			
VDE rated Data			
Rated wire size			
Rated voltage			
Rated current			
Power loss			
Connection diagram			
Ordering Data			
Modular terminal used to widen component area	For TS 32		Type
			Part No.
	For TS 35		Type
			Part No.
Contour frame used to widen component area (6 mm width)	For TS 32		Type
			Part No.
	For TS 35		Type
			Part No.
Accessories			
Mounting rail (2 m long)			
End bracket (thickness mm)	For TS 32		
	For TS 35		
End plate (thickness mm)			
Small partition			
Socket for test plug			
Test plug (pin diameter)			
Jumpers (preassembled)	2-pole		
	3-pole		
	4-pole		
	10-pole		
Switchable jumper bracket			
Connection sleeve			
Screw			
Cover plate (4 terminals)			
Screw (plastic)			
Jumper bridge			

DK 4



DKT 4



WDK 2.5



WDK 2.5 F



WDK 2.5 FF



6 mm	6 mm	5 mm	5 mm	5 mm	5 mm
9 mm	9 mm	10 mm	10 mm	10 mm	–
0.5...4 mm²	0.5...4 mm²	0.5...4 mm²	0.5...4 mm²	0.5...4 mm²	
0.5...4 mm²	0.5...4 mm²	0.5...2.5 mm²	0.5...2.5 mm²	0.5...2.5 mm²	
AWG #22...12	AWG #22...17	AWG #26...4	AWG #26...4	AWG #26...4	
4 mm²	4 mm²	2.5 mm²	2.5 mm²	1 mm²	
380 VAC	380 VAC	380 VAC	380 VAC	380 VAC	
10 A	10 A	26 A	12 A (2 x 6A)	12 A (2 x 6 A)	
0.5 W	0.5 W	0.5 W	0.5 W	0.5 W	
DK 4 PA 204988	DK 4 PA 111546	DKT 4 PA 68736	DKT 4 PA 111566		
DK 4/35 PA 202684	DK 4/35 PA 111556	DKT 4 /35 PA 68746	DKT 4/35 PA 111576	WDK 2.5 102320	WDK 2.5 102310
DK 4 RA 69096	DK 4 RA 69096			WDK 2.5 F 102160	WDK 2.5 FF 102170
DK 4 RA/35 69106	DK 4 RA/35 69106				
Type	Part No.	Type	Part No.	Type	Part No.
TS 32	12280	TS 32	12280	TS 35 x 7.5	38340
TS 35 x 7.5	38340	TS 35 x 7.5	38340	Slotted	51450
TS 35 x 15	49800	TS 35 x 15	49800	Slotted	51450
EWK 1 (8.5)	20616	EWK 1 (8.5)	20616	TS 35 x 15	49800
EW 35 (8.5)	38356	EW 35 (8.5)	38356	TS 35 x 15	49800
AP PA (1.5)	35926	AP PA (1.5)	68756	TS 35 x 15	49800
TSch 4	36336	TSch 4	36336	TS 35 x 15	49800
StB 8.5	21570				
PS (ø 2.3)	18040				
Q 2	33640				
Q 3	33650				
Q 4	33660				
Q 10	36860				
VL 2	44670				
VH 10	44660				
BS M 2.5 x 14	26680				
AD 4	30340				
BSK M 2.5 x 18	30330				
QB 2*	48270	QB 2*	48270		
QB 3*	48280	QB 3*	48280		
QB 4*	48290	QB 4*	48290		
QB 75 bare*	52640	QB 75 blank*	52640		
Insulation prof.	52670	Insulation prof.	52670		

*When using QB: conductor connection = max. 2.5 mm²

WDK...N
for electronic components

390 PART NUMBER SELECTION TABLES
Weidmüller 

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru