



# Hybrid Couplers 3 dB, 90°

### **Description**

The JP503AS is a low profile, high performance 3dB hybrid coupler in an easy to use, manufacturing friendly surface mount package. It is designed for W-CDMA and other 3G applications. The JP503AS is designed for balanced amplifiers, variable phase shifters and attenuators, LNAs, signal distribution and is an ideal solution for the ever-increasing demands of the wireless industry for smaller printed circuit boards and high performance. Parts have been subjected to rigorous qualification testing and they are manufactured using materials with coefficients of thermal expansion (CTE) compatible with common substrates such as FR4, G-10, RF-35, RO4003 and polyimide. Produced with 6 of 6 RoHS compliant tin immersion finish.

## Features:


- 2.0 2.3 GHz.
- 3G Frequencies
- Low Loss
- High Isolation
- 90° Quadrature
- Surface Mountable
- Tape And Reel
- Lead Free
- 100% Tested

## **ELECTRICAL SPECIFICATIONS\*\***

Frequency	Isolation	Insertion Loss	VSWR	
GHz	dB Min	dB Max	Max:1	
2.0 – 2.3	20	0.30	1.20	
Amplitude Balance	Phase Balance	Power	ΘJC	Operating Temp.
dB Max	Degrees	Ave. CW Watts	°C/Watt	°C
± 0.25	± 3	25	27.5	-55 to +85

<sup>\*\*</sup>Specification based on performance of unit properly installed on microstrip printed circuit boards with 50  $\Omega$  nominal impedance. Specifications subject to change without notice.

## **Outline Drawing**








Available on Tape and Reel For Pick and Place Manufacturing.



## **Hybrid Coupler Pin Configuration**

The JP503AS has an orientation marker to denote Pin 1. Once port one has been identified the other ports are known automatically. Please see the chart below for clarification:



Configuration	Pin 1	Pin 2	Pin 3	Pin 4
Splitter	Input	Isolated	-3dB $\angle \theta$ - $90$	-3dB $\angle  heta$
Splitter	Isolated	Input	-3dB $∠\theta$	-3dB $\angle \theta$ - 90
Splitter	-3dB $\angle \theta$ - 90	-3dB $\angle  heta$	Input	Isolated
Splitter	-3dB $\angle  heta$	-3dB $\angle \theta$ - 90	Isolated	Input
*Combiner	$A \angle \theta - 90$	A∠θ	Isolated	Output
*Combiner	$A \angle  heta$	$A \angle \theta - 90$	Output	Isolated
*Combiner	Isolated	Output	A∠θ-90	A∠θ
*Combiner	Output	Isolated	A∠θ	$A \angle \theta - 90$

\*Notes: "A" is the amplitude of the applied signals. When two quadrature signals with equal amplitudes are applied to the coupler as described in the table, they will combine at the output port. If the amplitudes are not equal, some of the applied energy will be directed to the isolated port.


The actual phase,  $\angle \theta$ , or amplitude at a given frequency for all ports, can be seen in our deembedded s-parameters, that can be downloaded at <a href="https://www.anaren.com">www.anaren.com</a>.


USA/Canada: Toll Free: Europe: (315) 432-8909 (800) 544-2414 +44 2392-232392







## Typical Performance (-55°C, 25°C & 125°C): 2000 - 2300 MHz














Available on Tape and Reel For Pick and Place Manufacturing. USA/Canada: Toll Free: Europe: (315) 432-8909 (800) 544-2414 +44 2392-232392




## Typical Performance (-55°C, 25°C & 125°C): 2000 - 2300 MHz









USA/Canada: Toll Free: Europe: (315) 432-8909 (800) 544-2414 +44 2392-232392





## **Definition of Measured Specifications**


Parameter	Definition	Mathematical Representation	
VSWR (Voltage Standing Wave Ratio)	The impedance match of the coupler to a $50\Omega$ system. A VSWR of 1:1 is optimal.	$\text{VSWR} = \frac{V_{\text{max}}}{V_{\text{min}}}$ $\text{Vmax} = \text{voltage maxima of a standing wave}$ $\text{Vmin} = \text{voltage minima of a standing wave}$	
Return Loss	The impedance match of the coupler to a 50Ω system. Return Loss is an alternate means to express VSWR.	Return Loss (dB)= 20log $\frac{VSWR + 1}{VSWR - 1}$	
Insertion Loss	The input power divided by the sum of the power at the two output ports.	Insertion Loss(dB)= 10log $\frac{P_{in}}{P_{cpl} + P_{direct}}$	
Isolation	The input power divided by the power at the isolated port.	Isolation(dB)= 10log $\frac{P_{in}}{P_{iso}}$	
Phase Balance	The difference in phase angle between the two output ports.	Phase at coupled port – Phase at direct port	
Amplitude Balance	The power at each output divided by the average power of the two outputs.	$10log \; \frac{P_{cpl}}{\left(\frac{P_{cpl} + P_{direct}}{2}\right)} \; \text{and} \; 10log \; \frac{P_{direct}}{\left(\frac{P_{cpl} + P_{direct}}{2}\right)}$	



Available on Tape and Reel For Pick and Place Manufacturing.



## **JP503AS Power Derating Curve**




## **Power Derating:**

The power handling and corresponding power derating plots are a function of the thermal resistance, mounting surface temperature (base plate temperature), maximum continuous operating temperature of the coupler, and the thermal insertion loss. The thermal insertion loss is defined in the Power Handling section of the data sheet

As the mounting interface temperature approaches the maximum continuous operating temperature, the power handling decreases to zero.

USA/Canada: Toll Free: Europe: (315) 432-8909 (800) 544-2414 +44 2392-232392







#### **Mounting**


In order for Xinger surface mount couplers to work optimally, there must be  $50\Omega$  transmission lines leading to and from all of the RF ports. Also, there must be a very good ground plane underneath the part to ensure proper electrical performance. If either of these two conditions is not satisfied, electrical performance may not meet published specifications.


Overall ground is improved if a dense population of plated through holes connect the top and bottom ground layers of the PCB. This minimizes ground inductance and improves ground continuity. All of the Xinger hybrid and directional couplers are constructed from ceramic filled PTFE composites which possess excellent electrical and mechanical stability having X and Y thermal coefficient of expansion (CTE) of 17-25 ppm/°C.

When a surface mount hybrid coupler is mounted to a printed circuit board, the primary concerns are; ensuring the RF pads of the device are in contact with the circuit trace of the PCB and insuring the ground plane of neither the component nor the PCB is in contact with the RF signal.

#### **Mounting Footprint**

To ensure proper electrical and thermal performance there must be a ground plane with 100% solder conection underneath the part





Dimensions are in Inches [Millimeters]

## **Coupler Mounting Process**

The process for assembling this component is a conventional surface mount process as shown in Figure 1. This process is conducive to both low and high volume usage.



Figure 1: Surface Mounting Process Steps

**Storage of Components:** Xinger products are available in either an immersion tin or tin-lead finish. Commonly used storage procedures used to control oxidation should be followed for these surface mount components. The storage temperatures should be held between 15°C and 60°C.

**Substrate:** Depending upon the particular component, the circuit material has an x and y coefficient of thermal expansion of between 17 and 25 ppm/°C. This coefficient minimizes solder joint stresses due to similar expansion rates of most commonly used board substrates such as RF35, RO4003, FR4, polyimide and G-10 materials. Mounting to "hard" substrates (alumina etc.) is possible depending upon operational temperature requirements. The solder surfaces of the coupler are all copper plated with either an immersion tin or tin-lead exterior finish.

**Solder Paste:** All conventional solder paste formulations will work well with Anaren's Xinger surface mount components. Solder paste can be applied with stencils or syringe dispensers. An example of a stenciled solder paste deposit is shown in Figure 2. As shown in the figure solder paste is applied to the four RF pads and the entire ground plane underneath the body of the part.





**Reflow:** The surface mount coupler is conducive to most of today's conventional reflow methods. A low and high

temperature thermal reflow profile are shown in Figures 5 and 6, respectively. Manual soldering of these components can be done with conventional surface mount non-contact hot air soldering tools. Board pre-heating is highly recommended for these selective hot air soldering methods. Manual soldering with conventional irons should

be avoided.




Figure 2: Solder Paste Application

Coupler Positioning: The surface mount coupler can be placed manually or with automatic pick and place mechanisms. Couplers should be placed (see Figure 3 and 4) onto wet paste with common surface mount techniques and parameters. Pick and place systems must supply adequate vacuum to hold a 0.106 gram coupler.




Figure 3: Component Placement




Figure 4: Mounting Features Example

USA/Canada: (315) 432-8909 Toll Free: (800) 544-2414 Europe: +44 2392-232392








Figure 5 – Low Temperature Solder Reflow Thermal Profile




Figure 6 - High Temperature Solder Reflow Thermal Profile








## **Packaging and Ordering Information**

Packaging follows EIA-481-2. Parts are oriented in tape as shown below. Minimum order quantities are 2000 per reel.




#### SECTION A-A

Dimensions are in inches [mm]



## Xinger® Tape & Reel Diagram



USA/Canada: Toll Free: Europe: (315) 432-8909 (800) 544-2414 +44 2392-232392





OOO «ЛайфЭлектроникс" "LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 P/C 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

#### Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru