



Introducing WPM White Polyester Matte Finish Label

TE Connectivity's (TE) new high-durability, white polyester label with matte finish is a thermal transfer printable label with a permanent acrylic adhesive. Its excellent clarity, high initial tack, high shear and ultimate adhesion make this label the perfect choice for a variety of indoor low surface energy applications. Where glossy labels can be highly reflective, the matte label finish effectively reduces glare when adhered to polished lighting fixtures, electronic components, etc. The label supports applications such as bar coding, PCB and component labeling, as well as general purpose labeling applications that require a high-durability white label. Even when exposed to a variety of solvents and elevated temperatures of as much as 200°F (93°C), the WPM white polyester matte finish label resists cracking and splitting, maintaining both its print quality and initial appearance.

KEY FEATURES

- Excellent dimensional stability at elevated temperatures
- Excellent chemical resistance
- Various colors available
- Thermal transfer printable
- Ink receptive topcoat

APPLICATIONS

- Bar code labeling
- Electronic device and equipment labeling
- Lighting
- Racks and panels
- General purpose label application

ENVIRONMENTAL AND STORAGE PROPERTIES

- Service temperature: -54°C to +93°C (-65°F to +200°F)
- Minimum application temperature: +2°C (+35°F)
- Shelf life: 2 years when stored at 21°C (+70°F) at 50% RH

PRINT TECHNOLOGY

- Thermal transfer label
- Recommended printer: T300 series
- Recommended ribbon: 1330-0607-10

STANDARDS

- Compliant to EU RoHS Directive 2002/95/EC

PRODUCT SAMPLES

Samples are available upon request. Please call +1 800-430-7226.

TECHNICAL DATASHEET

The technical datasheet TTDS-234 is available on te.com

te.com/products/identification-labeling



PRODUCT OFFERING

| Part number | Part Description | Packaging Quantity | # AC | Label Width | | Label Height | | Horizontal Repeat | | Vertical Repeat | | Web Width | | SAP # |
|-------------|------------------|--------------------|------|-------------|-------|--------------|-------|-------------------|-------|-----------------|-------|-----------|-------|------------|
| | | | | mm | in | mm | in | mm | in | mm | in | mm | in | |
| 5-1899668-6 | WPM-064064-25-9 | 25000 | 12 | 6,4 | 0,250 | 6,4 | 0,250 | 6,4 | 0,250 | 9,5 | 0,375 | 82,2 | 3,24 | CR3436-000 |
| 5-1899668-7 | WPM-080080-10-9 | 10000 | 8 | 8,0 | 0,315 | 8,0 | 0,315 | 9,9 | 0,39 | 13,3 | 0,525 | 83,3 | 3,28 | CR3437-000 |
| 5-1899668-8 | WPM-089047-10-9 | 10000 | 5 | 8,9 | 0,350 | 4,7 | 0,185 | 11,4 | 0,45 | 7,9 | 0,313 | 60,6 | 2,386 | CR3446-000 |
| 6-1899668-0 | WPM-095095-10-9 | 10000 | 7 | 9,5 | 0,375 | 9,5 | 0,375 | 11,1 | 0,437 | 12,7 | 0,5 | 64,3 | 2,531 | CR3447-000 |
| 6-1899668-1 | WPM-114040-25-9 | 25000 | 6 | 11,4 | 0,450 | 4,0 | 0,158 | 11,4 | 0,45 | 7,1 | 0,282 | 74,6 | 2,936 | CR3448-000 |
| 6-1899668-2 | WPM-127032-10-9 | 10000 | 5 | 12,7 | 0,500 | 3,2 | 0,126 | 19,1 | 0,75 | 6,4 | 0,25 | 94,6 | 3,736 | CR3449-000 |
| 6-1899668-3 | WPM-127064-10-9 | 10000 | 6 | 12,7 | 0,500 | 6,4 | 0,252 | 15,2 | 0,6 | 9,5 | 0,375 | 95,3 | 3,75 | CR3450-000 |
| 6-1899668-4 | WPM-127111-10-9 | 10000 | 5 | 12,7 | 0,500 | 11,1 | 0,437 | 16,8 | 0,662 | 14,3 | 0,563 | 86 | 3,38 | CR3451-000 |
| 6-1899668-5 | WPM-127127-10-9 | 10000 | 5 | 12,7 | 0,500 | 12,7 | 0,500 | 15,9 | 0,625 | 15,9 | 0,625 | 82,6 | 3,25 | CR3452-000 |
| 6-1899668-6 | WPM-165051-25-9 | 25000 | 4 | 16,5 | 0,650 | 5,1 | 0,200 | 17,8 | 0,7 | 8,3 | 0,325 | 75,8 | 2,99 | CR3453-000 |
| 6-1899668-7 | WPM-171171-10-9 | 10000 | 5 | 17,1 | 0,674 | 17,1 | 0,674 | 19,7 | 0,774 | 20,3 | 0,8 | 101,8 | 4,006 | CR3454-000 |
| 6-1899668-8 | WPM-178095-10-9 | 10000 | 4 | 17,8 | 0,700 | 9,5 | 0,375 | 19,1 | 0,75 | 12,7 | 0,5 | 80,9 | 3,19 | CR3455-000 |
| 7-1899668-0 | WPM-191064-10-9 | 10000 | 4 | 19,1 | 0,750 | 6,4 | 0,250 | 21,6 | 0,85 | 9,5 | 0,375 | 89,9 | 3,54 | CR3457-000 |
| 7-1899668-1 | WPM-203127-10-9 | 10000 | 4 | 20,3 | 0,800 | 12,7 | 0,500 | 22,9 | 0,9 | 15,9 | 0,625 | 94,6 | 3,73 | CR3458-000 |
| 7-1899668-2 | WPM-229064-10-9 | 10000 | 3 | 22,9 | 0,900 | 6,4 | 0,250 | 28,6 | 1,125 | 9,5 | 0,375 | 86 | 3,39 | CR3459-000 |
| 7-1899668-3 | WPM-254064-10-9 | 10000 | 3 | 25,4 | 1,000 | 6,4 | 0,250 | 27,9 | 1,1 | 9,5 | 0,375 | 95,3 | 3,75 | CR3460-000 |
| 7-1899668-4 | WPM-254097-10-9 | 10000 | 3 | 25,4 | 1,000 | 9,7 | 0,380 | 27,9 | 1,1 | 12,7 | 0,5 | 87,4 | 3,44 | CR3461-000 |
| 7-1899668-5 | WPM-254254-10-9 | 10000 | 3 | 25,4 | 1,000 | 25,4 | 1,000 | 27,9 | 1,1 | 28,6 | 1,125 | 87,4 | 3,44 | CR3463-000 |
| 7-1899668-6 | WPM-318064-10-9 | 10000 | 1 | 31,8 | 1,250 | 6,4 | 0,250 | N/A | N/A | 9,5 | 0,375 | 37,9 | 1,49 | CR3464-000 |
| 7-1899668-7 | WPM-318097-10-9 | 10000 | 1 | 31,8 | 1,250 | 9,7 | 0,380 | N/A | N/A | 12,7 | 0,5 | 37,9 | 1,49 | CR3465-000 |
| 7-1899668-8 | WPM-381064-10-9 | 10000 | 1 | 38,1 | 1,500 | 6,4 | 0,250 | N/A | N/A | 9,5 | 0,375 | 44,5 | 1,75 | CR3466-000 |
| 7-1899668-9 | WPM-381127-5-9 | 5000 | 2 | 38,1 | 1,500 | 12,7 | 0,500 | 44,2 | 1,74 | 15,9 | 0,625 | 88,2 | 3,47 | CR3467-000 |
| 8-1899668-0 | WPM-381191-5-9 | 5000 | 2 | 38,1 | 1,500 | 19,1 | 0,750 | 43,2 | 1,7 | 22,2 | 0,875 | 87,6 | 3,45 | CR3468-000 |
| 8-1899668-1 | WPM-445102-5-9 | 5000 | 1 | 44,5 | 1,750 | 10,2 | 0,400 | N/A | N/A | 12,7 | 0,5 | 50,4 | 1,986 | CR3469-000 |
| 8-1899668-2 | WPM-478175-5-9 | 5000 | 1 | 47,8 | 1,880 | 17,5 | 0,690 | N/A | N/A | 24,4 | 0,962 | 66 | 2,6 | CR3470-000 |
| 8-1899668-3 | WPM-508064-10-9 | 10000 | 1 | 50,8 | 2,000 | 6,4 | 0,250 | N/A | N/A | 9,5 | 0,375 | 56,9 | 2,24 | CR3471-000 |
| 8-1899668-4 | WPM-508095-5-9 | 5000 | 1 | 50,8 | 2,000 | 9,5 | 0,375 | N/A | N/A | 12,7 | 0,5 | 57,2 | 2,25 | CR3472-000 |
| 8-1899668-5 | WPM-508127-5-9 | 5000 | 1 | 50,8 | 2,000 | 12,7 | 0,500 | N/A | N/A | 15,9 | 0,625 | 56,9 | 2,24 | CR3473-000 |
| 8-1899668-6 | WPM-508254-5-9 | 5000 | 1 | 50,8 | 2,000 | 25,4 | 1,000 | N/A | N/A | 28,6 | 1,125 | 57,2 | 2,25 | CR3474-000 |
| 8-1899668-7 | WPM-508318-2.5-9 | 2500 | 1 | 50,8 | 2,000 | 31,8 | 1,250 | N/A | N/A | 34,9 | 1,375 | 56,9 | 2,24 | CR3475-000 |
| 8-1899668-8 | WPM-523841-1.5-9 | 1500 | 1 | 52,3 | 2,060 | 84,1 | 3,310 | N/A | N/A | 88,9 | 3,5 | 58,2 | 2,29 | CR3476-000 |
| 8-1899668-9 | WPM-699191-5-9 | 5000 | 1 | 69,9 | 2,750 | 19,1 | 0,750 | N/A | N/A | 23,3 | 0,917 | 76,2 | 3 | CR3477-000 |
| 9-1899668-0 | WPM-699254-5-9 | 5000 | 1 | 69,9 | 2,750 | 25,4 | 1,000 | N/A | N/A | 28,6 | 1,125 | 76,2 | 3 | CR3478-000 |
| 9-1899668-1 | WPM-762127-1-9 | 1000 | 1 | 76,2 | 3,000 | 127,0 | 5,000 | N/A | N/A | 129,5 | 5,1 | 79,4 | 3,13 | CR3479-000 |
| 9-1899668-2 | WPM-762254-5-9 | 5000 | 1 | 76,2 | 3,000 | 25,4 | 1,000 | N/A | N/A | 28,6 | 1,125 | 82,3 | 3,24 | CR3480-000 |
| 9-1899668-3 | WPM-762508-2.5-9 | 2500 | 1 | 76,2 | 3,000 | 50,8 | 2,000 | N/A | N/A | 54 | 2,125 | 82,6 | 3,24 | CR3481-000 |

PART NUMBERING SYSTEM



te.com/products/identification-labeling



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru