PRODUCT PARTNUMBER
10146065-XXXXXLF











DETAIL B
SCALE 8:1



SECTION E-E
SCALE 8:1



SECTION E-E
SCALE 3:1

spec ref	-			dr	Cheong, Matthe	2017/11/06	projection	MM
tolerance std ISO 406 ISO 1101	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Cheong, Matthe	2018/07/19		
				chr	-	-		
				appr	Koon-Poh Tay	2018/07/26	product family	PCI express
surface - ISO 1302	linear	0.X	±0.30	Amphenol FCI	title	PCI Express 4.0 SMT Type	dwg no	10146065
		0.XX	±0.20					
		0.XXX	±0.1					
	angular	0°	±2°	www.fci.com	cat. no.	-	Product - Customer Drw	

size	scale	rev
A3	3:1	E

ecn no ELX-S-30728-1

rel level **Released**

sheet 1 of 4

© 2016 AFCI

Creo File - REV E - 2016-02-12

PDS: Rev :E STATUS:Released Printed: Jul 26, 2018

CONNECTOR LINK WIDTH	POSITION	N	DIM "G"	DIM "F"	PIN "L"
X1	36	6	8.15	6.00	B17
X4	64	20	22.15	20.00	B31
X8	98	37	39.15	37.00	B48
X16	164	70	72.15	70.00	B81





← I/O PANEL DIRECTION
PRIMARY (COMPONENT) SIDE



I/O PANEL DIRECTION →
SECONDARY (SOLDER) SIDE

1. NO TIE BAR PERMITTED FROM CARD EDGE TO LEADING EDGE OF PAD FOR PIN A1 AND PIN "L".
2. CHAMFER EDGES MUST BE FREE OF CUTTING BURRS.
3. TOLERANCE : ± 0.13

spec ref	-			dr	Cheong, Matthe	2017/11/06	projection	MM	size A3	scale 2:1
tolerance std ISO 406 ISO 1101	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Cheong, Matthe	2018/07/19			ecn no	ELX-S-30728-1
				chr	-	-			rel level	Released
surface ISO 1302	linear	0.X	±0.30	appr	Koon-Poh Tay	2018/07/26	product family	PCI express		
		0.XX	±0.20	Amphenol FCI	title	PCI Express 4.0 SMT Type	dwg no	10146065	rev	E
		0.XXX	±0.1	www.fci.com	cat. no.		Product - Customer Drw		sheet 2 of 4	
	angular	0°	±2°							

© 2016 AFCI

Creo File - REV E - 2016-02-12

PDS: Rev :E STATUS:Released Printed: Jul 26, 2018



RECOMMENDED PCB LAYOUT, PAD TYPE

DIMENSIONS								
POSITION	A	B $^{+0.15}_{-0.05}$	C ±0.10	D ±0.23	E ±0.20	H ±0.10	J	K ±0.10
36	6.00	7.65	9.15	25.00	27.00	28.00	6.00	9.15
64	20.00	21.65	23.15	39.00	41.00	42.00	20.00	23.15
98	37.00	38.65	40.15	56.00	58.00	59.00	37.00	40.15
164	70.00	71.65	73.15	89.00	91.00	92.00	70.00	73.15
98 (SEE NOTE)	37.00	38.65	40.15	56.00	56.60	59.00	37.00	40.15
164 (SEE NOTE)	70.00	71.65	73.15	89.00	89.60	92.00	70.00	73.15

© 2016 AFCI

spec ref -

tolerance std ISO 406 ISO 1101

TOLERANCES UNLESS OTHERWISE SPECIFIED

linear	0.X	±0.30
	0.XX	±0.20
	0.XXX	±0.1
angular	0°	±2°

surface - ISO 1302

dr	Cheong, Matthe	2017/11/06	
eng	Cheong, Matthe	2018/07/19	
chr	-	-	
appr	Koon-Poh Tay	2018/07/26	

projection | MM | size A3 | scale 4:1

ecn no ELX-S-30728-1

product family PCI express | rel level **Released**

Amphenol FCI | www.fci.com

title: PCI Express 4.0 SMT Type

dwg no 10146065 | rev **E**

cat. no. - | Product - Customer Drw | sheet 3 of 4

Creo File - REV E - 2016-02-12

PDS: Rev :E | STATUS:Released | Printed: Jul 26, 2018

PRODUCT NUMBER CODE



10146065- □□□□□LF

HOUSING COLOR

1: BLACK

CONTACT AREA PLATING

1: 30u" Au
2: 15u" Au

NO. OF POSITION

0: 36 POSITIONS
1: 64 POSITIONS
2: 98 POSITIONS
3: 164 POSITIONS

HOLDDOWN CLIP

0: NORMAL
1: SHORTER (BY 0.7MM PER SIDE)

PACKAGING OPTIONS

A: HARD TRAY (DIM: 323 x 136 x 19) WITH KAPTON TAPE, 22MM (164 POS)
B: HARD TRAY (DIM: 323 x 136 x 19) WITH KAPTON TAPE, 86.5MM (164 POS) E
Q: HARD TRAY (DIM: 323 x 136 x 19) (98 & 164 POS)
C: SOFT TRAY (317.5 x 235 x 18) WITH PICK-UP CAP (36 & 64 POS)
T: SOFT TRAY (317.5 x 235 x 18) WITH KAPTON TAPE, 22MM (36 & 64 POS)
W: HARD TRAY (DIM: 330 x 235 x 19.3) WITH KAPTON TAPE. 30MM (98 & 164 POS)
X: HARD TRAY (DIM: 330 x 235 x 19.3) WITH PICK UP CAP (98 & 164 POS)
Y: HARD TRAY (DIM: 330 x 235 x 19.3) WITH KAPTON TAPE. 22MM (98 & 164 POS)
Z: HARD TRAY (DIM: 330 x 235 x 19.3) WITH KAPTON TAPE, 8.56MM (164 POS)

NOTES:

1. MATERIAL:
   HOUSING: LCP
   CONTACT: COPPER ALLOY.
   HOLDDOWN CLIP: COPPER ALLOY

2. PLATING:
   CONTACT: UNDERPLATE: 50u" NICKEL OVER ALL.
   SOLDER AREA: 100u" TIN (LEAD FREE).
   MATING AREA: SEE PRODUCT NUMBER CODE.
   HOLDDOWN CLIP: 100u" TIN OVER 50 u" NICKEL.

3. PRODUCT SPECIFICATION: GS-12-1406

4. PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-47-004.

5. DATE CODE "MMDDYYL", MMDDYY IS ASSEMBLY DATE. L IS AFCI PRODUCTION SITE.

6. THE HOUSING WILL WITHSTAND EXPOSURE TO 260° PEAK TEMPERATURE FOR 10 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.

7. PARTNO: 10146065-**2*ILF & 10146065-**3*ILF, ARE OPTIONS WITH SHORTER HOLDDOWN CLIP FLAT AND PAD LENGTH



POSITION OF KAPTON TAPE



POSITION OF PICK UP CAP



spec ref	-			dr	Cheong, Matthe	2017/11/06	projection: MM
tolerance std ISO 406 ISO 1101	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Cheong, Matthe	2018/07/19	size: A3 scale: 2:1
				chr	-	-	ecn no: ELX-S-30728-1
surface ISO 1302	linear	0.X	±0.30	appr	Koon-Poh Tay	2018/07/26	product family: PCI express rel level: Released
		0.XX	±0.20	Amphenol FCI	title: PCI Express 4.0 SMT Type		dwg no: 10146065 rev: E
		0.XXX	±0.1	www.fci.com	cat. no.		Product - Customer Drw sheet 4 of 4
	angular	0°	±2°				

© 2016 AFCI

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru