TAPE PACKING OPTIONS



TAPE DIMENSIONS

TAPE STYLE

AMMOPACK STYLE "T2" 12,14





TAPE DIMENSIONS

AMMOPACK STYLE "T3" 12,14





TAPE DIMENSIONS

DIRECTION OF FEED FROM REEL

TAPE STYLE "P" 15





OPTIONAL SURFACE MOUNT LEAD STYLE



NOTES
1. CENTERLINE OF HALL CELL
2. THE + MAGNETIC FLUX IS IN THE DIRECTION SHOWN (THIS ASSUMES THE CONVENTION THAT THE DIRECTION OF THE EXTERNAL FLUX OF A MAGNET IS FROM THE NORTH TO THE SOUTH POLE OF THE MAGNET)
3. – THE DEVICE CANNOT BE DAMAGED BY MAGNETIC OVERDRIVE
4. – OUTPUT TYPE – RATIOMETRIC
5. – LEADS MUST BE ADEQUATELY SUPPORTED DURING ANY FORMING/SHEERING OPERATION TO ASSURE THAT THE LEADS ARE NOT STRESSED WITHIN THE PLASTIC
6. – PCB WAVE SOLDERING GUIDELINES ARE AS FOLLOWS:
   250°C PEAK FOR 10 S MAX OR 260°C PEAK FOR 5 S MAX
7. BURRS ARE ALLOWED ONLY IF FULL LENGTH OF LEADS WILL PASS THROUGH Ø.023 HOLE. LEAD REFERENCE DIMENSIONS DO NOT INCLUDE SOLDER THICKNESS
8. DIMENSION REFERS TO THE LOCATION OF LEAD CENTERLINES AS THE EXIT THE PLASTIC PACKAGE
9. – SOME COMBINATIONS OF BASIC LISTING AND PACKAGE OPTIONS MAY NOT BE AVAILABLE
10. ABSOLUTE MAXIMUM RATINGS ARE THE EXTREME LIMITS THE DEVICE WILL MOMENTARILY WITHSTAND WITHOUT DAMAGE TO THE DEVICE. ELECTRICAL AND MAGNETIC CHARACTERISTICS ARE NOT GUARANTEED IF THE RATED VOLTAGE AND/OR CURRENTS ARE EXCEEDED NOR WILL THE DEVICE NECESSARILY OPERATE AT ABSOLUTE MAXIMUM RATINGS
11. LEAD STRAIGHTNESS MAY BE DETERIORATED ON SOME UNITS BY BULK PACKAGING. APPLICATIONS HAVING A CRITICAL LEAD STRAIGHTNESS REQUIREMENT SHOULD USE A TAPE PACKAGING OPTION
12. AMMOPACK STYLE "T2" & "T3". 24 SWITCHES BETWEEN FOLDS, SKIP 1 SPACE AT FOLD. MAY BE REFERRED TO AS "FAN FOLD"
13. MOLDED PART DIMENSIONS DO NOT INCLUDE FLASH. FLASH IS LIMITED TO .005 MAXIMUM
14. TAPE AND AMMOPACK PER EIA–468
15. POCKET TAPE PER EIA–481

CATALOG LISTING	TAPE STYLE	DIM "L" ±.015	DIM "W" +.015 -.004	COMMENTS 1
SS496A	NONE	.590	.050	BULK–1000/BAG
SS496A–T2	T2	.590	.100	5000/BOX
SS496A–T3	T3	.590	.050	5000/BOX
SS496A–S	NONE	.125	.050	BULK–1000/BAG
SS496A–SP	P	.125	.050	1000/PACKET TAPE AND REEL
SS496A1	NONE	.590	.050	BULK–1000/BAG
SS496A1–T2	T2	.590	.100	5000/BOX
SS496A1–T3	T3	.590	.050	5000/BOX
SS496A1–S	NONE	.125	.050	BULK–1000/BAG
SS496A1–SP	P	.125	.050	1000/PACKET TAPE AND REEL
SS496B	**NONE**	**.590**	**.050**	**BULK–1000/BAG**
SS496B–F	NONE	.590	.100	BULK–1000/BAG
SS496B–T2	**T2**	**.590**	**.100**	**5000/BOX**
SS496B–T3	**T3**	**.590**	**.050**	**5000/BOX**
SS496B–S	**NONE**	**.125**	**.050**	**BULK–1000/BAG**
SS496B–SP	**P**	**.125**	**.050**	**1000/PACKET TAPE AND REEL**

CAUTION ELECTROSTATIC SENSITIVE DEVICES
ESD SENSITIVITY: CLASS 3
MASTER REDUCED ANSI Y14.5M–1982 APPLIES
THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

MICRO SWITCH a Honeywell Division

MINIATURE RATIOMETRIC LINEAR HALL EFFECT SENSOR

CATALOG LISTING: SS496 SERIES CHART 1

THIRD ANGLE PROJECTION

SCALE 5 : 1

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

ONE PLACE	(.X)	±.030
TWO PLACES	(.XX)	±.015
THREE PLACES	(.XXX)	±.005
ANGLES		± 2°

WEIGHT

DRAWING NUMBER M SS496 SERIES CHART 1 PAGE 1 OF 4
RELEASE NO. PR-22400 RELEASED X00795 SS
ISSUE 10 DATE 21 JUN 10 DRAWN R.M. CHECKED J.A.F. DATE 15 SEP 96 CHECKED J.A.F. DATE 15 SEP 96
RASTER DRAWN J.A.F. DATE 15 SEP 96
REVISIONS PER 00034535 PER 25 OCT 00 00063541 21 JUN 10

SS496A

CHARACTERISTICS ARE AT Vs=5.00 WITH 4.7K OUTPUT TO MINUS WITH TA= −40°C TO +125°C UNLESS OTHERWISE SPECIFIED

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
SENSITIVITY	TA = 25°C	2.4	2.5	2.6	mV/GAUSS
NULL	TA = 25°C	2.425	2.50	2.575	VOLTS
SUPPLY CURRENT	TA = 25°C		7	8.7	mA
OUTPUT CURRENT SOURCE	Vs > 4.5	1mA	1.5mA		
SINK	Vs > 4.5	.6mA	1.5mA		
SINK	Vs > 5.0	1mA	1.5mA		
RESPONSE TIME			3µS		
OUTPUT VOLTAGE SWING					
VOM −	−B APPLIED	.4	.2		VOLTS
VOM +	+B APPLIED	Vs −.4	Vs −.2		VOLTS
B LIMITS FOR LINEAR	−B MAX	−750	−840		GAUSS
OPERATION	+B MAX	+750	+840		GAUSS
Vnull DRIFT	B = 0, TA = 25°C TO 125°C	−.048		+.048	% /°C
Vnull DRIFT	B = 0, TA = +125°C TO +150°C	−.064		+.064	% /°C
SENSITIVITY DRIFT	TA=+25°C TO +125°C	−.01		+.05	% /°C
SENSITIVITY DRIFT	TA=−40°C TO +25°C	0		+.06	% /°C
LINEARITY	B = −600 TO +600	0	−1.0	−1.5	% OF SPAN
SUPPLY VOLTAGE	−40°C TO +125°C	4.5	5.0	10.5	VOLTS
OPERATING TEMP	SEE MAX TEMPERATURE CHART	−40		+150	°C

BLOCK DIAGRAM CURRENT SINKING OR SOURCING OUTPUT



ABSOLUTE MAXIMUM CHARACTERISTICS ⚠

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN	MAX	UNITS
SUPPLY VOLTAGE	Vcc		−0.5	11	V
OUTPUT VOLTAGE	Vout		−0.5	11	V
OUTPUT CURRENT	Iout	SOURCE OR SINK		10	mA
TEMPERATURE	TA	OPERATING	−55	150	°C
	Ts	STORAGE (Vcc=0)	−55	165	°C

NULL SHIFT VERSUS TEMPERATURE



RATIO OF Vnull TO Vs



SENSITIVITY SHIFT VERSUS TEMPERATURE



SENSITIVITY/V VERSUS Vs
(mV/GAUSS/VOLT)



LINEARITY VERSUS Vs
END POINT OF SPAN METHOD



TRANSFER CHARACTERISTICS AT Vs=5.0 VDC



SUPPLY CURRENT VERSUS TEMPERATURE



TYPICAL FREQUENCY RESPONSE
RL=33k PARALLEL WITH 100pF



MAXIMUM ALLOWABLE AMBIENT TEMPERATURE



ESD SENSITIVITY: CLASS 3

MASTER REDUCED
ANSI Y14.5M−1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

FED. MFR. CODE 01929

MICRO SWITCH a Honeywell Division

MINIATURE RATIOMETRIC LINEAR HALL EFFECT SENSOR

CATALOG LISTING: SS496 SERIES CHART 1

THIRD ANGLE PROJECTION

SCALE NONE

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

ONE PLACE	(.0)	±.030
TWO PLACES	(.00)	±.015
THREE PLACES	(.000)	±.005
ANGLES		±2°

WEIGHT

DRAWING NUMBER SS496 SERIES CHART 1 | PAGE 2 OF 4 | RELEASED TO PRR 22400 | RELEASED X100795 SS | ISSUE 10 | DATE JUN 10

SERIES LOCK 0003453 | PRR 22400 | 0063546 | DATE 21 JUN 10

DRAWN J A F | DATE SEP 96 | CHECK K A G | DATE 18 DEC 98 | CHECK R.M. | DATE 21 JUN 10 | CHECK

RASTER

CHARACTERISTICS ARE AT Vs=5.00 WITH 4.7K OUTPUT TO MINUS WITH TA= −40°C TO +125°C UNLESS OTHERWISE SPECIFIED

SS496A1

MSS496 SERIES CHART 1

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
SENSITIVITY	TA = 25°C	2.425	2.500	2.575	mV/GAUSS
NULL	TA = 25°C	2.425	2.50	2.575	VOLTS
SUPPLY CURRENT	TA = 25°C		7	8.7	mA
OUTPUT CURRENT SOURCE	Vs > 4.5	1mA	1.5mA		
SINK	Vs > 4.5	.6mA	1.5mA		
SINK	Vs > 5.0	1mA	1.5mA		
RESPONSE TIME			3µS		
OUTPUT VOLTAGE SWING					
VOM −	−B APPLIED	.4	.2		VOLTS
VOM +	+B APPLIED	Vs −.4	Vs −.2		VOLTS
B LIMITS FOR LINEAR	−B MAX	−750	−840		GAUSS
OPERATION	+B MAX	+750	+840		GAUSS
Vnull DRIFT	B = 0, TA = 25° TO 125°C	−.032		+.032	% /°C
Vnull DRIFT	B = 0, TA = +125° TO +150°C	−.064		+.064	% /°C
SENSITIVITY DRIFT	TA=+25°C TO + 125°C	−.01		+.05	% /°C
SENSITIVITY DRIFT	TA=−40°C TO +25°C	0		+.06	% /°C
SENSITIVITY DRIFT	TA=+125°C TO +150°C	−.04		+.08	% /°C
LINEARITY	B = −600 TO +600	0	−1.0	−1.5	% OF SPAN
SUPPLY VOLTAGE	−40°C TO +125°C	4.5	5.0	10.5	VOLTS
OPERATING TEMP	SEE MAX TEMPERATURE CHART	−40		+150	°C

BLOCK DIAGRAM CURRENT SINKING OR SOURCING OUTPUT



ABSOLUTE MAXIMUM CHARACTERISTICS ⚠10

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN	MAX	UNITS
SUPPLY VOLTAGE	Vcc		−0.5	11	V
OUTPUT VOLTAGE	Vout		−0.5	11	V
OUTPUT CURRENT	Iout	SOURCE OR SINK		10	mA
TEMPERATURE	TA	OPERATING	−55	150	°C
	Ts	STORAGE (Vcc=0)	−55	165	°C

NULL SHIFT VERSUS TEMPERATURE



RATIO OF Vnull TO Vs



SENSITIVITY SHIFT VERSUS TEMPERATURE



SENSITIVITY/V VERSUS Vs (mV/GAUSS/VOLT)



LINEARITY VERSUS Vs
END POINT OF SPAN METHOD



TRANSFER CHARACTERISTICS AT Vs=5.0 VDC



SUPPLY CURRENT VERSUS TEMPERATURE



TYPICAL FREQUENCY RESPONSE
RL=3.3k PARALLEL WITH 100pF



MAXIMUM ALLOWABLE AMBIENT TEMPERATURE



CAUTION ELECTROSTATIC SENSITIVE DEVICE
ESD SENSITIVITY: CLASS 3

MASTER REDUCED
ANSI Y14.5M−1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

PROD. MFG. CODE 81828

MICRO SWITCH a Honeywell Division

MINIATURE RATIOMETRIC LINEAR HALL EFFECT SENSOR

CATALOG LISTING: SS496 SERIES CHART 1

THIRD ANGLE PROJECTION

SCALE NONE

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

ONE PLACE	(.0)	±.030
TWO PLACES	(.00)	±.015
THREE PLACES	(.000)	±.005
ANGLES		±2°

WEIGHT

ISSUE 10 | DRAWING NUMBER MSS496 SERIES CHART 1 PAGE 3 OF 4 | RELEASE NO. PRR-22400 | RELEASED X100796-SS

REVISIONS
E10034536 | K.A.G. | 30DEC98
P68 | J.A.F. | 15SEP96
21DEC10 | R.M. | 21JUN10
E10063540 | JUN 10

SS496B

CHARACTERISTICS ARE AT Vs=5.00 WITH 4.7K OUTPUT TO MINUS WITH TA= −40°C TO +125°C UNLESS OTHERWISE SPECIFIED

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
SENSITIVITY	TA = 25°C	2.300	2.500	2.700	mV/GAUSS
NULL	TA = 25°C	2.350	2.50	2.650	VOLTS
SUPPLY CURRENT	TA = 25°C		7	8.7	mA
OUTPUT CURRENT SOURCE	Vs > 4.5	1mA	1.5mA		
SINK	Vs > 4.5	.6mA	1.5mA		
SINK	Vs > 5.0	1mA	1.5mA		
RESPONSE TIME			3µs		
OUTPUT VOLTAGE SWING					
VOM −	−B APPLIED	.4	.2		VOLTS
VOM +	+B APPLIED	Vs −.4	Vs −.2		VOLTS
B LIMITS FOR LINEAR	−B MAX	−750	−840		GAUSS
OPERATION	+B MAX	+750	+840		GAUSS
Vnull DRIFT	B = 0, TA = 25° TO 125°C	−.064		+.064	% /°C
Vnull DRIFT	B = 0, TA = +125° TO +150°C	−.064		+.064	% /°C
SENSITIVITY DRIFT	TA=+25°C TO +150°C	−.02		+.08	% /°C
SENSITIVITY DRIFT	TA=−40°C TO +25°C	−.02		+.08	% /°C
LINEARITY	B = −600 TO +600	0	−1.0	−1.5	% OF SPAN
SUPPLY VOLTAGE	−40°C TO +125°C	4.5	5.0	10.5	VOLTS
OPERATING TEMP	SEE MAX TEMPERATURE CHART	−40		+150	°C

BLOCK DIAGRAM CURRENT SINKING OR SOURCING OUTPUT



ABSOLUTE MAXIMUM CHARACTERISTICS ⚠10

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN	MAX	UNITS
SUPPLY VOLTAGE	Vcc		−0.5	11	V
OUTPUT VOLTAGE	Vout		−0.5	11	V
OUTPUT CURRENT	Iout	SOURCE OR SINK		10	mA
TEMPERATURE	TA	OPERATING	−55	150	°C
	Ts	STORAGE (Vcc=0)	−55	165	°C

NULL SHIFT VERSUS TEMPERATURE



RATIO OF Vnull TO Vs



SENSITIVITY SHIFT VERSUS TEMPERATURE



SENSITIVITY/V VERSUS Vs (mV/GAUSS/VOLT)



LINEARITY VERSUS Vs END POINT OF SPAN METHOD



TRANSFER CHARACTERISTICS AT Vs=5.0 VDC



SUPPLY CURRENT VERSUS TEMPERATURE



TYPICAL FREQUENCY RESPONSE
RL=33k PARALLEL WITH 100pF



MAXIMUM ALLOWABLE AMBIENT TEMPERATURE



ESD SENSITIVITY: CLASS 3

MASTER REDUCED ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

MICRO SWITCH a Honeywell Division

MINIATURE RATIOMETRIC LINEAR HALL EFFECT SENSOR

CATALOG LISTING: SS496 SERIES CHART 1

THIRD ANGLE PROJECTION

SCALE NONE

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

ONE PLACE	(.0)	±.030
TWO PLACES	(.00)	±.015
THREE PLACES	(.000)	±.005
ANGLES		±2°

WEIGHT

M SS496 SERIES CHART 1 PAGE 2 OF 2 ISSUE 10 PR-24063

REVISIONS				
LTR	DESCRIPTION	DATE	APPROVED	
A	0003636 PDS	21JUN99	RM	
B	0003640 PDS	21JUN99	RM	
C	0003641 PDS	21JUN99	RM	
D	ISSUE 10	21JUN99	RM	

RASTER TSM 22JUN99 JAE 22JUN99

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru