



**Is Now Part of**



**ON Semiconductor®**

**To learn more about ON Semiconductor, please visit our website at**  
**[www.onsemi.com](http://www.onsemi.com)**

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at [www.onsemi.com](http://www.onsemi.com). Please email any questions regarding the system integration to [Fairchild\\_questions@onsemi.com](mailto:Fairchild_questions@onsemi.com).

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## MM74HC540 • MM74HC541

### Inverting Octal 3-STATE Buffer • Octal 3-STATE Buffer

#### General Description

The MM74HC540 and MM74HC541 3-STATE buffers utilize advanced silicon-gate CMOS technology. They possess high drive current outputs which enable high speed operation even when driving large bus capacitances. These circuits achieve speeds comparable to low power Schottky devices, while retaining the advantage of CMOS circuitry, i.e., high noise immunity, and low power consumption. Both devices have a fanout of 15 LS-TTL equivalent inputs.

The MM74HC540 is an inverting buffer and the MM74HC541 is a non-inverting buffer. The 3-STATE control gate operates as a two-input NOR such that if either G1 or G2 are HIGH, all eight outputs are in the high-impedance state.

In order to enhance PC board layout, the MM74HC540 and MM74HC541 offers a pinout having inputs and outputs on opposite sides of the package. All inputs are protected from damage due to static discharge by diodes to  $V_{CC}$  and ground.

#### Features

- Typical propagation delay: 12 ns
- 3-STATE outputs for connection to system buses
- Wide power supply range: 2–6V
- Low quiescent current: 80  $\mu$ A maximum (74HC Series)
- Output current: 6 mA



#### Ordering Code:

| Order Number | Package Number | Package Description                                                         |
|--------------|----------------|-----------------------------------------------------------------------------|
| MM74HC540WM  | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  |
| MM74HC540SJ  | M20D           | 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| MM74HC540MTC | MTC20          | 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide |
| MM74HC540N   | N20A           | 20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide      |
| MM74HC541WM  | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  |
| MM74HC541SJ  | M20D           | 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| MM74HC541MTC | MTC20          | 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide |
| MM74HC541N   | N20A           | 20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide      |

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

#### Connection Diagrams

##### Pin Assignments for DIP, SOIC, SOP and TSSOP



**Absolute Maximum Ratings** (Note 1)

(Note 2)

|                                                  |                         |
|--------------------------------------------------|-------------------------|
| Supply Voltage ( $V_{CC}$ )                      | -0.5 to +7.0V           |
| DC Input Voltage ( $V_{IN}$ )                    | -1.5 to $V_{CC} + 1.5V$ |
| DC Output Voltage ( $V_{OUT}$ )                  | -0.5 to $V_{CC} + 0.5V$ |
| Clamp Diode Current ( $I_{CD}$ )                 | $\pm 20$ mA             |
| DC Output Current, per pin ( $I_{OUT}$ )         | $\pm 35$ mA             |
| DC $V_{CC}$ or GND Current, per pin ( $I_{CC}$ ) | $\pm 70$ mA             |
| Storage Temperature Range ( $T_{STG}$ )          | -65°C to +150°C         |
| Power Dissipation ( $P_D$ )                      |                         |
| (Note 3)                                         | 600 mW                  |
| S.O. Package only                                | 500 mW                  |
| Lead Temperature ( $T_L$ )                       |                         |
| (Soldering 10 seconds)                           | 260°C                   |

**Recommended Operating Conditions**

|                                                  | Min | Max      | Units |
|--------------------------------------------------|-----|----------|-------|
| Supply Voltage ( $V_{CC}$ )                      | 2   | 6        | V     |
| DC Input or Output Voltage ( $V_{IN}, V_{OUT}$ ) | 0   | $V_{CC}$ | V     |
| Operating Temperature Range ( $T_A$ )            | -40 | +85      | °C    |
| Input Rise or Fall Times ( $t_r, t_f$ )          |     |          |       |
| $V_{CC} = 2.0V$                                  |     | 1000     | ns    |
| $V_{CC} = 4.5V$                                  |     | 500      | ns    |
| $V_{CC} = 6.0V$                                  |     | 400      | ns    |

**Note 1:** Absolute Maximum Ratings are those values beyond which damage to the device may occur.

**Note 2:** Unless otherwise specified all voltages are referenced to ground.

**Note 3:** Power Dissipation temperature derating — plastic "N" package: -12 mW/°C from 65°C to 85°C.

**DC Electrical Characteristics** (Note 4)

| Symbol          | Parameter                              | Conditions                                                                                                                           | V <sub>CC</sub> | T <sub>A</sub> = 25°C |                   | T <sub>A</sub> = −40 to 85°C | T <sub>A</sub> = −55 to 125°C | Units |   |
|-----------------|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------------|-------------------|------------------------------|-------------------------------|-------|---|
|                 |                                        |                                                                                                                                      |                 | Typ                   | Guaranteed Limits |                              |                               |       |   |
| V <sub>IH</sub> | Minimum HIGH Level Input Voltage       |                                                                                                                                      | 2.0V            |                       | 1.5               | 1.5                          | 1.5                           | V     |   |
|                 |                                        |                                                                                                                                      | 4.5V            |                       | 3.15              | 3.15                         | 3.15                          | V     |   |
|                 |                                        |                                                                                                                                      | 6.0V            |                       | 4.2               | 4.2                          | 4.2                           | V     |   |
| V <sub>IL</sub> | Maximum LOW Level Input Voltage        |                                                                                                                                      | 2.0V            |                       | 0.5               | 0.5                          | 0.5                           | V     |   |
|                 |                                        |                                                                                                                                      | 4.5V            |                       | 1.35              | 1.35                         | 1.35                          | V     |   |
|                 |                                        |                                                                                                                                      | 6.0V            |                       | 1.8               | 1.8                          | 1.8                           | V     |   |
| V <sub>OH</sub> | Minimum HIGH Level Output Voltage      | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 20 μA                                                  | 2.0V            | 2.0                   | 1.9               |                              | 1.9                           | V     |   |
|                 |                                        |                                                                                                                                      | 4.5V            | 4.5                   | 4.4               |                              | 4.4                           | V     |   |
|                 |                                        |                                                                                                                                      | 6.0V            | 6.0                   | 5.9               |                              | 5.9                           | V     |   |
|                 |                                        | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 6.0 mA<br> I <sub>OUT</sub>   ≤ 7.8 mA                 | 4.5V            | 4.2                   | 3.98              |                              | 3.84                          | 3.7   | V |
|                 |                                        |                                                                                                                                      | 6.0V            | 5.7                   | 5.48              |                              | 5.34                          | 5.2   | V |
|                 |                                        |                                                                                                                                      |                 |                       |                   |                              |                               |       |   |
| V <sub>OL</sub> | Maximum LOW Level Output Voltage       | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 20 μA                                                  | 2.0V            | 0                     | 0.1               |                              | 0.1                           | V     |   |
|                 |                                        |                                                                                                                                      | 4.5V            | 0                     | 0.1               |                              | 0.1                           | V     |   |
|                 |                                        |                                                                                                                                      | 6.0V            | 0                     | 0.1               |                              | 0.1                           | V     |   |
|                 |                                        | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 6.0 mA<br> I <sub>OUT</sub>   ≤ 7.8 mA                 | 4.5V            | 0.2                   | 0.26              |                              | 0.33                          | 0.4   | V |
|                 |                                        |                                                                                                                                      | 6.0V            | 0.2                   | 0.26              |                              | 0.33                          | 0.4   | V |
|                 |                                        |                                                                                                                                      |                 |                       |                   |                              |                               |       |   |
| I <sub>IN</sub> | Maximum Input Current                  | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                                                             | 6.0V            |                       | ±0.1              | ±1.0                         | ±1.0                          | μA    |   |
| I <sub>OZ</sub> | Maximum 3-STATE Output Leakage Current | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> , $\overline{G}$ = V <sub>IH</sub><br>V <sub>OUT</sub> = V <sub>CC</sub> or GND | 6.0V            |                       | ±0.5              | ±5                           | ±10                           | μA    |   |
| I <sub>CC</sub> | Maximum Quiescent Supply Current       | V <sub>IN</sub> = V <sub>CC</sub> or GND<br>I <sub>OUT</sub> = 0 μA                                                                  | 6.0V            |                       | 8.0               | 80                           | 160                           | μA    |   |

**Note 4:** For a power supply of  $5V \pm 10\%$  the worst case output voltages ( $V_{OH}$  and  $V_{OL}$ ) occur for HC at 4.5V. Thus the 4.5V values should be used when designing with this supply. Worst case  $V_{IH}$  and  $V_{IL}$  occur at  $V_{CC} = 5.5V$  and 4.5V respectively. (The  $V_{IH}$  value at 5.5V is 3.85V.) The worst case leakage current ( $I_{IN}$ ,  $I_{CC}$ , and  $I_{OZ}$ ) occur for CMOS at the higher voltage and so the 6.0V values should be used.


**AC Electrical Characteristics** $V_{CC} = 5V$ ,  $T_A = 25^\circ C$ ,  $t_r = t_f = 6\text{ ns}$ 

| Symbol                | Parameter                       | Conditions                                       | Typ | Guaranteed Limit | Units |
|-----------------------|---------------------------------|--------------------------------------------------|-----|------------------|-------|
| $t_{PHL}$ , $t_{PLH}$ | Maximum Propagation Delay (540) | $C_L = 45\text{ pF}$                             | 12  | 18               | ns    |
| $t_{PHL}$ , $t_{PLH}$ | Maximum Propagation Delay (541) | $C_L = 45\text{ pF}$                             | 14  | 20               | ns    |
| $t_{PZH}$ , $t_{PZL}$ | Maximum Output Enable Time      | $R_L = 1\text{ k}\Omega$<br>$C_L = 45\text{ pF}$ | 17  | 28               | ns    |
| $t_{PHZ}$ , $t_{PLZ}$ | Maximum Output Disable Time     | $R_L = 1\text{ k}\Omega$<br>$C_L = 5\text{ pF}$  | 15  | 25               | ns    |

**AC Electrical Characteristics** $V_{CC} = 2.0V$  to  $6.0V$ ,  $C_L = 50\text{ pF}$ ,  $t_r = t_f = 6\text{ ns}$  (unless otherwise specified)

| Symbol                              | Parameter                              | Conditions                                         | V <sub>CC</sub> | T <sub>A</sub> = 25°C |                   | T <sub>A</sub> = -40 to 85°C | T <sub>A</sub> = -55 to 125°C | Units    |
|-------------------------------------|----------------------------------------|----------------------------------------------------|-----------------|-----------------------|-------------------|------------------------------|-------------------------------|----------|
|                                     |                                        |                                                    |                 | Typ                   | Guaranteed Limits |                              |                               |          |
| t <sub>PHL</sub> , t <sub>PLH</sub> | Maximum Propagation Delay (540)        | C <sub>L</sub> = 50 pF                             | 2.0V            | 55                    | 100               | 126                          | 149                           | ns       |
|                                     |                                        | C <sub>L</sub> = 150 pF                            | 2.0V            | 83                    | 150               | 190                          | 224                           | ns       |
|                                     |                                        | C <sub>L</sub> = 50 pF                             | 4.5V            | 12                    | 20                | 25                           | 30                            | ns       |
|                                     |                                        | C <sub>L</sub> = 150 pF                            | 4.5V            | 22                    | 30                | 38                           | 45                            | ns       |
|                                     |                                        | C <sub>L</sub> = 50 pF                             | 6.0V            | 11                    | 17                | 21                           | 25                            | ns       |
|                                     |                                        | C <sub>L</sub> = 150 pF                            | 6.0V            | 18                    | 26                | 32                           | 38                            | ns       |
| t <sub>PHL</sub> , t <sub>PLH</sub> | Maximum Propagation Delay (541)        | C <sub>L</sub> = 50 pF                             | 2.0V            | 58                    | 115               | 145                          | 171                           | ns       |
|                                     |                                        | C <sub>L</sub> = 150 pF                            | 2.0V            | 83                    | 165               | 208                          | 246                           | ns       |
|                                     |                                        | C <sub>L</sub> = 50 pF                             | 4.5V            | 14                    | 23                | 29                           | 34                            | ns       |
|                                     |                                        | C <sub>L</sub> = 150 pF                            | 4.5V            | 17                    | 33                | 42                           | 49                            | ns       |
|                                     |                                        | C <sub>L</sub> = 50 pF                             | 6.0V            | 11                    | 20                | 25                           | 29                            | ns       |
|                                     |                                        | C <sub>L</sub> = 150 pF                            | 6.0V            | 14                    | 28                | 35                           | 42                            | ns       |
| t <sub>PZH</sub> , t <sub>PZL</sub> | Maximum Output Enable Time             | R <sub>L</sub> = 1 kΩ                              |                 |                       |                   |                              |                               |          |
|                                     |                                        | C <sub>L</sub> = 50 pF                             | 2.0V            | 75                    | 150               | 189                          | 224                           | ns       |
|                                     |                                        | C <sub>L</sub> = 150 pF                            | 2.0V            | 100                   | 200               | 252                          | 298                           | ns       |
|                                     |                                        | C <sub>L</sub> = 50 pF                             | 4.5V            | 15                    | 30                | 38                           | 45                            | ns       |
|                                     |                                        | C <sub>L</sub> = 150 pF                            | 4.5V            | 30                    | 40                | 50                           | 60                            | ns       |
|                                     |                                        | C <sub>L</sub> = 50 pF                             | 6.0V            | 13                    | 26                | 32                           | 38                            | ns       |
| t <sub>PHZ</sub> , t <sub>PLZ</sub> | Maximum Output Disable Time            | C <sub>L</sub> = 150 pF                            | 6.0V            | 17                    | 34                | 43                           | 51                            | ns       |
|                                     |                                        | R <sub>L</sub> = 1 kΩ                              | 2.0V            | 75                    | 150               | 189                          | 224                           | ns       |
|                                     |                                        | C <sub>L</sub> = 50 pF                             | 4.5V            | 15                    | 30                | 38                           | 45                            | ns       |
| t <sub>THL</sub> , t <sub>TLH</sub> | Maximum Output Rise and Fall Time      |                                                    | 6.0V            | 13                    | 26                | 32                           | 38                            | ns       |
|                                     |                                        | C <sub>L</sub> = 50 pF                             | 2.0V            | 25                    | 60                | 75                           | 90                            | ns       |
|                                     |                                        |                                                    | 4.5V            | 7                     | 12                | 15                           | 18                            | ns       |
|                                     |                                        |                                                    | 6.0V            | 6                     | 10                | 13                           | 15                            | ns       |
| C <sub>PD</sub>                     | Power Dissipation Capacitance (Note 5) | $\overline{G} = V_{IH}$<br>$\overline{G} = V_{IL}$ |                 | 10<br>50              |                   |                              |                               | pF<br>pF |
| C <sub>IN</sub>                     | Maximum Input Capacitance              |                                                    |                 | 5                     | 10                | 10                           | 10                            | pF       |
| C <sub>OUT</sub>                    | Maximum Output Capacitance             |                                                    |                 | 15                    | 20                | 20                           | 20                            | pF       |

**Note 5:**  $C_{PD}$  determines the no load dynamic power consumption,  $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$ , and the no load dynamic current consumption,  $I_S = C_{PD} V_{CC} f + I_{CC}$ .




**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)



LAND PATTERN RECOMMENDATION




DIMENSIONS ARE IN MILLIMETERS



NOTES:

- CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.
- DIMENSIONS ARE IN MILLIMETERS.
- DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.



M20DRevB1





DETAIL A

**20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide  
Package Number M20D**

# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



DIMENSIONS ARE IN MILLIMETERS



DETAIL A


## NOTES:

- CONFORMS TO JEDEC REGISTRATION MO-153, VARIATION AC, REF NOTE 6, DATE 7/93.
- DIMENSIONS ARE IN MILLIMETERS.
- DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLDS FLASH, AND TIE BAR EXTRUSIONS.
- DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.

MTC20REV D1

20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide  
Package Number MTC20

# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide  
Package Number N20A

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[MM74HC541WM](#) [MM74HC541WMX](#) [MM74HC541SJ](#) [MM74HC541MTCX](#) [MM74HC541SJX](#) [MM74HC541MTC](#)  
[MM74HC541N](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)