

## 8.3kV E-Rated

Medium voltage fuses for feeder circuit, switchgear and transformer protection



### Description:

- E-Rated, current-limiting, medium voltage fuses for feeder circuit, switchgear and transformer protection.

### Features and benefits:

- Current-limiting E-Rated medium voltage fuses are defined by their melting time-current characteristic that permit their electrical interchangeability with other fuses of the same E Rating.
- E-Rated fuses must have a defined current response time specified by ANSI C37.46. E-Rated fuse of 100 amps and below must melt in 300 seconds at an RMS current within the range of 200% to 240% of the fuse's nameplate current rating. E-Rated fuses greater than 100 amps must melt in 600 seconds at an RMS current within the range of 220% to 264% of the fuse's nameplate current rating.
- E-Rated fuses are physically dimensioned for easy installation in existing hardware.
- Current-limiting fuses provide positive interruption even on low fault currents. The fuse limits the magnitude of electromechanical stresses in the protected apparatus.
- Constructions available in ferrule, bolt-on and clip lock, and specialty mount fuses for AMPGARD™ motor starters.
- Outdoor rating available on select catalog numbers (requires installation in a suitable enclosure).
- Open fuse indicator easily integrates into automation schemes and speeds troubleshooting by providing a positive visual indication of fuse operation.
- 50/60Hz operating frequency for worldwide application.
- Mountings are available in disconnect and non-disconnect versions with porcelain or glass polyester insulators.
- Live parts and end fittings available.

### Typical applications:

- Medium voltage transformer primary protection
- Medium voltage feeder circuit protection
- Medium voltage switches
- Medium voltage metal-enclosed switchgear



Powering Business Worldwide

## E-Rated medium voltage ferrule fuses

### Catalog symbols:

- 8CLE-E-D (10-25A)
- 8CLE-E (10-350A)
- 8HLE-E (10-350A)


### Ratings\*:

- Volts
  - 8.3kV
- Amps 10 to 350A
- Interrupting ratings — 50kA RMS Sym

\* See catalog number tables for voltages, ampacities and interrupting ratings by catalog number.

### Agency information:

E-Rated fuses meet the performance characteristics of ANSI C37.46



### Recommended fuse holders:

|                                          |                     |                  |                                  |               |            | Catalog number                                  |                           |                                     |                                |
|------------------------------------------|---------------------|------------------|----------------------------------|---------------|------------|-------------------------------------------------|---------------------------|-------------------------------------|--------------------------------|
| Amp rating                               | Fuse mounting type* | Voltage BIL (kV) | Approximate dimensions - in (mm) |               |            | Mounting (including live parts, end fittings)** |                           | Live parts (including end fittings) | End fittings (disconnect only) |
|                                          |                     |                  | Diameter A                       | Clip center B | Length C   | Porcelain insulator                             | Glass-polyester insulator |                                     |                                |
| CLE                                      |                     |                  |                                  |               |            |                                                 |                           |                                     |                                |
| 10E-D-25E-D<br>30E-175E<br>Single barrel | Non-disconnect      | 75               | 3.0 (76)                         | 14 (356)      | 17.9 (455) | 8CLE-PNM-D                                      | 8CLE-GNM-D                | CLE-NL-D                            | —                              |
|                                          | Disconnect†         | 75               |                                  |               |            | 8CLE-PDM-D                                      | 8CLE-GDM-D                | CLE-DL-D                            | CLE-DF-D                       |
| 15E-25E<br>Single Barrel                 | Non-disconnect      | 75               | 2.0 (51)                         | 14 (356)      | 15.5 (394) | 8CLE-PNM-C                                      | 8CLE-GNM-C                | CLE-NL-C                            | —                              |
|                                          | Disconnect†         | 75               |                                  |               |            | 8CLE-PDM-C                                      | 8CLE-GDM-C                | CLE-DL-C                            | CLE-DF-C                       |
| 200E-350E<br>Double barrel               | Non-disconnect      | 75               | 3.0 (76)                         | 14 (356)      | 17.9 (455) | 8CLE-PNM-E                                      | 8CLE-GNM-E                | CLE-NL-E                            | —                              |
|                                          | Disconnect          | 75               |                                  |               |            | 8CLE-PDM-E                                      | 8CLE-GDM-E                | CLE-DL-E                            | CLE-DF-E                       |
| HLE                                      |                     |                  |                                  |               |            |                                                 |                           |                                     |                                |
| 10E-175E<br>Single barrel                | Non-disconnect      | 75               | 3.0 (76)                         | 12 (305)      | 15.9 (404) | 8HLE-PNM-D                                      | 8HLE-GNM-D                | CLE-NL-D                            | —                              |
|                                          | Disconnect†         | 75               |                                  |               |            | 8HLE-PDM-D                                      | 8HLE-GDM-D                | CLE-DL-D                            | CLE-DF-D                       |
| 200E-350E<br>Double barrel               | Non-disconnect      | 75               | 3.0 (76)                         | 12 (305)      | 15.9 (404) | 8HLE-PNM-E                                      | 8HLE-GNM-E                | CLE-NL-E                            | —                              |
|                                          | Disconnect†         | 75               |                                  |               |            | 8HLE-PDM-E                                      | 8HLE-GDM-E                | CLE-DL-E                            | CLE-DF-E                       |

\* See page 4 for illustrations and dimensions

\*\* End fittings supplied only when required.

### Recommended fuseclips:

| Description                 | Fuse diameter - in (mm) | Figure | Clip dimensions - in (mm) |           |           |           |            |           |          | Catalog number |
|-----------------------------|-------------------------|--------|---------------------------|-----------|-----------|-----------|------------|-----------|----------|----------------|
|                             |                         |        | A                         | B         | C         | D         | E          | F         | G        |                |
| Enclosed fuseclip           | 2 (51)                  | 1      | 3.75 (95)                 | 1.98 (50) | 2.01 (51) | 1.19 (30) | 4.54 (115) | 1.51 (38) | 0.4 (10) | A3354710*      |
| Enclosed fuseclip           | 3 (76)                  | 1      | 4.14 (105)                | 2.45 (62) | 3.01 (76) | 1.19 (30) | 5.64 (143) | 1.51 (38) | 0.4 (10) | A3354730*      |
| Open fuseclip               | 3 (76)                  | 2      | See dimensions drawing    |           |           |           |            |           |          | 1A0065         |
| Spring loaded open fuseclip | 3 (76)                  | 3      | See dimensions drawing    |           |           |           |            |           |          | 9078A67G04     |

\*For single barrel applications only. Not sold in pairs.

Figure 1




Figure 2



Figure 3



**CLE and HLE type fuses**

| Amp rating                           | Dimensions - in (mm) |            |                | Interrupting<br>rating kA<br>(RMS Sym.) | Number of<br>barrels | Installation<br>location | Catalog<br>number |
|--------------------------------------|----------------------|------------|----------------|-----------------------------------------|----------------------|--------------------------|-------------------|
|                                      | Length A             | Diameter B | Clip centers C |                                         |                      |                          |                   |
| CLE Long construction (Westinghouse) |                      |            |                |                                         |                      |                          |                   |
| 10                                   | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-10E-D        |
| 15                                   | 15.5 (394)           | 2 (51)     | 14 (356)       | 50                                      | 1                    | Indoor                   | 8CLE-15E*         |
| 15                                   | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-15E-D        |
| 20                                   | 15.5 (394)           | 2 (51)     | 14 (356)       | 50                                      | 1                    | Indoor                   | 8CLE-20E*         |
| 20                                   | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-20E-D        |
| 25                                   | 15.5 (394)           | 2 (51)     | 14 (356)       | 50                                      | 1                    | Indoor                   | 8CLE-25E*         |
| 25                                   | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-25E-D        |
| 30                                   | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-30E          |
| 40                                   | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-40E          |
| 50                                   | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-50E          |
| 65                                   | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-65E          |
| 80                                   | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-80E          |
| 100                                  | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-100E         |
| 125                                  | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-125E         |
| 150                                  | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-150E         |
| 175                                  | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 8CLE-175E         |
| 200                                  | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 2                    | Indoor/outdoor           | 8CLE-200E         |
| 250                                  | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 2                    | Indoor/outdoor           | 8CLE-250E         |
| 300                                  | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 2                    | Indoor/outdoor           | 8CLE-300E         |
| 350                                  | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 2                    | Indoor/outdoor           | 8CLE-350E         |
| HLE Short construction               |                      |            |                |                                         |                      |                          |                   |
| 10                                   | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-10E          |
| 15                                   | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-15E          |
| 20                                   | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-20E          |
| 25                                   | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-25E          |
| 30                                   | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-30E          |
| 40                                   | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-40E          |
| 50                                   | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-50E          |
| 65                                   | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-65E          |
| 80                                   | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-80E          |
| 100                                  | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-100E         |
| 125                                  | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-125E         |
| 150                                  | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-150E         |
| 175                                  | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 1                    | Indoor/outdoor           | 8HLE-175E         |
| 200                                  | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 2                    | Indoor/outdoor           | 8HLE-200E         |
| 250                                  | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 2                    | Indoor/outdoor           | 8HLE-250E         |
| 300                                  | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 2                    | Indoor/outdoor           | 8HLE-300E         |
| 350                                  | 15.9 (404)           | 3 (76)     | 12 (305)       | 50                                      | 2                    | Indoor/outdoor           | 8HLE-350E         |

\* Fuses conform to dimensional standards established by Westinghouse.


**CLE and HLE type mountings - in (mm)**

| Catalog<br>number            | Hole centers  |           | Overall length | Hole Inset  | Hole centers | Contact<br>height | Overall height | BIL<br>kV |
|------------------------------|---------------|-----------|----------------|-------------|--------------|-------------------|----------------|-----------|
|                              | A             | B         |                |             |              |                   |                |           |
| Disconnect single barrel†    |               |           |                |             |              |                   |                |           |
| 8CLE-GDM-C                   | 15.24 (387.1) | 6 (152.4) | 28 (711.2)     | 0.75 (19)   | 1.75 (44.4)  | 7 (177.8)         | 12.25 (311.1)  | 75        |
| 8CLE-GDM-D                   | 15.24 (387.1) | 6 (152.4) | 25 (647.7)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 14.22 (361.2)  | 75        |
| 8CLE-PDM-C                   | 15.24 (387.1) | 6 (152.4) | 28 (711.2)     | 0.75 (19)   | 1.75 (44.4)  | 7 (177.8)         | 12.25 (311.1)  | 75        |
| 8CLE-PDM-C                   | 15.24 (387.1) | 6 (152.4) | 25 (647.7)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 14.22 (361.2)  | 75        |
| 8HLE-GDM-D                   | 16.25 (412.8) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 11.72 (297.7)  | 75        |
| 8HLE-PDM-D                   | 16.25 (412.8) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 11.72 (297.7)  | 75        |
| Disconnect double barrel†    |               |           |                |             |              |                   |                |           |
| 8CLE-GDM-E                   | 15.24 (387.1) | 6 (152.4) | 25 (647.7)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 17.78 (451.6)  | 75        |
| 8CLE-PDM-E                   | 15.24 (387.1) | 6 (152.4) | 25 (647.7)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 17.78 (451.6)  | 75        |
| 8HLE-GDM-E                   | 16.25 (412.8) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 17.78 (451.6)  | 75        |
| 8HLE-PDM-E                   | 16.25 (412.8) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 17.78 (451.6)  | 75        |
| Non-disconnect single barrel |               |           |                |             |              |                   |                |           |
| 8CLE-GNM-C                   | 15.25 (387.3) | 6 (152.4) | 24.5 (622.3)   | 0.75 (19)   | 1.75 (44.4)  | 7 (177.8)         | 9.75 (247.6)   | 75        |
| 8CLE-PNM-C                   | 15.25 (387.3) | 6 (152.4) | 24.5 (622.3)   | 0.75 (19)   | 1.75 (44.4)  | 7 (177.8)         | 9.75 (247.6)   | 75        |
| 8CLE-GNM-D                   | 15.25 (387.3) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 11.29 (286.7)  | 75        |
| 8CLE-PNM-D                   | 15.25 (387.3) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 11.29 (286.7)  | 75        |
| 8HLE-GNM-D                   | 16.25 (412.7) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 8.79 (223.3)   | 75        |
| 8HLE-PNM-D                   | 16.25 (412.7) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 8.79 (223.3)   | 75        |
| Non-disconnect double barrel |               |           |                |             |              |                   |                |           |
| 8CLE-GNM-E                   | 15.24 (387.1) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 14.98 (380.5)  | 75        |
| 8CLE-PNM-E                   | 15.24 (387.1) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 14.98 (380.5)  | 75        |
| 8HLE-GNM-E                   | 16.25 (412.7) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 14.98 (380.5)  | 75        |
| 8HLE-PNM-E                   | 16.25 (412.7) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 7 (177.8)         | 14.98 (380.5)  | 75        |

**CLE and HLE type disconnect mounting†**



**CLE and HLE type non-disconnect mounting**



† Disconnect mountings provide a means for fuse extraction only. Do not use a disconnect mounting for load switching or fuse removal while energized.

## E-Rated medium voltage specialty mount fuses

### Catalog symbols:

- 8AHLE\_E (special dimension fuses for use with 7.2kV rated, 800 amp AMPGARD motor starting assemblies)
- 8BHLE\_E (bolt-on version)
- 8HCL\_E (clip-lock version)

### Ratings\*:

- Volts
  - 8.3kV
- Amps
  - 10 to 350A
- Interrupting ratings
  - 50kA RMS Sym

\* See catalog number tables for voltages, ampacities and interrupting ratings by catalog number.


### Agency information:

- E-Rated fuses meet the performance characteristics of ANSI C37.46


### Recommended live parts for clip-lock fuses

- Catalog number HCL-NL-1

### Dimensions for HCL - in (mm)



### Dimensions for BHLE - in (mm)



**AHLE type fuses (special dimension fuses for use with 7.2kV rated, 800 amp AMPGARD motor starting assemblies)**

| Amp rating | Interrupting rating kA (RMS Sym.) | Number of barrels | Catalog number |
|------------|-----------------------------------|-------------------|----------------|
| 10         | 50                                | 1                 | 8AHLE-10E      |
| 15         | 50                                | 1                 | 8AHLE-15E      |
| 20         | 50                                | 1                 | 8AHLE-20E      |
| 25         | 50                                | 1                 | 8AHLE-25E      |
| 30         | 50                                | 1                 | 8AHLE-30E      |
| 40         | 50                                | 1                 | 8AHLE-40E      |
| 50         | 50                                | 1                 | 8AHLE-50E      |
| 65         | 50                                | 1                 | 8AHLE-65E      |
| 80         | 50                                | 1                 | 8AHLE-80E      |
| 100        | 50                                | 1                 | 8AHLE-100E     |
| 125        | 50                                | 1                 | 8AHLE-125E     |
| 150        | 50                                | 1                 | 8AHLE-150E     |
| 175        | 50                                | 1                 | 8AHLE-175E     |
| 200        | 50                                | 2                 | 8AHLE-200E     |
| 250        | 50                                | 2                 | 8AHLE-250E     |
| 300        | 50                                | 2                 | 8AHLE-300E     |
| 350        | 50                                | 2                 | 8AHLE-350E     |

**BHLE bolt-on versions**

| Amp rating | Dimensions - in (mm) |          |               | Interrupting rating kA (RMS Sym.) | Number of barrels | Installation location | Catalog number |
|------------|----------------------|----------|---------------|-----------------------------------|-------------------|-----------------------|----------------|
|            | Overall length       | Diameter | Hole centers  |                                   |                   |                       |                |
| 10         | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-10E      |
| 15         | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-15E      |
| 20         | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-20E      |
| 25         | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-25E      |
| 30         | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-30E      |
| 40         | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-40E      |
| 50         | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-50E      |
| 65         | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-65E      |
| 80         | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-80E      |
| 100        | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-100E     |
| 125        | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-125E     |
| 150        | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-150E     |
| 175        | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 1                 | Indoor                | 8BHLE-175E     |
| 200        | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 2                 | Indoor                | 8BHLE-200E     |
| 250        | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 2                 | Indoor                | 8BHLE-250E     |
| 300        | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 2                 | Indoor                | 8BHLE-300E     |
| 350        | 19.25 (488.9)        | 3 (76.2) | 17.88 (454.2) | 50                                | 2                 | Indoor                | 8BHLE-350E     |

**HCL clip lock versions**

| Amp rating | Dimensions - in (mm) |          |              | Interrupting rating kA (RMS Sym.) | Number of barrels | Installation location | Catalog number |
|------------|----------------------|----------|--------------|-----------------------------------|-------------------|-----------------------|----------------|
|            | Overall length       | Diameter | Hole centers |                                   |                   |                       |                |
| 65         | 22.5 (571.5)         | 3 (76.2) | N/A          | 50                                | 1                 | Indoor/outdoor        | 8HCL-65E       |
| 80         | 22.5 (571.5)         | 3 (76.2) | N/A          | 50                                | 1                 | Indoor/outdoor        | 8HCL-80E       |
| 100        | 22.5 (571.5)         | 3 (76.2) | N/A          | 50                                | 1                 | Indoor/outdoor        | 8HCL-100E      |
| 125        | 22.5 (571.5)         | 3 (76.2) | N/A          | 50                                | 1                 | Indoor/outdoor        | 8HCL-125E      |
| 150        | 22.5 (571.5)         | 3 (76.2) | N/A          | 50                                | 1                 | Indoor/outdoor        | 8HCL-150E      |
| 175        | 22.5 (571.5)         | 3 (76.2) | N/A          | 50                                | 1                 | Indoor/outdoor        | 8HCL-175E      |
| 200        | 22.5 (571.5)         | 3 (76.2) | N/A          | 50                                | 2                 | Indoor/outdoor        | 8HCL-200E      |
| 250        | 22.5 (571.5)         | 3 (76.2) | N/A          | 50                                | 2                 | Indoor/outdoor        | 8HCL-250E      |
| 300        | 22.5 (571.5)         | 3 (76.2) | N/A          | 50                                | 2                 | Indoor/outdoor        | 8HCL-300E      |
| 350        | 22.5 (571.5)         | 3 (76.2) | N/A          | 50                                | 2                 | Indoor/outdoor        | 8HCL-350E      |

8.3kV time-current curves — minimum melt for 8CLE-\_E and 8CLE-\_D



8CLE-\_

Curve 70548501  
April 16, 1999  
Reference # 563532

Curve 70546201  
April 1999  
Reference # 705462

Curve 70546401  
April 1999  
Reference # 705464

8.3kV time-current curves — total clear for 8CLE-<sub>E</sub> and 8CLE-<sub>-D</sub>



8CLE-<sub>-</sub>

|                    |                    |                    |
|--------------------|--------------------|--------------------|
| Curve 70548601     | Curve 70546301     | Curve 70546501     |
| April 16, 1999     | April 1999         | April 1999         |
| Reference # 563533 | Reference # 705463 | Reference # 705465 |

8.3kV peak let-through for 8CLE-\_E and 8CLE-\_-D




8CLE-\_

Curve 70548801  
September 1999  
Reference # 705488

Curve 70547301  
April 1999  
Reference # 705473

8.3kV Time-current curves — minimum melt for 8HLE- \_E, 8AHLE- \_E and 8BHLE- \_E



|                                                                                    |                                                        |                                                        |
|------------------------------------------------------------------------------------|--------------------------------------------------------|--------------------------------------------------------|
| 8HLE-_, 8BHLE-_, 8AHLE-_<br>Curve 70548507<br>April 16, 1999<br>Reference # 563532 | <br>Curve 70546203<br>April 1999<br>Reference # 705462 | <br>Curve 70546403<br>April 1999<br>Reference # 705464 |
|------------------------------------------------------------------------------------|--------------------------------------------------------|--------------------------------------------------------|

8.3kV Time-current curves — total clear for 8HLE- \_E, 8AHLE- \_E and 8BHLE- \_E



Available current in amperes

8HLE-\_, 8BHLE-\_, 8AHLE- \_

Curve 70548607

April 16, 1999

Reference # 563533

Curve 70546303

April 1999


Reference # 705463

Curve 70546503

April 1999

Reference # 705465

8.3kV peak let-through for 8HLE- \_E, 8AHLE- \_E and 8BHLE- \_E



8HLE-\_, 8BHLE-\_, 8AHLE- \_

Curve 70548804      Curve 70547201  
September 1999      April 1999  
Reference # 705488      Reference # 705472

The only controlled copy of this data sheet is the electronic read-only version located on the Eaton network drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

**Eaton**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
Eaton.com

Bussmann Division  
114 Old State Road  
Ellisville, MO 63021  
United States  
Eaton.com/bussmannseries



© 2015 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 10352 – BU-SB15152  
December 2015

Eaton, Bussmann and AMPGARD are valuable trademarks of Eaton in the US and other countries. You are not permitted to use the Eaton trademarks without prior written consent of Eaton.

For Eaton's Bussmann series product information, call **1-855-287-7626** or visit: **Eaton.com/bussmannseries**

Follow us on social media to get the latest product and support information.



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)