



Standard Recovery Diodes, 165 A to 230 A (INT-A-PAK Power Modules)



INT-A-PAK

FEATURES

- High voltage
- Electrically isolated by DBC ceramic (Al_2O_3)
- 3500 V_{RMS} isolating voltage
- Industrial standard package
- High surge capability
- Glass passivated chips
- Modules uses high voltage power diodes in four basic configurations
- Simple mounting
- UL approved file E78996 
- Designed and qualified for multiple level
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT

| PRODUCT SUMMARY | |
|-----------------|------------------------------------------------------------------------------------------------|
| $I_{F(AV)}$ | 165 A to 230 A |
| Type | Modules - Diode, High Voltage |
| Package | INT-A-PAK |
| Circuit | Single diode, Two diodes common cathode, Two diodes common cathode, Two diodes doubler circuit |

APPLICATIONS

- DC motor control and drives
- Battery chargers
- Welders
- Power converters

| MAJOR RATINGS AND CHARACTERISTICS | | | | | |
|-----------------------------------|-----------------|-------------|-----------|-----------|----------------|
| SYMBOL | CHARACTERISTICS | VSK.166.. | VSK.196.. | VSK.236.. | UNITS |
| $I_{F(AV)}$ | | 165 | 195 | 230 | A |
| | T_C | 100 | 100 | 100 | $^{\circ}C$ |
| $I_{F(RMS)}$ | | 260 | 305 | 360 | A |
| I_{FSM} | 50 Hz | 4000 | 4750 | 5500 | |
| | 60 Hz | 4200 | 4980 | 5765 | |
| I^2t | 50 Hz | 80 | 113 | 151 | kA^2s |
| | 60 Hz | 73 | 103 | 138 | |
| $I^2\sqrt{t}$ | | 798 | 1130 | 1516 | $kA^2\sqrt{s}$ |
| V_{RRM} | | 400 to 1600 | | | V |
| T_J | Range | -40 to +150 | | | $^{\circ}C$ |

ELECTRICAL SPECIFICATIONS

| VOLTAGE RATINGS | | | | |
|----------------------------------------|--------------|----------------------------------------------------------|--------------------------------------------------------------|------------------------------------|
| TYPE NUMBER | VOLTAGE CODE | V_{RRM} , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE V | V_{RSM} , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V | I_{RRM} AT 150 $^{\circ}C$ mA |
| VS-VSK.166 VS-VSK.196 VS-VSK.236 | 04 | 400 | 500 | 20 |
| | 08 | 800 | 900 | |
| | 12 | 1200 | 1300 | |
| | 14 | 1400 | 1500 | |
| | 16 | 1600 | 1700 | |



| FORWARD CONDUCTION | | | | | | | |
|----------------------------------------------------------------|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|---------|---------|---------|--------------------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VSK.166 | VSK.196 | VSK.236 | UNITS |
| Maximum average on-state current at case temperature | $I_{F(AV)}$ | 180° conduction, half sine wave | | 165 | 195 | 230 | A |
| | | | | 100 | 100 | 100 | °C |
| Maximum RMS on-state current | $I_{F(RMS)}$ | | | 260 | 305 | 360 | A |
| Maximum peak, one-cycle on-state, non-repetitive surge current | I_{FSM} | t = 10 ms | No voltage reapplied | 4000 | 4750 | 5500 | |
| | | t = 8.3 ms | No voltage reapplied | 4200 | 4980 | 5765 | |
| | | t = 10 ms | 100 % V_{RRM} reapplied | 3350 | 4000 | 4630 | |
| | | t = 8.3 ms | 100 % V_{RRM} reapplied | 3500 | 4200 | 4850 | |
| Maximum I^2t for fusing | I^2t | t = 10 ms | No voltage reapplied | 80 | 113 | 151 | kA ² s |
| | | t = 8.3 ms | No voltage reapplied | 73 | 103 | 138 | |
| | | t = 10 ms | 100 % V_{RRM} reapplied | 56 | 80 | 107 | |
| | | t = 8.3 ms | 100 % V_{RRM} reapplied | 52 | 73 | 98 | |
| Maximum $I^2\sqrt{t}$ for fusing | $I^2\sqrt{t}$ | t = 0.1 ms to 10 ms, no voltage reapplied | | 798 | 1130 | 1516 | kA ² √s |
| Low level value of threshold voltage | $V_{F(TO)1}$ | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, T_J maximum | | 0.73 | 0.69 | 0.7 | V |
| High level value of threshold voltage | $V_{F(TO)2}$ | $(I > \pi \times I_{F(AV)})$, T_J maximum | | 0.88 | 0.78 | 0.83 | |
| Low level value on-state slope resistance | r_{t1} | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, T_J maximum | | 1.5 | 1.3 | 1.2 | mΩ |
| High level value on-state | r_{t2} | $(I > \pi \times I_{F(AV)})$, T_J maximum | | 1.26 | 1.2 | 1.07 | |
| Maximum forward voltage drop | V_{FM} | $I_{FM} = \pi \times I_{F(AV)}$, $T_J = 25\text{ °C}$, 180° conduction Average power = $V_{F(TO)} \times I_{F(AV)} + r_f \times (I_{F(RMS)})^2$ | | 1.43 | 1.38 | 1.46 | V |

| BLOCKING | | | | | | | |
|----------------------------------------------------|-----------|--------------------------------------------------------|--|---------|---------|---------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | VSK.166 | VSK.196 | VSK.236 | UNITS |
| Maximum peak reverse and off-state leakage current | I_{RRM} | $T_J = 150\text{ °C}$ | | 20 | | | mA |
| RMS insulation voltage | V_{INS} | 50 Hz, circuit to base, all terminals shorted, t = 1 s | | 3500 | | | V |

| THERMAL AND MECHANICAL SPECIFICATIONS | | | | | | |
|-----------------------------------------------------------|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------|---------|-------|
| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | | | UNITS |
| | | | VSK.166 | VSK.196 | VSK.236 | |
| Maximum junction operating and storage temperature range | T_J, T_{Stg} | -40 to +150 | | | °C | |
| Maximum thermal resistance, junction to case per junction | R_{thJC} | DC operation | 0.2 | 0.16 | 0.14 | K/W |
| Maximum thermal resistance, case to heatsink per module | R_{thCS} | Mounting surface smooth, flat and greased | 0.05 | | | |
| Mounting torque ± 10 % | IAP to heatsink busbar to IAP | A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound. Lubricated threads. | 4 to 6 | | | Nm |
| Approximate weight | | | 200 | | | g |
| | | | 7.1 | | | oz. |
| Case style | | INT-A-PAK | | | | |



| ΔR CONDUCTION PER JUNCTION | | | | | | | | | | | |
|-----------------------------------|-------------------------------------------------|-------|-------|-------|-------|--------------------------------------------------|-------|-------|-------|-------|-------|
| DEVICES | SINUSOIDAL CONDUCTION AT T _J MAXIMUM | | | | | RECTANGULAR CONDUCTION AT T _J MAXIMUM | | | | | UNITS |
| | 180° | 120° | 90° | 60° | 30° | 180° | 120° | 90° | 60° | 30° | |
| VSK.166 | 0.025 | 0.03 | 0.038 | 0.055 | 0.089 | 0.018 | 0.031 | 0.041 | 0.057 | 0.089 | K/W |
| VSK.196 | 0.016 | 0.019 | 0.024 | 0.034 | 0.053 | 0.012 | 0.02 | 0.026 | 0.035 | 0.054 | |
| VSK.236 | 0.009 | 0.010 | 0.014 | 0.018 | 0.025 | 0.008 | 0.012 | 0.015 | 0.019 | 0.025 | |

Note

- Table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 3 - On-State Power Loss Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current



Fig. 6 - Maximum Non-Repetitive Surge Current



Fig. 7 - On-State Power Loss Characteristics




Fig. 8 - On-State Power Loss Characteristics






Fig. 9 - On-State Power Loss Characteristics



Fig. 10 - Current Ratings Characteristics

Fig. 12 - On-State Power Loss Characteristics



Fig. 11 - Current Ratings Characteristics

Fig. 13 - On-State Power Loss Characteristics



Fig. 14 - Maximum Non-Repetitive Surge Current



Fig. 15 - Maximum Non-Repetitive Surge Current



Fig. 16 - On-State Power Loss Characteristics





Fig. 17 - On-State Power Loss Characteristics






Fig. 18 - On-State Power Loss Characteristics



Fig. 19 - Current Ratings Characteristics




Fig. 21 - On-State Power Loss Characteristics



Fig. 20 - Current Ratings Characteristics




Fig. 22 - On-State Power Loss Characteristics



Fig. 23 - Maximum Non-Repetitive Surge Current



Fig. 24 - Maximum Non-Repetitive Surge Current



Fig. 25 - On-State Power Loss Characteristics



Fig. 26 - On-State Power Loss Characteristics







Fig. 27 - On-State Power Loss Characteristics




Fig. 28 - On-State Voltage Drop Characteristics




Fig. 30 - On-State Voltage Drop Characteristics




Fig. 29 - On-State Voltage Drop Characteristics




Fig. 31 - Thermal Impedance $Z_{\theta JC}$ Characteristics



Fig. 32 - Thermal Impedance Z_{thJC} Characteristics



Fig. 33 - Thermal Impedance Z_{thJC} Characteristics

ORDERING INFORMATION TABLE

| | | | | | |
|-------------|--------------|-----------|--------------------------------|-----------|------------|
| Device code | VS-VS | KD | 236 | 16 | PbF |
| | ① | ② | ③ | ④ | ⑤ |
| | 1 | - | Vishay Semiconductors product | | |
| | 2 | - | Circuit configuration | | |
| | 3 | - | Current rating: $I_{F(AV)}$ | | |
| | 4 | - | Voltage code x 100 = V_{RRM} | | |
| | 5 | - | PbF = Lead (Pb)-free | | |

Note

- To order the optional hardware go to www.vishay.com/doc?95172



| CIRCUIT CONFIGURATION | | |
|----------------------------|----------------------------|------------------------|
| CIRCUIT DESCRIPTION | CIRCUIT CONFIGURATION CODE | CIRCUIT DRAWING |
| Two diodes doubler circuit | D | <p>VSKD...</p> |
| Two diodes common cathodes | C | <p>VS KC...</p> |
| Two diodes common anodes | J | <p>VSKJ...</p> |
| Single diode | E | <p>VS KE...</p> |

| LINKS TO RELATED DOCUMENTS | |
|----------------------------|------------------------------------------------------------------------|
| Dimensions | www.vishay.com/doc?95254 |

INT-A-PAK DBC

DIMENSIONS in millimeters (inches)





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru