

9116 Coax - CATV Cable

For more Information
please call

1-800-Belden1



Description:

Series 6, 18 AWG solid .040" bare copper-covered steel conductor, gas-injected foam polyethylene insulation, Duobond® II + aluminum braid shield (60% coverage), PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

| # Coax | AWG | Stranding | Conductor Material | Dia. (in.) |
|--------|-----|-----------|----------------------------------|------------|
| 1 | 18 | Solid | BCCS - Bare Copper Covered Steel | .040 |

Total Number of Conductors: 1

Insulation

Insulation Material:

| Insulation Material | Dia. (in.) |
|--------------------------------------|------------|
| Gas-injected FPE - Foam Polyethylene | .180 |

Outer Shield

Outer Shield Material:

| Layer # | Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|---------|-------------------------|-------|---|--------------|
| 1 | Bonded Duofoil® | Tape | Bonded Aluminum Foil-Polyester Tape-Aluminum Foil | 100 |
| 2 | | Braid | AL - Aluminum | 60 |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Overall Cable

Overall Nominal Diameter: 0.270 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +80°C

Bulk Cable Weight: 27 lbs/1000 ft.

Max. Recommended Pulling Tension: 126 lbs.

Min. Bend Radius/Minor Axis: 2.750 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CATV, CM

CEC/C(UL) Specification: CM

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Series Type: Series 6

Flame Test

UL Flame Test: UL1581 Vertical Flame and FT-1 Flame Test

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 9116P

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

| Impedance (Ohm) | Tolerance (Ohms) |
|-----------------|------------------|
| 75 | ± 3 |

Nom. Inductance:

| Inductance (µH/ft) |
|--------------------|
| .097 |

Nom. Capacitance Conductor to Shield:

| Capacitance (pF/ft) |
|---------------------|
| 16.2 |

Nominal Velocity of Propagation:

| VP (%) |
|--------|
| 83 |

Nominal Delay:

| Delay (ns/ft) |
|---------------|
| 1.2 |

Nom. Conductor DC Resistance:

| DCR @ 20°C (Ohm/1000 ft) |
|--------------------------|
| 28 |

Nominal Outer Shield DC Resistance:

| DCR @ 20°C (Ohm/1000 ft) |
|--------------------------|
| 9 |

Max. Attenuation:

| Freq. (MHz) | Attenuation (dB/100 ft.) |
|-------------|--------------------------|
| 5 | 0.67 |
| 55 | 1.60 |
| 211 | 2.87 |
| 270 | 3.24 |
| 300 | 3.43 |
| 350 | 3.72 |
| 400 | 4.00 |
| 450 | 4.26 |
| 550 | 4.71 |
| 750 | 5.59 |
| 870 | 6.00 |
| 1000 | 6.54 |

Max. Operating Voltage - UL:

| Voltage |
|-----------|
| 350 V RMS |

Minimum Structural Return Loss:

| Description | Freq. (MHz) | Start Freq. (MHz) | Stop Freq. (MHz) | Min. SRL (dB) |
|-------------|-------------|-------------------|------------------|---------------|
| | | 5 | 1000 | 20 |

Sweep Test

Sweep Testing: 5 MHz - 1 GHz

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|----------|-------------|----------------|-------|-----------------------|
| 9116 Q5HU1000 | 1,000 FT | 29.000 LB | WHITE, NEUTRAL | | #18 GIFHDLDPPE SH PVC |
| 9116 Q5H1000 | 1,000 FT | 30.000 LB | WHITE, NEUTRAL | | #18 GIFHDLDPPE SH PVC |
| 9116 009U1000 | 1,000 FT | 29.000 LB | WHITE | | #18 GIFHDLDPPE SH PVC |
| 9116 0091000 | 1,000 FT | 30.000 LB | WHITE | | #18 GIFHDLDPPE SH PVC |
| 9116 009500 | 500 FT | 15.500 LB | WHITE | | #18 GIFHDLDPPE SH PVC |
| 9116 010S700 | 700 FT | 18.900 LB | BLACK | | #18 GIFHDLDPPE SH PVC |
| 9116 010U1000 | 1,000 FT | 29.000 LB | BLACK | | #18 GIFHDLDPPE SH PVC |
| 9116 010U500 | 500 FT | 15.000 LB | BLACK | | #18 GIFHDLDPPE SH PVC |
| 9116 0101000 | 1,000 FT | 30.000 LB | BLACK | C | #18 GIFHDLDPPE SH PVC |
| 9116 010500 | 500 FT | 15.500 LB | BLACK | | #18 GIFHDLDPPE SH PVC |
| 9116 290U1000 | 1,000 FT | 29.000 LB | BEIGE, LIGHT | | #18 GIFHDLDPPE SH PVC |

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 08-08-2012

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru