



## **CLIPLINE complete**

PT – Push-in connection



# PHOENIX CONTACT – worldwide in dialog with customers and partners

Phoenix Contact is a global market leader in the field of electrical engineering, electronics, and automation. Founded in 1923, the family-owned company now employs around 12,800 people worldwide. A sales network with over 50 sales subsidiaries and more than 30 additional sales partners guarantees customer proximity directly on site, anywhere in the world.

Our range of services consists of products surrounding various different electrotechnical applications. This includes numerous connection technologies for device manufacturers and machine building, components for modern control cabinets, and tailor-made solutions for many applications and industries, such as automobile production, wind energy, photovoltaics, the process industry or applications in the field of water supply, power distribution, and transportation infrastructure.



## Global player with personal customer contact

Company independence is an integral part of our corporate policy. Phoenix Contact therefore relies on in-house competence and expertise in many respects: the design and development departments constantly come up with innovative product ideas, developing special solutions to meet customer requirements. Numerous patents emphasize the fact that many of Phoenix Contact's products have been developed in-house.



PT push-in connection terminal blocks have been developed for direct conductor connection. This means that solid conductors or conductors with ferrules can be inserted directly into the terminal block without tools.

The special spring profile enables the easy insertion of conductors with ferrules from 0.25 mm<sup>2</sup>. The contact spring is opened automatically when the conductor is pushed in and thereby provides the required pressure force against the current bar. Both for releasing conductors and connecting small cross sections from 0.14 mm<sup>2</sup>, the spring is opened by means of the actuation lever – easily and without direct contact with live parts. The actuation lever can be operated with all standard screwdrivers.

The PT connection terminal blocks are subjected to tests which go beyond the basic modular terminal block standard, enabling them to be used in all sectors of industry, such as energy supply, transportation technology, process engineering, in particular the chemical and petrochemical industry or shipbuilding.

### Push-in Technology

Designed by PHOENIX CONTACT



### Table of contents

|                                                                                           |           |
|-------------------------------------------------------------------------------------------|-----------|
| <b>Push-in connection technology –</b><br>Easy to use –<br>high-performance connection    | <b>4</b>  |
| <b>Simply consistent –</b><br>PT modular terminal blocks                                  | <b>6</b>  |
| <b>Quick, easy and reliable –</b><br>PTPOWER high-current terminal blocks                 | <b>16</b> |
| <b>Compact and flexible –</b><br>PTIO sensor/actuator terminal blocks                     | <b>20</b> |
| <b>Compact and functional –</b><br>PT disconnect and knife disconnect terminal blocks     | <b>22</b> |
| <b>Three-dimensional marshalling –</b><br>PT four-level terminal blocks                   | <b>28</b> |
| <b>Simple, reliable and intuitive marshalling –</b><br>PTRV marshalling terminals         | <b>30</b> |
| PTMC marshalling patchboards                                                              | <b>34</b> |
| <b>Flexible for all transformer test wiring –</b><br>PTME test disconnect terminal blocks | <b>40</b> |
| FAME plug-in test system                                                                  | <b>46</b> |
| <b>Modular connection solutions –</b><br>PT plug-in modular terminal blocks               | <b>48</b> |
| <b>CLIP PROJECT –</b><br>Planning and marking software                                    | <b>66</b> |
| <b>Push-in connection technology –</b><br>Consistent from the field to the controller     | <b>68</b> |
| <b>Push-in connection technology –</b><br>Reliable and can be used worldwide              | <b>70</b> |

# Push-in connection technology

## Easy to use – high-performance connection



### Push-in Technology

Designed by PHOENIX CONTACT

The reduction in insertion forces of up to 50% permits easy and direct insertion of solid and stranded conductors with ferrules of cross section  $0.25 \text{ mm}^2$  or greater.

The integrated lever enables you to release connected conductors using any type of tool – easily and without direct contact with live parts. Stranded conductors of cross section  $0.14 \text{ mm}^2$  and above can be connected without ferrules using the actuation lever.

High-quality hard-faced copper alloys ensure the lowest contact resistances and, as a result, maximum current transfer.

The special contact spring is manufactured from high-quality spring steel. This ensures maximum contact and conductor pull-out forces with vibration-resistant and gas-tight contacting.



The push-in connection technology is tested for maximum vibration and shock resistance. The test runs through a frequency range of 5 Hz to 150 Hz at a speed of up to  $5.72 \text{ m/s}^2$ . The test objects are tested on each of the three axes (x, y, z). No contact interruptions  $> 1 \mu\text{s}$  are permitted during the test. Push-in connection technology meets these high requirements in terms of vibration and shock loads up to 350 g.



C u EAC J I



X

m





CB  
scheme

X



Push-in connection technology is subjected to tests which go beyond the basic standard, enabling them to be used in all sectors of industry, such as energy supply, transportation technology, process engineering, and the chemical, petrochemical, and shipbuilding industries in particular.



Correctly wired modular conductor contact points must offer a high degree of mechanical safety. The new push-in connection technology, requiring up to 50% lower conductor insertion forces, achieves 180 N in the conductor pull-out test of a 2.5 mm<sup>2</sup> terminal block with a 1.0 mm<sup>2</sup> conductor, for example, where only 35 N is required according to the standard.


The key role of the metal parts of electrical connections becomes particularly apparent in aggressive environments. A test method describes a corrosion test in condensation climates with an atmosphere containing sulfur dioxide and salt mist. The push-in connection technology creates high-grade, gas-tight connections that cannot be impaired even by aggressive substances.

Conductor contact points must, in practice, also be capable of resisting short-circuit currents until the relevant safety equipment cuts off the current without sustaining any damage. This can take up to several tenths of a second. Maximum contact reliability, even under extreme overload – illustrated with a plug-in push-in modular terminal block.


# Simply consistent – PT modular terminal blocks with push-in connection

The consistent function shaft in all push-in modular terminal blocks gives you a high degree of flexibility and simplifies project planning and configuration of the control cabinet. All terminal blocks can be freely combined with one another.


The CLIPLINE complete system accessories, such as jumpering, marking, and testing accessories, are standardized and greatly reduce your logistics costs.



Extremely small, but they can be labeled and bridged just like their larger counterparts.




To allow fast and individual potential distribution, the terminal blocks have two function shafts. They are arranged in a line. This makes it possible to implement all the tasks of potential bridging within a short time.




Bridging between non-adjacent terminal blocks is established by removing individual contact tabs from the standard bridge. This means that two potentials can be routed in parallel through one terminal strip.


Each terminal point supports clear, large-surface labeling to ensure the best possible overview of the control cabinet.



The reducing bridge allows terminal blocks with different nominal cross sections to be connected with ease. It can be used to quickly create power blocks, e.g., a 10 mm<sup>2</sup> terminal block with a 2.5 mm<sup>2</sup> or 4 mm<sup>2</sup> terminal block, regardless of the connection technology.



All disconnect terminal blocks in the CLIPLINE complete system have a standardized disconnect zone. The disconnect zone accommodates various plugs such as fuse plugs, component connectors, and isolating plugs.



All test plugs in the system make contact in the freely accessible function shaft. For individual measuring lines, a 2.3 mm diameter test plug is available. More complex testing tasks can be implemented using alignable test plugs. Test adapters can be assembled individually and are perfectly suited for use in test laboratories.

## Two-conductor terminal blocks

|                                                   |           |                              |                                                                                   |                               |                                                                                    |                               |                                                                                     |                               |
|---------------------------------------------------|-----------|------------------------------|-----------------------------------------------------------------------------------|-------------------------------|------------------------------------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------------------|-------------------------------|
|                                                   |           |                              |  |                               |  |                               |  |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow | PT 1,5/S<br>PT 1,5/S BU<br>PT 1,5/S-PE                                            | 3208100<br>3208126<br>3208139 | PT 2,5<br>PT 2,5 BU<br>PT 2,5-PE                                                   | 3209510<br>3209523<br>3209536 | PT 4<br>PT 4 BU<br>PT 4-PE                                                          | 3211757<br>3211760<br>3211766 |
| Width / Length / Height                           |           | [mm]                         | 3.5 / 45 / 32                                                                     |                               | 5.2 / 48.5 / 36.5                                                                  |                               | 6.2 / 56 / 36.5                                                                     |                               |
| Current / Voltage // UL                           |           | [A] / [V]                    | 17.5 / 500 // 15 / 600                                                            |                               | 30 / 800 // 20 / 600                                                               |                               | 38 / 800 // 30 / 600                                                                |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -       | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                      |                               | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                         |                               | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                              |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]           | 0.14 - 1.5 / 0.14 - 1                                                             |                               | 0.14 - 2.5                                                                         |                               | 0.25 - 4                                                                            |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]           | 0.34 - 1.5 / 0.25 - 1.5                                                           |                               | 0.34 - 2.5 / 0.34 - 4                                                              |                               | 0.5 - 4 / 0.5 - 6                                                                   |                               |
|                                                   |           |                              |  |                               |  |                               |  |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow | PT 6<br>PT 6 BU<br>PT 6-PE                                                        | 3211813<br>3211819<br>3211822 | PT 10<br>PT 10 BU<br>PT 10-PE                                                      | 3212120<br>3212123<br>3212131 | PT 16 N<br>PT 16 N BU<br>PT 16 N-PE                                                 | 3212138<br>3212142<br>3212147 |
| Width / Length / Height                           |           | [mm]                         | 8.2 / 57.7 / 43.5                                                                 |                               | 10.2 / 67.7 / 50.5                                                                 |                               | 12.2 / 75.4 / 52.6                                                                  |                               |
| Current / Voltage // UL                           |           | [A] / [V]                    | 41 / 1000 // 40 / 600                                                             |                               | 57 / 1000 // 60 / 600                                                              |                               | 76 / 1000 // -                                                                      |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -       | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 8                                             |                               | 0.5 - 16 / 20 - 6 // 0.5 - 10 / 20 - 6                                             |                               | 0.5 - 25 / 20 - 4 // 0.5 - 16 / 20 - 6                                              |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]           | 0.5 - 6                                                                           |                               | 0.5 - 10                                                                           |                               | 0.5 - 16                                                                            |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]           | 1 - 6 / 1 - 10                                                                    |                               | 2.5 - 10 / 1 - 16                                                                  |                               | 2.5 - 16 / 2.5 - 25                                                                 |                               |

## Three-conductor terminal blocks

|                                                   |           |                              |                                                                                     |                               |                                                                                      |                               |                                                                                       |                               |
|---------------------------------------------------|-----------|------------------------------|-------------------------------------------------------------------------------------|-------------------------------|--------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|-------------------------------|
|                                                   |           |                              |  |                               |  |                               |  |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow | PT 1,5/S-TWIN<br>PT 1,5/S-TWIN BU<br>PT 1,5/S-TWIN-PE                               | 3208155<br>3208168<br>3208171 | PT 2,5-TWIN<br>PT 2,5-TWIN BU<br>PT 2,5-TWIN-PE                                      | 3209549<br>3209552<br>3209565 | PT 4-TWIN<br>PT 4-TWIN BU<br>PT 4-TWIN-PE                                             | 3211771<br>3211775<br>3211780 |
| Width / Length / Height                           |           | [mm]                         | 3.5 / 54 / 32                                                                       |                               | 5.2 / 60.5 / 36.5                                                                    |                               | 6.2 / 66.5 / 36.5                                                                     |                               |
| Current / Voltage // UL                           |           | [A] / [V]                    | 17.5 / 500 // 15 / 600                                                              |                               | 30 / 800 // 20 / 600                                                                 |                               | 32 / 800 // 30 / 600                                                                  |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -       | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                               | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                           |                               | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                                |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]           | 0.14 - 1.5 / 0.14 - 1                                                               |                               | 0.14 - 2.5                                                                           |                               | 0.25 - 4                                                                              |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]           | 0.34 - 1.5 / 0.25 - 1.5                                                             |                               | 0.34 - 2.5 / 0.34 - 4                                                                |                               | 0.5 - 4 / 0.5 - 6                                                                     |                               |
|                                                   |           |                              |  |                               |  |                               |  |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow | PT 6-TWIN<br>PT 6-TWIN BU<br>PT 6-TWIN-PE                                           | 3211929<br>3211485<br>3211498 | PT 10-TWIN<br>PT 10-TWIN BU<br>PT 10-TWIN-PE                                         | 3208746<br>3208747<br>3208745 | PT 16-TWIN N<br>PT 16-TWIN N BU<br>PT 16-TWIN N-PE                                    | 3208760<br>3208773<br>3208786 |
| Width / Length / Height                           |           | [mm]                         | 8.2 / 74.2 / 43.5                                                                   |                               | 10.2 / 88.9 / 50.5                                                                   |                               | 12.2 / 100.2 / 52.6                                                                   |                               |
| Current / Voltage // UL                           |           | [A] / [V]                    | 41 / 1000 // 40 / 600                                                               |                               | 57 / 1000 // 60 / 600                                                                |                               | 76 / 1000 // -                                                                        |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -       | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 8                                               |                               | 0.5 - 16 / 20 - 6 // 0.5 - 10 / 20 - 6                                               |                               | 0.5 - 25 / 20 - 4 // 0.5 - 16 / 20 - 6                                                |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]           | 0.5 - 6                                                                             |                               | 0.5 - 10                                                                             |                               | 0.5 - 16                                                                              |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]           | 1 - 6 / 1 - 10                                                                      |                               | 2.5 - 10 / 1 - 16                                                                    |                               | 2.5 - 25 / 2.5 - 16                                                                   |                               |

 More detailed information on use in an Ex "e" and "i" area is available on the Internet as a download for the approved products.

## Four-conductor terminal blocks

...-U = with interrupted current bar

|                                                   |           |                                      |                                                                                      |                                          |                                                                                    |                               |                                                                                     |                               |
|---------------------------------------------------|-----------|--------------------------------------|--------------------------------------------------------------------------------------|------------------------------------------|------------------------------------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------------------|-------------------------------|
|                                                   |           |                                      |     |                                          |  |                               |  |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow<br>Gray | PT 1,5/S-QUATTRO<br>PT 1,5/S-QUATTRO BU<br>PT 1,5/S-QUATTRO-PE<br>PT 1,5/S-QUATTRO-U | 3208197<br>3208208<br>3208333<br>3208359 | PT 2,5-QUATTRO<br>PT 2,5-QUATTRO BU<br>PT 2,5-QUATTRO-PE                           | 3209578<br>3209581<br>3209594 | PT 4-QUATTRO<br>PT 4-QUATTRO BU<br>PT 4-QUATTRO-PE                                  | 3211797<br>3211802<br>3211809 |
| Width / Length / Height                           |           | [mm]                                 | 3.5 / 63.2 / 32                                                                      |                                          | 5.2 / 72.2 / 36.8                                                                  |                               | 6.2 / 77 / 36.5                                                                     |                               |
| Current / Voltage // UL                           |           | [A] / [V]                            | 17.5 / 500 // 15 / 600                                                               |                                          | 24 / 800 // 20 / 600                                                               |                               | 32 / 800 // 30 / 600                                                                |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                            | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                         |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                         |                               | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                              |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                | 0.14 - 1.5 / 0.14 - 1                                                                |                                          | 0.14 - 2.5                                                                         |                               | 0.25 - 4                                                                            |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                | 0.34 - 1.5 / 0.25 - 1.5                                                              |                                          | 0.34 - 2.5 / 0.34 - 4                                                              |                               | 0.5 - 4 / 0.5 - 6                                                                   |                               |
|                                                   |           |                                      |     |                                          |                                                                                    |                               |                                                                                     |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow         | PT 6-QUATTRO<br>PT 6-QUATTRO BU<br>PT 6-QUATTRO-PE                                   | 3212934<br>3212947<br>3212950            |                                                                                    |                               |                                                                                     |                               |
| Width / Length / Height                           |           | [mm]                                 | 8.2 / 90.5 / 43.5                                                                    |                                          |                                                                                    |                               |                                                                                     |                               |
| Current / Voltage // UL                           |           | [A] / [V]                            | 41 / 1000 // 40 / 600                                                                |                                          |                                                                                    |                               |                                                                                     |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                            | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 8                                                |                                          |                                                                                    |                               |                                                                                     |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                | 0.5 - 6                                                                              |                                          |                                                                                    |                               |                                                                                     |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                | 1 - 6 / 1 - 10                                                                       |                                          |                                                                                    |                               |                                                                                     |                               |

## Double-level terminal blocks

...-PV = with equipotential bonding




|                                                   |           |                                      |                                                                                     |                                          |                                                                                      |                                          |                                                                                       |                                          |
|---------------------------------------------------|-----------|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------|--------------------------------------------------------------------------------------|------------------------------------------|---------------------------------------------------------------------------------------|------------------------------------------|
|                                                   |           |                                      |  |                                          |  |                                          |  |                                          |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow<br>Gray | PTTB 1,5/S<br>PTTB 1,5/S BU<br>PTTB 1,5/S-PE<br>PTTB 1,5/S-PV                       | 3208511<br>3208524<br>3208537<br>3208540 | PTTB 2,5<br>PTTB 2,5 BU<br>PTTB 2,5-PE<br>PTTB 2,5-PV                                | 3210567<br>3210570<br>3210596<br>3210583 | PTTB 4<br>PTTB 4 BU<br>PTTB 4-PE<br>PTTB 4-PV                                         | 3211786<br>3211793<br>3211854<br>3211825 |
| Width / Length / Height                           |           | [mm]                                 | 3.5 / 65.4 / 42.6                                                                   |                                          | 5.2 / 68 / 47.5                                                                      |                                          | 6.2 / 83.5 / 47.5                                                                     |                                          |
| Current / Voltage // UL                           |           | [A] / [V]                            | 16 / 500 // 15 / 600                                                                |                                          | 22 / 500 // 20 / 600                                                                 |                                          | 38 / 800 // 28 / 600                                                                  |                                          |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                            | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                           |                                          | 0.2 - 6 / 28 - 10 // 0.2 - 4 / 24 - 12                                                |                                          |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                | 0.14 - 1.5 / 0.14 - 1                                                               |                                          | 0.14 - 2.5                                                                           |                                          | 0.25 - 4                                                                              |                                          |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                | 0.34 - 1.5 / 0.25 - 1.5                                                             |                                          | 0.34 - 2.5 / 0.34 - 4                                                                |                                          | 0.5 - 4 / 0.5 - 6                                                                     |                                          |
| PTTB 4-L 1000 V enclosed housing                  |           |                                      |  |                                          |  |                                          |  |                                          |
| Type                                              | Order No. | Gray<br>Gray<br>Gray<br>Gray         | PTTB 1,5/S-L/N<br>PTTB 1,5/S-PE/L<br>PTTB 1,5/S-PE/N                                | 3208544<br>3208553<br>3208566            | PTTB 2,5-L/N<br>PTTB 2,5-PE/L<br>PTTB 2,5-PE/N                                       | 3210994<br>3210978<br>3210981            | PTTB 4-L 1000V                                                                        | 3062744                                  |
| Width / Length / Height                           |           | [mm]                                 | 3.5 / 65.4 / 42.6                                                                   |                                          | 5.2 / 68 / 47.5                                                                      |                                          | 8.2 / 83.5 / 47.5                                                                     |                                          |
| Current / Voltage // UL                           |           | [A] / [V]                            | 16 / 500 // 15 / 600                                                                |                                          | 22 / 500 // 20 / 300                                                                 |                                          | 38 / 1000 // 30 / 1000                                                                |                                          |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                            | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                           |                                          | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                                |                                          |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                | 0.14 - 1.5 / 0.14 - 1                                                               |                                          | 0.14 - 2.5                                                                           |                                          | 0.25 - 4                                                                              |                                          |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                | 0.34 - 1.5 / 0.25 - 1.5                                                             |                                          | 0.34 - 2.5 / 0.34 - 4                                                                |                                          | 0.5 - 4 / 0.5 - 6                                                                     |                                          |

## Multi-conductor double-level terminal blocks

|                                                   |           |                                      |                                                                                   |                                          |                                                                                           |                                          |
|---------------------------------------------------|-----------|--------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------|-------------------------------------------------------------------------------------------|------------------------------------------|
|                                                   |           |                                      |  |                                          |         |                                          |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow<br>Gray | PTTBS 2,5-TWIN<br>PTTBS 2,5-TWIN BU<br>PTTBS 2,5-TWIN-PE<br>PTTBS 2,5-TWIN-PV     | 3210600<br>3210601<br>3210602<br>3210603 | PTTBS 2,5-QUATTRO<br>PTTBS 2,5-QUATTRO BU<br>PTTBS 2,5-QUATTRO-PE<br>PTTBS 2,5-QUATTRO-PV | 3210609<br>3210610<br>3210611<br>3210612 |
| Width / Length / Height                           |           | [mm]                                 | 5.2 / 111.8 / 55                                                                  |                                          | 5.2 / 115.2 / 55                                                                          |                                          |
| Current / Voltage // UL                           |           | [A] / [V]                            | 24 / 500 //                                                                       |                                          | 24 / 500 //                                                                               |                                          |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -               | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                        |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                                |                                          |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                   | 0.14 - 2.5                                                                        |                                          | 0.14 - 2.5                                                                                |                                          |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                   | 0.34 - 2.5 / 0.34 - 4                                                             |                                          | 0.34 - 2.5 / 0.34 - 4                                                                     |                                          |

## Three-level terminal blocks

...-PV = with equipotential bonding

|                                                                                                                                                                                       |           |                                                                  |                                                                                     |                                          |                                                                                       |                                            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------|---------------------------------------------------------------------------------------|--------------------------------------------|
|                                                                                                                                                                                       |           |                                                                  |    |                                          |     |                                            |
| Type                                                                                                                                                                                  | Order No. | Gray<br>Blue<br>Green-yellow<br>Gray                             | PT 1,5/S-3L<br>PT 1,5/S-3L BU<br>PT 1,5/S-3PE<br>PT 1,5/S-3PV                       | 3213713<br>3213726<br>3213739<br>3213742 | PT 2,5-3L<br>PT 2,5-3L BU<br>PT 2,5-3PE<br>PT 2,5-3PV                                 | 3210499<br>3210509<br>3210525<br>3210512   |
| Width / Length / Height                                                                                                                                                               |           | [mm]                                                             | 3.5 / 97.2 / 53.2                                                                   |                                          | 5.2 / 102 / 58                                                                        |                                            |
| Current / Voltage // UL                                                                                                                                                               |           | [A] / [V]                                                        | 17.5 / 500 // 15 / 600                                                              |                                          | 20 / 500 // 20 / 300                                                                  |                                            |
| Solid / AWG // Stranded / AWG                                                                                                                                                         |           | [mm <sup>2</sup> ] / -                                           | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                            |                                            |
| Stranded with ferrule without/with plastic sleeve                                                                                                                                     |           | [mm <sup>2</sup> ]                                               | 0.14 - 1.5 / 0.14 - 1                                                               |                                          | 0.14 - 2.5                                                                            |                                            |
| Can be plugged in directly: with ferrule / solid                                                                                                                                      |           | [mm <sup>2</sup> ]                                               | 0.34 - 1.5 / 0.25 - 1.5                                                             |                                          | 0.34 - 2.5 / 0.34 - 4                                                                 |                                            |
|                                                                                                                                                                                       |           |                                                                  |  |                                          |   |                                            |
| Type                                                                                                                                                                                  | Order No. | Blue/Gray/Green-yellow<br>Gray/Green-yellow                      | PT 1,5/S-PE/L/N<br>PT 1,5/S-PE/L/L                                                  | 3213755<br>3213768                       | PT 2,5-PE/L/N<br>PT 2,5-PE/L/L                                                        | 3210538<br>3210541                         |
| Width / Length / Height                                                                                                                                                               |           | [mm]                                                             | 3.5 / 97.2 / 53.2                                                                   |                                          | 5.2 / 102 / 58                                                                        |                                            |
| Current / Voltage // UL                                                                                                                                                               |           | [A] / [V]                                                        | 15 / 500 // 15 / 600                                                                |                                          | 20 / 500 // 20 / 300                                                                  |                                            |
| Solid / AWG // Stranded / AWG                                                                                                                                                         |           | [mm <sup>2</sup> ] / -                                           | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                            |                                            |
| Stranded with ferrule without/with plastic sleeve                                                                                                                                     |           | [mm <sup>2</sup> ]                                               | 0.14 - 1.5 / 0.14 - 1                                                               |                                          | 0.14 - 2.5                                                                            |                                            |
| Can be plugged in directly: with ferrule / solid                                                                                                                                      |           | [mm <sup>2</sup> ]                                               | 0.34 - 1.5 / 0.25 - 1.5                                                             |                                          | 0.34 - 2.5 / 0.34 - 4                                                                 |                                            |
| The PTI 2,5... three-level terminal blocks offer optimum operating convenience with an extremely compact design. Wire load circuits can be wired quickly with a pitch of just 5.2 mm. |           |                                                                  |  |                                          |   |                                            |
| Type                                                                                                                                                                                  | Order No. | Blue/Gray/Yellow-green<br>Gray/Green-yellow<br>Blue/Gray<br>Gray | PTI 2,5-PE/L/N<br>PTI 2,5-PE/L/L                                                    | 3213950<br>3213949                       | PTI 2,5-L/N<br>PTI 2,5-L/L                                                            | 3213954<br>3213953                         |
| Width / Length / Height                                                                                                                                                               |           | [mm]                                                             | 5.2 / 101 / 50.5                                                                    |                                          | 5.2 / 101 / 50.5                                                                      | 5.2 / 118 / 42.3                           |
| Current / Voltage // UL                                                                                                                                                               |           | [A] / [V]                                                        | 24 / 400 // 20 / 300                                                                |                                          | 24 / 400 // 20 / 300                                                                  | 24 / 400 //                                |
| Solid / AWG // Stranded / AWG                                                                                                                                                         |           | [mm <sup>2</sup> ] / -                                           | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                          |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                            | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |
| Stranded with ferrule without/with plastic sleeve                                                                                                                                     |           | [mm <sup>2</sup> ]                                               | 0.14 - 2.5                                                                          |                                          | 0.14 - 2.5                                                                            | 0.14 - 2.5                                 |
| Can be plugged in directly: with ferrule / solid                                                                                                                                      |           | [mm <sup>2</sup> ]                                               | 0.34 - 2.5 / 0.34 - 4                                                               |                                          | 0.34 - 2.5 / 0.34 - 4                                                                 | 0.34 - 2.5 / 0.34 - 4                      |
|                                                                                                                                                                                       |           |                                                                  |                                                                                     |                                          |  |                                            |
| Type                                                                                                                                                                                  | Order No. | Blue/Gray/Yellow-green<br>Gray/Green-yellow<br>Blue/Gray<br>Gray | PTI 2,5-PE/L/N<br>PTI 2,5-PE/L/L                                                    | 3213950<br>3213949                       | PTI 2,5-L/N<br>PTI 2,5-L/L                                                            | 3213954<br>3213953                         |
| Width / Length / Height                                                                                                                                                               |           | [mm]                                                             | 5.2 / 101 / 50.5                                                                    |                                          | 5.2 / 101 / 50.5                                                                      | 5.2 / 118 / 42.3                           |
| Current / Voltage // UL                                                                                                                                                               |           | [A] / [V]                                                        | 24 / 400 // 20 / 300                                                                |                                          | 24 / 400 // 20 / 300                                                                  | 24 / 400 //                                |
| Solid / AWG // Stranded / AWG                                                                                                                                                         |           | [mm <sup>2</sup> ] / -                                           | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                          |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                            | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |
| Stranded with ferrule without/with plastic sleeve                                                                                                                                     |           | [mm <sup>2</sup> ]                                               | 0.14 - 2.5                                                                          |                                          | 0.14 - 2.5                                                                            | 0.14 - 2.5                                 |
| Can be plugged in directly: with ferrule / solid                                                                                                                                      |           | [mm <sup>2</sup> ]                                               | 0.34 - 2.5 / 0.34 - 4                                                               |                                          | 0.34 - 2.5 / 0.34 - 4                                                                 | 0.34 - 2.5 / 0.34 - 4                      |

 More detailed information on use in an Ex "e" and "i" area is available on the Internet at [phoenixcontact.com](http://phoenixcontact.com) as a download for the approved products.

## Three-level terminal blocks

|                                                   |           |           |                                                                                   |         |                                                                                    |         |
|---------------------------------------------------|-----------|-----------|-----------------------------------------------------------------------------------|---------|------------------------------------------------------------------------------------|---------|
|                                                   |           |           |  |         |  |         |
| Type                                              | Order No. | Gray      | PTI 4-PE/L/L                                                                      | 3214050 | PTI 4-L/L                                                                          | 3214052 |
|                                                   |           | Gray      | PTI 4-PE/L/N                                                                      | 3214049 | PTI 4-L/N                                                                          | 3214051 |
| Width / Length / Height                           |           | [mm]      | 6.2 / 114 / 50.5                                                                  |         | 6.2 / 114 / 50.5                                                                   |         |
| Current / Voltage // UL                           |           | [A] / [V] | 32 / 400 // -                                                                     |         | 32 / 400 // -                                                                      |         |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / - | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                            |         | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                             |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]     | 0.25 - 4                                                                          |         | 0.25 - 4                                                                           |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]     | 0.5 - 4 / 0.5 - 6                                                                 |         | 0.5 - 4 / 0.5 - 6                                                                  |         |

## Motor terminals

|                                                   |           |           |                                                                                   |         |                                                                                    |         |
|---------------------------------------------------|-----------|-----------|-----------------------------------------------------------------------------------|---------|------------------------------------------------------------------------------------|---------|
|                                                   |           |           |  |         |  |         |
| Type                                              | Order No. | Gray      | PT 2,5-PE/3L                                                                      | 3210542 | PT 4-PE/3L                                                                         | 3210442 |
| Width / Length / Height                           |           | [mm]      | 5.2 / 99.5 / 85.4                                                                 |         | 6.2 / 104.5 / 96.9                                                                 |         |
| Current / Voltage // UL                           |           | [A] / [V] | 25 / 800 // -                                                                     |         | 32 / 800 // -                                                                      |         |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                        |         | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                             |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]     | 0.14 - 2.5                                                                        |         | 0.25 - 4                                                                           |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]     | 0.34 - 2.5 / 0.34 - 4                                                             |         | 0.5 - 4 / 0.5 - 6                                                                  |         |

## Fuse terminal blocks

|                                                                                                                                                                                                                                                                                                                                 |           |           |                                                                                     |         |                                                                                      |         |                                                                                       |         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-----------|-------------------------------------------------------------------------------------|---------|--------------------------------------------------------------------------------------|---------|---------------------------------------------------------------------------------------|---------|
| <sup>1)</sup> For 12 - 30 V AC/DC, 0.31 - 0.95 mA<br><sup>2)</sup> For 30 - 60 V AC/DC, 0.40 - 0.86 mA<br><sup>3)</sup> For 110 - 250 V AC/DC, 0.41 - 0.96 mA<br><br>PT 4-FSI/F... Fuse terminal block for auto flat-type fuses<br>Type F (miniature)<br><sup>4)</sup> For 12 V DC, 1.7 mA<br><sup>5)</sup> For 24 V DC, 1.9 mA |           |           |  |         |  |         |  |         |
| Type                                                                                                                                                                                                                                                                                                                            | Order No. | Black     | PT 4-HESI (5X20)                                                                    | 3211861 | PTC 4-HESI (5X20)                                                                    | 3270200 | PT 4-FSI/F                                                                            | 3208943 |
|                                                                                                                                                                                                                                                                                                                                 |           | Black     | PT 4-HESILED 24 (5X20) <sup>1)</sup>                                                | 3211903 | PTC 4-HESILED 24 (5X20)                                                              | 3270203 | PT 4-FSI/F-LED 12 <sup>4)</sup>                                                       | 3208951 |
|                                                                                                                                                                                                                                                                                                                                 |           | Black     | PT 4-HESILED 60 (5X20) <sup>2)</sup>                                                | 3207908 | PTC 4-HESILED 60 (5X20)                                                              | 3270205 | PT 4-FSI/F-LED 24 <sup>5)</sup>                                                       | 3208964 |
|                                                                                                                                                                                                                                                                                                                                 |           | Black     | PT 4-HESILA 250 (5X20) <sup>3)</sup>                                                | 3211907 | PTC 4-HESILA 250 (5X20)                                                              | 3270197 |                                                                                       |         |
| Width / Length / Height                                                                                                                                                                                                                                                                                                         |           | [mm]      | 6.2 / 56 / 63.4                                                                     |         | 8.2 / 67.8 / 39.9                                                                    |         | 6.2 / 56 / 35.3                                                                       |         |
| Current / Voltage // UL                                                                                                                                                                                                                                                                                                         |           | [A] / [V] | 6.3 / 500 // 6.3 / 300                                                              |         | 6.3 / 500 // -                                                                       |         | 10 / 400 // 15 / 300                                                                  |         |
| Solid / AWG // Stranded / AWG                                                                                                                                                                                                                                                                                                   |           | [mm²] / - | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                              |         | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                               |         | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                                |         |
| Stranded with ferrule without/with plastic sleeve                                                                                                                                                                                                                                                                               |           | [mm²]     | 0.25 - 4                                                                            |         | 0.25 - 4                                                                             |         | 0.25 - 4                                                                              |         |
| Can be plugged in directly: with ferrule / solid                                                                                                                                                                                                                                                                                |           | [mm²]     | 0.5 - 4 / 0.5 - 6                                                                   |         | 0.5 - 4 / 0.5 - 6                                                                    |         | 0.5 - 4 / 0.5 - 6                                                                     |         |

## Device circuit breakers

You can find information on the modular CB device circuit breakers and the multi-channel electronic CBM device circuit breakers with push-in connection technology online at [phoenixcontact.net/products](http://phoenixcontact.net/products)



## Miniature terminal blocks

|                                                   |           |                              |                                                                                   |                               |                                                                                    |                               |
|---------------------------------------------------|-----------|------------------------------|-----------------------------------------------------------------------------------|-------------------------------|------------------------------------------------------------------------------------|-------------------------------|
|                                                   |           |                              |  |                               |  |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow | MPT 1,5/S<br>MPT 1,5/S BU<br>MPT 1,5/S-PE                                         | 3248100<br>3248101<br>3248110 | MPT 2,5<br>MPT 2,5 BU<br>MPT 2,5-PE                                                | 3248125<br>3248126<br>3248130 |
| Width / Length / Height                           |           | [mm]                         | 3.5 / 33.55 / 28.1                                                                |                               | 5.2 / 36 / 34.8                                                                    |                               |
| Current / Voltage // UL                           |           | [A] / [V]                    | 17.5 / 500 // 15 / 600                                                            |                               | 24 / 500 // 20 / 600                                                               |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                    | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                      |                               | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                         |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                        | 0.14 - 1.5 / 0.14 - 1                                                             |                               | 0.14 - 2.5                                                                         |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                        | 0.34 - 1.5 / 0.25 - 1.5                                                           |                               | 0.34 - 2.5 / 0.34 - 4                                                              |                               |

## Fuse, diode and disconnect terminal blocks for 1000 V photovoltaic applications

|                                                                                                                                                                                                                                                           |           |                                                                                    |                                                                                     |                               |                                                                                                                                                                                  |                                                                                                                                                  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| For detailed information on PV applications and power dissipation data, visit <a href="http://phoenixcontact.com">phoenixcontact.com</a>                                                                                                                  |           |                                                                                    |    |                               | Fuse-links in accordance with IEC                                                                                                                                                | Fuse-links in accordance with UL                                                                                                                 |
| Type                                                                                                                                                                                                                                                      | Order No. | Black<br>Black<br>2 A<br>4 A<br>6 A<br>8 A<br>10 A<br>12 A<br>15 A<br>16 A<br>20 A | PT 10,3-HESI-1000V<br>PT 10,3-HESI-LED-1000V                                        | 3062142<br>3062142            |                                                                                                                                                                                  |                                                                                                                                                  |
| Width / Length / Height                                                                                                                                                                                                                                   |           | [mm]                                                                               | 17.6 / 63 / 87                                                                      |                               | FUSE 10,3X38 2A PV<br>FUSE 10,3X38 4A PV<br>FUSE 10,3X38 6A PV<br>FUSE 10,3X38 8A PV<br>FUSE 10,3X38 10A PV<br>FUSE 10,3X38 12A PV<br>FUSE 10,3X38 16A PV<br>FUSE 10,3X38 20A PV | FUSE 10,3X38 6A PV A<br>FUSE 10,3X38 8A PV A<br>FUSE 10,3X38 10A PV A<br>FUSE 10,3X38 12A PV A<br>FUSE 10,3X38 15A PV A<br>FUSE 10,3X38 16A PV A |
| Current / Voltage // UL                                                                                                                                                                                                                                   |           | [A] / [V]                                                                          | 32 / 1000 // -                                                                      |                               | 3061295<br>3061305<br>3061318<br>3061321<br>3061334<br>3061347<br>3061350<br>3061363                                                                                             | 3062778<br>3062779<br>3062780<br>3062781<br>3062784<br>3062782                                                                                   |
| Solid / AWG // Stranded / AWG                                                                                                                                                                                                                             |           | [mm²] / -                                                                          | 1.5 - 10 / 16 - 6 // 1.5 - 10 / 16 - 6                                              |                               |                                                                                                                                                                                  |                                                                                                                                                  |
| Stranded with ferrule without/with plastic sleeve                                                                                                                                                                                                         |           | [mm²]                                                                              | 1.5 - 10                                                                            |                               |                                                                                                                                                                                  |                                                                                                                                                  |
| Can be plugged in directly: with ferrule / solid                                                                                                                                                                                                          |           | [mm²]                                                                              | 1.5 - 10                                                                            |                               |                                                                                                                                                                                  |                                                                                                                                                  |
| ... L-R = Diode conducting direction from left to right<br>... R-L = Diode conducting direction from right to left<br>... BE = For soldering components in place<br><sup>1)</sup> If the diode is loaded with 5 A, the surface temperature reaches 140 °C |           |                                                                                    |  |                               |                                                                                              |                                                                                                                                                  |
| Type                                                                                                                                                                                                                                                      | Order No. | Gray<br>Gray<br>Gray                                                               | PTME 6-DIO/L-R HV<br>PTME 6-DIO/R-L HV<br>PTME 6-BE                                 | 3035697<br>3035698<br>3035687 | PTME 6 HV<br>PTME 6 HV BU                                                                                                                                                        | 3035696<br>3035695                                                                                                                               |
| Width / Length / Height                                                                                                                                                                                                                                   |           | [mm]                                                                               | 8.2 / 100.8 / 67.5                                                                  |                               | 8.2 / 100.8 / 49.6                                                                                                                                                               |                                                                                                                                                  |
| Current / Voltage // UL                                                                                                                                                                                                                                   |           | [A] / [V]                                                                          | 5 <sup>1)</sup> / 1000 (reverse voltage) // -                                       |                               | 41 / 1000 // 30 / 600                                                                                                                                                            |                                                                                                                                                  |
| Solid / AWG // Stranded / AWG                                                                                                                                                                                                                             |           | [mm²] / -                                                                          | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                              |                               | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                                                                                                                           |                                                                                                                                                  |
| Stranded with ferrule without/with plastic sleeve                                                                                                                                                                                                         |           | [mm²]                                                                              | 0.5 - 6                                                                             |                               | 0.5 - 6                                                                                                                                                                          |                                                                                                                                                  |
| Can be plugged in directly: with ferrule / solid                                                                                                                                                                                                          |           | [mm²]                                                                              | 1 - 6 / 1 - 10                                                                      |                               | 1 - 6 / 1 - 10                                                                                                                                                                   |                                                                                                                                                  |
| <sup>2)</sup> The DP-STMD 6 spacer plate ensures sufficient spacing between two adjacent diodes                                                                                                                                                           |           |                                                                                    |  |                               |                                                                                                                                                                                  |                                                                                                                                                  |
| Type                                                                                                                                                                                                                                                      | Order No. | Gray                                                                               | DP-STMD 6 <sup>2)</sup>                                                             | 3035690                       |                                                                                                                                                                                  |                                                                                                                                                  |
| Width / Length / Height                                                                                                                                                                                                                                   |           | [mm]                                                                               | 8.2 / 100.8 / 49.6                                                                  |                               |                                                                                                                                                                                  |                                                                                                                                                  |

## Diode terminal blocks

Diode 1N 4007, reverse voltage 1000 V  
... L-R = Diode conducting direction from left to right  
... R-L = Diode conducting direction from right to left

|      |           |      |                |         |                     |         |                        |         |
|------|-----------|------|----------------|---------|---------------------|---------|------------------------|---------|
| Type | Order No. | Gray | PT 2,5-DIO/L-R | 3210224 | PT 2,5-TWIN-DIO/L-R | 3210240 | PT 2,5-QUATTRO-DIO/L-R | 3210266 |
|      |           | Gray | PT 2,5-DIO/R-L | 3210237 | PT 2,5-TWIN-DIO/R-L | 3210253 | PT 2,5-QUATTRO-DIO/R-L | 3210279 |

|                                                   |                        |                                            |                                            |                                            |
|---------------------------------------------------|------------------------|--------------------------------------------|--------------------------------------------|--------------------------------------------|
| Width / Length / Height                           | [mm]                   | 5.2 / 48.5 / 36.5                          | 5.2 / 60.5 / 36.5                          | 5.2 / 72 / 36.5                            |
| Current / Voltage // UL                           | [A] / [V]              | 0.5 / 800 // 20 / 300                      | 0.5 / 800 // 20 / 300                      | 0.5 / 800 // 20 / 300                      |
| Solid / AWG // Stranded / AWG                     | [mm <sup>2</sup> ] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |
| Stranded with ferrule without/with plastic sleeve | [mm <sup>2</sup> ] / - | 0.14 - 2.5                                 | 0.14 - 2.5                                 | 0.14 - 2.5                                 |
| Can be plugged in directly: with ferrule / solid  | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                      | 0.34 - 2.5 / 0.34 - 4                      | 0.34 - 2.5 / 0.34 - 4                      |

Diode 1N 4007, reverse voltage 1300 V  
... L-R = Diode conducting direction from left to right  
... R-L = Diode conducting direction from right to left

| Type | Order No. | Gray | PT 4-DIO 1N 5408/L-R | 3212112 | PT 4-QUATTRO-DIO 1N 5408/L-R | 3211919 |
|------|-----------|------|----------------------|---------|------------------------------|---------|
|      |           | Gray | PT 4-DIO 1N 5408/R-L | 3212125 | PT 4-QUATTRO-DIO 1N 5408/R-L | 3211921 |

|                                                   |                        |                                        |                                        |
|---------------------------------------------------|------------------------|----------------------------------------|----------------------------------------|
| Width / Length / Height                           | [mm]                   | 6.2 / 56 / 36.5                        | 6.2 / 77 / 36.5                        |
| Current / Voltage // UL                           | [A] / [V]              | 1.5 / 800 // 1.5 / 600                 | 1.5 / 800 // 1.5 / 600                 |
| Solid / AWG // Stranded / AWG                     | [mm <sup>2</sup> ] / - | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12 | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12 |
| Stranded with ferrule without/with plastic sleeve | [mm <sup>2</sup> ] / - | 0.25 - 4                               | 0.25 - 4                               |
| Can be plugged in directly: with ferrule / solid  | [mm <sup>2</sup> ]     | 0.5 - 4 / 0.5 - 6                      | 0.5 - 4 / 0.5 - 6                      |

Diode 1N 4007, reverse voltage 1000 V,  
maximum continuous current 0.5A  
... O-U = Throughput from top to bottom  
... U-O = Throughput from bottom to top  
... UL-UR = Throughput from bottom left to bottom right  
... O-UL/UR-UL = Throughput from top left to bottom left  
and from bottom right to bottom left  
... O-UL/O-UR = Throughput from top left to bottom left and  
from top right to bottom right

| Type | Order No. | Gray | PTTB 2,5-DIO/O-U | 3210923 | PTTB 2,5-DIO/UL-UR | 3211427 | PTTB 2,5-2DIO/O-UL/UR-UL | 3211430 |
|------|-----------|------|------------------|---------|--------------------|---------|--------------------------|---------|
|      |           | Gray | PTTB 2,5-DIO/U-O | 3210936 |                    |         | PTTB 2,5-2DIO/O-UL/O-UR  | 3211443 |
|      |           | Gray |                  |         |                    |         |                          |         |
|      |           | Gray |                  |         |                    |         |                          |         |
|      |           | Gray |                  |         |                    |         |                          |         |

|                                                   |                        |                                            |                                            |                                            |
|---------------------------------------------------|------------------------|--------------------------------------------|--------------------------------------------|--------------------------------------------|
| Width / Length / Height                           | [mm]                   | 5.2 / 68 / 47.5                            | 5.2 / 68 / 47.5                            | 5.2 / 68 / 47.5                            |
| Current / Voltage // UL                           | [A] / [V]              | 20 / 500 // 20 / 300                       | 20 / 500 // 20 / 300                       | 20 / 500 // 20 / 300                       |
| Solid / AWG // Stranded / AWG                     | [mm <sup>2</sup> ] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |
| Stranded with ferrule without/with plastic sleeve | [mm <sup>2</sup> ] / - | 0.14 - 2.5                                 | 0.14 - 2.5                                 | 0.14 - 2.5                                 |
| Can be plugged in directly: with ferrule / solid  | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                      | 0.34 - 2.5 / 0.34 - 4                      | 0.34 - 2.5 / 0.34 - 4                      |

... R499 O-U = 499 Ω From top to bottom  
... LA = LED display  
1) For 12 - 30 V DC, 0.7 - 2.4 mA  
2) For 30 - 60 V DC, 0.8 - 1.8 mA  
3) For 110 - 250 V AC/DC, 0.1 - 0.5 mA  
... 2BE = For soldering components in place

| Type | Order No. | Gray | PTTB 2,5-R499/O-U | 3210925 | PTTB 2,5-LA 24 RD <sup>1)</sup> | 3211456 | PTTB 2,5-2BE | 3211480 |
|------|-----------|------|-------------------|---------|---------------------------------|---------|--------------|---------|
|      |           | Gray |                   |         | PTTB 2,5-LA 60 RD <sup>2)</sup> | 3211469 |              |         |
|      |           | Gray |                   |         | PTTB 2,5-LA 230 <sup>3)</sup>   | 3211472 |              |         |
|      |           | Gray |                   |         |                                 |         |              |         |

|                                                   |                        |                                            |                                            |                                            |
|---------------------------------------------------|------------------------|--------------------------------------------|--------------------------------------------|--------------------------------------------|
| Width / Length / Height                           | [mm]                   | 5.2 / 68 / 47.5                            | 5.2 / 68 / 47.5                            | 5.2 / 68 / 47.5                            |
| Current / Voltage // UL                           | [A] / [V]              | 20 / 500 // -                              | 20 / 500 // 20 / 300                       | 22 / 500 // -                              |
| Solid / AWG // Stranded / AWG                     | [mm <sup>2</sup> ] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |
| Stranded with ferrule without/with plastic sleeve | [mm <sup>2</sup> ] / - | 0.14 - 2.5                                 | 0.14 - 2.5                                 | 0.14 - 2.5                                 |
| Can be plugged in directly: with ferrule / solid  | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                      | 0.34 - 2.5 / 0.34 - 4                      | 0.34 - 2.5 / 0.34 - 4                      |

## Hybrid terminal blocks with screw connection on one side

|                                                                                                                                                                         |           |                              |                                                                                     |                               |                                                                                      |                               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------------------|-------------------------------------------------------------------------------------|-------------------------------|--------------------------------------------------------------------------------------|-------------------------------|
|                                                                                                                                                                         |           |                              |    |                               |    |                               |
| Type                                                                                                                                                                    | Order No. | Gray<br>Blue<br>Green-yellow | PTU 2,5<br>PTU 2,5 BU<br>PTU 2,5-PE                                                 | 3209519<br>3209521<br>3209520 | PTU 2,5-TWIN<br>PTU 2,5-TWIN BU<br>PTU 2,5-TWIN-PE                                   | 3209515<br>3209516<br>3209517 |
| Width / Length / Height                                                                                                                                                 |           | [mm]                         | 5.2 / 53.5 / 42.8                                                                   |                               | 5.2 / 65.3 / 42.8                                                                    |                               |
| Current / Voltage // UL                                                                                                                                                 |           | [A] / [V]                    | 24 / 800 // -                                                                       |                               | 28 / 800 // -                                                                        |                               |
| Solid / AWG                                                                                                                                                             |           | [mm²] / -                    | 0.14 - 4 / 28 - 12                                                                  | 0.14 - 4 / 28 - 12            | 0.14 - 4 / 28 - 12                                                                   | 0.14 - 4 / 28 - 12            |
| Stranded with ferrule without/with plastic sleeve                                                                                                                       |           | [mm²]                        | 0.14 - 2.5                                                                          | 0.14 - 2.5                    | 0.14 - 2.5                                                                           | 0.14 - 2.5                    |
| Can be plugged in directly: with ferrule / solid                                                                                                                        |           | [mm²]                        | -                                                                                   | 0.34 - 2.5 / 0.34 - 4         | -                                                                                    | 0.34 - 2.5 / 0.34 - 4         |
|                                                                                                                                                                         |           |                              |    |                               |    |                               |
| Type                                                                                                                                                                    | Order No. | Gray<br>Blue<br>Green-yellow | PTU 4<br>PTU 4 BU<br>PTU 4-PE                                                       | 3211855<br>3211856<br>3211857 | PTU 4-TWIN<br>PTU 4-TWIN BU<br>PTU 4-TWIN-PE                                         | 3211859<br>3211860<br>3211862 |
| Width / Length / Height                                                                                                                                                 |           | [mm]                         | 6.2 / 58.8 / 42.8                                                                   |                               | 6.2 / 69.3 / 42.8                                                                    |                               |
| Current / Voltage // UL                                                                                                                                                 |           | [A] / [V]                    | 32 / 800 // -                                                                       |                               | 32 / 800 // -                                                                        |                               |
| Solid/AWG                                                                                                                                                               |           | [mm²] / -                    | 0.14 - 6 / 26 - 10                                                                  | 0.14 - 6 / 26 - 10            | 0.14 - 6 / 26 - 10                                                                   | 0.14 - 6 / 26 - 10            |
| Stranded with ferrule without/with plastic sleeve                                                                                                                       |           | [mm²]                        | 0.14 - 4                                                                            | 0.14 - 4                      | 0.14 - 4                                                                             | 0.14 - 4                      |
| Can be plugged in directly: with ferrule / solid                                                                                                                        |           | [mm²]                        | -                                                                                   | 0.5 - 6                       | -                                                                                    | 0.5 - 6                       |
| ...-MTD = Feed-through terminal block with the same shape                                                                                                               |           |                              |  |                               |  |                               |
| Type                                                                                                                                                                    | Order No. | Gray<br>Gray                 | PTU 4-MT<br>PTU 4-MT-P                                                              | 3209538<br>3209532            | PTU 4-MTD<br>PTU 4-MTD-P                                                             | 3209539<br>3209540            |
| Width / Length / Height                                                                                                                                                 |           | [mm]                         | 6.2 / 71 / 42.8                                                                     |                               | 6.2 / 71 / 42.8                                                                      | 6.2 / 71 / 42.8               |
| Current / Voltage // UL                                                                                                                                                 |           | [A] / [V]                    | 20 / 400 // -                                                                       |                               | 20 / 400 // -                                                                        | 20 / 400 // -                 |
| Solid / AWG                                                                                                                                                             |           | [mm²] / -                    | 0.14 - 6 / 26 - 10                                                                  | 0.14 - 6 / 26 - 10            | 0.14 - 6 / 26 - 10                                                                   | 0.14 - 6 / 26 - 10            |
| Stranded with ferrule without/with plastic sleeve                                                                                                                       |           | [mm²]                        | 0.14 - 4                                                                            | 0.14 - 4                      | 0.14 - 4                                                                             | 0.14 - 4                      |
| Can be plugged in directly: with ferrule / solid                                                                                                                        |           | [mm²]                        | -                                                                                   | 0.5 - 6                       | 0.5 - 6                                                                              | 0.5 - 6                       |
| Note:<br>You can find wiring and testing accessories in the product area on our website at <a href="http://phoenixcontact.net/products">phoenixcontact.net/products</a> |           |                              |  |                               |  |                               |
| Type                                                                                                                                                                    | Order No. | Gray<br>Gray                 | PTU 6-T<br>PTU 6-T-P                                                                | 3209535<br>3209530            | PTUD 6<br>PTUD 6-P                                                                   | 3209531<br>3209537            |
| Width / Length / Height                                                                                                                                                 |           | [mm]                         | 8.2 / 73.9 / 48                                                                     |                               | 8.2 / 73.9 / 48                                                                      |                               |
| Current / Voltage // UL                                                                                                                                                 |           | [A] / [V]                    | 52 / 500 // -                                                                       |                               | 52 / 800 // -                                                                        |                               |
| Solid/AWG                                                                                                                                                               |           | [mm²] / -                    | 0.5 - 10 / 20 - 8                                                                   | 0.5 - 10 / 20 - 8             | 0.5 - 10 / 20 - 8                                                                    | 0.5 - 10 / 20 - 8             |
| Stranded with ferrule without/with plastic sleeve                                                                                                                       |           | [mm²]                        | 0.5 - 6                                                                             | 0.5 - 6                       | 0.5 - 6                                                                              | 0.5 - 6                       |
| Can be plugged in directly: with ferrule / solid                                                                                                                        |           | [mm²]                        | -                                                                                   | 1 - 6                         | -                                                                                    | 1 - 6                         |

## Desk-design terminal blocks

|                                                   |           |                                      |                                                                                     |                                          |                                                                                           |                                          |                                                                                     |                               |
|---------------------------------------------------|-----------|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------|-------------------------------------------------------------------------------------------|------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------|
|                                                   |           |                                      |    |                                          |         |                                          |  |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow         | PTS 1,5/S<br>PTS 1,5/S BU<br>PTS 1,5/S-PE                                           | 3214547<br>3214550<br>3214563            | PTS 2,5<br>PTS 2,5 BU<br>PTS 2,5-PE                                                       | 3211799<br>3211812<br>3211867            | PTS 1,5/S-TWIN<br>PTS 1,5/S-TWIN BU<br>PTS 1,5/S-TWIN-PE                            | 3214589<br>3214592<br>3214602 |
| Width / Length / Height                           |           | [mm]                                 | 3.5 / 50.7 / 38.5                                                                   |                                          | 5.2 / 49 / 43                                                                             |                                          | 3.5 / 50.7 / 38.5                                                                   |                               |
| Current / Voltage // UL                           |           | [A] / [V]                            | 17.5 / 500 // 15 / 600                                                              |                                          | 24 / 800 // 20 / 600                                                                      |                                          | 17.5 / 500 // 15 / 600                                                              |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -               | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                                |                                          | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                   | 0.14 - 1.5 / 0.14 - 1                                                               |                                          | 0.14 - 2.5                                                                                |                                          | 0.14 - 1.5 / 0.14 - 1                                                               |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                   | 0.34 - 1.5 / 0.25 - 1.5                                                             |                                          | 0.34 - 2.5 / 0.34 - 4                                                                     |                                          | 0.34 - 1.5 / 0.25 - 1.5                                                             |                               |
|                                                   |           |                                      |    |                                          |         |                                          |  |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow         | PTS 2,5 TWIN<br>PTS 2,5 TWIN BU<br>PTS 2,5 TWIN-PE                                  | 3211896<br>3211906<br>3211935            | PTS 1,5/S-QUATTRO<br>PTS 1,5/S-QUATTRO BU<br>PTS 1,5/S-QUATTRO-PE                         | 3214615<br>3214631<br>3214644            | PTS 2,5-QUATTRO<br>PTS 2,5-QUATTRO BU<br>PTS 2,5-QUATTRO-PE                         | 3211993<br>3212002<br>3212011 |
| Width / Length / Height                           |           | [mm]                                 | 5.2 / 49 / 43                                                                       |                                          | 3.5 / 50.7 / 38.5                                                                         |                                          | 5.2 / 49 / 43                                                                       |                               |
| Current / Voltage // UL                           |           | [A] / [V]                            | 24 / 800 // 20 / 600                                                                |                                          | 17.5 / 500 // 15 / 600                                                                    |                                          | 24 / 800 // 20 / 600                                                                |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -               | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                          |                                          | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                              |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                          |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                   | 0.14 - 2.5                                                                          |                                          | 0.14 - 1.5 / 0.14 - 1                                                                     |                                          | 0.14 - 2.5                                                                          |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                   | 0.34 - 2.5 / 0.34 - 4                                                               |                                          | 0.34 - 1.5 / 0.25 - 1.5                                                                   |                                          | 0.34 - 2.5 / 0.34 - 4                                                               |                               |
| ...-PV = with equipotential bonding               |           |                                      |   |                                          |        |                                          |                                                                                     |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow<br>Gray | PTTBS 1,5/S<br>PTTBS 1,5/S BU<br>PTTBS 1,5/S-PE<br>PTTBS 1,5/S-PV                   | 3214657<br>3214660<br>3214673<br>3214686 | PTTBS 2,5<br>PTTBS 2,5 BU<br>PTTBS 2,5-PE<br>PTTBS 2,5-PV                                 | 3209604<br>3209617<br>3209620<br>3210211 |                                                                                     |                               |
| Width / Length / Height                           |           | [mm]                                 | 3.5 / 78.8 / 48.2                                                                   |                                          | 5.2 / 78 / 55                                                                             |                                          |                                                                                     |                               |
| Current / Voltage // UL                           |           | [A] / [V]                            | 17.5 / 500 // 15 / 600                                                              |                                          | 22 / 500 // 20 / 600                                                                      |                                          |                                                                                     |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -               | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                                |                                          |                                                                                     |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                   | 0.14 - 1.5 / 0.14 - 1                                                               |                                          | 0.14 - 2.5                                                                                |                                          |                                                                                     |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                   | 0.34 - 1.5 / 0.25 - 1.5                                                             |                                          | 0.34 - 2.5 / 0.34 - 4                                                                     |                                          |                                                                                     |                               |
|                                                   |           |                                      |  |                                          |       |                                          |                                                                                     |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow<br>Gray | PTTBS 2,5-TWIN<br>PTTBS 2,5-TWIN BU<br>PTTBS 2,5-TWIN-PE<br>PTTBS 2,5-TWIN-PV       | 3210600<br>3210601<br>3210602<br>3210603 | PTTBS 2,5-QUATTRO<br>PTTBS 2,5-QUATTRO BU<br>PTTBS 2,5-QUATTRO-PE<br>PTTBS 2,5-QUATTRO-PV | 3210609<br>3210610<br>3210611<br>3210612 |                                                                                     |                               |
| Width / Length / Height                           |           | [mm]                                 | 5.2 / 111.8 / 55                                                                    |                                          | 5.2 / 115.2 / 55                                                                          |                                          |                                                                                     |                               |
| Current / Voltage // UL                           |           | [A] / [V]                            | 24 / 500 // -                                                                       |                                          | 24 / 500 // -                                                                             |                                          |                                                                                     |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -               | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                          |                                          | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                                |                                          |                                                                                     |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                   | 0.14 - 2.5                                                                          |                                          | 0.14 - 2.5                                                                                |                                          |                                                                                     |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                   | 0.34 - 2.5 / 0.34 - 4                                                               |                                          | 0.34 - 2.5 / 0.34 - 4                                                                     |                                          |                                                                                     |                               |

# Quick, easy, and reliable – PTPOWER high-current terminal blocks with Power-Turn connection

With PTPOWER, the spring high-current terminal blocks can be used to quickly, safely, and easily wire conductors up to 150 mm<sup>2</sup> and 309 ampere thanks to the unique Power-Turn connection technology.

Compact versions of the DIN rail and direct mounting are available.

The patented Power-Turn spring connection technology enables large conductors to be connected quickly and easily using a standard screwdriver and a single lever movement. Up to three high-quality spring steel pressure springs work with the prismatic terminal body base to create a vibration-resistant conductor connection that is stable in the long-term.


## Power-Turn Technology

Designed by PHOENIX CONTACT



Quick and easy connection is now also possible for large conductors. Alternatively, conductors can also be quickly and easily inserted directly when the lever is closed by means of the push-in method.


Two-sided test connection  
for standard 2.3 mm test plugs



For maximum overview in the control cabinet



With the fully isolated and snap-on (optional) tap-off terminal block, you can easily achieve your voltage pick-off for two conductors up to 16 mm². Large-surface marking and integrated 2.3 mm test connections.



Distribute your potentials with the isolated insertion bridges. They can be installed easily without any tools and latch securely in the clamping space.



Pre-assembled terminal block bases reduce mounting and storage costs. The right terminal block base for DIN rail or direct mounting is available for every function.

## High-current terminal blocks and blocks for DIN rail mounting

... P = With 4 mm test connection

|                                                   |           |                                                                                                      |                                                                                                  |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |
|---------------------------------------------------|-----------|------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|----------------------------------------------------------------|--------------------------------------------------------------------------------------------------|----------------------------------------------------------------|--------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
|                                                   |           |                                                                                                      |                 |                                                                |                |                                                                |               |                                                                |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow<br>Black-yellow<br>Gray<br>Blue                                         | PTPOWER 35<br>PTPOWER 35 BU<br>PTPOWER 35-PE<br>PTPOWER 35-FE<br>PTPOWER 35 P<br>PTPOWER 35 P BU | 3212064<br>3212065<br>3212066<br>3212081<br>3212091<br>3212092 | PTPOWER 50<br>PTPOWER 50 BU<br>PTPOWER 50-PE<br>PTPOWER 50-FE<br>PTPOWER 50 P<br>PTPOWER 50 P BU | 3260050<br>3260051<br>3260052<br>3260063<br>3260065<br>3260066 | PTPOWER 95<br>PTPOWER 95 BU<br>PTPOWER 95-PE<br>PTPOWER 95-FE<br>PTPOWER 95 P<br>PTPOWER 95 P BU | 3260100<br>3260103<br>3260106<br>3260139<br>3260163<br>3260166 |
| Width / Length / Height                           |           | [mm]                                                                                                 | 16 / 90.6 / 62.3                                                                                 |                                                                | 20 / 101 / 105                                                                                   |                                                                | 25 / 105.5 / 108.7                                                                               |                                                                |
| Current / Voltage // UL                           |           | [A] / [V]                                                                                            | 125 / 1500 // -                                                                                  |                                                                | 150 / 1000 // -                                                                                  |                                                                | 232 / 1500 // 230 / 1000                                                                         |                                                                |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                                                                                            | 6 - 35 / 10 - 2 // 6 - 35 / 10 - 2                                                               |                                                                | 10 - 70 / 8 - 2/0 // 10 - 70 / 8 - 2/0                                                           |                                                                | 25 - 95 / 4 - 3/0 // 25 - 95 / 4 - 3/0                                                           |                                                                |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                                                                                | 6 - 35 / 6 - 35                                                                                  |                                                                | 10 - 50 / 10 - 50                                                                                |                                                                | 25 - 95 / 25 - 95                                                                                |                                                                |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                                                                                | 6 - 35 / 6 - 35                                                                                  |                                                                | 10 - 50 / 10 - 50                                                                                |                                                                | 25 - 95 / 25 - 95                                                                                |                                                                |
|                                                   |           |                                                                                                      |                 |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |
| Type                                              | Order No. | Gray<br>Blue<br>Black-yellow<br>Gray<br>Blue                                                         | PTPOWER 150<br>PTPOWER 150 BU<br>PTPOWER 150-FE<br>PTPOWER 150-P<br>PTPOWER 150 P BU             | 3215000<br>3215001<br>3215002<br>3215003<br>3215004            |                                                                                                  |                                                                |                                                                                                  |                                                                |
| Width / Length / Height                           |           | [mm]                                                                                                 | 31 / 116.4 / 116.5                                                                               |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |
| Current / Voltage // UL                           |           | [A] / [V]                                                                                            | 309 / 1500 // -                                                                                  |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                                                                                            | 35 - 150/2 - 300 Kcmil//35 - 150/2 - 300 Kcmil                                                   |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                                                                                | 35 - 150 / 35 - 150                                                                              |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                                                                                | 35 - 150 / 35 - 150                                                                              |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |
|                                                   |           |                                                                                                      |               |                                                                |              |                                                                |             |                                                                |
| Type                                              | Order No. | 3 x gray<br>3 x gray, 1 x blue<br>3 x gray, 1 x black-yellow<br>3 x gray, 1 x blue, 1 x black-yellow | PTPOWER 35-3L<br>PTPOWER 35-3L/N<br>PTPOWER 35-3L/FE<br>PTPOWER 35-3L/N/FE                       | 3212068<br>3212069<br>3212070<br>3212071                       | PTPOWER 50-3L<br>PTPOWER 50-3L/N<br>PTPOWER 50-3L/FE<br>PTPOWER 50-3L/N/FE                       | 3260053<br>3260054<br>3260055<br>3260056                       | PTPOWER 95-3L<br>PTPOWER 95-3L/N<br>PTPOWER 95-3L/FE<br>PTPOWER 95-3L/N/FE                       | 3260109<br>3260112<br>3260115<br>3260118                       |
| Current / Voltage // UL                           |           | [A] / [V]                                                                                            | 125 / 1000 // -                                                                                  |                                                                | 150 / 1000 // -                                                                                  |                                                                | 232 / 1500 // 230 / 1000                                                                         |                                                                |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                                                                                            | 6 - 35 / 10 - 2 // 6 - 35 / 10 - 2                                                               |                                                                | 10 - 70 / 8 - 2/0 // 10 - 70 / 8 - 2/0                                                           |                                                                | 25 - 95 / 4 - 3/0 // 25 - 95 / 4 - 3/0                                                           |                                                                |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                                                                                | 6 - 35 / 6 - 35                                                                                  |                                                                | 10 - 50 / 10 - 50                                                                                |                                                                | 25 - 95 / 25 - 95                                                                                |                                                                |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                                                                                | 6 - 35 / 6 - 35                                                                                  |                                                                | 10 - 50 / 10 - 50                                                                                |                                                                | 25 - 95 / 25 - 95                                                                                |                                                                |
|                                                   |           |                                                                                                      |               |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |
| Type                                              | Order No. | 3 x gray<br>3 x gray, 1 x blue<br>3 x gray, 1 x black-yellow<br>3 x gray, 1 x blue, 1 x black-yellow | PTPOWER 150-3L<br>PTPOWER 150-3L/N<br>PTPOWER 150-3L/FE<br>PTPOWER 150-3L/N/FE                   | 3215005<br>3215006<br>3215007<br>3215008                       |                                                                                                  |                                                                |                                                                                                  |                                                                |
| Current / Voltage // UL                           |           | [A] / [V]                                                                                            | 309 / 1500 // -                                                                                  |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                                                                                            | 35 - 150/2 - 300 Kcmil//35 - 150/2 - 300 Kcmil                                                   |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                                                                                | 35 - 150 / 35 - 150                                                                              |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                                                                                | 35 - 150 / 35 - 150                                                                              |                                                                |                                                                                                  |                                                                |                                                                                                  |                                                                |


## High-current terminal blocks and blocks for direct mounting

|                                                   |           |                                                                                                      |                                                                                        |                                          |                                                                                     |                                          |                                                                                      |                                          |
|---------------------------------------------------|-----------|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------|--------------------------------------------------------------------------------------|------------------------------------------|
|                                                   |           |                                                                                                      |       |                                          |   |                                          |   |                                          |
| Type                                              | Order No. | Gray<br>Blue<br>Black-yellow                                                                         | PTPOWER 35-F<br>PTPOWER 35-F BU<br>PTPOWER 35-FE-F                                     | 3212078<br>3212079<br>3212082            | PTPOWER 50-F<br>PTPOWER 50-F BU<br>PTPOWER 50-FE-F                                  | 3260061<br>3260062<br>3260064            | PTPOWER 95-F<br>PTPOWER 95-F BU<br>PTPOWER 95-FE-F                                   | 3260133<br>3260136<br>3260142            |
| Width / Length / Height                           |           | [mm]                                                                                                 | 16 / 91.6 / 62.3                                                                       |                                          | 20 / 91.01 / 105                                                                    |                                          | 25 / 139.1 / 99.8                                                                    |                                          |
| Current / Voltage // UL                           |           | [A] / [V]                                                                                            | 125 / 1000 // -                                                                        |                                          | 150 / 1000 // -                                                                     |                                          | 232 / 1500 // 230 / 1000                                                             |                                          |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -                                                                               | 6 - 35 / 10 - 2/0 // 6 - 35 / 10 - 2/0                                                 |                                          | 10 - 70 / 8 - 2/0 // 70 - 70 / 8 - 2/0                                              |                                          | 25 - 95 / 4 - 3/0 // 25 - 95 / 4 - 3/0                                               |                                          |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                                                                                   | 6 - 35 / 6 - 35                                                                        |                                          | 10 - 50 / 10 - 50                                                                   |                                          | 25 - 95 / 25 - 95                                                                    |                                          |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                                                                                   | 6 - 35 / 6 - 35                                                                        |                                          | 10 - 50 / 10 - 50                                                                   |                                          | 25 - 95 / 25 - 95                                                                    |                                          |
|                                                   |           |                                                                                                      |       |                                          |                                                                                     |                                          |                                                                                      |                                          |
| Type                                              | Order No. | Gray<br>Blue<br>Black-yellow                                                                         | PTPOWER 150-F<br>PTPOWER 150-F BU<br>PTPOWER 150-FE-F                                  | 3215030<br>3215031<br>3215032            |                                                                                     |                                          |                                                                                      |                                          |
| Width / Length / Height                           |           | [mm]                                                                                                 | 31 / 150 / 108.3                                                                       |                                          |                                                                                     |                                          |                                                                                      |                                          |
| Current / Voltage // UL                           |           | [A] / [V]                                                                                            | 309 / 1500 // -                                                                        |                                          |                                                                                     |                                          |                                                                                      |                                          |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -                                                                               | 35 - 150 / 2 - 300 Kcmil // 35 - 150 / 2 - 300 Kcmil                                   |                                          |                                                                                     |                                          |                                                                                      |                                          |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                                                                                   | 35 - 150 / 35 - 150                                                                    |                                          |                                                                                     |                                          |                                                                                      |                                          |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                                                                                   | 35 - 150 / 35 - 150                                                                    |                                          |                                                                                     |                                          |                                                                                      |                                          |
|                                                   |           |                                                                                                      |     |                                          |  |                                          |  |                                          |
| Type                                              | Order No. | 3 x gray<br>3 x gray, 1 x blue<br>3 x gray, 1 x black-yellow<br>3 x gray, 1 x blue, 1 x black-yellow | PTPOWER 35-3L-F<br>PTPOWER 35-3L/N-F<br>PTPOWER 35-3L/FE-F<br>PTPOWER 35-3L/N/FE-F     | 3212072<br>3212073<br>3212075<br>3212076 | PTPOWER 50-3L-F<br>PTPOWER 50-3L/N-F<br>PTPOWER 50-3L/FE-F<br>PTPOWER 50-3L/N/FE-F  | 3260057<br>3260058<br>3260059<br>3260060 | PTPOWER 95-3L-F<br>PTPOWER 95-3L/N-F<br>PTPOWER 95-3L/FE-F<br>PTPOWER 95-3L/N/FE-F   | 3260121<br>3260124<br>2360127<br>3260130 |
| Current / Voltage // UL                           |           | [A] / [V]                                                                                            | 125 / 1000 // -                                                                        |                                          | 150 / 1000 // -                                                                     |                                          | 232 / 1500 // 230 / 1000                                                             |                                          |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -                                                                               | 6 - 35 / 10 - 2 // 6 - 35 / 10 - 2                                                     |                                          | 10 - 70 / 8 - 2/0 // 70 - 70 / 8 - 2/0                                              |                                          | 25 - 95 / 4 - 3/0 // 25 - 95 / 4 - 3/0                                               |                                          |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                                                                                   | 6 - 35 / 6 - 35                                                                        |                                          | 10 - 50 / 10 - 50                                                                   |                                          | 25 - 95 / 25 - 95                                                                    |                                          |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                                                                                   | 6 - 35 / 6 - 35                                                                        |                                          | 10 - 50 / 10 - 50                                                                   |                                          | 25 - 95 / 25 - 95                                                                    |                                          |
|                                                   |           |                                                                                                      |     |                                          |                                                                                     |                                          |                                                                                      |                                          |
| Type                                              | Order No. | 3 x gray<br>3 x gray, 1 x blue<br>3 x gray, 1 x black-yellow<br>3 x gray, 1 x blue, 1 x black-yellow | PTPOWER 150-3L-F<br>PTPOWER 150-3L/N-F<br>PTPOWER 150-3L/FE-F<br>PTPOWER 150-3L/N/FE-F | 3215033<br>3215034<br>3215035<br>3215036 |                                                                                     |                                          |                                                                                      |                                          |
| Current / Voltage // UL                           |           | [A] / [V]                                                                                            | 309 / 1500 // -                                                                        |                                          |                                                                                     |                                          |                                                                                      |                                          |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -                                                                               | 35 - 150 / 2 - 300 Kcmil // 35 - 150 / 2 - 300 Kcmil                                   |                                          |                                                                                     |                                          |                                                                                      |                                          |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                                                                                   | 35 - 150 / 35 - 150                                                                    |                                          |                                                                                     |                                          |                                                                                      |                                          |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                                                                                   | 35 - 150 / 35 - 150                                                                    |                                          |                                                                                     |                                          |                                                                                      |                                          |

# Compact and flexible – PTIO sensor/actuator terminal blocks with push-in connection

Wire sensors and actuators easily and clearly in state-of-the-art machine and system controllers using compact sensor/actuator terminal blocks with 3.5 mm terminal width.

All PTIO terminal blocks feature the same shape and can be consistently bridged with the CLIPLINE complete jumper system to offer maximum flexibility.



Power terminal blocks of the same shape allow easy potential distribution and simple expansion of terminal block groups.



The signal level can be given a large label for ease of recognition. LED indicator variants are available to uniquely signal the switching states. Potentials from the signal conducting level can optionally be bridged.

## Three-conductor initiator/actuator terminal blocks

... LED 24 RD = Red LED display  
 ... LED 24 GN = Green LED display  
 \*) For 15 - 30 V DC, 0.31- 0.95 mA



| Type                                              | Order No. | Gray<br>Gray<br>Gray<br>Gray | PTIO 1,5/S/3                                 | 3244410 | PTIO 1,5/S/3-LED 24 RD*)<br>PTIO 1,5/S/3-LED 24 GN*) | 3244423<br>3244436 | PTIO 1,5/S/3-PE                              | 3244449 |
|---------------------------------------------------|-----------|------------------------------|----------------------------------------------|---------|------------------------------------------------------|--------------------|----------------------------------------------|---------|
| Width / Length / Height                           |           | [mm]                         | 3.5 / 74.4 / 41.5                            |         | 3.5 / 74.4 / 41.5                                    |                    | 3.5 / 74.4 / 41.5                            |         |
| Current / Voltage // UL                           |           | [A] / [V]                    | 13.5 / 250 //                                |         | 13.5 / 250 //                                        |                    | 13.5 / 250 //                                |         |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                    | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14 |         | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14         |                    | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14 |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                        | 0.14 - 1.5 / 0.14 - 1                        |         | 0.14 - 1.5 / 0.14 - 1                                |                    | 0.14 - 1.5 / 0.14 - 1                        |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                        | 0.34 - 1.5 / 0.25 - 1.5                      |         | 0.34 - 1.5 / 0.25 - 1.5                              |                    | 0.34 - 1.5 / 0.25 - 1.5                      |         |


Three-wire power terminal



| Type                                              | Order No. | Orange    | PTIO-IN 2,5/3 OG                         | 3244559 |  |  |  |  |
|---------------------------------------------------|-----------|-----------|------------------------------------------|---------|--|--|--|--|
| Width / Length / Height                           |           | [mm]      | 7 / 74.4 / 41.5                          |         |  |  |  |  |
| Current / Voltage // UL                           |           | [A] / [V] | 20 / 250 //                              |         |  |  |  |  |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / - | 0.2 - 4 / 24 - 12 // 0.2 - 2.5 / 24 - 14 |         |  |  |  |  |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]     | 0.2 - 2.5                                |         |  |  |  |  |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]     | 0.34 - 2.5 / 0.34 - 4                    |         |  |  |  |  |

## Four-wire proximity switch/actuator terminal blocks

... LED 24 RD = Red LED display  
 ... LED 24 GN = Green LED display  
 \*) For 15 - 30 V DC, 0.31- 0.95 mA



| Type                                              | Order No. | Gray<br>Gray<br>Gray<br>Gray | PTIO 1,5/S/4                                 | 3244452 | PTIO 1,5/S/4-LED 24 RD*)<br>PTIO 1,5/S/4-LED 24 GN*) | 3244517<br>3244520 | PTIO 1,5/S/4-PE                              | 3244465 |
|---------------------------------------------------|-----------|------------------------------|----------------------------------------------|---------|------------------------------------------------------|--------------------|----------------------------------------------|---------|
| Width / Length / Height                           |           | [mm]                         | 3.5 / 90.8 / 41.5                            |         | 3.5 / 90.8 / 41.5                                    |                    | 3.5 / 90.8 / 41.5                            |         |
| Current / Voltage // UL                           |           | [A] / [V]                    | 13.5 / 250 //                                |         | 13.5 / 250 //                                        |                    | 13.5 / 250 //                                |         |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                    | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14 |         | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14         |                    | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14 |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                        | 0.14 - 1.5 / 0.14 - 1                        |         | 0.14 - 1.5 / 0.14 - 1                                |                    | 0.14 - 1.5 / 0.14 - 1                        |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                        | 0.34 - 1.5 / 0.25 - 1.5                      |         | 0.34 - 1.5 / 0.25 - 1.5                              |                    | 0.34 - 1.5 / 0.25 - 1.5                      |         |

Four-wire power terminal




| Type                                              | Order No. | Orange    | PTIO-IN 2,5/4-PE OG                      | 3244481 |  |  |  |  |
|---------------------------------------------------|-----------|-----------|------------------------------------------|---------|--|--|--|--|
| Width / Length / Height                           |           | [mm]      | 7 / 90.8 / 41.5                          |         |  |  |  |  |
| Current / Voltage // UL                           |           | [A] / [V] | 20 / 250 //                              |         |  |  |  |  |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / - | 0.2 - 4 / 24 - 12 // 0.2 - 2.5 / 24 - 14 |         |  |  |  |  |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]     | 0.2 - 2.5                                |         |  |  |  |  |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]     | 0.34 - 2.5 / 0.34 - 4                    |         |  |  |  |  |

# Compact and functional – PT disconnect and knife disconnect terminal blocks with push-in connection


With a width of just 3.5 mm, the new terminal blocks now combine push-in connection and knife disconnection for conductors up to 1.5 mm<sup>2</sup>.

The product program of the compact modular terminal blocks include feed-through, multiple conductor, and double-level terminal blocks.


With the space-saving knife disconnect terminal blocks, you can achieve as yet unrivaled signal density for modular terminal blocks. This allows saving up to 30% in the control cabinet for the control wiring.




**Push-in Technology**  
Designed by PHOENIX CONTACT



The actuation cross on the disconnect knife enables the use of different size screwdrivers. All terminal blocks offer an additional test contact on both sides of the disconnect point for test plugs with a 2.3 mm diameter.



Disconnect knives and actuation levers of the same color provide clear assignment of connection levels when dealing with two disconnect levels. Each terminal point can be given a large label for ease of recognition, a prerequisite for a safe and time-saving installation.



In the range of 2.5 mm<sup>2</sup> terminal blocks, two-tier disconnect terminal blocks with one or two universal disconnect zones are available. The disconnect zone accommodates various plugs such as fuse plugs, component connectors, and isolating plugs.

## Disconnect terminal blocks for accommodating function connectors


... MTD = Feed-through terminal block with the same shape



| Type                                              | Order No. | Gray                   | PTC 2,5-TG                                 | 3270088 | PTC 2,5-TWIN-TG                            | 3270091 | PTC 2,5-QUATTRO-TG                         | 3270094 |
|---------------------------------------------------|-----------|------------------------|--------------------------------------------|---------|--------------------------------------------|---------|--------------------------------------------|---------|
|                                                   |           | Gray                   | PTC 2,5-MTD                                | 3270106 | PTC 2,5-TWIN-MTD                           | 3270110 |                                            |         |
|                                                   |           | Blue                   | PTC 2,5-MTD BU                             | 3270109 | PTC 2,5-TWIN-MTD BU                        | 3270111 |                                            |         |
| Width / Length / Height                           |           | [mm]                   | 5.2 / 56 / 36.5                            |         | 5.2 / 67.8 / 36.5                          |         | 5.2 / 79.6 / 36.5                          |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 20 / 400 // -                              |         | 20 / 400 // -                              |         | 20 / 400 // -                              |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.14 - 2.5                                 |         | 0.14 - 2.5                                 |         | 0.14 - 2.5                                 |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                      |         | 0.34 - 2.5 / 0.34 - 4                      |         | 0.34 - 2.5 / 0.34 - 4                      |         |



| Type                                              | Order No. | Gray                   | PT 2,5-TG                                  | 3210185 | PT 2,5-TWIN-TG                             | 3210198 | PT 2,5-QUATTRO-TG                          | 3210208 |
|---------------------------------------------------|-----------|------------------------|--------------------------------------------|---------|--------------------------------------------|---------|--------------------------------------------|---------|
| Width / Length / Height                           |           | [mm]                   | 5.2 / 62 / 36.5                            |         | 5.2 / 74 / 36.5                            |         | 5.2 / 84 / 36.5                            |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 20 / 400 // 20 / 300                       |         | 20 / 400 // 20 / 300                       |         | 20 / 400 // 20 / 300                       |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.14 - 2.5                                 |         | 0.14 - 2.5                                 |         | 0.14 - 2.5                                 |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                      |         | 0.34 - 2.5 / 0.34 - 4                      |         | 0.34 - 2.5 / 0.34 - 4                      |         |






| Type                                              | Order No. | Gray                   | PT 2,5-TGB                                 | 3210192 | PT 2,5-TWIN-TGB                            | 3210193 | PT 2,5-QUATTRO-TGB                         | 3210194 |
|---------------------------------------------------|-----------|------------------------|--------------------------------------------|---------|--------------------------------------------|---------|--------------------------------------------|---------|
| Width / Length / Height                           |           | [mm]                   | 5.2 / 70.1 / 36.8                          |         | 5.2 / 81.9 / 36.7                          |         | 5.2 / 92.2 / 36.7                          |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 16 / 400 // 16 / 600                       |         | 16 / 400 // 16 / 600                       |         | 16 / 400 // 16 / 600                       |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.14 - 2.5                                 |         | 0.14 - 2.5                                 |         | 0.14 - 2.5                                 |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                      |         | 0.34 - 2.5 / 0.34 - 4                      |         | 0.34 - 2.5 / 0.34 - 4                      |         |



| Type                                              | Order No. | Gray                   | PT 4-TG                                | 3211922 | PTU 4-TG                               | 3209542 |  |  |
|---------------------------------------------------|-----------|------------------------|----------------------------------------|---------|----------------------------------------|---------|--|--|
|                                                   |           | Gray                   |                                        |         | PTU 4-TG-P                             | 3209541 |  |  |
| Width / Length / Height                           |           | [mm]                   | 6.2 / 56 / 36.5                        |         | 6.2 / 71 / 42.8                        |         |  |  |
| Current / Voltage // UL                           |           | [A] / [V]              | 20 / 400 // 20 / 300                   |         | 20 / 400 // -                          |         |  |  |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12 |         | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12 |         |  |  |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.25 - 4                               |         | 0.25 - 4                               |         |  |  |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.5 - 4 / 0.5 - 6                      |         | 0.5 - 4 / 0.5 - 6                      |         |  |  |

## Disconnect terminal blocks for accommodating function connectors

|                                                   |           |                        |                                                                                   |                    |                                                                                    |         |
|---------------------------------------------------|-----------|------------------------|-----------------------------------------------------------------------------------|--------------------|------------------------------------------------------------------------------------|---------|
|                                                   |           |                        |  |                    |  |         |
| Type                                              | Order No. | Gray Blue              | PTT 2,5-L/TG<br>PTT 2,5-L/TG BU                                                   | 3210230<br>3210270 | PTTBS 2,5-2TGB                                                                     | 3210402 |
| Width / Length / Height                           |           | [mm]                   | 5.2 / 92.4 / 47.4                                                                 |                    | 5.2 / 127.5 / 64.3                                                                 |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 16 / 400 // 16 / 300                                                              |                    | 16 / 400 // 16 / 300                                                               |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / – | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                        |                    | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                         |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]     | 0.14 - 2.5                                                                        |                    | 0.14 - 2.5                                                                         |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                                                             |                    | 0.34 - 2.5 / 0.34 - 4                                                              |         |
| ') 16 A disconnect level                          |           |                        |  |                    |  |         |
| Type                                              | Order No. | Gray                   | PTI 2,5-L/TG                                                                      | 3213961            | PTI 2,5-PE/L/TG                                                                    | 3213960 |
| Width / Length / Height                           |           | [mm]                   | 5.2 / 101 / 50.5                                                                  |                    | 5.2 / 101 / 50.5                                                                   |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 24 <sup>3)</sup> / 400 // 20 / 300                                                |                    | 24 <sup>3)</sup> / 400 // 20 / 300                                                 |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / – | 0.14 - 4 / 26 - 12 // 0.14 - 4 / 26 - 12                                          |                    | 0.14 - 4 / 26 - 12 // 0.14 - 4 / 26 - 12                                           |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]     | 0.14 - 2.5                                                                        |                    | 0.14 - 2.5                                                                         |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                                                             |                    | 0.34 - 2.5 / 0.34 - 4                                                              |         |

## Function plugs for disconnect terminal blocks

|                                                                                                                                                                                                                                                               |           |                                   |                                                                                     |                               |                                                                                                                                                      |                                |                                                                                       |         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-----------------------------------|-------------------------------------------------------------------------------------|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|---------------------------------------------------------------------------------------|---------|
|                                                                                                                                                                                                                                                               |           |                                   |    |                               |                                                                    |                                |                                                                                       |         |
| Type                                                                                                                                                                                                                                                          | Order No. | Gray<br>Orange                    | P-FIX                                                                               | 3038956                       | P-DI                                                                                                                                                 | 3036783                        |                                                                                       |         |
| Width / Length / Height<br>Current / Voltage                                                                                                                                                                                                                  |           | [mm]<br>[A] / [V]                 | 4 / 10.5 / -<br>20 / -                                                              |                               | 3.5 / 10.8 / 23.1<br>20 / -                                                                                                                          |                                |                                                                                       |         |
| Diode 1N 4007,<br>reverse voltage 1300 V,<br>maximum continuous current 1 A<br><br>... L-R = Diode conducting direction from left to right<br>... R-L = Diode conducting direction from right to left<br>1) Max. 1 W power dissipation for single arrangement |           |                                   |    |                               |                                                                    |                                |                                                                                       |         |
| Type                                                                                                                                                                                                                                                          | Order No. | Gray<br>Gray<br>Gray<br><br>Black | P-CO<br>P-CO 1N4007/R-L<br>P-CO 1N4007/L-R                                          | 3036796<br>3032457<br>3032460 | P-CO 2-5 R47K component connector, with<br>47 kohm resistor, contacts two adjacent terminal<br>blocks at 5.2 mm in bridge shaft<br><br>P-CO 2-5 R47K |                                | 3032447                                                                               |         |
| Width / Length / Height<br>Current / Voltage                                                                                                                                                                                                                  |           | [mm]<br>[A] / [V]                 | 5.2 / 24 / 22<br>6 <sup>3)</sup> / -                                                |                               |                                                                                                                                                      |                                |                                                                                       |         |
| ... LED = LED display<br><br>1) For 12 - 30 V DC, 0.31 - 0.95 mA<br>2) For 30 - 60 V AC/DC, 0.40 - 0.86 mA<br>3) For 110 - 250 V AC/DC, 0.41 - 0.96 mA                                                                                                        |           |                                   |  |                               |                                                                  |                                |  |         |
| Type                                                                                                                                                                                                                                                          | Order No. | Black<br>Black                    | P-FU 5X20-5                                                                         | 3209235                       | P-FU 5X20 LED 24-5 <sup>1)</sup><br>P-FU 5X20 LED 60-5 <sup>2)</sup>                                                                                 | 3209248<br>3209251             | P-FU 5X20 LED 250-5 <sup>3)</sup>                                                     | 3209264 |
| Width / Length / Height<br>Current / Voltage                                                                                                                                                                                                                  |           | [mm]<br>[A] / [V]                 | 5.2 / 23.5 / 45.5<br>6.3 / 400                                                      |                               | 5.2 / 23.5 / 45.5<br>6.3 / 24, 60                                                                                                                    | 5.2 / 23.5 / 45.5<br>6.3 / 250 |                                                                                       |         |
| ... LED / ...LA = LED display<br><br>1) For 12 - 30 V DC, 0.31 - 0.95 mA<br>2) For 30 - 60 V AC/DC, 0.40 - 0.86 mA<br>3) For 110 - 250 V AC/DC, 0.41 - 0.96 mA                                                                                                |           |                                   |  |                               |                                                                  |                                |  |         |
| Type                                                                                                                                                                                                                                                          | Order No. | Black<br>Black                    | P-FU 5X20                                                                           | 3036806                       | P-FU 5X20 LED 24 <sup>1)</sup><br>P-FU 5X20 LED 60 <sup>2)</sup>                                                                                     | 3036819<br>3036822             | P-FU 5X20 LA 250 <sup>3)</sup>                                                        | 3036835 |
| Width / Length / Height<br>Current / Voltage                                                                                                                                                                                                                  |           | [mm]<br>[A] / [V]                 | 6.2 / 28 / 25<br>6.3 / 500                                                          |                               | 6.2 / 28 / 25<br>6.3 / 24, 60                                                                                                                        | 6.2 / 28 / 25<br>6.3 / 250     |                                                                                       |         |

## Knife disconnect terminal blocks

... MTD = Feed-through terminal block with the same shape

|                                                   |           |                              |                                                                  |                                          |                                                                                      |                                          |                                                                                                  |                                          |
|---------------------------------------------------|-----------|------------------------------|------------------------------------------------------------------|------------------------------------------|--------------------------------------------------------------------------------------|------------------------------------------|--------------------------------------------------------------------------------------------------|------------------------------------------|
| Type                                              | Order No. | Gray<br>Blue<br>Gray<br>Blue | PT 1,5/S-MT<br>PT 1,5/S-MT BU<br>PT 1,5/S-MTD<br>PT 1,5/S-MTD BU | 3210301<br>3210302<br>3210308<br>3210309 | PT 1,5/S-TWIN-MT<br>PT 1,5/S-TWIN-MT BU<br>PT 1,5/S-TWIN-MTD<br>PT 1,5/S-TWIN-MTD BU | 3210311<br>3210312<br>3210317<br>3210319 | PT 1,5/S-QUATTRO-MT<br>PT 1,5/S-QUATTRO-MT BU<br>PT 1,5/S-QUATTRO-MTD<br>PT 1,5/S-QUATTRO-MTD BU | 3210321<br>3210322<br>3210328<br>3210329 |
| Width / Length / Height                           |           | [mm]                         | 3.5 / 58.9 / 32                                                  |                                          | 3.5 / 67.8 / 32                                                                      |                                          | 3.5 / 76.9 / 32                                                                                  |                                          |
| Current / Voltage // UL                           |           | [A] / [V]                    | 10 / 400 // 10 / 300                                             |                                          | 10 / 400 // 10 / 300                                                                 |                                          | 10 / 400 // 10 / 300                                                                             |                                          |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -       | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                     |                                          | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                         |                                          | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                                     |                                          |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / -       | 0.14 - 1.5 / 0.14 - 1                                            |                                          | 0.14 - 1.5 / 0.14 - 1                                                                |                                          | 0.14 - 1.5 / 0.14 - 1                                                                            |                                          |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]           | 0.34 - 1.5 / 0.25 - 1.5                                          |                                          | 0.34 - 1.5 / 0.25 - 1.5                                                              |                                          | 0.34 - 1.5 / 0.25 - 1.5                                                                          |                                          |

... MTD = Feed-through terminal block with the same shape





|                                                   |           |                        |                                                   |                               |                                                            |                               |                                            |         |
|---------------------------------------------------|-----------|------------------------|---------------------------------------------------|-------------------------------|------------------------------------------------------------|-------------------------------|--------------------------------------------|---------|
| Type                                              | Order No. | Gray<br>Gray<br>Blue   | PTC 2,5-MT<br>PTC 2,5-MT-MTD<br>PTC 2,5-MT-MTD BU | 3270079<br>3270106<br>3270109 | PTC 2,5-TWIN-MT<br>PTC 2,5-TWIN-MTD<br>PTC 2,5-TWIN-MTD BU | 3270082<br>3270110<br>3270111 | PTC 2,5-QUATTRO-MT                         | 3270085 |
| Width / Length / Height                           |           | [mm]                   | 5.2 / 56 / 36.5                                   |                               | 5.2 / 67.8 / 36.5                                          |                               | 5.2 / 79.6 / 36.5                          |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 20 / 400 // -                                     |                               | 20 / 400 // -                                              |                               | 20 / 400 // -                              |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14        |                               | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                 |                               | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.14 - 2.5                                        |                               | 0.14 - 2.5                                                 |                               | 0.14 - 2.5                                 |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                             |                               | 0.34 - 2.5 / 0.34 - 4                                      |                               | 0.34 - 2.5 / 0.34 - 4                      |         |

|                                                   |           |                        |                                            |                    |                                            |                    |                                            |                    |
|---------------------------------------------------|-----------|------------------------|--------------------------------------------|--------------------|--------------------------------------------|--------------------|--------------------------------------------|--------------------|
| Type                                              | Order No. | Gray<br>Blue           | PT 2,5-MT<br>PT 2,5-MT BU                  | 3210156<br>3211650 | PT 2,5-TWIN-MT<br>PT 2,5-TWIN-MT BU        | 3210169<br>3211663 | PT 2,5-QUATTRO-MT<br>PT 2,5-QUATTRO-MT BU  | 3210172<br>3211676 |
| Width / Length / Height                           |           | [mm]                   | 5.2 / 62 / 36.5                            |                    | 5.2 / 74 / 36.5                            |                    | 5.2 / 84 / 36.5                            |                    |
| Current / Voltage // UL                           |           | [A] / [V]              | 20 / 400 // 20 / 300                       |                    | 20 / 400 // 20 / 300                       |                    | 20 / 400 // 20 / 300                       |                    |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |                    | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |                    | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |                    |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.14 - 2.5                                 |                    | 0.14 - 2.5                                 |                    | 0.14 - 2.5                                 |                    |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                      |                    | 0.34 - 2.5 / 0.34 - 4                      |                    | 0.34 - 2.5 / 0.34 - 4                      |                    |

|                                                   |           |                        |                                            |                    |                                            |                    |                                             |                    |
|---------------------------------------------------|-----------|------------------------|--------------------------------------------|--------------------|--------------------------------------------|--------------------|---------------------------------------------|--------------------|
| Type                                              | Order No. | Gray<br>Blue           | PT 2,5-MTB<br>PT 2,5-MTB BU                | 3210157<br>3210163 | PT 2,5-TWIN-MTB<br>PT 2,5-TWIN-MTB BU      | 3210170<br>3210177 | PT 2,5-QUATTRO-MTB<br>PT 2,5-QUATTRO-MTB BU | 3210184<br>3210191 |
| Width / Length / Height                           |           | [mm]                   | 5.2 / 70.1 / 36.7                          |                    | 5.2 / 81.9 / 36.7                          |                    | 5.2 / 92.2 / 36.7                           |                    |
| Current / Voltage // UL                           |           | [A] / [V]              | 16 / 400 // 20 / 600                       |                    | 16 / 400 // 16 / 600                       |                    | 16 / 400 // 16 / 600                        |                    |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |                    | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |                    | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14  |                    |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.14 - 2.5                                 |                    | 0.14 - 2.5                                 |                    | 0.14 - 2.5                                  |                    |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                      |                    | 0.34 - 2.5 / 0.34 - 4                      |                    | 0.34 - 2.5 / 0.34 - 4                       |                    |

## Knife disconnect terminal blocks


... MTD = Feed-through terminal block with the same shape

|                                                   |           |                        |                                                                                     |         |                                                                                      |         |                                                                                                   |         |
|---------------------------------------------------|-----------|------------------------|-------------------------------------------------------------------------------------|---------|--------------------------------------------------------------------------------------|---------|---------------------------------------------------------------------------------------------------|---------|
|                                                   |           |                        |    |         |    |         |                |         |
| Type                                              | Order No. | Gray                   | PT 4-MT                                                                             | 3211933 | PTU 4-MT                                                                             | 3209538 | PTU 4-MT-P                                                                                        | 3209532 |
|                                                   |           | Gray                   |                                                                                     |         | PTU 4-MTD                                                                            | 3209539 | PTU 4-MTD-P                                                                                       | 3209540 |
| Width / Length / Height                           |           | [mm]                   | 6.2 / 56 / 36.5                                                                     |         | 6.2 / 71 / 42.8                                                                      |         | 6.2 / 71 / 42.8                                                                                   |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 20 / 400 // 20 / 300                                                                |         | 20 / 400 // -                                                                        |         | 20 / 400 // -                                                                                     |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                              |         | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                               |         | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                                            |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.25 - 4                                                                            |         | 0.25 - 4                                                                             |         | 0.25 - 4                                                                                          |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.5 - 4 / 0.5 - 6                                                                   |         | 0.5 - 4 / 0.5 - 6                                                                    |         | 0.5 - 4 / 0.5 - 6                                                                                 |         |
|                                                   |           |                        |    |         |    |         |                |         |
| Type                                              | Order No. | Gray                   | PTT 1,5/S-L/MT                                                                      | 3210341 | PTT 1,5/S-2MT                                                                        | 3210351 | PTT 1,5/S-2L                                                                                      | 3210356 |
|                                                   |           | Blue                   | PTT 1,5/S-L/MT BU                                                                   | 3210342 | PTT 1,5/S-2MT BU                                                                     | 3210352 | PTT 1,5/S-2L BU                                                                                   | 3210357 |
| Width / Length / Height                           |           | [mm]                   | 3.5 / 86 / 42.6                                                                     |         | 3.5 / 86 / 42.6                                                                      |         | 3.5 / 86 / 42.6                                                                                   |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 9 / 400 // 10 / 300                                                                 |         | 9 / 400 // 10 / 300                                                                  |         | 9 / 400 // 10 / 300                                                                               |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |         | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                         |         | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                                      |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.14 - 1.5 / 0.14 - 1                                                               |         | 0.14 - 1.5 / 0.14 - 1                                                                |         | 0.14 - 1.5 / 0.14 - 1                                                                             |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 1.5 / 0.25 - 1.5                                                             |         | 0.34 - 1.5 / 0.25 - 1.5                                                              |         | 0.34 - 1.5 / 0.25 - 1.5                                                                           |         |
|                                                   |           |                        |   |         |   |         |               |         |
| Type                                              | Order No. | Gray                   | PTT 2,5-L/MT                                                                        | 3210251 | PTT 2,5-2MT                                                                          | 3210258 | PTTBS 2,5-2MTB                                                                                    | 3210400 |
|                                                   |           | Blue                   | PTT 2,5-L/MT BU                                                                     | 3210257 | PTT 2,5-2MT BU                                                                       | 3210265 | PTTBS 2,5-2MTB BU                                                                                 | 3210401 |
|                                                   |           | Gray                   | PTT 2,5-2L                                                                          | 3210267 | PTT 2,5-2L                                                                           | 3210267 |                                                                                                   |         |
|                                                   |           | Blue                   | PTT 2,5-2L BU                                                                       | 3210268 | PTT 2,5-2L BU                                                                        | 3210268 |                                                                                                   |         |
| Width / Length / Height                           |           | [mm]                   | 5.2 / 92.4 / 47.4                                                                   |         | 5.2 / 92.4 / 47.4                                                                    |         | 5.2 / 127.5 / 64.3                                                                                |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 20 / 400 // 16 / 300                                                                |         | 16 / 400 // 16 / 300                                                                 |         | 16 / 400 // 16 / 300                                                                              |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                          |         | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                           |         | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                                        |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.14 - 2.5                                                                          |         | 0.14 - 2.5                                                                           |         | 0.14 - 2.5                                                                                        |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                                                               |         | 0.34 - 2.5 / 0.34 - 4                                                                |         | 0.34 - 2.5 / 0.34 - 4                                                                             |         |
| *) 16 A disconnect level                          |           |                        |  |         |  |         |              |         |
| Type                                              | Order No. | Gray                   | PTI 2,5-L/LTB                                                                       | 3213958 | PTI 2,5-PE/L/LTB                                                                     | 3213957 | S-MT                                                                                              | 3247954 |
|                                                   |           | White                  |                                                                                     |         |                                                                                      |         |                                                                                                   |         |
| Width / Length / Height                           |           | [mm]                   | 5.2 / 101 / 50.5                                                                    |         | 5.2 / 101 / 50.5                                                                     |         | Switching lock for all knife disconnect terminal blocks of the PT... 2.5... and PT... 4... series |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 24 <sup>3)</sup> / 400 // -                                                         |         | 24 <sup>3)</sup> / 400 // 20 / 300                                                   |         |                                                                                                   |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 4 / 26 - 12 // 0.14 - 4 / 26 - 12                                            |         | 0.14 - 4 / 26 - 12 // 0.14 - 4 / 26 - 12                                             |         |                                                                                                   |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.14 - 2.5                                                                          |         | 0.14 - 2.5                                                                           |         |                                                                                                   |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5 / 0.34 - 4                                                               |         | 0.34 - 2.5 / 0.34 - 4                                                                |         |                                                                                                   |         |


# Three-dimensional jumpering – PT four-level terminal blocks with push-in connection

The PT 2,5-4L... four-level terminal blocks allow you to jumper signals in your controllers and system sections using minimal space.

Based on the different jumper options in a terminal strip as well as the jumpering options in the freely configurable 4-pos. plugs, this terminal system allows extremely compact, three-dimensional signal distributors to be constructed.



The four-level terminal blocks are equipped with two slots and increase system modularity by adding a further jumpering level. They enable the use of jumper plugs for free assembly that can be used for horizontal, vertical, and diagonal signal wiring.



The plug-in vertical bridge FBS-PV PT 2,5-4L enables potential to be distributed easily between the levels of a terminal block. One function shaft is available for the cross connection of the potentials for each level.




The jumper plug accessories feature a modular design and can be assembled tailored to the application. Screwless flange covers and corresponding flange terminal blocks have been implemented for additional fixing of the jumper and field plugs.

## Four-level terminal blocks

|                                                   |           |                              |                                                                                   |                    |                                                                                    |                    |                                                                                     |                    |
|---------------------------------------------------|-----------|------------------------------|-----------------------------------------------------------------------------------|--------------------|------------------------------------------------------------------------------------|--------------------|-------------------------------------------------------------------------------------|--------------------|
|                                                   |           |                              |  |                    |  |                    |  |                    |
| Type                                              | Order No. | Gray                         | PT 2,5-4L/1P                                                                      | 3012300            | PT 2,5-4L/2P                                                                       | 3012310            | PT 2,5-PE/3L/2P                                                                     | 3012316            |
| Width / Length / Height                           |           | [mm]                         | 5.2 / 105.6 / 59                                                                  |                    | 5.2 / 125 / 59                                                                     |                    | 5.2 / 125 / 59                                                                      |                    |
| Current / Voltage // UL                           |           | [A] / [V]                    | 10 / 250 // -                                                                     |                    | 10 / 250 // -                                                                      |                    | 10 / 250 // -                                                                       |                    |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -       | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                        |                    | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                         |                    | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                          |                    |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]           | 0.14 - 2.5                                                                        |                    | 0.14 - 2.5                                                                         |                    | 0.14 - 2.5                                                                          |                    |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]           | 0.34 - 2.5 / 0.34 - 4                                                             |                    | 0.34 - 2.5 / 0.34 - 4                                                              |                    | 0.34 - 2.5 / 0.34 - 4                                                               |                    |
|                                                   |           |                              |  |                    |  |                    |  |                    |
| Type                                              | Order No. | Gray<br>Gray<br>Gray<br>Gray | CP-H 2,5-4L<br>CP-H 2,5-4L-Z                                                      | 3012313<br>3012314 | CP-H 2,5-4L<br>CP-H 2,5-4L-Z                                                       | 3012313<br>3012314 | CP-H 2,5-4L-PE<br>CP-H 2,5-4L-Z-PE                                                  | 3012323<br>3012324 |
| Width / Length / Height                           |           | [mm]                         | 5.2 / 31.6 / 31.7                                                                 |                    | 5.2 / 31.6 / 31.7                                                                  |                    | 5.2 / 31.6 / 31.7                                                                   |                    |
| Current / Voltage                                 |           | [A] / [V]                    |                                                                                   |                    |                                                                                    |                    |                                                                                     |                    |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -       |                                                                                   |                    |                                                                                    |                    |                                                                                     |                    |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]           |                                                                                   |                    |                                                                                    |                    |                                                                                     |                    |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]           |                                                                                   |                    |                                                                                    |                    |                                                                                     |                    |

## Four-level terminal block accessories




- ① CP-H 2,5-4L-Z 4-pos. plug with securing pin, Order No. 3012314
- ② DP-CP-H 2,5-4L spacer plate, Order No. 3012319
- ③ CP-H 2,5-4L 4-pos. plug, Order No. 3012313
- ④ D-CP-H 2,5-4L cover profile carrier, Order No. 3012320
- ⑤ DFS-CP-H 2,5-4L cover profile carrier with self-locking flange cover, Order No. 3012317
- ⑥ DFS-CP 2,5-4L self-locking flange cover, Order No. 3012321
- ⑦ AP-CP-H cover profile, Order No. 3012315
- ⑧ FBS-PV PT 2,5-4L vertical potential bridge, Order No. 3012318
- ⑨ PT 2,5-4L/1P-FS self-locking flange for one slot, Order No. 3012302  
PT 2,5-4L/2P-FS self-locking flange for two slots, Order No. 3012312
- ⑩ Crimp contact, Order No. 3190438 and 3190506

# Simple, reliable and intuitive marshalling – PTRV marshalling terminals with push-in connection

Jumper sensors and actuators easily and clearly with a compact solution. The configurable color coding ensures quick orientation and secure wiring. Large individually insertable label carriers enable matrix identification and provide the best possible overview in a control cabinet.


Potential distributors of the same shape and a comprehensive range of accessories complete the product line.



Maximize your signal density using the only design of its kind on the market for compact marshalling terminals. Optional cabling duct combs also reduce expenses and space requirements.



Wire by color: Freely configurable color assignment for conductors and terminal points enable reliable and intuitive installation. Configure the right marshalling terminal for your needs from eleven available colors.



The easily accessible 2.3 mm test connection are centered between connection points. This lets you conveniently check the marshalling terminals at any level.

## Marshalling terminals and potential distributors

|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        |                                              |                                                                                                                                                                                |         |                                                                                      |         |                                                                                       |         |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------------------------------------------------------------------------------------|---------|---------------------------------------------------------------------------------------|---------|
| .../WH = Levels white<br>.../RD = Levels red<br>...BU/BU = Levels blue<br>...BU/WH = Levels white<br>...BU/RD = Levels red<br>.../BK = Levels black<br>...BU/RK = Levels black<br>.../YEBK = Top 2 levels yellow, bottom 2 levels black<br>.../BKYE = Top 2 levels black, bottom 2 levels yellow<br>PTRVB 4-FI with a 4 mm <sup>2</sup> connection chamber                                                               |                        |                                              |                                                                                               |         |    |         |    |         |
| Type                                                                                                                                                                                                                                                                                                                                                                                                                     | Order No.              | Gray                                         | PTRV 4 /WH                                                                                                                                                                     | 3270115 |                                                                                      |         | Bridgeable <sup>1)</sup>                                                              |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Gray                                         | PTRV 4 /RD                                                                                                                                                                     | 3270121 |                                                                                      |         |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Blue                                         | PTRV 4 BU/BU                                                                                                                                                                   | 3270118 |                                                                                      |         |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Blue                                         | PTRV 4 BU/WH                                                                                                                                                                   | 3270119 |                                                                                      |         |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Blue                                         | PTRV 4 BU/RD                                                                                                                                                                   | 3270120 |                                                                                      |         |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Gray                                         |                                                                                                                                                                                |         | PTRV 4-PV /BK                                                                        | 3270125 |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Blue                                         |                                                                                                                                                                                |         | PTRV 4-PV BU/BK                                                                      | 3270126 |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Gray                                         |                                                                                                                                                                                |         | PTRV 4-FE /YEBK                                                                      | 3270130 | PTRVB 4-FI                                                                            | 3270158 |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Gray                                         |                                                                                                                                                                                |         | PTRV 4-FE /BKYE                                                                      | 3270131 | PTRVB 4-PV                                                                            | 3270157 |
| Width / Length / Height                                                                                                                                                                                                                                                                                                                                                                                                  | [mm]                   | 8.3 / 64 / 55.5                              |                                                                                                                                                                                |         | 8.3 / 64 / 55.5                                                                      |         | 8.3 / 64 / 55.5                                                                       |         |
| Current / Voltage // UL                                                                                                                                                                                                                                                                                                                                                                                                  | [A] / [V]              | 10 / 250 // -                                |                                                                                                                                                                                |         | 17.5 / 250 // -                                                                      |         | 17.5 / 250 // -                                                                       |         |
| Solid / AWG // Stranded / AWG                                                                                                                                                                                                                                                                                                                                                                                            | [mm <sup>2</sup> ] / - | 0.14 - 2.5 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |                                                                                                                                                                                |         | 0.14 - 2.5 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                         |         | 0.14 - 2.5 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                          |         |
| Stranded with ferrule without/with plastic sleeve                                                                                                                                                                                                                                                                                                                                                                        | [mm <sup>2</sup> ]     | 0.14 - 2.5 / 0.14 - 1.5                      |                                                                                                                                                                                |         | 0.14 - 2.5 / 0.14 - 1.5                                                              |         | 0.14 - 2.5 / 0.14 - 1.5                                                               |         |
| Can be plugged in directly: with ferrule / solid                                                                                                                                                                                                                                                                                                                                                                         | [mm <sup>2</sup> ]     | 0.34 - 2.5                                   |                                                                                                                                                                                |         | 0.34 - 2.5                                                                           |         | 0.34 - 2.5                                                                            |         |
| .../WHRD = Top 4 levels white, bottom 4 levels red<br>.../RDWH = Top 4 levels red, bottom 4 levels white<br>...BU/BU = Levels blue<br>...BU/WHRD = Top 4 levels white, bottom 4 levels red<br>...BU/RDWH = Top 4 levels red, bottom 4 levels white<br>.../BK = Levels black<br>...BU/BK = Levels black<br>.../BKYE = Top 4 levels black, bottom 4 levels yellow<br>.../YEBK = Top 4 levels yellow, bottom 4 levels black |                        |                                              |                                                                                               |         |    |         |    |         |
| Type                                                                                                                                                                                                                                                                                                                                                                                                                     | Order No.              | Gray                                         | PTRV 8 /WHRD                                                                                                                                                                   | 3270133 |                                                                                      |         | Bridgeable <sup>1)</sup>                                                              |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Gray                                         | PTRV 8 /RDWH                                                                                                                                                                   | 3270137 |                                                                                      |         |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Blue                                         | PTRV 8 BU/BU                                                                                                                                                                   | 3270136 |                                                                                      |         |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Blue                                         | PTRV 8 BU/WHRD                                                                                                                                                                 | 3270134 |                                                                                      |         |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Blue                                         | PTRV 8 BU/RDWH                                                                                                                                                                 | 3270135 |                                                                                      |         |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Gray                                         |                                                                                                                                                                                |         | PTRV 8-PV /BK                                                                        | 3270142 |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Blue                                         |                                                                                                                                                                                |         | PTRV 8-PV BU/BK                                                                      | 3270145 |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Gray                                         |                                                                                                                                                                                |         | PTRV 8-FE /BKYE                                                                      | 3270149 | PTRVB 8-FI                                                                            | 3270160 |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | Gray                                         |                                                                                                                                                                                |         | PTRV 8-FE /YEBK                                                                      | 3270148 | PTRVB 8-PV                                                                            | 3270159 |
| Width / Length / Height                                                                                                                                                                                                                                                                                                                                                                                                  | [mm]                   | 8.3 / 100 / 55.5                             |                                                                                                                                                                                |         | 8.3 / 100 / 55.5                                                                     |         | 8.3 / 100 / 55.5                                                                      |         |
| Current / Voltage // UL                                                                                                                                                                                                                                                                                                                                                                                                  | [A] / [V]              | 8 / 250 // -                                 |                                                                                                                                                                                |         | 17.5 / 250 // -                                                                      |         | 17.5 / 250 // -                                                                       |         |
| Solid / AWG // Stranded / AWG                                                                                                                                                                                                                                                                                                                                                                                            | [mm <sup>2</sup> ] / - | 0.14 - 2.5 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |                                                                                                                                                                                |         | 0.14 - 2.5 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                         |         | 0.14 - 2.5 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                          |         |
| Stranded with ferrule without/with plastic sleeve                                                                                                                                                                                                                                                                                                                                                                        | [mm <sup>2</sup> ]     | 0.14 - 2.5 / 0.14 - 1.5                      |                                                                                                                                                                                |         | 0.14 - 2.5 / 0.14 - 1.5                                                              |         | 0.14 - 2.5 / 0.14 - 1.5                                                               |         |
| Can be plugged in directly: with ferrule / solid                                                                                                                                                                                                                                                                                                                                                                         | [mm <sup>2</sup> ]     | 0.34 - 2.5                                   |                                                                                                                                                                                |         | 0.34 - 2.5                                                                           |         | 0.34 - 2.5                                                                            |         |
| Marker carrier and cover<br>... A-D printed from A to D<br>... 1-4 printed from 1 to 4<br>... A-H printed from A to H<br>... 1-8 printed from 1 to 8                                                                                                                                                                                                                                                                     |                        |                                              |                                                                                             |         |  |         |  |         |
| Type                                                                                                                                                                                                                                                                                                                                                                                                                     | Order No.              | White                                        | DP-PTRV 4                                                                                                                                                                      | 3270163 | D-PTRV 4 WH A-D                                                                      | 3270153 | Center groove labeling                                                                |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | White                                        |                                                                                                                                                                                |         | D-PTRV 4 WH 1-4                                                                      | 3270152 |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | White/Unprinted                              |                                                                                                                                                                                |         | D-PTRV 4 WH                                                                          | 3270151 |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | White                                        | DP-PTRV 8                                                                                                                                                                      | 3270154 | D-PTRV 8 WH A-H                                                                      | 3270156 |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | White                                        |                                                                                                                                                                                |         | D-PTRV 8 WH 1-8                                                                      | 3270155 |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        | White/Unprinted                              |                                                                                                                                                                                |         | D-PTRV 8 WH                                                                          | 3270154 | ZB 8,3,LGS:FORTL.ZAHLEN                                                               | 0803445 |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        |                                              |                                                                                                                                                                                |         |                                                                                      |         | ZB 8,3,QR:FORTL.ZAHLEN                                                                | 0803446 |
| ...LG = Labelled lengthwise from 1-8 or A-H                                                                                                                                                                                                                                                                                                                                                                              |                        |                                              | Visit us online to view suitable marking material<br>ZBF 6/9,2 S8;LGS:1-8<br>ZBF 6/9,2 S8;LGS:A-H<br>ZBF 6/9,2 S8;QR:1-8<br>ZBF 6/9,2 S8;QR:A-H<br>ZBF 6/9,2 S8;LGS:UNBEDRUCKT |         |                                                                                      |         |                                                                                       |         |
| ...QR = Labelled crosswise from 1-8 or A-H                                                                                                                                                                                                                                                                                                                                                                               |                        |                                              |                                                                                                                                                                                |         |                                                                                      |         |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        |                                              |                                                                                                                                                                                |         |                                                                                      |         |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        |                                              |                                                                                                                                                                                |         |                                                                                      |         |                                                                                       |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                          |                        |                                              |                                                                                                                                                                                |         |                                                                                      |         |                                                                                       |         |

<sup>1)</sup> Can be bridged with FBST 500 PLC RD continuous bridge, Order No.: 2966786

## Freely configurable marshalling terminals, see ordering example

### Options for color configuration:

.../COL-RD = Left color can be configured, right red  
 .../COL-WH = Left color can be configured, right white  
 .../RD-COL = Left red, right color can be configured  
 .../WH-COL = Left white, red color can be configured  
 .../COL-COL = Left and right colors can be configured  
 (one color per level)



| Type                                              | Order No. | Gray      | PTRV 4 /COL-RD                               | 3001754 |
|---------------------------------------------------|-----------|-----------|----------------------------------------------|---------|
|                                                   |           | Gray      | PTRV 4 /COL-WH                               | 3001871 |
|                                                   |           | Gray      | PTRV 4 /RD-COL                               | 3001872 |
|                                                   |           | Gray      | PTRV 4 /WH-COL                               | 3001874 |
|                                                   |           | Gray      | PTRV 4 /COL-COL                              | 3001875 |
| Width / Length / Height                           |           | [mm]      | 8.3 / 64 / 55.5                              |         |
| Current / Voltage // UL                           |           | [A] / [V] | 10 / 250 // -                                |         |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / - | 0.14 - 2.5 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]     | 0.14 - 2.5 / 0.14 - 1.5                      |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]     | 0.34 - 2.5                                   |         |

### Options for color configuration:

.../COL-RDWH = Left color can be configured;  
 right top for 4 levels red, bottom 4 levels white  
 .../COL-WHRD = Left color can be configured;  
 right top 4 levels white, bottom 4 levels red  
 .../RDWH-COL = Left top 4 levels red,  
 bottom 4 levels white; right color can be configured  
 .../WHRD-COL = Left top 4 levels white,  
 bottom 4 levels red; right color can be configured  
 .../COL-COL = Left and right color can be configured  
 (one color per level)



|                                                   |           |           |                                              |         |
|---------------------------------------------------|-----------|-----------|----------------------------------------------|---------|
| Type                                              | Order No. | Gray      | PTRV 8 /COL-RDWH                             | 3001851 |
|                                                   |           | Gray      | PTRV 8 /COL-WHRD                             | 3001876 |
|                                                   |           | Gray      | PTRV 8 /RDWH-COL                             | 3001877 |
|                                                   |           | Gray      | PTRV 8 /WHRD-COL                             | 3001878 |
|                                                   |           | Gray      | PTRV 8 /COL-COL                              | 3001879 |
| Width / Length / Height                           |           | [mm]      | 8.3 / 100 / 87.5                             |         |
| Current / Voltage // UL                           |           | [A] / [V] | 8 / 250 // -                                 |         |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / - | 0.14 - 2.5 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]     | 0.14 - 2.5 / 0.14 - 1.5                      |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]     | 0.34 - 2.5                                   |         |

## Ordering example: Configurable marshalling terminals

### Ordering example:

An 8-level marshalling terminal is to have the following configuration in accordance with DIN VDE 0815:

The right side is marked red in the upper levels 1 - 4, and the lower levels 5 - 8 are marked white.

Please select order number 3001851 from the configurable items.

The levels on the left side should be colored.

Level 1: blue  
Level 2: red  
Level 3: gray  
Level 4: yellow  
Level 5: green  
Level 6: brown  
Level 7: white  
Level 8: black

Specify the color sequence when ordering, as illustrated below in the ordering example.


### Available colors:

|    |        |
|----|--------|
| BU | Blue   |
| RD | Red    |
| GY | Gray   |
| YE | Yellow |
| GN | Green  |
| BN | Brown  |
| WH | White  |
| BK | Black  |
| VT | Violet |
| OG | Orange |
| PK | Pink   |



### The order data for this order example is therefore:

| Order No. | Level 1 | Level 2 | Level 3 | Level 4 | Level 5 | Level 6 | Level 7 | Level 8 |
|-----------|---------|---------|---------|---------|---------|---------|---------|---------|
| 3001851   | BU      | RD      | GY      | YE      | GN      | BN      | WH      | BK      |




To ensure that your order is correct, you need a defined view. This is achieved when the snap-on foot in the top view is located on the left-hand side. In the top level, the letter L is visible.




# Simple, reliable and intuitive marshalling – PTMC marshalling patchboard with push-in connection

Due to its design, the PTMC marshalling patchboard provides you with the highest signal density during marshalling in automation applications. The modular structure, accurate to the number of poles and with colored matrix elements, ensures space-saving, clearly arranged and error-free wiring.


Adapters are available for rack mounting as an alternative to DIN rail mounting.



The patchboard's marshalling system features a modular design and the positions can be configured specifically tailored to the application. The elements snap into place easily and securely, creating an extremely stable patchboard construction resistant to warping in its blocked form.



Up to 20% higher signal density compared to 19 inch variants available on the market thanks to its compact design.



Wire by color: Freely configurable color assignment for conductors and terminal points enables reliable and intuitive installation. Configure the right marshalling patchboard from eleven available colors.

## Marshalling patchboards, for self-assembly

|                                                   |           |                                                                                   |                                              |                                                                                    |                                              |         |
|---------------------------------------------------|-----------|-----------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------------------------------------|----------------------------------------------|---------|
|                                                   |           |  |                                              |  |                                              |         |
| Type                                              | Order No. | Gray                                                                              | PTMC 1,5-2 /GY                               | 3270302                                                                            | PTMC 1,5-3 /GY                               | 3270300 |
|                                                   |           | White                                                                             | PTMC 1,5-2 /WH                               | 3270303                                                                            | PTMC 1,5-3 /WH                               | 3270301 |
|                                                   |           | Blue                                                                              | PTMC 1,5-2 /BU                               | 3270430                                                                            | PTMC 1,5-3 /BU                               | 3270420 |
|                                                   |           | Red                                                                               | PTMC 1,5-2 /RD                               | 3270431                                                                            | PTMC 1,5-3 /RD                               | 3270421 |
|                                                   |           | Green                                                                             | PTMC 1,5-2 /GN                               | 3270432                                                                            | PTMC 1,5-3 /GN                               | 3270422 |
|                                                   |           | Brown                                                                             | PTMC 1,5-2 /BN                               | 3270433                                                                            | PTMC 1,5-3 /BN                               | 3270423 |
|                                                   |           | Black                                                                             | PTMC 1,5-2 /BK                               | 3270434                                                                            | PTMC 1,5-3 /BK                               | 3270424 |
|                                                   |           | Violet                                                                            | PTMC 1,5-2 /VT                               | 3270435                                                                            | PTMC 1,5-3 /VT                               | 3270425 |
|                                                   |           | Orange                                                                            | PTMC 1,5-2 /OG                               | 3270436                                                                            | PTMC 1,5-3 /OG                               | 3270426 |
|                                                   |           | Yellow                                                                            | PTMC 1,5-2 /YE                               | 3270437                                                                            | PTMC 1,5-3 /YE                               | 3270427 |
|                                                   |           | Pink                                                                              | PTMC 1,5-2 /PK                               | 3270438                                                                            | PTMC 1,5-3 /PK                               | 3270428 |
| Width / Length / Height                           |           | [mm]                                                                              | 11 / 12.2 / 30                               |                                                                                    | 11 / 12.2 / 30                               |         |
| Current / Voltage // UL                           |           | [A] / [V]                                                                         | 17.5 / 500 //                                |                                                                                    | 17.5 / 500 //                                |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -                                                            | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12 |                                                                                    | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12 |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                                                                | 0.14 - 1.5 / 0.14 - 1.5                      |                                                                                    | 0.14 - 1.5 / 0.14 - 1.5                      |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                                                                | 0.34 - 2.5                                   |                                                                                    | 0.34 - 2.5                                   |         |

## Cover flange for direct mounting and marker adapter

|                                                                                    |           |                                                                                    |           |                                                                                     |           |                                                                                      |                |         |
|------------------------------------------------------------------------------------|-----------|------------------------------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------|-----------|--------------------------------------------------------------------------------------|----------------|---------|
|  |           |  |           |  |           |  |                |         |
| Type                                                                               | Order No. | Gray                                                                               | DF-PTMC-O | 3270400                                                                             | DF-PTMC-U | 3270401                                                                              | DF-PTMC-ZB     | 3270410 |
|                                                                                    |           |                                                                                    | Top       |                                                                                     |           | Bottom                                                                               |                |         |
|                                                                                    |           |                                                                                    |           |                                                                                     |           |                                                                                      | Marker carrier |         |

## Adapter for DIN rail mounting

|                                                                                     |           |                                                                                     |                  |                                                                                      |                |         |  |
|-------------------------------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------|------------------|--------------------------------------------------------------------------------------|----------------|---------|--|
|  |           |  |                  |  |                |         |  |
| Type                                                                                | Order No. | Gray                                                                                | DF-PTMC-NS       | 3270403                                                                              | DF-PTMC-ZB     | 3270410 |  |
|                                                                                     |           |                                                                                     | DIN rail adapter |                                                                                      | Marker carrier |         |  |

## Marshalling patchboards, pre-assembled with four connections per element

|                                                   |           |              |  |                    |  |                    |  |                    |
|---------------------------------------------------|-----------|--------------|-----------------------------------------------------------------------------------|--------------------|------------------------------------------------------------------------------------|--------------------|-------------------------------------------------------------------------------------|--------------------|
| Type                                              | Order No. | Gray<br>Blue | PTMC 1,5/32-2<br>PTMC 1,5/32-2 BU                                                 | 3270314<br>3270315 | PTMC 1,5/48-2<br>PTMC 1,5/48-2 BU                                                  | 3270322<br>3270323 | PTMC 1,5/80-2<br>PTMC 1,5/80-2 BU                                                   | 3270329<br>3270330 |
| Width / Length / Height                           |           | [mm]         | 44 / 73.2 / 30                                                                    |                    | 66 / 73.2 / 30                                                                     |                    | 110 / 73.2 / 30                                                                     |                    |
| Current / Voltage // UL                           |           | [A] / [V]    | 17.5 / 500 // -                                                                   |                    | 17.5 / 500 // -                                                                    |                    | 17.5 / 500 // -                                                                     |                    |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -    | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                      |                    | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                       |                    | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                        |                    |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]        | 0.14 - 1.5 / 0.14 - 1.5                                                           |                    | 0.14 - 1.5 / 0.14 - 1.5                                                            |                    | 0.14 - 1.5 / 0.14 - 1.5                                                             |                    |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]        | 0.34 - 2.5                                                                        |                    | 0.34 - 2.5                                                                         |                    | 0.34 - 2.5                                                                          |                    |

## Marshalling patchboards, pre-assembled with six connections per element

|                                                   |           |              |  |                    |  |                    |  |                    |
|---------------------------------------------------|-----------|--------------|-----------------------------------------------------------------------------------|--------------------|------------------------------------------------------------------------------------|--------------------|-------------------------------------------------------------------------------------|--------------------|
| Type                                              | Order No. | Gray<br>Blue | PTMC 1,5/32-3<br>PTMC 1,5/32-3 BU                                                 | 3270310<br>3270312 | PTMC 1,5/48-3<br>PTMC 1,5/48-3 BU                                                  | 3270318<br>3270320 | PTMC 1,5/80-3<br>PTMC 1,5/80-3 BU                                                   | 3270324<br>3270326 |
| Width / Length / Height                           |           | [mm]         | 44 / 102 / 30                                                                     |                    | 66 / 102 / 30                                                                      |                    | 110 / 102 / 30                                                                      |                    |
| Current / Voltage // UL                           |           | [A] / [V]    | 17.5 / 500 // -                                                                   |                    | 17.5 / 500 // -                                                                    |                    | 17.5 / 500 // -                                                                     |                    |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -    | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                      |                    | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                       |                    | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                        |                    |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]        | 0.14 - 1.5 / 0.14 - 1.5                                                           |                    | 0.14 - 1.5 / 0.14 - 1.5                                                            |                    | 0.14 - 1.5 / 0.14 - 1.5                                                             |                    |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]        | 0.34 - 2.5                                                                        |                    | 0.34 - 2.5                                                                         |                    | 0.34 - 2.5                                                                          |                    |

## Marshalling patchboards, pre-assembled for 19 inch rack, four connections per element

|                                                   |           |              |                                                                                   |                    |  |  |  |
|---------------------------------------------------|-----------|--------------|-----------------------------------------------------------------------------------|--------------------|--|--|--|
|                                                   |           |              |  |                    |  |  |  |
| Type                                              | Order No. | Gray<br>Blue | PTMC 1,5/32-2H 19Z<br>PTMC 1,5/32-2H /BU 19Z                                      | 3270316<br>3270317 |  |  |  |
| Width / Length / Height                           |           | [mm]         | 34.4 / 111 / 30                                                                   |                    |  |  |  |
| Current / Voltage // UL                           |           | [A] / [V]    | 17.5 / 500 // -                                                                   |                    |  |  |  |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -    | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                      |                    |  |  |  |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]        | 0.14 - 1.5 / 0.14 - 1.5                                                           |                    |  |  |  |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]        | 0.34 - 2.5                                                                        |                    |  |  |  |

## Marshalling patchboards, pre-assembled for 19 inch rack, six connections per element

|                                                   |           |              |                                                                                   |                                              |                                                                                    |                                              |                                                                                     |                    |
|---------------------------------------------------|-----------|--------------|-----------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------------------------------------|----------------------------------------------|-------------------------------------------------------------------------------------|--------------------|
|                                                   |           |              |  |                                              |  |                                              |  |                    |
| Type                                              | Order No. | Gray<br>Blue | PTMC 1,5/32-3 19Z<br>PTMC 1,5/32-3 /BU 19Z                                        | 3270311<br>3270313                           | PTMC 1,5/48-3 19Z<br>PTMC 1,5/48-3 /BU 19Z                                         | 3270319<br>3270321                           | PTMC 1,5/80-3 19Z<br>PTMC 1,5/80-3 /BU 19Z                                          | 3270325<br>3270327 |
| Width / Length / Height                           |           | [mm]         | 44 / 111 / 30                                                                     | 66 / 111 / 30                                |                                                                                    | 110 / 111 / 30                               |                                                                                     |                    |
| Current / Voltage // UL                           |           | [A] / [V]    | 17.5 / 500 // -                                                                   | 17.5 / 500 // -                              |                                                                                    | 17.5 / 500 // -                              |                                                                                     |                    |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -    | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                      | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12 |                                                                                    | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12 |                                                                                     |                    |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]        | 0.14 - 1.5 / 0.14 - 1.5                                                           | 0.14 - 1.5 / 0.14 - 1.5                      |                                                                                    | 0.14 - 1.5 / 0.14 - 1.5                      |                                                                                     |                    |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]        | 0.34 - 2.5                                                                        | 0.34 - 2.5                                   |                                                                                    | 0.34 - 2.5                                   |                                                                                     |                    |

## Marshalling patchboards for free assembly for direct mounting

|                                                   |           |                        |                                                                                   |         |                                                                                     |         |  |
|---------------------------------------------------|-----------|------------------------|-----------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------|---------|--|
|                                                   |           |                        |  |         |  |         |  |
| Type                                              | Order No. | Gray                   | PTMC 1,5/1-2-DF                                                                   | 3001937 | PTMC 1,5/1-3-DF                                                                     | 3001929 |  |
|                                                   |           |                        | PTMC 1,5/2-2-DF                                                                   | 3001940 | PTMC 1,5/2-3-DF                                                                     | 3001930 |  |
|                                                   |           |                        | PTMC 1,5/3-2-DF                                                                   | 3001942 | PTMC 1,5/3-3-DF                                                                     | 3001931 |  |
|                                                   |           |                        | PTMC 1,5/4-2-DF                                                                   | 3001943 | PTMC 1,5/4-3-DF                                                                     | 3001932 |  |
|                                                   |           |                        | PTMC 1,5/5-2-DF                                                                   | 3001944 | PTMC 1,5/5-3-DF                                                                     | 3001933 |  |
|                                                   |           |                        | PTMC 1,5/6-2-DF                                                                   | 3001945 | PTMC 1,5/6-3-DF                                                                     | 3001934 |  |
|                                                   |           |                        | PTMC 1,5/7-2-DF                                                                   | 3001946 | PTMC 1,5/7-3-DF                                                                     | 3001935 |  |
|                                                   |           |                        | PTMC 1,5/8-2-DF                                                                   | 3001947 | PTMC 1,5/8-3-DF                                                                     | 3001936 |  |
| Width / Length / Height                           |           | [mm]                   | - / 30 / -                                                                        |         | - / 30 / -                                                                          |         |  |
| Current / Voltage // UL                           |           | [A] / [V]              | 10 / 500 //                                                                       |         | 10 / 500 //                                                                         |         |  |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                      |         | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                        |         |  |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]     | 0.14 - 1.5 / 0.14 - 1.5                                                           |         | 0.14 - 1.5 / 0.14 - 1.5                                                             |         |  |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5                                                                        |         | 0.34 - 2.5                                                                          |         |  |

## Marshalling patchboards for free assembly for DIN rail mounting

|                                                   |           |                        |                                                                                   |         |                                                                                    |         |  |
|---------------------------------------------------|-----------|------------------------|-----------------------------------------------------------------------------------|---------|------------------------------------------------------------------------------------|---------|--|
|                                                   |           |                        |  |         |  |         |  |
| Type                                              | Order No. | Gray                   | PTMC 1,5/1-2-NS                                                                   | 3001915 | PTMC 1,5/1-3-NS                                                                    | 3001905 |  |
|                                                   |           |                        | PTMC 1,5/2-2-NS                                                                   | 3001916 | PTMC 1,5/2-3-NS                                                                    | 3001906 |  |
|                                                   |           |                        | PTMC 1,5/3-2-NS                                                                   | 3001917 | PTMC 1,5/3-3-NS                                                                    | 3001907 |  |
|                                                   |           |                        | PTMC 1,5/4-2-NS                                                                   | 3001918 | PTMC 1,5/4-3-NS                                                                    | 3001908 |  |
|                                                   |           |                        | PTMC 1,5/5-2-NS                                                                   | 3001919 | PTMC 1,5/5-3-NS                                                                    | 3001910 |  |
|                                                   |           |                        | PTMC 1,5/6-2-NS                                                                   | 3001920 | PTMC 1,5/6-3-NS                                                                    | 3001911 |  |
|                                                   |           |                        | PTMC 1,5/7-2-NS                                                                   | 3001921 | PTMC 1,5/7-3-NS                                                                    | 3001913 |  |
|                                                   |           |                        | PTMC 1,5/8-2-NS                                                                   | 3001922 | PTMC 1,5/8-3-NS                                                                    | 3001914 |  |
| Width / Length / Height                           |           | [mm]                   | - / 63 / 22.6                                                                     |         | - / 63 / 22.6                                                                      |         |  |
| Current / Voltage // UL                           |           | [A] / [V]              | 10 / 500 //                                                                       |         | 10 / 500 //                                                                        |         |  |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                      |         | 0.14 - 2.5 / 26 - 12 // 0.14 - 1.5 / 26 - 12                                       |         |  |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]     | 0.14 - 1.5 / 0.14 - 1.5                                                           |         | 0.14 - 1.5 / 0.14 - 1.5                                                            |         |  |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 2.5                                                                        |         | 0.34 - 2.5                                                                         |         |  |

# Ordering example: configurable marshalling patchboard

## Ordering example:

A marshalling patchboard should be configured as follows:

Actuation lever, screw fixing of marshalling patchboard. three connections per individual element.  
Four rows in the X direction and ten columns in the Y direction.

Please select order number 3001932 from the configurable items.  
In the order designation, the 4 means -> four rows in the X direction  
In the order designation, the 3 means -> three connections


Row 1: blue  
Row 2: red  
Row 3: gray  
Row 4: yellow

Only rows of the same color are viable in the X direction.  
Please state the number of columns when ordering.  
A minimum of 2 columns and a maximum of 20 columns can be ordered.

Please order marker adapter, DF-PTMC-ZB Order No. 3270410, as an accessory.

## Available colors:


|    |        |
|----|--------|
| BU | Blue   |
| RD | Red    |
| GY | Gray   |
| YE | Yellow |
| GN | Green  |
| BN | Brown  |
| WH | White  |
| BK | Black  |
| VT | Violet |
| OG | Orange |
| PK | Pink   |



## The order data for this order example is therefore:

| Order No. | Columns | Row 1 | Row 2 | Row 3 | Row 4 |
|-----------|---------|-------|-------|-------|-------|
| 3001932   | 10      | BU    | RD    | GY    | YE    |

Fixing material for panel or DIN rail mounting will be supplied in sufficient quantities.




# Flexible for all transformer test wiring – PTME test disconnect terminal blocks



The new test disconnect terminal blocks can be used to design space-saving and modular switchgear. Feed-through and PE terminal blocks of the same shape are also available for the test disconnect terminal blocks. The patented short-circuit plug is particularly user-friendly and safe: measuring transducers are protected against damage by means of automatic short circuit.

CLIP PROJECT planning software provides support in planning your terminal strips quickly and conveniently.


The triple function shaft on both sides of the longitudinal disconnect point enables the individual placement of bridging, testing, and switching accessories. Non-adjacent jumpers allow the star point to be formed conveniently within the terminal strip, without the need for additional wire jumpers.



The plug-in current transformer disconnect terminal blocks also enable the safe plug-in wiring of current transformers. When the transformer plug is removed, a leading current transformer short circuit is automatically ensured. Additional coding accessories prevent the plug's polarity from being reversed.




The section disconnecter reliably makes contact and latches with a swiveling movement in the respective switching state. Switching symbols and optional switching locks also ensure a clear overview inside the measuring transducer terminal strip.




The plug-in current transformer short-circuit jumpers can be used individually, based on the switching task, in the terminal block function shafts.

The switching jumper disconnect element is operated with a screwdriver, which means that the switching operation is only ever activated intentionally.



The current transformer short circuit can be easily implemented using standard FBL jumpers. FBSRH versions with molded extraction tool are available as 2, 3 and 4 position.



Cover profiles and covering hoods are available as accessories. These can be mounted and sealed on measuring transducer strips as protection against external influences and tampering.

## Push-in connection technology 4 mm<sup>2</sup>

|                                                   |           |                        |                                                                                   |         |                                                                                    |         |                                                                                     |         |
|---------------------------------------------------|-----------|------------------------|-----------------------------------------------------------------------------------|---------|------------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------|---------|
|                                                   |           |                        |  |         |  |         |  |         |
| Type                                              | Order No. | Gray<br>Green-yellow   | PTME 4                                                                            | 3212139 | PTMED 4                                                                            | 3212141 | PTMED 4-PE                                                                          | 3212154 |
| Width / Length / Height                           |           | [mm]                   | 6.2 / 70.5 / 49.5                                                                 |         | 6.2 / 70.5 / 49.5                                                                  |         | 6.2 / 70.5 / 49.5                                                                   |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 24 / 500 // 26 / 300                                                              |         | 24 / 500 // 26 / 300                                                               |         | - / - // - / -                                                                      |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                            |         | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                             |         | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                              |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]     | 0.25 - 4                                                                          |         | 0.25 - 4                                                                           |         | 0.25 - 4                                                                            |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.5 - 4 / 0.5 - 6                                                                 |         | 0.5 - 4 / 0.5 - 6                                                                  |         | 0.5 - 4 / 0.5 - 6                                                                   |         |

## Push-in connection technology 6 mm<sup>2</sup>

|                                                   |           |                                      |                                                                                   |                               |                                                                                    |         |                                                                                     |         |
|---------------------------------------------------|-----------|--------------------------------------|-----------------------------------------------------------------------------------|-------------------------------|------------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------|---------|
| '1) Rated voltage for open disconnect point 500 V |           |                                      |  |                               |  |         |  |         |
| Type                                              | Order No. | Gray<br>Gray<br>Blue<br>Green-yellow | PTME 6<br>PTME 6 HV <sup>1)</sup><br>PTME 6 HV BU <sup>1)</sup>                   | 3212170<br>3035696<br>3035695 | PTMED 6                                                                            | 3212183 | PTMED 6-PE                                                                          | 3212196 |
| Width / Length / Height                           |           | [mm]                                 | 8.2 / 100.8 / 49.6                                                                |                               | 8.2 / 100.8 / 49.6                                                                 |         | 8.2 / 100.8 / 49.6                                                                  |         |
| Current / Voltage // UL                           |           | [A] / [V]                            | 30 / 500 // 30 / 600                                                              |                               | 30 / 500 // 30 / 600                                                               |         | - / - // - / -                                                                      |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -               | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                            |                               | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                             |         | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                              |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                   | 0.5 - 6                                                                           |                               | 0.5 - 6                                                                            |         | 0.5 - 6                                                                             |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                   | 1 - 6 / 1 - 10                                                                    |                               | 1 - 6 / 1 - 10                                                                     |         | 1 - 6 / 1 - 10                                                                      |         |

## Hybrid terminal blocks with screw connection on one side 6 mm<sup>2</sup>

|                                                                                                                                                                                |           |                        |                                                                                     |                              |                                                                                      |                              |  |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------------|-------------------------------------------------------------------------------------|------------------------------|--------------------------------------------------------------------------------------|------------------------------|--|--|
| <b>Note:</b><br>You can find wiring and testing accessories in the product area on our website at <a href="http://phoenixcontact.net/products">phoenixcontact.net/products</a> |           |                        |  |                              |  |                              |  |  |
| Type                                                                                                                                                                           | Order No. | Gray<br>Gray           | PTU 6-T<br>PTU 6-T-P                                                                | 3209535<br>3209530           | PTUD 6<br>PTUD 6-P                                                                   | 3209531<br>3209537           |  |  |
| Width / Length / Height                                                                                                                                                        |           | [mm]                   | 8.2 / 73.9 / 48                                                                     |                              | 8.2 / 73.9 / 48                                                                      |                              |  |  |
| Current / Voltage // UL                                                                                                                                                        |           | [A] / [V]              | 52 / 500 // -                                                                       |                              | 52 / 800 // -                                                                        |                              |  |  |
| Solid/AWG                                                                                                                                                                      |           | [mm <sup>2</sup> ] / - | Screw<br>0.5 - 10 / 20 - 8                                                          | Push-in<br>0.5 - 10 / 20 - 8 | Screw<br>0.5 - 10 / 20 - 8                                                           | Push-in<br>0.5 - 10 / 20 - 8 |  |  |
| Stranded with ferrule without/with plastic sleeve                                                                                                                              |           | [mm <sup>2</sup> ]     | 0.5 - 6                                                                             | 0.5 - 6                      | 0.5 - 6                                                                              | 0.5 - 6                      |  |  |
| Can be plugged in directly: with ferrule / solid                                                                                                                               |           | [mm <sup>2</sup> ]     |                                                                                     | 1 - 6                        |                                                                                      | 1 - 6                        |  |  |

## PT-COMBI push-in connection terminal blocks 6 mm<sup>2</sup>, plug-in connection

|                                                   |           |                        |                                                                                                                                                                      |         |                                       |
|---------------------------------------------------|-----------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------------------------------------|
| <sup>1)</sup> Derating curve on request           |           |                        |   |         |                                       |
| Type                                              | Order No. | Gray                   | PTME 6/1P                                                                                                                                                            | 3212306 | Vertical conductor connection         |
| 1-pos.                                            |           | Gray                   |                                                                                                                                                                      |         | PP-H 6/1 <sup>1)</sup> 3061541        |
| 2-pos.                                            |           | Gray                   |                                                                                                                                                                      |         | PP-H 6/2 3061570                      |
| 3-pos.                                            |           | Gray                   |                                                                                                                                                                      |         | PP-H 6/3 3061583                      |
| 4-pos.                                            |           | Gray                   |                                                                                                                                                                      |         | PP-H 6/4 3061596                      |
| 5-pos.                                            |           | Gray                   |                                                                                                                                                                      |         | PP-H 6/5 3061606                      |
| 6-pos.                                            |           | Gray                   |                                                                                                                                                                      |         | PP-H 6/6 3061619                      |
| 7-pos.                                            |           | Gray                   |                                                                                                                                                                      |         | PP-H 6/7 3061622                      |
| 8-pos.                                            |           | Gray                   |                                                                                                                                                                      |         | PP-H 6/8 3061635                      |
| 9-pos.                                            |           | Gray                   |                                                                                                                                                                      |         | PP-H 6/9 3061648                      |
| 10-pos.                                           |           | Gray                   |                                                                                                                                                                      |         | PP-H 6/10 3061651                     |
| 1-pos.                                            |           | Blue                   |                                                                                                                                                                      |         | PP-H 6/1 BU 3061554                   |
| 1-pos.                                            |           | Green-yellow           |                                                                                                                                                                      |         | PP-H 6/1 GNYE 3061567                 |
| Width / Length / Height                           |           | [mm]                   | 8.2 / 99.4 / 49.6                                                                                                                                                    |         | 8.2 / 21 / 49.3                       |
| Current / Voltage // UL                           |           | [A] / [V]              | 30 / 500 // 30 / 600                                                                                                                                                 |         | 41 / 1000 // 40 / 600                 |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 8                                                                                                                                |         | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 8 |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]     | 0.5 - 6                                                                                                                                                              |         | 0.5 - 6                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 1.0 - 10                                                                                                                                                             |         | 1.0 - 10                              |

## PT-COMBI push-in connection terminal blocks 6 mm<sup>2</sup>, plug-in connection, with automatic short-circuit function

|                                                             |           |                                      |                                                                                    |         |                                                                                     |                    |                                                                                      |  |
|-------------------------------------------------------------|-----------|--------------------------------------|------------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------|--------------------|--------------------------------------------------------------------------------------|--|
| <sup>1)</sup> Rated voltage for open disconnect point 500 V |           |                                      |  |         |  |                    |  |  |
| Type                                                        | Order No. | Gray<br>Green-yellow<br>Gray<br>Gray | PTME 6-CT/1P                                                                       | 3212300 | PTMED 6-CT/1P<br>PTMED 6-CT/1P-PE                                                   | 3212301<br>3212302 | 2-pos. and 3-pos. plugs                                                              |  |
| Width / Length / Height                                     |           | [mm]                                 | 8.2 / 114.9 / 49.6                                                                 |         | 8.2 / 114.9 / 49.6                                                                  |                    | 16.4 / 38.5 / 48.5                                                                   |  |
| Current / Voltage // UL                                     |           | [A] / [V]                            | 30 / 500 // 30 / 600                                                               |         | 30 / 500 // 30 / 600                                                                |                    | 20 / 320 // 30 / 600                                                                 |  |
| Solid / AWG // Stranded / AWG                               |           | [mm²] / –                            | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 8                                              |         | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 8                                               |                    | 0.5 - 10 / 20 - 10 // 0.5 - 6 / 20 - 10                                              |  |
| Stranded with ferrule without/with plastic sleeve           |           | [mm²]                                | 0.5 - 6                                                                            |         | 0.5 - 6                                                                             |                    | 0.5 - 6                                                                              |  |
| Can be plugged in directly: with ferrule / solid            |           | [mm²]                                | 1 - 10                                                                             |         | 1 - 10                                                                              |                    | 1 - 10                                                                               |  |
|                                                             |           |                                      |                                                                                    |         |                                                                                     |                    | PPCT 6/2 3212304<br>PPCT 6/3 3212305                                                 |  |

## Accessories for plugs

|            |            |         |               |         |                            |         |                   |         |
|------------|------------|---------|---------------|---------|----------------------------|---------|-------------------|---------|
|            |            |         |               |         |                            |         |                   |         |
|            | Coding set |         | Strain relief |         | Latching and strain relief |         | Locking mechanism |         |
| PP-H 6 ... | PC         | 3040588 | PZ/2          | 3040627 | PRZ                        | 3040614 | PR/2              | 3040630 |
| PPCT 6/2   | PC-CT 6/2  | 3212308 | PZ/2          | 3040627 | PRZ                        | 3040614 | PR/2              | 3040630 |
| PPCT 6/3   | PC-CT 6/3  | 3212309 | PZ/2          | 3040627 | PRZ                        | 3040614 | PR/2              | 3040630 |

## PTME test disconnect terminal blocks – accessories


| Mounting material                                                                                                       | Type                                               | Order No.          | Mounting material                                                                                                                                          | Type                                                                                                               | Order No.                                                                                                                                                                                                                                           |
|-------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 6 35 x 7.5 mm DIN rail<br>galvanized and thick layer passivated<br>unperforated<br>perforated                           | NS 35/7,5 UNPERF 2000 MM<br>NS 35/7,5 PERF 2000 MM | 0801681<br>0801733 | 16 Connection bridge, for connecting test dis-<br>connect terminal blocks,<br>for PTME 4<br><br>for PTME 6                                                 | 2-pos.<br>3-pos.                                                                                                   | C-ME 4/2<br>C-ME 4/3<br><br>3035759<br>3035760                                                                                                                                                                                                      |
| 7 Terminal strip marker carriers,<br>adjustable height,<br>for CLIPFIX 35-5,<br>can be marked with label                | KLM 3-L                                            | 0814788            |                                                                                                                                                            | 1-pos.<br>2-pos.<br>3-pos.                                                                                         | C-ME 6/1<br>C-ME 6/2<br>C-ME 6/3<br><br>3034441<br>3034442<br>3034390                                                                                                                                                                               |
| 8 Separating disk,<br>with storage option<br>for jumpers FBS ...-8                                                      | CARRIER 35-8                                       | 3034387            |                                                                                                                                                            | 17 Test adapter,<br>for PTME 6<br><br>Orange<br>Yellow<br>Green<br>Violet<br>Black<br>Blue<br>Red<br>Gray<br>Brown | PAI-4-FIX OG<br>PAI-4-FIX YE<br>PAI-4-FIX GN<br>PAI-4-FIX VT<br>PAI-4-FIX BK<br>PAI-4-FIX BU<br>PAI-4-FIX RD<br>PAI-4-FIX GY<br>PAI-4-FIX BN<br><br>3034455<br>3032745<br>3032758<br>3032761<br>3032774<br>3032729<br>3032732<br>3032790<br>3032787 |
| 9 Screwdriver                                                                                                           | SZF 2-0,8X4,0                                      | 1204520            |                                                                                                                                                            |                                                                                                                    | 17 Test adapter,<br>for PTME(D) 4<br><br>Orange<br>Yellow<br>Green<br>Violet<br>Black<br>Blue<br>Red<br>Gray<br>Brown                                                                                                                               |
| 10 Quick mounting end bracket,<br>with parking option for FBS...-6<br>Width / Length / Height<br>5 mm / 48,5 mm / 35 mm | CLIPFIX 35-5                                       | 3022276            | 1) Jumpers with molded extraction tool,<br>for PTME 6<br><br>2-pos. FBSRH 2-8<br>3-pos. FBSRH 3-8<br>4-pos. FBSRH 4-8<br><br>3033802<br>3033803<br>3033804 |                                                                                                                    |                                                                                                                                                                                                                                                     |
| 11 DIN rail end cap,<br>for DIN rail NS 35/7,5<br>for DIN rail NS 35/15                                                 | NS 35/7,5 CAP<br>NS 35/15 CAP                      | 1206560<br>1206573 |                                                                                                                                                            |                                                                                                                    |                                                                                                                                                                                                                                                     |
| 12 Cover profile                                                                                                        | AP-ME METER                                        | 3034361            |                                                                                                                                                            |                                                                                                                    |                                                                                                                                                                                                                                                     |
| Covering hood <sup>1)</sup>                                                                                             | AH-ME                                              | 3240265            |                                                                                                                                                            |                                                                                                                    |                                                                                                                                                                                                                                                     |
| 13 End brackets,<br>for AP-ME cover profile, sealable,<br>with storage option<br>for jumpers                            | APH-ME                                             | 3034374            |                                                                                                                                                            |                                                                                                                    |                                                                                                                                                                                                                                                     |
| 14 Holder,<br>for AP-ME cover profile                                                                                   | APT-ME                                             | 3034358            |                                                                                                                                                            |                                                                                                                    |                                                                                                                                                                                                                                                     |
| 15 Switching lock, plug-in,<br>for PTME 4                                                                               | S-ME 4<br>S-ME 6                                   | 3035758<br>3034439 |                                                                                                                                                            |                                                                                                                    |                                                                                                                                                                                                                                                     |

1) The figure can be found in the product area on the website.

<sup>1)</sup> The figure can be found in the product area on the website.

| Terminal        | 1                  |                    |                    |                    |                     |                  | 2                             |                               |                               |                                 |                                       |
|-----------------|--------------------|--------------------|--------------------|--------------------|---------------------|------------------|-------------------------------|-------------------------------|-------------------------------|---------------------------------|---------------------------------------|
|                 | Jumpers            |                    |                    |                    |                     |                  | Pre-assembled jumpers         |                               |                               |                                 |                                       |
|                 | 2-pos.             | 3-pos.             | 4-pos.             | 5-pos.             | 10-pos.             | I <sub>max</sub> | 3-pos.<br>Position 1<br>and 3 | 4-pos.<br>Position 1<br>and 4 | 5-pos.<br>Position 1<br>and 5 | 5-pos.<br>Position 1.3<br>and 5 | 10-pos.<br>Position 1, 4, 7<br>and 10 |
| PTME ... 4 ...  | FBS 2-6<br>3030336 | FBS 3-6<br>3030242 | FBS 4-6<br>3030255 | FBS 5-6<br>3030349 | FBS 10-6<br>3030271 | 32 A             | –                             | –                             | –                             | –                               | –                                     |
| PTME ... 6 ...  | FBS 2-8<br>3030284 | FBS 3-8<br>3030297 | FBS 4-8<br>3030307 | FBS 5-8<br>3030310 | FBS 10-8<br>3030323 | 41 A             | FBS 1/3-8<br>3032363          | FBS 1/4-8<br>3032376          | FBS 1/5-8<br>3032381          | FBS 1/3/5-8<br>3032389          | FBS 1/4/7/10-8<br>3032402             |
| PTME ... 6/1P   | FBS 2-8<br>3030284 | FBS 3-8<br>3030297 | FBS 4-8<br>3030307 | FBS 5-8<br>3030310 | FBS 10-8<br>3030323 | 41 A             | FBS 1/3-8<br>3032363          | FBS 1/4-8<br>3032376          | FBS 1/5-8<br>3032381          | FBS 1/3/5-8<br>3032389          | FBS 1/4/7/10-8<br>3032402             |
| PTME 6-CT/1P-PE | FBS 2-8<br>3030284 | FBS 3-8<br>3030297 | FBS 4-8<br>3030307 | FBS 5-8<br>3030310 | FBS 10-8<br>3030323 | –                | FBS 1/3-8<br>3032363          | FBS 1/4-8<br>3032376          | FBS 1/5-8<br>3032381          | FBS 1/3/5-8<br>3032389          | FBS 1/4/7/10-8<br>3032402             |

Additional jumpers and numbers of positions can be found in main catalog 3 or the product area on our website at [phenixcontact.net/products](http://phenixcontact.net/products).



| I <sub>max</sub> | Switching jumper <sup>2)</sup> |                      |                      | I <sub>max</sub> | Cover                     | Marking            |                           |
|------------------|--------------------------------|----------------------|----------------------|------------------|---------------------------|--------------------|---------------------------|
|                  | 2-pos.                         | 3-pos.               | 4-pos.               |                  |                           | Center groove      | Center and lateral groove |
| –                | SB-ME 2-6<br>3035755           | SB-ME 3-6<br>3035756 | SB-ME 4-6<br>3035757 | 25 A             | D-PTME 4<br>3212167       | UC-TM 6<br>0818085 | UC-TMF 6<br>0818140       |
| 41 A             | SB-ME 2-8<br>3034468           | SB-ME 3-8<br>3032800 | SB-ME 4-8<br>3034484 | 30 A             | D-DTME 6<br>3034426       | UC-TM 8<br>0818072 | UC-TMF 8<br>0818137       |
| 41 A             | SB-ME 2-8<br>3034468           | SB-ME 3-8<br>3032800 | SB-ME 4-8<br>3034484 | 30 A             | D-PTME 6/1P<br>3212307    | UC-TM 8<br>0818072 | UC-TMF 8<br>0818137       |
| 41 A             | –                              | –                    | –                    | –                | D-PTME 6-CT/1P<br>3212303 | UC-TM 8<br>0818072 | UC-TMF 8<br>0818137       |

<sup>2)</sup> Additional jumpers can be found in main catalog 3 or in the product area on the website at [phoenixcontact.net/products](http://phoenixcontact.net/products).

# Safe and reliable testing – FAME test system with push-in connection

FAME 2 is the innovative test system for all measuring and testing tasks in network protection technology for medium and high-voltage switchgear. With the modular system, you can now perform manual testing automatically, safely, and more quickly.

The test system combines the switching operations of the functions current transformer, voltage transformer and signal contact in just one single block.



Variants for the control cabinet wall or DIN rail.




Step 1:  
Plug is locked  
– Transformer and  
signals isolated safely



Step 2:  
Plug is partially unlocked  
– Transformer makes  
contact



Step 3:  
Plug is completely  
unlocked  
– Signal lines make  
contact




The test plug features three different contact tab lengths. With just one switching operation, it is possible to carry out the switching sequence of the individual functions with safe chronological disconnection. The plugs can be easily configured and ordered with just a click of the mouse in the E-shop.




The patented wall fastening is easy to use and has a robust design.

## Push-in Technology

Designed by PHOENIX CONTACT



reddot award 2014  
winner industrial design



The test plug provides three function shafts. Horizontally aligned, as leading short-circuit jumper - vertically aligned as through connection in the plug. Staggered test sockets enable the use of safety test leads in a confined space.

In addition to the two marking grooves, the test terminal strips for wall mounting also offer two function shafts, or six function shafts in the case of the DIN rail version, inside the control cabinet for forming and grounding the star point.

The compact and modular design of the system, as well as the plugs and test terminal strips, provides an extensive range of options for every application with positions from 4 to 25.


# Modular connection solutions – PT plug-in modular terminal blocks with push-in connection

The COMBI connection system enables the time-saving and modular configuration of your application.

The nominal ratings up to 41 A and 1000 V provide a basis for a unique connection system for signal and power wiring. The system meets the most stringent of vibration requirements. Extensive accessories are available, from latching mechanisms to shield connections.



The CES cable entry system allows you to insert a variety of pre-assembled conductors, cables, and protective hoses into areas with limited space in control cabinets, distributor boxes or devices, in a way which protects them against water and dust.






The COMBI connection system enables the time-saving and modular configuration of your application. Its distinguishing feature is its standardized plug-in zone. This plug-in zone allows terminal blocks and plugs to be combined to suit the application, regardless of the connection technology.

Plug and coupling can be assembled to meet the application requirement thanks to their modular design.



Plug latching, strain relief, or cable housing can be snapped on as required. All terminal points and plugs support clear, large-surface labeling.




The COMBI connection system enables a plug-in wiring solution up to a nominal current of 41 A and a nominal voltage of 1000 V to be implemented. The contact system meets the most stringent of vibration requirements due to the integrated covering spring.

The COMBI system offers the highest levels of protection for users, as both the basic terminal blocks and the plugs are touch-proof. Alongside the safety aspect, this offers great flexibility for configuration work: The supply may be routed via the terminal blocks or the plugs.

Thanks to the straightforward, custom-coding option, wiring reliability is increased and incorrect connections are avoided. For this purpose, the individual coding elements are inserted at the coding position in the basic terminal block and the coding tab is removed at the corresponding point on the plug.

## Plug-in COMBI terminal blocks

|                                                   |           |                                                              |                                                                                     |                               |                                                                                      |                               |                                                                                       |                               |
|---------------------------------------------------|-----------|--------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------|--------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------|-------------------------------|
|                                                   |           |                                                              |    |                               |    |                               |    |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow<br>Gray<br>Blue<br>Green-yellow | MPT 1,5/S/1P<br>MPT 1,5/S/1P BU<br>MPT 1,5/S/1P-PE                                  | 3248115<br>3248116<br>3248117 | PT 1,5/S/1P<br>PT 1,5/S/1P BU<br>PT 1,5/S/1P-PE                                      | 3208582<br>3208595<br>3212332 | PT 2,5/1P<br>PT 2,5/1P BU<br>PT 2,5/1P-PE                                             | 3210033<br>3210046<br>3210059 |
| Width / Length / Height                           |           | [mm]                                                         | 3.5 / 33.55 / 28.1                                                                  |                               | 3.5 / 46 / 32                                                                        |                               | 5.2 / 48.5 / 36.5                                                                     |                               |
| Current / Voltage // UL                           |           | [A] / [V]                                                    | 17.5 / 500 // 15 / 600                                                              |                               | 17.5 / 500 // 15 / 600                                                               |                               | 24 / 500 // 20 / 600                                                                  |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                                                    | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                               | 0.14 - 1.5 / 26 - 16 // 0.14 - 1.5 / 26 - 14                                         |                               | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                            |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                                        | 0.14 - 1.5 / 0.14 - 1                                                               |                               | 0.14 - 1.5 / 0.14 - 1                                                                |                               | 0.14 - 2.5                                                                            |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                                        | 0.34 - 1.5 / 0.25 - 1.5                                                             |                               | 0.34 - 1.5 / 0.25 - 1.5                                                              |                               | 0.34 - 2.5 / 0.34 - 4                                                                 |                               |
|                                                   |           |                                                              |    |                               |    |                               |                                                                                       |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow                                 | PT 4/1P<br>PT 4/1P BU<br>PT 4/1P-PE                                                 | 3211937<br>3212007<br>3211942 | PT 6/1P<br>PT 6/1P BU<br>PT 6/1P-PE                                                  | 3061758<br>3061761<br>3061774 |                                                                                       |                               |
| Width / Length / Height                           |           | [mm]                                                         | 6.2 / 56 / 36.5                                                                     |                               | 8.2 / 57.7 / 43.5                                                                    |                               |                                                                                       |                               |
| Current / Voltage // UL                           |           | [A] / [V]                                                    | 32 / 800 // 28 / 600                                                                |                               | 41 / 1000 // 40 / 600                                                                |                               |                                                                                       |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                                                    | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                              |                               | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                               |                               |                                                                                       |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                                        | 0.25 - 4                                                                            |                               | 0.5 - 6                                                                              |                               |                                                                                       |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                                        | 0.5 - 4 / 0.5 - 6                                                                   |                               | 1 - 6 / 1 - 10                                                                       |                               |                                                                                       |                               |
|                                                   |           |                                                              |  |                               |  |                               |                                                                                       |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow                                 | PT 1,5/S-TWIN/1P<br>PT 1,5/S-TWIN/1P BU<br>PT 1,5/S-TWIN/1P-PE                      | 3212358<br>3212361<br>3212374 | PT 2,5-TWIN/1P<br>PT 2,5-TWIN/1P BU<br>PT 2,5-TWIN/1P-PE                             | 3209633<br>3209646<br>3209659 |                                                                                       |                               |
| Width / Length / Height                           |           | [mm]                                                         | 3.5 / 55 / 32                                                                       |                               | 5.2 / 60.5 / 36.5                                                                    |                               |                                                                                       |                               |
| Current / Voltage // UL                           |           | [A] / [V]                                                    | 17.5 / 500 // 15 / 600                                                              |                               | 24 / 500 // 20 / 600                                                                 |                               |                                                                                       |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                                                    | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                               | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                           |                               |                                                                                       |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                                        | 0.14 - 1.5 / 0.14 - 1                                                               |                               | 0.14 - 2.5                                                                           |                               |                                                                                       |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                                        | 0.34 - 1.5 / 0.25 - 1.5                                                             |                               | 0.34 - 2.5 / 0.34 - 4                                                                |                               |                                                                                       |                               |
|                                                   |           |                                                              |  |                               |  |                               |  |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow                                 | PT 1,5/S-QUATTRO/2P<br>PT 1,5/S-QUATTRO/2P BU<br>PT 1,5/S-QUATTRO/2P-PE             | 3212390<br>3212400<br>3212413 | PT 2,5-QUATTRO/2P<br>PT 2,5-QUATTRO/2P BU<br>PT 2,5-QUATTRO/2P-PE                    | 3209662<br>3209675<br>3209688 | PT 6-QUATTRO/2P<br>PT 6-QUATTRO/2P BU<br>PT 6-QUATTRO/2P-PE                           | 3061826<br>3061839<br>3061842 |
| Width / Length / Height                           |           | [mm]                                                         | 3.5 / 78.5 / 32                                                                     |                               | 5.2 / 81 / 36.5                                                                      |                               | 8.2 / 99.8 / 43.5                                                                     |                               |
| Current / Voltage // UL                           |           | [A] / [V]                                                    | 17.5 / 500 // 15 / 600                                                              |                               | 24 / 500 // 20 / 600                                                                 |                               | 41 / 1000 // 40 / 600                                                                 |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                                                    | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                               | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                           |                               | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                                |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                                        | 0.14 - 1.5 / 0.14 - 1                                                               |                               | 0.14 - 2.5                                                                           |                               | 0.5 - 6                                                                               |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                                        | 0.34 - 1.5 / 0.25 - 1.5                                                             |                               | 0.34 - 2.5 / 0.34 - 4                                                                |                               | 1 - 6 / 1 - 10                                                                        |                               |

## Plug-in COMBI terminal blocks



| Type | Order No. | Gray         | PT 2,5-HEXA/3P    | 3040044 |
|------|-----------|--------------|-------------------|---------|
|      |           | Blue         | PT 2,5-HEXA/3P BU | 3040048 |
|      |           | Green-yellow | PT 2,5-HEXA/3P-PE | 3040052 |

|                                                   |           |                                            |
|---------------------------------------------------|-----------|--------------------------------------------|
| Width / Length / Height                           | [mm]      | 5.2 / 111.2 / 35.3                         |
| Current / Voltage // UL                           | [A] / [V] | 24 / 500 // -                              |
| Solid / AWG // Stranded / AWG                     | [mm²] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |
| Stranded with ferrule without/with plastic sleeve | [mm²]     | 0.14 - 2.5                                 |
| Can be plugged in directly: with ferrule / solid  | [mm²]     | 0.34 - 2.5 / 0.34 - 4                      |

...-PV = with equipotential bonding



| Type | Order No. | Gray         | PTTB 1,5/S/2P    | 3212439 |
|------|-----------|--------------|------------------|---------|
|      |           | Blue         | PTTB 1,5/S/2P BU | 3212442 |
|      |           | Green-yellow | PTTB 1,5/S/2P-PE | 3212455 |

|                                                   |           |                                              |
|---------------------------------------------------|-----------|----------------------------------------------|
| Width / Length / Height                           | [mm]      | 3.5 / 69.3 / 42.6                            |
| Current / Voltage // UL                           | [A] / [V] | 16 / 500 // 15 / 600                         |
| Solid / AWG // Stranded / AWG                     | [mm²] / - | 0.14 - 1.5 / 26 - 16 // 0.14 - 1.5 / 26 - 14 |
| Stranded with ferrule without/with plastic sleeve | [mm²]     | 0.14 - 1.5 / 0.14 - 1                        |
| Can be plugged in directly: with ferrule / solid  | [mm²]     | 0.34 - 1.5 / 0.25 - 1.5                      |



| Type | Order No. | Gray | PTTB 1,5/S/2P-PV | 3212468 |
|------|-----------|------|------------------|---------|
|------|-----------|------|------------------|---------|

|                                                   |           |                                              |
|---------------------------------------------------|-----------|----------------------------------------------|
| Width / Length / Height                           | [mm]      | 3.5 / 69.3 / 42.6                            |
| Current / Voltage // UL                           | [A] / [V] | 16 / 500 // 15 / 600                         |
| Solid / AWG // Stranded / AWG                     | [mm²] / - | 0.14 - 1.5 / 26 - 16 // 0.14 - 1.5 / 26 - 14 |
| Stranded with ferrule without/with plastic sleeve | [mm²]     | 0.14 - 1.5 / 0.14 - 1                        |
| Can be plugged in directly: with ferrule / solid  | [mm²]     | 0.34 - 1.5 / 0.25 - 1.5                      |



| Type | Order No. | Gray         | PTTB 2,5/2P    | 3210871 |
|------|-----------|--------------|----------------|---------|
|      |           | Blue         | PTTB 2,5/2P BU | 3210884 |
|      |           | Green-yellow | PTTB 2,5/2P-PE | 3210897 |

|                                                   |           |                                            |
|---------------------------------------------------|-----------|--------------------------------------------|
| Width / Length / Height                           | [mm]      | 5.2 / 71.5 / 47.5                          |
| Current / Voltage // UL                           | [A] / [V] | 22 / 500 // 20 / 600                       |
| Solid / AWG // Stranded / AWG                     | [mm²] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |
| Stranded with ferrule without/with plastic sleeve | [mm²]     | 0.14 - 2.5                                 |
| Can be plugged in directly: with ferrule / solid  | [mm²]     | 0.34 - 2.5 / 0.34 - 4                      |





| Type | Order No. | Gray | PTTB 2,5/2P-PV | 3210907 |
|------|-----------|------|----------------|---------|
|------|-----------|------|----------------|---------|

|                                                   |           |                                            |
|---------------------------------------------------|-----------|--------------------------------------------|
| Width / Length / Height                           | [mm]      | 5.2 / 71.5 / 47.5                          |
| Current / Voltage // UL                           | [A] / [V] | 22 / 500 // 20 / 600                       |
| Solid / AWG // Stranded / AWG                     | [mm²] / - | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14 |
| Stranded with ferrule without/with plastic sleeve | [mm²]     | 0.14 - 2.5                                 |
| Can be plugged in directly: with ferrule / solid  | [mm²]     | 0.34 - 2.5 / 0.34 - 4                      |

## Plug-in desk-design COMBI terminal blocks

|                                                   |           |                                      |                                                                                           |                                          |                                                                                    |                               |
|---------------------------------------------------|-----------|--------------------------------------|-------------------------------------------------------------------------------------------|------------------------------------------|------------------------------------------------------------------------------------|-------------------------------|
|                                                   |           |                                      |          |                                          |  |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow         | PTS 1,5/5/1P<br>PTS 1,5/5/1P BU<br>PTS 1,5/5/1P-PE                                        | 3214453<br>3214466<br>3214479            | PTS 1,5/5-TWIN/1P<br>PTS 1,5/5-TWIN/1P BU<br>PTS 1,5/5-TWIN/1P-PE                  | 3214709<br>3214712<br>3214725 |
| Width / Length / Height                           |           | [mm]                                 | 3,5 / 50,7 / 38,5                                                                         |                                          | 3,5 / 50,7 / 38,5                                                                  |                               |
| Current / Voltage // UL                           |           | [A] / [V]                            | 17,5 / 500 // 15 / 600                                                                    |                                          | 17,5 / 500 // 15 / 600                                                             |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                            | 0,14 - 1,5 / 26 - 14 // 0,14 - 1,5 / 26 - 14                                              |                                          | 0,14 - 1,5 / 26 - 14 // 0,14 - 1,5 / 26 - 14                                       |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                | 0,14 - 1,5 / 0,14 - 1                                                                     |                                          | 0,14 - 1,5 / 0,14 - 1                                                              |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                | 0,34 - 1,5 / 0,25 - 1,5                                                                   |                                          | 0,34 - 1,5 / 0,25 - 1,5                                                            |                               |
| ...-PV = with equipotential bonding               |           |                                      |          |                                          |                                                                                    |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Gray<br>Green-yellow | PTTBS 1,5/5/2P<br>PTTBS 1,5/5/2P BU<br>PTTBS 1,5/5/2P-PV<br>PTTBS 1,5/5/2P-PE             | 3214495<br>3214505<br>3214521<br>3214518 |                                                                                    |                               |
| Width / Length / Height                           |           | [mm]                                 | 3,5 / 78 / 55                                                                             |                                          |                                                                                    |                               |
| Current / Voltage // UL                           |           | [A] / [V]                            | 16 / 500 // 15 / 600                                                                      |                                          |                                                                                    |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                            | 0,14 - 1,5 / 26 - 14 // 0,14 - 1,5 / 26 - 14                                              |                                          |                                                                                    |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                | 0,14 - 1,5 / 0,14 - 1                                                                     |                                          |                                                                                    |                               |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]                                | 0,34 - 1,5 / 0,25 - 1,5                                                                   |                                          |                                                                                    |                               |
| ...-PV = with equipotential bonding               |           |                                      |         |                                          |                                                                                    |                               |
| Type                                              | Order No. | Gray<br>Blue<br>Gray<br>Green-yellow | PTTBS 2,5-TWIN/2P<br>PTTBS 2,5-TWIN/2P BU<br>PTTBS 2,5-TWIN/2P-PV<br>PTTBS 2,5-TWIN/2P-PE | 3210604<br>3210605<br>3210607<br>3210606 |                                                                                    |                               |
| Width / Length / Height                           |           | [mm]                                 | 5,2 / 111,8 / 55                                                                          |                                          |                                                                                    |                               |
| Current / Voltage // UL                           |           | [A] / [V]                            | 24 / 500 // -                                                                             |                                          |                                                                                    |                               |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -                            | 0,14 - 4 / 26 - 12 // 0,14 - 2,5 / 26 - 14                                                |                                          |                                                                                    |                               |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]                                | 0,14 - 2,5                                                                                |                                          |                                                                                    |                               |
|                                                   |           |                                      | 0,34 - 2,5 / 0,34 - 4                                                                     |                                          |                                                                                    |                               |

## Plug-in COMBI PIN/PIN terminal blocks

|                                                   |           |                                      |                                                                                   |                               |                                                                           |                                                                                    |                                                                   |                                          |                                                                                     |  |  |
|---------------------------------------------------|-----------|--------------------------------------|-----------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------|------------------------------------------|-------------------------------------------------------------------------------------|--|--|
|                                                   |           |                                      |  |                               |                                                                           |  |                                                                   |                                          |  |  |  |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow         | PT 1,5/S/2P<br>PT 1,5/S/2P BU<br>PT 1,5/S/2P-PE                                   | 3213784<br>3213797<br>3213810 | ST 2,5/2P<br>ST 2,5/2P BU<br>ST 2,5/2P-PE                                 | 3042133<br>3042094<br>3042146                                                      | ST 4/2P<br>ST 4/2P BU<br>ST 4/2P-PE                               | 3042735<br>3043789<br>3042748            |                                                                                     |  |  |
| Width / Length / Height                           |           | [mm]                                 | 3.5 / 45.8 / 32                                                                   |                               | 5.2 / 49.1 / 36.5                                                         |                                                                                    | 6.2 / 55.9 / 36.5                                                 |                                          |                                                                                     |  |  |
| Current / Voltage // UL                           |           | [A] / [V]                            | 17.5 / 500 // 15 / 600                                                            |                               | 24 / 500 // 20 / 600                                                      |                                                                                    | 32 / 800 // -                                                     |                                          |                                                                                     |  |  |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -               | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                      |                               | 0.08 - 4 / 28 - 12 // 0.08 - 2.5 / 28 - 14                                |                                                                                    | 0.08 - 6 / 28 - 10 // 0.08 - 4 / 28 - 12                          |                                          |                                                                                     |  |  |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                   | 0.14 - 1.5 / 0.14 - 1                                                             |                               | 0.14 - 2.5                                                                |                                                                                    | 0.14 - 4                                                          |                                          |                                                                                     |  |  |
| ...-PV = with equipotential bonding               |           |                                      |  |                               |                                                                           |  |                                                                   |                                          |  |  |  |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow<br>Gray | ST 2,5-QUATTRO/4P<br>ST 2,5-QUATTRO/4P BU<br>ST 2,5-QUATTRO/4P-PE                 | 3042159<br>3042081<br>3042162 | PTTB 1,5/S/4P<br>PTTB 1,5/S/4P BU<br>PTTB 1,5/S/4P-PE<br>PTTB 1,5/S/4P-PV | 3213865<br>3213878<br>3213881<br>3213852                                           | STTB 2,5/4P<br>STTB 2,5/4P BU<br>STTB 2,5/4P-PE<br>STTB 2,5/4P-PV | 3061486<br>3061512<br>3061499<br>3061509 |                                                                                     |  |  |
| Width / Length / Height                           |           | [mm]                                 | 5.2 / 89.5 / 36.5                                                                 |                               | 3.5 / 93.9 / 42.6                                                         |                                                                                    | 5.2 / 98.8 / 47.5                                                 |                                          |                                                                                     |  |  |
| Current / Voltage // UL                           |           | [A] / [V]                            | 24 / 500 // 20 / 600                                                              |                               | 16 / 500 // 15 / 600                                                      |                                                                                    | 22 / 500 // 20 / 600                                              |                                          |                                                                                     |  |  |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -               | 0.08 - 4 / 28 - 12 // 0.08 - 2.5 / 28 - 14                                        |                               | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                              |                                                                                    | 0.08 - 4 / 28 - 12 // 0.08 - 2.5 / 28 - 14                        |                                          |                                                                                     |  |  |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]                   | 0.14 - 2.5                                                                        |                               | 0.14 - 1.5 / 0.14 - 1                                                     |                                                                                    | 0.14 - 2.5                                                        |                                          |                                                                                     |  |  |

## COMBI couplings

|                                                   |           |                                                                                                                                                |                                                                                                                                                                                                                              |                                                                                                                                                        |                                                                                                  |                                                                                                 |
|---------------------------------------------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
|                                                   |           |                                                                                                                                                |                                                                                                                                             |                                                                                                                                                        |                |                                                                                                 |
| Type                                              | Order No. | 2-pos.<br>3-pos.<br>4-pos.<br>5-pos.<br>6-pos.<br>7-pos.<br>8-pos.<br>9-pos.<br>10-pos.<br>11-pos.<br>12-pos.<br>13-pos.<br>14-pos.<br>15-pos. | PPC 1,5/S/ 2<br>PPC 1,5/S/ 3<br>PPC 1,5/S/ 4<br>PPC 1,5/S/ 5<br>PPC 1,5/S/ 6<br>PPC 1,5/S/ 7<br>PPC 1,5/S/ 8<br>PPC 1,5/S/ 9<br>PPC 1,5/S/10<br>PPC 1,5/S/11<br>PPC 1,5/S/12<br>PPC 1,5/S/13<br>PPC 1,5/S/14<br>PPC 1,5/S/15 | 3213386<br>3213399<br>3213409<br>3213412<br>3213425<br>3213438<br>3213441<br>3213454<br>3213467<br>3213470<br>3213483<br>3213496<br>3213506<br>3213519 | PPC 6/2<br>PPC 6/3<br>PPC 6/4<br>PPC 6/5<br>PPC 6/6<br>PPC 6/7<br>PPC 6/8<br>PPC 6/9<br>PPC 6/10 | 3000693<br>3000694<br>3000695<br>3000697<br>3000698<br>3000699<br>3000700<br>3000701<br>3000702 |
| Width / Length / Height                           |           | [mm]                                                                                                                                           | - / 27 / 17,8                                                                                                                                                                                                                |                                                                                                                                                        | - / 47 / 24,7                                                                                    |                                                                                                 |
| Current / Voltage // UL                           |           | [A] / [V]                                                                                                                                      | 17,5 / 500 // 15 / 600                                                                                                                                                                                                       |                                                                                                                                                        | 41 / 1000 // 40 / 600                                                                            |                                                                                                 |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -                                                                                                                         | 0.14 - 1.5 / 26 - 16 // 0.14 - 1.5 / 26 - 14                                                                                                                                                                                 |                                                                                                                                                        | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                                           |                                                                                                 |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / -                                                                                                                         | 0.14 - 1.5 / 0.14 - 1                                                                                                                                                                                                        |                                                                                                                                                        | 0.5 - 6                                                                                          |                                                                                                 |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                                                                                                                             | 0.34 - 1.5 / 0.25 - 1.5                                                                                                                                                                                                      |                                                                                                                                                        | 1 - 6 / 1 - 10                                                                                   |                                                                                                 |


## Self-assembly COMBI couplings

|                                                   |           |                                       |                                                                                    |                                          |                                                                                     |                                          |
|---------------------------------------------------|-----------|---------------------------------------|------------------------------------------------------------------------------------|------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------|
|                                                   |           |                                       |  |                                          |  |                                          |
| Type                                              | Order No. | Gray<br>Blue<br>Green-yellow<br>Cover | PPC 1,5/S/1-L<br>PPC 1,5/S/1-L BU<br>PPC 1,5/S/1-L GNYE<br>D-PPC 1,5/S             | 3213357<br>3213360<br>3213373<br>3213690 | PPC 6/1-L<br>PPC 6/1-L BU<br>PPC 6/1-L GNYE<br>D-PPC 6                              | 3000690<br>3000691<br>3000692<br>3000703 |
| Width / Length / Height                           |           | [mm]                                  | 3.5 / 27 / 17,8                                                                    |                                          | 8.2 / 47 / 24,7                                                                     |                                          |
| Current / Voltage // UL                           |           | [A] / [V]                             | 17,5 / 500 // 15 / 600                                                             |                                          | 41 / 1000 // 40 / 600                                                               |                                          |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / -                | 0.14 - 1.5 / 26 - 16 // 0.14 - 1.5 / 26 - 14                                       |                                          | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                              |                                          |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / -                | 0.14 - 1.5 / 0.14 - 1                                                              |                                          | 0.5 - 6                                                                             |                                          |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]                    | 0.34 - 1.5 / 0.25 - 1.5                                                            |                                          | 1 - 6 / 1 - 10                                                                      |                                          |


## Self-assembly COMBI couplings for DIN rail mounting

|                                                   |           |                        |                                                                                     |                    |                                                                                      |                    |
|---------------------------------------------------|-----------|------------------------|-------------------------------------------------------------------------------------|--------------------|--------------------------------------------------------------------------------------|--------------------|
|                                                   |           |                        |  |                    |  |                    |
| Type                                              | Order No. | Gray<br>Cover          | PPC 1,5/NS/1-L<br>D-PPC 1,5/S                                                       | 3213700<br>3213690 | PPC 6-NS/1-L<br>D-PPC 6                                                              | 3000689<br>3000703 |
| Width / Length / Height                           |           | [mm]                   | 3.5 / 27.1 / 28,3                                                                   |                    | 8.2 / 27 / 38                                                                        |                    |
| Current / Voltage // UL                           |           | [A] / [V]              | 17,5 / 500 // 15 / 600                                                              |                    | 41 / 1000 // 40 / 600                                                                |                    |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                        |                    | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                               |                    |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ] / - | 0.14 - 1.5 / 0.14 - 1                                                               |                    | 0.5 - 6                                                                              |                    |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 1.5 / 0.25 - 1.5                                                             |                    | 1 - 6 / 1 - 10                                                                       |                    |

## Self-assembly COMBI headers for PCB connection



| Type                    | Order No. | 2-pos.    | ST 2,5-PCB/ 2-G-5,2  | 1980378 | ST 4-PCB/ 2-G-6,2  | 1980598 |
|-------------------------|-----------|-----------|----------------------|---------|--------------------|---------|
|                         |           | 3-pos.    | ST 2,5-PCB/ 3-G-5,2  | 1980381 | ST 4-PCB/ 3-G-6,2  | 1980608 |
|                         |           | 4-pos.    | ST 2,5-PCB/ 4-G-5,2  | 1980394 | ST 4-PCB/ 4-G-6,2  | 1980611 |
|                         |           | 5-pos.    | ST 2,5-PCB/ 5-G-5,2  | 1980404 | ST 4-PCB/ 5-G-6,2  | 1980624 |
|                         |           | 6-pos.    | ST 2,5-PCB/ 6-G-5,2  | 1980417 | ST 4-PCB/ 6-G-6,2  | 1980637 |
|                         |           | 7-pos.    | ST 2,5-PCB/ 7-G-5,2  | 1980420 | ST 4-PCB/ 7-G-6,2  | 1980640 |
|                         |           | 8-pos.    | ST 2,5-PCB/ 8-G-5,2  | 1980433 | ST 4-PCB/ 8-G-6,2  | 1980653 |
|                         |           | 9-pos.    | ST 2,5-PCB/ 9-G-5,2  | 1980446 | ST 4-PCB/ 9-G-6,2  | 1980666 |
|                         |           | 10-pos.   | ST 2,5-PCB/ 10-G-5,2 | 1980459 | ST 4-PCB/ 10-G-6,2 | 1980679 |
|                         |           | 11-pos.   | ST 2,5-PCB/ 11-G-5,2 | 1980462 | ST 4-PCB/ 11-G-6,2 | 1980682 |
|                         |           | 12-pos.   | ST 2,5-PCB/ 12-G-5,2 | 1980475 | ST 4-PCB/ 12-G-6,2 | 1980695 |
| Pitch                   |           | [mm]      | 5.2                  |         | 6.2                |         |
| Current / Voltage // UL |           | [A] / [V] | 24 / 500 // -        |         | 32 / 800 // -      |         |



|                         |           |           |                       |         |                     |         |  |
|-------------------------|-----------|-----------|-----------------------|---------|---------------------|---------|--|
| Type                    | Order No. | 2-pos.    | ST 2,5-PCBV/ 2-G-5,2  | 1980488 | ST 4-PCBV/ 2-G-6,2  | 1980705 |  |
|                         |           | 3-pos.    | ST 2,5-PCBV/ 3-G-5,2  | 1980491 | ST 4-PCBV/ 3-G-6,2  | 1980718 |  |
|                         |           | 4-pos.    | ST 2,5-PCBV/ 4-G-5,2  | 1980501 | ST 4-PCBV/ 4-G-6,2  | 1980721 |  |
|                         |           | 5-pos.    | ST 2,5-PCBV/ 5-G-5,2  | 1980514 | ST 4-PCBV/ 5-G-6,2  | 1980734 |  |
|                         |           | 6-pos.    | ST 2,5-PCBV/ 6-G-5,2  | 1980527 | ST 4-PCBV/ 6-G-6,2  | 1980747 |  |
|                         |           | 7-pos.    | ST 2,5-PCBV/ 7-G-5,2  | 1980530 | ST 4-PCBV/ 7-G-6,2  | 1980750 |  |
|                         |           | 8-pos.    | ST 2,5-PCBV/ 8-G-5,2  | 1980543 | ST 4-PCBV/ 8-G-6,2  | 1980763 |  |
|                         |           | 9-pos.    | ST 2,5-PCBV/ 9-G-5,2  | 1980556 | ST 4-PCBV/ 9-G-6,2  | 1980776 |  |
|                         |           | 10-pos.   | ST 2,5-PCBV/ 10-G-5,2 | 1980569 | ST 4-PCBV/ 10-G-6,2 | 1980789 |  |
|                         |           | 11-pos.   | ST 2,5-PCBV/ 11-G-5,2 | 1980572 | ST 4-PCBV/ 11-G-6,2 | 1980792 |  |
|                         |           | 12-pos.   | ST 2,5-PCBV/ 12-G-5,2 | 1980585 | ST 4-PCBV/ 12-G-6,2 | 1980802 |  |
|                         |           | Pitch     |                       | [mm]    | 5.2                 |         |  |
| Current / Voltage // UL |           | [A] / [V] | 24 / 500 // -         |         | 32 / 800 // -       |         |  |

## COMBI connectors


|                                                   |           |                        |                                                                                    |         |                                                                                    |         |                                                                                     |         |
|---------------------------------------------------|-----------|------------------------|------------------------------------------------------------------------------------|---------|------------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------|---------|
|                                                   |           |                        |   |         |  |         |  |         |
| Type                                              | Order No. | 1-pos.                 | PP-H 1,5/S/1                                                                       | 3212484 | PP-H 2,5/1                                                                         | 3209866 | PP-H 4/1                                                                            | 3212010 |
|                                                   |           | 2-pos.                 | PP-H 1,5/S/2                                                                       | 3212510 | PP-H 2,5/2                                                                         | 3209879 | PP-H 4/2                                                                            | 3212016 |
|                                                   |           | 3-pos.                 | PP-H 1,5/S/3                                                                       | 3212523 | PP-H 2,5/3                                                                         | 3209883 | PP-H 4/3                                                                            | 3212022 |
|                                                   |           | 4-pos.                 | PP-H 1,5/S/4                                                                       | 3212536 | PP-H 2,5/4                                                                         | 3209895 | PP-H 4/4                                                                            | 3212029 |
|                                                   |           | 5-pos.                 | PP-H 1,5/S/5                                                                       | 3212549 | PP-H 2,5/5                                                                         | 3209905 | PP-H 4/5                                                                            | 3212035 |
|                                                   |           | 6-pos.                 | PP-H 1,5/S/6                                                                       | 3212552 | PP-H 2,5/6                                                                         | 3209918 | PP-H 4/6                                                                            | 3212041 |
|                                                   |           | 7-pos.                 | PP-H 1,5/S/7                                                                       | 3212565 | PP-H 2,5/7                                                                         | 3209921 | PP-H 4/7                                                                            | 3212048 |
|                                                   |           | 8-pos.                 | PP-H 1,5/S/8                                                                       | 3212578 | PP-H 2,5/8                                                                         | 3209934 | PP-H 4/8                                                                            | 3212054 |
|                                                   |           | 9-pos.                 | PP-H 1,5/S/9                                                                       | 3212581 | PP-H 2,5/9                                                                         | 3209947 | PP-H 4/9                                                                            | 3212061 |
|                                                   |           | 10-pos.                | PP-H 1,5/S/10                                                                      | 3212594 | PP-H 2,5/10                                                                        | 3209950 | PP-H 4/10                                                                           | 3212067 |
|                                                   |           | 11-pos.                | PP-H 1,5/S/11                                                                      | 3212604 | PP-H 2,5/11                                                                        | 3209963 | PP-H 4/11                                                                           | 3212074 |
|                                                   |           | 12-pos.                | PP-H 1,5/S/12                                                                      | 3212617 | PP-H 2,5/12                                                                        | 3209976 | PP-H 4/12                                                                           | 3212080 |
|                                                   |           | 13-pos.                | PP-H 1,5/S/13                                                                      | 3212620 | PP-H 2,5/13                                                                        | 3209989 | PP-H 4/13                                                                           | 3212087 |
|                                                   |           | 14-pos.                | PP-H 1,5/S/14                                                                      | 3212633 | PP-H 2,5/14                                                                        | 3209992 | PP-H 4/14                                                                           | 3212093 |
|                                                   |           | 15-pos.                | PP-H 1,5/S/15                                                                      | 3212646 | PP-H 2,5/15                                                                        | 3210004 | PP-H 4/15                                                                           | 3212100 |
|                                                   |           | Blue                   | PP-H 1,5/S/1 BU                                                                    | 3212497 | PP-H 2,5/1 BU                                                                      | 3210017 | PP-H 4/1 BU                                                                         | 3212077 |
|                                                   |           | Green-yellow           | PP-H 1,5/S/1 GNYE                                                                  | 3212507 | PP-H 2,5/1 GNYE                                                                    | 3210020 | PP-H 4/1 GNYE                                                                       | 3212088 |
| Width / Length / Height                           |           | [mm]                   | - / 16.5 / 31.3                                                                    |         | - / 15.8 / 39                                                                      |         | - / 21 / 42.3                                                                       |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 17.5 / 500 // 15 / 600                                                             |         | 24 / 500 // 20 / 600                                                               |         | 32 / 800 // 28 / 600                                                                |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                       |         | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                         |         | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                              |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]     | 0.14 - 1.5 / 0.14 - 1                                                              |         | 0.14 - 2.5                                                                         |         | 0.25 - 4                                                                            |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 0.34 - 1.5 / 0.25 - 1.5                                                            |         | 0.34 - 2.5 / 0.34 - 4                                                              |         | 0.5 - 4 / 0.5 - 6                                                                   |         |
|                                                   |           |                        |  |         |                                                                                    |         |                                                                                     |         |
| Type                                              | Order No. | 1-pos.                 | PP-H 6/1                                                                           | 3061541 |                                                                                    |         |                                                                                     |         |
|                                                   |           | 2-pos.                 | PP-H 6/2                                                                           | 3061570 |                                                                                    |         |                                                                                     |         |
|                                                   |           | 3-pos.                 | PP-H 6/3                                                                           | 3061583 |                                                                                    |         |                                                                                     |         |
|                                                   |           | 4-pos.                 | PP-H 6/4                                                                           | 3061596 |                                                                                    |         |                                                                                     |         |
|                                                   |           | 5-pos.                 | PP-H 6/5                                                                           | 3061606 |                                                                                    |         |                                                                                     |         |
|                                                   |           | 6-pos.                 | PP-H 6/6                                                                           | 3061619 |                                                                                    |         |                                                                                     |         |
|                                                   |           | 7-pos.                 | PP-H 6/7                                                                           | 3061622 |                                                                                    |         |                                                                                     |         |
|                                                   |           | 8-pos.                 | PP-H 6/8                                                                           | 3061635 |                                                                                    |         |                                                                                     |         |
|                                                   |           | 9-pos.                 | PP-H 6/9                                                                           | 3061648 |                                                                                    |         |                                                                                     |         |
|                                                   |           | 10-pos.                | PP-H 6/10                                                                          | 3061651 |                                                                                    |         |                                                                                     |         |
|                                                   |           | Blue                   | PP-H 6/1 BU                                                                        | 3061554 |                                                                                    |         |                                                                                     |         |
|                                                   |           | Green-yellow           | PP-H 6/1 GNYE                                                                      | 3061567 |                                                                                    |         |                                                                                     |         |
| Width / Length / Height                           |           | [mm]                   | - / 21 / 49.3                                                                      |         |                                                                                    |         |                                                                                     |         |
| Current / Voltage // UL                           |           | [A] / [V]              | 32 / 800 // 40 / 600                                                               |         |                                                                                    |         |                                                                                     |         |
| Solid / AWG // Stranded / AWG                     |           | [mm <sup>2</sup> ] / - | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                             |         |                                                                                    |         |                                                                                     |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm <sup>2</sup> ]     | 0.5 - 6                                                                            |         |                                                                                    |         |                                                                                     |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm <sup>2</sup> ]     | 1 - 6 / 1 - 10                                                                     |         |                                                                                    |         |                                                                                     |         |

## Self-assembly COMBI connectors

|                                                   |           |              |                                                                                   |         |                                                                                    |         |                                                                                     |         |
|---------------------------------------------------|-----------|--------------|-----------------------------------------------------------------------------------|---------|------------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------|---------|
|                                                   |           |              |  |         |  |         |  |         |
| Type                                              | Order No. | Gray         | PP-H 1,5/S/1-L                                                                    | 3212659 | PP-H 2,5/1-L                                                                       | 3210062 | PP-H 4/1-L                                                                          | 3211948 |
|                                                   |           | Blue         | PP-H 1,5/S/1-L BU                                                                 | 3212662 | PP-H 2,5/1-L BU                                                                    | 3210075 | PP-H 4/1-L BU                                                                       | 3211951 |
|                                                   |           | Green-yellow | PP-H 1,5/S/1-L GNYE                                                               | 3212675 | PP-H 2,5/1-L GNYE                                                                  | 3210088 | PP-H 4/1-L GNYE                                                                     | 3211958 |
|                                                   |           | Gray         | PP-H 1,5/S/1-M                                                                    | 3212688 | PP-H 2,5/1-M                                                                       | 3210091 | PP-H 4/1-M                                                                          | 3211965 |
|                                                   |           | Blue         | PP-H 1,5/S/1-M BU                                                                 | 3212691 | PP-H 2,5/1-M BU                                                                    | 3210101 | PP-H 4/1-M BU                                                                       | 3211964 |
|                                                   |           | Green-yellow | PP-H 1,5/S/1-M GNYE                                                               | 3212701 | PP-H 2,5/1-M GNYE                                                                  | 3210114 | PP-H 4/1-M GNYE                                                                     | 3211971 |
|                                                   |           | Gray         | PP-H 1,5/S/1-R                                                                    | 3212714 | PP-H 2,5/1-R                                                                       | 3210127 | PP-H 4/1-R                                                                          | 3211977 |
|                                                   |           | Blue         | PP-H 1,5/S/1-R BU                                                                 | 3212727 | PP-H 2,5/1-R BU                                                                    | 3210130 | PP-H 4/1-R BU                                                                       | 3211980 |
|                                                   |           | Green-yellow | PP-H 1,5/S/1-R GNYE                                                               | 3212730 | PP-H 2,5/1-R GNYE                                                                  | 3210143 | PP-H 4/1-R GNYE                                                                     | 3211987 |
| Width / Length / Height                           |           | [mm]         | 3.5 / 16.5 / 31.3                                                                 |         | 5.2 / 15.8 / 39                                                                    |         | 6.2 / 21 / 42.3                                                                     |         |
| Current / Voltage // UL                           |           | [A] / [V]    | 17.5 / 500 // 15 / 600                                                            |         | 24 / 500 // 20 / 600                                                               |         | 32 / 800 // 28 / 600                                                                |         |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -    | 0.14 - 1.5 / 26 - 14 // 0.14 - 1.5 / 26 - 14                                      |         | 0.14 - 4 / 26 - 12 // 0.14 - 2.5 / 26 - 14                                         |         | 0.2 - 6 / 24 - 10 // 0.2 - 4 / 24 - 12                                              |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]        | 0.14 - 1.5 / 0.14 - 1                                                             |         | 0.14 - 2.5                                                                         |         | 0.25 - 4                                                                            |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]        | 0.34 - 1.5 / 0.25 - 1.5                                                           |         | 0.34 - 2.5 / 0.34 - 4                                                              |         | 0.5 - 4 / 0.5 - 6                                                                   |         |
|                                                   |           |              |  |         |                                                                                    |         |                                                                                     |         |
| Type                                              | Order No. | Gray         | PP-H 6/1-L                                                                        | 3061664 |                                                                                    |         |                                                                                     |         |
|                                                   |           | Blue         | PP-H 6/1-L BU                                                                     | 3061677 |                                                                                    |         |                                                                                     |         |
|                                                   |           | Green-yellow | PP-H 6/1-L GNYE                                                                   | 3061680 |                                                                                    |         |                                                                                     |         |
|                                                   |           | Gray         | PP-H 6/1-M                                                                        | 3061693 |                                                                                    |         |                                                                                     |         |
|                                                   |           | Blue         | PP-H 6/1-M BU                                                                     | 3061703 |                                                                                    |         |                                                                                     |         |
|                                                   |           | Green-yellow | PP-H 6/1-M GNYE                                                                   | 3061716 |                                                                                    |         |                                                                                     |         |
|                                                   |           | Gray         | PP-H 6/1-R                                                                        | 3061729 |                                                                                    |         |                                                                                     |         |
|                                                   |           | Blue         | PP-H 6/1-R BU                                                                     | 3061732 |                                                                                    |         |                                                                                     |         |
|                                                   |           | Green-yellow | PP-H 6/1-R GNYE                                                                   | 3061745 |                                                                                    |         |                                                                                     |         |
| Width / Length / Height                           |           | [mm]         | 8.2 / 21 / 49.3                                                                   |         |                                                                                    |         |                                                                                     |         |
| Current / Voltage // UL                           |           | [A] / [V]    | 41 / 1000 // 40 / 600                                                             |         |                                                                                    |         |                                                                                     |         |
| Solid / AWG // Stranded / AWG                     |           | [mm²] / -    | 0.5 - 10 / 20 - 8 // 0.5 - 6 / 20 - 10                                            |         |                                                                                    |         |                                                                                     |         |
| Stranded with ferrule without/with plastic sleeve |           | [mm²]        | 0.5 - 6                                                                           |         |                                                                                    |         |                                                                                     |         |
| Can be plugged in directly: with ferrule / solid  |           | [mm²]        | 1 - 6 / 1 - 10                                                                    |         |                                                                                    |         |                                                                                     |         |

### Self-assembly COMBI connectors with push-in connection

- The push-in COMBI plugs for self-assembly provide solutions that users can implement themselves
- Robust cable housings for strain relief on connecting cables are available
- The plug is assembled directly on site by snapping together single-position plug elements. See an example of how these go together on the right.




- ① PP-H 1,5/S/1-L
- ② PP-H 1,5/S/1-M and PP-H 1,5/S/1-M BU
- ③ PP-H 1,5/S/1-R GNYE

## Cable housing for COMBI connectors

|                                                                                                                              |           |             |   |           |  |         |  |         |
|------------------------------------------------------------------------------------------------------------------------------|-----------|-------------|------------------------------------------------------------------------------------|-----------|------------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------|---------|
| Type                                                                                                                         | Order No. |             |                                                                                    |           |                                                                                    |         |                                                                                     |         |
| 2-pos.                                                                                                                       |           | PH 1,5/S/3  | 3212756                                                                            | PH 2,5/2  | 3209691                                                                            | PH 4/2  | 3000734                                                                             |         |
| 3-pos.                                                                                                                       |           | PH 1,5/S/4  | 3212769                                                                            | PH 2,5/3  | 3209701                                                                            | PH 4/3  | 3000736                                                                             |         |
| 4-pos.                                                                                                                       |           | PH 1,5/S/5  | 3212772                                                                            | PH 2,5/4  | 3209714                                                                            | PH 4/4  | 3000737                                                                             |         |
| 5-pos.                                                                                                                       |           | PH 1,5/S/6  | 3212785                                                                            | PH 2,5/5  | 3209727                                                                            | PH 4/5  | 3000738                                                                             |         |
| 6-pos.                                                                                                                       |           | PH 1,5/S/7  | 3212798                                                                            | PH 2,5/6  | 3209730                                                                            | PH 4/6  | 3000739                                                                             |         |
| 7-pos.                                                                                                                       |           | PH 1,5/S/8  | 3212808                                                                            | PH 2,5/7  | 3209743                                                                            | PH 4/7  | 3000740                                                                             |         |
| 8-pos.                                                                                                                       |           | PH 1,5/S/9  | 3212811                                                                            | PH 2,5/8  | 3209756                                                                            | PH 4/8  | 3000741                                                                             |         |
| 9-pos.                                                                                                                       |           | PH 1,5/S/10 | 3212824                                                                            | PH 2,5/9  | 3209507                                                                            | PH 4/9  | 3000742                                                                             |         |
| 10-pos.                                                                                                                      |           | PH 1,5/S/11 | 3212837                                                                            | PH 2,5/10 | 3209769                                                                            | PH 4/10 | 3000743                                                                             |         |
| 11-pos.                                                                                                                      |           | PH 1,5/S/12 | 3212840                                                                            | PH 2,5/11 | 3209772                                                                            |         |                                                                                     |         |
| 12-pos.                                                                                                                      |           | PH 1,5/S/13 | 3212853                                                                            | PH 2,5/12 | 3209785                                                                            |         |                                                                                     |         |
| 13-pos.                                                                                                                      |           | PH 1,5/S/14 | 3212888                                                                            | PH 2,5/13 | 3209798                                                                            |         |                                                                                     |         |
| 14-pos.                                                                                                                      |           | PH 1,5/S/15 | 3212879                                                                            | PH 2,5/14 | 3209808                                                                            |         |                                                                                     |         |
| 15-pos.                                                                                                                      |           | PH 1,5/S/15 | 3212879                                                                            | PH 2,5/15 | 3209811                                                                            |         |                                                                                     |         |
| <b>Bend protection sleeve</b> , for 3 - 9 mm cable diameter, suitable for PH 1,5/S/5 - PH 1,5/S/8 and PH 2,5/3 - PH 2,5/5    |           |             | CPH 3-9                                                                            | 3212015   | CPH 3-9                                                                            | 3212015 | CPH 3-9                                                                             | 3212015 |
| <b>Bend protection sleeve</b> , for 4 - 12 mm cable diameter, suitable for PH 1,5/S/9 - PH 1,5/S/15 and PH 2,5/6 - PH 2,5/15 |           |             | CPH 4-12                                                                           | 3212028   | CPH 4-12                                                                           | 3212028 | CPH 4-12                                                                            | 3212028 |
| <b>Cable clamp</b> , with screws, suitable for PH 1,5/S/9 - PH 1,5/S/15 and PH 2,5/6 - PH 2,5/15                             |           |             | HSR                                                                                | 3212031   | HSR                                                                                | 3212031 | HSR                                                                                 | 3212031 |
| <b>Shield connection</b> , suitable for PH 1,5/S/9 - PH 1,5/S/15 and PH 2,5/6 - PH 2,5/15                                    |           |             | HSH-METALL                                                                         | 3210910   | HSH-METALL                                                                         | 3210910 | HSH-METALL                                                                          | 3210910 |
|                                                                                                                              |           |             |  |           |                                                                                    |         |                                                                                     |         |
| Type                                                                                                                         | Order No. |             |                                                                                    |           |                                                                                    |         |                                                                                     |         |
| 2-pos.                                                                                                                       |           | PH 6/2      | 3000680                                                                            |           |                                                                                    |         |                                                                                     |         |
| 3-pos.                                                                                                                       |           | PH 6/3      | 3000681                                                                            |           |                                                                                    |         |                                                                                     |         |
| 4-pos.                                                                                                                       |           | PH 6/4      | 3000682                                                                            |           |                                                                                    |         |                                                                                     |         |
| 5-pos.                                                                                                                       |           | PH 6/5      | 3000683                                                                            |           |                                                                                    |         |                                                                                     |         |
| 6-pos.                                                                                                                       |           | PH 6/6      | 3000684                                                                            |           |                                                                                    |         |                                                                                     |         |
| 7-pos.                                                                                                                       |           | PH 6/7      | 3000685                                                                            |           |                                                                                    |         |                                                                                     |         |
| <b>Bend protection sleeve</b> , for 9 - 15 mm cable diameter, suitable for PH 6/2 - PH 6/7                                   |           |             | CPH 9-15                                                                           | 3000768   |                                                                                    |         |                                                                                     |         |
| <b>Cable clamp</b> , with screws, suitable for PH 6/2- PH 6/7                                                                |           |             | HSR 6/8                                                                            | 3000769   |                                                                                    |         |                                                                                     |         |
| <b>Shield connection</b> , suitable for PH 6/2 - PH 6/7                                                                      |           |             | HSH-METALL-6/8                                                                     | 3000770   |                                                                                    |         |                                                                                     |         |

## PT-COMBI self-locking flange and self-locking flange cover

|                            |           |  |  |         |  |                      |  |         |
|----------------------------|-----------|--|-------------------------------------------------------------------------------------|---------|--------------------------------------------------------------------------------------|----------------------|---------------------------------------------------------------------------------------|---------|
| Type                       | Order No. |  |                                                                                     |         |                                                                                      |                      |                                                                                       |         |
| <b>Self-locking flange</b> |           |  | ST 2,5/1P-FS                                                                        | 3061376 | For:                                                                                 | PT 2,5/1P...         | <b>Self-locking flange cover</b>                                                      |         |
|                            |           |  | ST 2,5-TWIN/1P-FS                                                                   | 3061389 |                                                                                      | PT 2,5-TWIN/1P...    | DFS-SP-H 2,5                                                                          | 3061431 |
|                            |           |  | ST 2,5-QUATTRO/2P-FS                                                                | 3061392 |                                                                                      | PT 2,5-QUATTRO/2P... | DFS-CP 2,5-4L                                                                         | 3012321 |
|                            |           |  | ST 2,5-QUATTRO/4P-FS                                                                | 3061402 |                                                                                      | PT 2,5-QUATTRO/4P... |                                                                                       |         |
|                            |           |  | ST 2,5/2P-FS                                                                        | 3061415 |                                                                                      | PT 2,5/2P...         |                                                                                       |         |
|                            |           |  | STTB 2,5/2P-FS                                                                      | 3061428 |                                                                                      | PTTB 2,5/2P...       |                                                                                       |         |



### Accessories PT-COMBI terminal blocks

17  
Terminal strip  
marker carriers

KLM 3-L  
0814788

18  
Quick mounting end brackets

CLIPFIX 35-5  
3022276

19  
Coding star

PC  
3040588

26  
Shielding

PSH 3-6  
3040591

PSH 5-10  
3040601

### Accessories PT-COMBI connectors

20  
Connectors

21  
Locking mechanism

22  
Strain relief

23  
Self-locking  
flange cover

24  
Latching and  
strain relief


25  
2-pos.

|             | 1-pos.              | 2-pos.                         | 2-pos.                | 4-pos.          |                         |                      |
|-------------|---------------------|--------------------------------|-----------------------|-----------------|-------------------------|----------------------|
| PP-H 1,5... | PR 1,5/S<br>3212882 | PR 1,5/S/2<br>3212895          | PZ 1,5/S/2<br>3212918 | —               | —                       | PRZ 1,5/S<br>3212905 |
| PP-H 2,5... | PR<br>3040559       | PR/2<br>3040630                | PZ/2<br>3040627       | PZ/4<br>3040643 | DFS-SP-H 2,5<br>3061431 | PRZ<br>3040614       |
|             | —                   | PTR/2 <sup>1)</sup><br>3040631 | —                     | —               | —                       | —                    |
| PP-H 4...   | PR<br>3040559       | PR/2<br>3040630                | PZ/2<br>3040627       | —               | —                       | PRZ<br>3040614       |
|             | —                   | PTR/2 <sup>1)</sup><br>3040631 | —                     | —               | —                       | —                    |
| PP-H 6...   | PR<br>3040559       | PR/2<br>3040630                | PZ/2<br>3040627       | —               | —                       | PRZ<br>3040614       |
|             | —                   | PTR/2 <sup>1)</sup><br>3040631 | —                     | —               | —                       | —                    |

<sup>1)</sup> Release with just a screwdriver

## PT accessories

Example of a 6 mm<sup>2</sup> central supply with  
RB ST 6-(2,5/4) reducing bridge on PT 2,5 and  
RB ST 6-1,5/S on PT 1,5/S



### Reduction bridging with standard feed-through terminal blocks

| Supply         |                     | Pick-off       |                     | Single-sided supply  | Central power feed   |                                |
|----------------|---------------------|----------------|---------------------|----------------------|----------------------|--------------------------------|
| Terminal block | Cross section [mm²] | Terminal block | Cross section [mm²] | I <sub>max</sub> [A] | I <sub>max</sub> [A] | Bridge                         |
| PT 2,5         | 2.5                 | PT 1,5/S       | 1.5                 | 24                   | 30                   | RB ST (2,5/4)-1,5/S<br>3214356 |
|                |                     | ST 1,5         | 1.5                 | 31                   | 31                   | RB ST (2,5/4)-1,5<br>3038943   |
|                |                     | QTC 1,5        | 1.5                 | 31                   | 31                   | FBS 2-5<br>3030161             |
| PT 4           | 4                   | PT 1,5/S       | 1.5                 | 24                   | 40                   | RB ST (2,5/4)-1,5/S<br>3214356 |
|                |                     | ST 1,5         | 1.5                 | 35                   | 40                   | RB ST (2,5/4)-1,5<br>3038943   |
|                |                     | PT 2,5         | 2.5                 | 40                   | 40                   | FBS 2-5<br>3030161             |
|                |                     | ST 2,5         | 2.5                 | 40                   | 40                   |                                |
|                |                     | QTC 1,5        | 1.5                 | 35                   | 40                   | FBS 2-6<br>3030336             |
|                |                     | QTC 2,5        | 2.5                 | 40                   | 40                   |                                |
|                |                     |                |                     |                      |                      |                                |
| PT 6           | 6                   | PT 1,5/S       | 1.5                 | 26                   | 52                   | RB ST 6-1,5/S<br>3213250       |
|                |                     | PT 2,5         | 2.5                 | 40                   | 56                   | RB ST 6-(2,5/4)<br>3030860     |
|                |                     | PT 4           | 4                   | 45                   | 56                   |                                |
|                |                     | ST 2,5         | 2.5                 | 40                   | 56                   |                                |
|                |                     | ST 4           | 4                   | 45                   | 56                   |                                |
|                |                     | QTC 1,5        | 1.5                 | 35                   | 56                   |                                |
|                |                     | QTC 2,5        | 2.5                 | 40                   | 56                   |                                |
| PT 10          | 10                  | PT 2,5         | 2.5                 | 40                   | 65                   | RB ST 10-(2,5/4)<br>3030873    |
|                |                     | PT 4           | 4                   | 45                   | 65                   |                                |
|                |                     | ST 2,5         | 2.5                 | 40                   | 65                   |                                |
|                |                     | ST 4           | 4                   | 45                   | 65                   |                                |
|                |                     | QTC 1,5        | 1.5                 | 35                   | 65                   |                                |
|                |                     | QTC 2,5        | 2.5                 | 40                   | 65                   |                                |
|                |                     |                |                     |                      |                      |                                |
| PT 16          | 16                  | PT 1,5/S       | 1.5                 | 24                   | 48                   | RB ST 16-1,5/S<br>3213254      |
|                |                     | PT 2,5         | 2.5                 | 40                   | 80                   | RB ST 16-(2,5/4)<br>3030886    |
|                |                     | PT 4           | 4                   | 45                   | 90                   |                                |
|                |                     | ST 2,5         | 2.5                 | 40                   | 80                   |                                |
|                |                     | ST 4           | 4                   | 45                   | 90                   |                                |
|                |                     | QTC 1,5        | 1.5                 | 35                   | 70                   |                                |
|                |                     | QTC 2,5        | 2.5                 | 40                   | 80                   |                                |
| PTPOWER 35     | 35                  | ST 16          | 16                  | 90                   | 90                   | RB 35-16<br>3032169            |


17

19

10

11

| Terminal block                 | Test plugs consist of:         |                           | Mounting material             |                          |                                    |
|--------------------------------|--------------------------------|---------------------------|-------------------------------|--------------------------|------------------------------------|
|                                | Metal part,<br>2.3 mm diameter | Insulating sleeve,<br>red | Quick mounting<br>end bracket | Group<br>labelling field | Terminal strips,<br>marker carrier |
| PT... 1.5<br>PTTB... 1.5...    | MPS-MT<br>0201744              | MPS-IH RD<br>0201676      | CLIPFIX 35-5<br>3022276       | —                        | KLM 3-L<br>0814788                 |
| PT... 2.5...<br>PTTB... 2.5... |                                |                           |                               |                          |                                    |
| PT 2,5-4L/1...                 |                                |                           |                               |                          |                                    |
| PT... 4...<br>PTTB... 4...     |                                |                           |                               |                          |                                    |
| PT... 6...                     |                                |                           |                               |                          |                                    |
| PT... 10...                    |                                |                           |                               |                          |                                    |
| PT... 16...                    |                                |                           |                               |                          |                                    |
|                                |                                |                           |                               |                          |                                    |



13

13

15

16

18

# Mounting material

DIN rail  
35 x 7.5 mm

DIN rail  
35 x 15 mm

DIN rail  
connection piece

Adhesive label with  
assembly instructions

Screwdriver

NS 35/7,5 UNPERF 2000MM  
0801681  
NS 35/7,5 PERF 2000MM  
0801733

NS 35/15 UNPERF 2000MM  
1201714  
NS 35/15 PERF 2000MM  
1201730

NS 35/7,5 CAP  
1206560  
NS 35/15 CAP  
1206573

PT-IL  
3208090

SZF 0-0,4X2,5  
1204504  
SZF 1-0,6X3,5  
1204517  
SZF 1-0,6X3,5  
1204517  
SZF 1-0,6X3,5  
1204517  
SZF 2-0,8X4,0  
1204520  
SZF 3-1,0X5,5  
1206612  
SZF 3-1,0X5,5  
1206612

## 1

62 PHOENIX CONTACT

# PT accessories

| 12                      | 2                                    | 3                    | 4                         | 14                    | 5                 | 6                          | 7                            | 8                                    | 9                     |
|-------------------------|--------------------------------------|----------------------|---------------------------|-----------------------|-------------------|----------------------------|------------------------------|--------------------------------------|-----------------------|
| Vertical bridge         | Cover                                | End cover segment    | Partition plate           | Test adapter 4 mm     | Modular test plug | Spacer plate for test plug | Center groove                | Marking<br>Center and lateral groove | Marker carrier        |
| –                       | D-PT 1,5/S<br>3208142                | –                    | ATP-ST 4<br>3030721       | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-PT 1,5/S-TWIN<br>3208184           | –                    | ATP-ST-TWIN<br>3030789    | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-PT 1,5/S-QUATTRO<br>3208375        | –                    | ATP-ST QUATTRO<br>3030815 | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-PT 1,5/S-QUATTRO/2P<br>3212426     | –                    | ATP-ST QUATTRO<br>3030815 | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| FBS 1,5/S-PV<br>3216263 | D-PTTB 1,5/S<br>3208579              | –                    | ATP-STTB 4<br>3030747     | –                     | –                 | –                          | –                            | UCT-TMF 3,5 or<br>ZBF 3,5            | STP 3,5-2<br>0830131  |
| FBS 1,5/S-PV<br>3216263 | D-PTTB 1,5/S/2P<br>3212471           | –                    | ATP-STTB 4<br>3030747     | –                     | –                 | –                          | –                            | UCT-TMF 3,5 or<br>ZBF 3,5            | STP 3,5-2<br>0830131  |
| FBS 1,5/S-PV<br>3216263 | D-PTTB 1,5/S/4P<br>3213894           | –                    | ATP-STTB 4<br>3030747     | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| FBS 1,5/S-PV<br>3216263 | D-PT 1,5/S-3L<br>3113771             | –                    | –                         | –                     | –                 | –                          | –                            | UCT-TMF 3,5 or<br>ZBF 3,5            | STP 3,5-2<br>0830131  |
| –                       | D-PTS 1,5/S<br>3214576               | –                    | ATP-ST 4<br>3030721       | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-PTS 1,5/S<br>3214576               | –                    | ATP-ST 4<br>3030721       | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| FBS 1,5/S-PV<br>3216263 | D-PTTBS 1,5/S<br>3214699             | –                    | ATP-STTB 4<br>3030747     | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| FBS 1,5/S-PV<br>3216263 | D-PTTBS 1,5/S/2P<br>3214534          | –                    | ATP-STTB 4<br>3030747     | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-PTIO 1,5/S/3<br>3244575            | –                    | ATP-ST QUATTRO<br>3030815 | –                     | –                 | –                          | –                            | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-PTIO 1,5/S/4<br>3244588            | –                    | –                         | –                     | –                 | –                          | –                            | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-PT 1,5/S-MT-0,8<br>3210303         | –                    | ATP-ST QUATTRO<br>3030815 | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-PT 1,5/S-TWIN-MT-0,8<br>3210313    | –                    | ATP-ST QUATTRO<br>3030815 | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-PT 1,5/S-QUATTRO-MT-0,8<br>3210333 | –                    | ATP-ST QUATTRO<br>3030815 | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-PTT 1,5/S-2MT-0,8<br>3210353       | –                    | ATP-STTB 4<br>3030747     | –                     | –                 | –                          | –                            | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-MPT 1,5/S<br>3248120               | –                    | –                         | –                     | –                 | –                          | –                            | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| FBS 1,5/S-PV<br>3216263 | D-PTTBS 1,5/S/2P<br>3214534          | –                    | ATP-STTB 4<br>3030747     | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | –                                    | –                     |
| FBS 1,5/S-PV<br>3216263 | D-PTTB 1,5/S/4P<br>3213894           | –                    | ATP-STTB 4<br>3030747     | –                     | –                 | –                          | UCT-TM 3,5 or<br>ZB 3,5      | UCT-TMF 3,5 or<br>ZBF 3,5            | –                     |
| –                       | D-ST 2,5<br>3030417                  | –                    | ATP-ST 4<br>3030721       | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | STP 5-2-ZB<br>3037643 |
| –                       | D-ST 2,5-TWIN<br>3030488             | DS-ST 2,5<br>3036602 | ATP-ST-TWIN<br>3030789    | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | STP 5-2-ZB<br>3037643 |
| –                       | D-ST 2,5-QUATTRO<br>3030514          | DS-ST 2,5<br>3036602 | ATP-ST QUATTRO<br>3030815 | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | STP 5-2-ZB<br>3037643 |
| –                       | D-ST 2,5-QUATTRO/2P<br>3040083       | –                    | ATP-ST QUATTRO<br>3030815 | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |
| –                       | D-PT 2,5-HEXA/3P<br>3040058          | –                    | –                         | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |
| –                       | D-ST 2,5-QUATTRO/4P<br>3042175       | –                    | ATP-ST QUATTRO<br>3030815 | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | –                                    | –                     |
| FBS-PV<br>3032185       | D-PTTB 2,5<br>3211634                | –                    | ATP-STTB 4<br>3030747     | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | –                            | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | STP 5-2<br>0800967    |
| FBS-PV<br>3032185       | D-STTB 2,5/2P<br>3040096             | –                    | ATP-STTB 4<br>3030747     | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | –                            | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |
| FBS-PV<br>3032185       | D-STTB 2,5/4P<br>3061538             | –                    | ATP-STTB 4<br>3030747     | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |
| FBS-PV<br>3032185       | D-PT 2,5-3L<br>3211647               | –                    | –                         | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | –                            | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | STP 5-3<br>0810562    |
| FBS-PV<br>3032185       | –                                    | –                    | –                         | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | –                                    | –                     |
| FBS-PV<br>3032185       | –                                    | –                    | –                         | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | –                                    | –                     |
| –                       | D-PTC 2,5-MT<br>3270097              | –                    | ATP-ST QUATTRO<br>3030815 | –                     | –                 | –                          | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |
| –                       | D-PTC 2,5-TWIN-MT<br>3270100         | –                    | ATP-ST QUATTRO<br>3030815 | –                     | –                 | –                          | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |
| –                       | D-PTC 2,5-QUATTRO-MT<br>3270103      | –                    | ATP-ST QUATTRO<br>3030815 | –                     | –                 | –                          | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |
| –                       | D-PT 2,5-MT<br>3211003               | –                    | ATP-ST QUATTRO<br>3030815 | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |
| –                       | D-PT 2,5-TWIN-MT<br>3211317          | –                    | ATP-ST QUATTRO<br>3030815 | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |
| –                       | D-ST 2,5-QUATTRO-MT<br>3038590       | –                    | –                         | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |
| –                       | D-PT 2,5-MTB<br>3210196              | –                    | –                         | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |
| –                       | D-PT 2,5-TWIN-MTB<br>3210202         | –                    | –                         | PAI-4-N GY<br>3032871 | PS-5<br>3030983   | DP PS-5<br>3036725         | UC-TM 5, UCT-TM 5<br>or ZB 5 | UC-TMF 5, UCT-TMF 5<br>or ZBF 5      | –                     |

# PT accessories

1

| Terminal                                       | Jumpers               |                     |                       |                     |                           |                     |                                 |                     |                     |                      |                     |  |
|------------------------------------------------|-----------------------|---------------------|-----------------------|---------------------|---------------------------|---------------------|---------------------------------|---------------------|---------------------|----------------------|---------------------|--|
|                                                | 2-pos.                |                     | 3-pos.                |                     | 4-pos.                    |                     | 5-pos.                          |                     | 10-pos.             |                      | 20-pos.             |  |
|                                                | FBS...                | FBSR...             | FBS...                | FBSR...             | FBS...                    | FBSR...             | FBS...                          | FBSR...             | FBS...              | FBSR...              | FBS...              |  |
| PT 2,5-QUATTRO-MTB/...-TGB                     | FBS 2-5<br>3030161    | FBSR 2-5<br>3033702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PTS 2,5.../ PTS 2,5-TWIN.../                   | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PTS 2,5-QUATTRO...                             | —                     | —                   | —                     | —                   | —                         | —                   | —                               | —                   | —                   | —                    | —                   |  |
| PTTBS 2,5...                                   | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PTI 2,5-L... / PTI 2,5-PE...                   | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PTB 2,5-PE...                                  | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PT 2,5-PE/3L                                   | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PTT 2,5...                                     | —                     | —                   | —                     | —                   | —                         | —                   | —                               | —                   | —                   | —                    | —                   |  |
| PTTBS 2,5-2MTB /<br>PTTBS 2,5-2TGB             | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PTI 2,5-...LTB /<br>PTI 2,5-...TG              | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PTU 2,5...                                     | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PTU 2,5-TWIN...                                | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| MPT 2,5...                                     | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PT 2,5-4L/1P                                   | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PT 2,5-4L/2P /<br>PT 2,5-PE/3L/2P              | FBS 2-5<br>3030161    | FBSR 2-5<br>3030702 | FBS 3-5<br>3030174    | FBSR 3-5<br>3001591 | FBS 4-5<br>3030187        | FBSR 4-5<br>3001592 | FBS 5-5<br>3030190              | FBSR 5-5<br>3001593 | FBS 10-5<br>3030213 | FBSR 10-5<br>3033710 | FBS 20-5<br>3030226 |  |
| PT 4-.../ PT 4-DIO... /<br>PT 4/1P.../ ST 4/2P | FBS 2-6<br>3030336    | FBSR 2-6<br>3033715 | FBS 3-6<br>3030242    | FBSR 3-6<br>3001594 | FBS 4-6<br>3030255        | FBSR 4-6<br>3001595 | FBS 5-6<br>3030349              | FBSR 5-6<br>3001596 | FBS 10-6<br>3030271 | FBSR 10-6<br>3033716 | FBS 20-6<br>3030365 |  |
| PT 4-TWIN...                                   | FBS 2-6<br>3030336    | FBSR 2-6<br>3033715 | FBS 3-6<br>3030242    | FBSR 3-6<br>3001594 | FBS 4-6<br>3030255        | FBSR 4-6<br>3001595 | FBS 5-6<br>3030349              | FBSR 5-6<br>3001596 | FBS 10-6<br>3030271 | FBSR 10-6<br>3033716 | FBS 20-6<br>3030365 |  |
| PT 4-QUATTRO... /<br>PT 4-QUATTRO-DIO...       | FBS 2-6<br>3030336    | FBSR 2-6<br>3033715 | FBS 3-6<br>3030242    | FBSR 3-6<br>3001594 | FBS 4-6<br>3030255        | FBSR 4-6<br>3001595 | FBS 5-6<br>3030349              | FBSR 5-6<br>3001596 | FBS 10-6<br>3030271 | FBSR 10-6<br>3033716 | FBS 20-6<br>3030365 |  |
| PTC 4-HESI...                                  | —                     | —                   | —                     | —                   | —                         | —                   | —                               | —                   | —                   | —                    | —                   |  |
| PT 4-HESI...                                   | FBS 2-6<br>3030336    | FBSR 2-6<br>3033715 | FBS 3-6<br>3030242    | FBSR 3-6<br>3001594 | FBS 4-6<br>3030255        | FBSR 4-6<br>3001595 | FBS 5-6<br>3030349              | FBSR 5-6<br>3001596 | FBS 10-6<br>3030271 | FBSR 10-6<br>3033716 | FBS 20-6<br>3030365 |  |
| PTU 4-TWIN...                                  | FBS 2-6<br>3030336    | FBSR 2-6<br>3033715 | FBS 3-6<br>3030242    | FBSR 3-6<br>3001594 | FBS 4-6<br>3030255        | FBSR 4-6<br>3001595 | FBS 5-6<br>3030349              | FBSR 5-6<br>3001596 | FBS 10-6<br>3030271 | FBSR 10-6<br>3033716 | FBS 20-6<br>3030365 |  |
| PTU 4-MT... /<br>PTU 4-TG...                   | FBS 2-6<br>3030336    | FBSR 2-6<br>3033715 | FBS 3-6<br>3030242    | FBSR 3-6<br>3001594 | FBS 4-6<br>3030255        | FBSR 4-6<br>3001595 | FBS 5-6<br>3030349              | FBSR 5-6<br>3001596 | FBS 10-6<br>3030271 | FBSR 10-6<br>3033716 | FBS 20-6<br>3030365 |  |
| PT 4-MT/...-TG /<br>PT 4-FSI/F...              | —                     | —                   | —                     | —                   | —                         | —                   | —                               | —                   | —                   | —                    | —                   |  |
| PTI 4...                                       | FBS 2-6<br>3030336    | FBSR 2-6<br>3033715 | FBS 3-6<br>3030242    | FBSR 3-6<br>3001594 | FBS 4-6<br>3030255        | FBSR 4-6<br>3001595 | FBS 5-6<br>3030349              | FBSR 5-6<br>3001596 | FBS 10-6<br>3030271 | FBSR 10-6<br>3033716 | FBS 20-6<br>3030365 |  |
| PTTB 4...                                      | FBS 2-6<br>3030336    | FBSR 2-6<br>3033715 | FBS 3-6<br>3030242    | FBSR 3-6<br>3001594 | FBS 4-6<br>3030255        | FBSR 4-6<br>3001595 | FBS 5-6<br>3030349              | FBSR 5-6<br>3001596 | FBS 10-6<br>3030271 | FBSR 10-6<br>3033716 | FBS 20-6<br>3030365 |  |
| PT 4-PE/3L                                     | FBS 2-6<br>3030336    | FBSR 2-6<br>3033715 | FBS 3-6<br>3030242    | FBSR 3-6<br>3001594 | FBS 4-6<br>3030255        | FBSR 4-6<br>3001595 | FBS 5-6<br>3030349              | FBSR 5-6<br>3001596 | FBS 10-6<br>3030271 | FBSR 10-6<br>3033716 | FBS 20-6<br>3030365 |  |
| PT 6...                                        | FBS 2-8<br>3030284    | FBSR 2-8<br>3033808 | FBS 3-8<br>3030297    | FBSR 3-8<br>3001597 | FBS 4-8<br>3030307        | FBSR 4-8<br>3000585 | FBS 5-8<br>3030310              | FBSR 5-8<br>3033809 | FBS 10-8<br>3030323 | FBSR 10-8<br>3001599 | —                   |  |
| PT 6-TWIN...                                   | FBS 2-8<br>3030284    | FBSR 2-8<br>3033808 | FBS 3-8<br>3030297    | FBSR 3-8<br>3001597 | FBS 4-8<br>3030307        | FBSR 4-8<br>3000585 | FBS 5-8<br>3030310              | FBSR 5-8<br>3033809 | FBS 10-8<br>3030323 | FBSR 10-8<br>3001599 | —                   |  |
| PT 6-QUATTRO...                                | FBS 2-8<br>3030284    | FBSR 2-8<br>3033808 | FBS 3-8<br>3030297    | FBSR 3-8<br>3001597 | FBS 4-8<br>3030307        | FBSR 4-8<br>3000585 | FBS 5-8<br>3030310              | FBSR 5-8<br>3033809 | FBS 10-8<br>3030323 | FBSR 10-8<br>3001599 | —                   |  |
| PTU 6...                                       | FBS 2-8<br>3030284    | FBSR 2-8<br>3033808 | FBS 3-8<br>3030297    | FBSR 3-8<br>3001597 | FBS 4-8<br>3030307        | FBSR 4-8<br>3000585 | FBS 5-8<br>3030310              | FBSR 5-8<br>3033809 | FBS 10-8<br>3030323 | FBSR 10-8<br>3001599 | —                   |  |
| PT 6-QUATTRO/2P...                             | FBS 2-8<br>3030284    | FBSR 2-8<br>3033808 | FBS 3-8<br>3030297    | FBSR 3-8<br>3001597 | FBS 4-8<br>3030307        | FBSR 4-8<br>3000585 | FBS 5-8<br>3030310              | FBSR 5-8<br>3033809 | FBS 10-8<br>3030323 | FBSR 10-8<br>3001599 | —                   |  |
| PT 10...                                       | FBS 2-10<br>3005947   | —                   | —                     | —                   | —                         | —                   | FBS 5-10<br>3005948             | —                   | —                   | —                    | —                   |  |
| PT 10-TWIN...                                  | FBS 2-10<br>3005947   | —                   | —                     | —                   | —                         | —                   | FBS 5-10<br>3005948             | —                   | —                   | —                    | —                   |  |
| PT 10-HESI...                                  | —                     | —                   | —                     | —                   | —                         | —                   | —                               | —                   | —                   | —                    | —                   |  |
| PT 16...                                       | FBS 2-12<br>3005950   | —                   | —                     | —                   | —                         | —                   | —                               | —                   | —                   | —                    | —                   |  |
| PT 16-TWIN...                                  | FBS 2-12<br>3005950   | —                   | —                     | —                   | —                         | —                   | —                               | —                   | —                   | —                    | —                   |  |
| High-current terminal block                    | Insertion bridges     |                     |                       |                     | Tap-off terminal blocks   |                     | Marking                         |                     | Screwdriver         |                      |                     |  |
|                                                | 2-pos.                |                     | 3-pos.                |                     |                           |                     |                                 |                     |                     |                      |                     |  |
| PTPOWER 35...                                  | EB 2-16/PT<br>3212089 |                     | EB 3-16/PT<br>3212090 |                     | —                         |                     | UC-TM 12, UCT-TM 12<br>or ZB 12 |                     | SZF 3-1,0X5,5       |                      |                     |  |
| PTPOWER 50...                                  | EB 2-20/PT<br>3260067 |                     | EB 3-20/PT<br>3260068 |                     | —                         |                     | UC-TM 12, UCT-TM 12<br>or ZB 12 |                     | SZF 3-1,0X5,5       |                      |                     |  |
| PTPOWER 95...                                  | EB 2-25/PT<br>3260157 |                     | EB 3-25/PT<br>3260160 |                     | AGK 10-PTPOWER<br>3260145 |                     | UC-TM 12, UCT-TM 12<br>or ZB 12 |                     | SZF 3-1,0X5,5       |                      |                     |  |
| PTPOWER 150...                                 | EB 2-31/PT<br>3215057 |                     | EB 3-31/PT<br>3215058 |                     | AGK 10-PTPOWER<br>3260145 |                     | UC-TM 12, UCT-TM 12<br>or ZB 12 |                     | SZF 3-1,0X5,5       |                      |                     |  |

# PT accessories

| 12                       | 2                            | 3                 | 4                      | 14                 | 5                 | 6                          | 7                            | 8                                 | 9                  |
|--------------------------|------------------------------|-------------------|------------------------|--------------------|-------------------|----------------------------|------------------------------|-----------------------------------|--------------------|
| Vertical bridge          | Cover                        | End cover segment | Partition plate        | Test adapter 4 mm  | Modular test plug | Spacer plate for test plug | Center groove                | Marking Center and lateral groove | Marker carrier     |
| –                        | D-PT 2,5-QUATTRO-MTB 3210209 | –                 | –                      | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | UC-TM 5, UCT-TM 5 or ZB 5    | UC-TMF 5, UCT-TMF 5 or ZBF 5      | –                  |
| –                        | D-ST 2,5 3031762             | –                 | ATP-ST 4 3030721       | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | UC-TM 5, UCT-TM 5 or ZB 5    | UC-TMF 5, UCT-TMF 5 or ZBF 5      | STP 5-2-ZB 3037643 |
| –                        | D-ST 2,5 3031762             | –                 | ATP-ST 4 3030721       | –                  | –                 | –                          | UC-TM 5, UCT-TM 5 or ZB 5    | –                                 | STP 5-2-ZB 3037643 |
| FBS-PV 3032185           | D-STTB 2,5 3038503           | –                 | ATP-STTB 4 3030747     | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | UC-TM 5, UCT-TM 5 or ZB 5    | UC-TMF 5, UCT-TMF 5 or ZBF 5      | STP 5-2-ZB 3037643 |
| –                        | D-PTI/3 3213975              | –                 | ATP-PTI/3 3213990      | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | UC-TM 5, UCT-TM 5 or ZB 5    | UC-TMF 5, UCT-TMF 5 or ZBF 5      | –                  |
| –                        | D-PTB 2,5/3 3210552          | –                 | –                      | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | UC-TM 5, UCT-TM 5 or ZB 5    | UC-TMF 5, UCT-TMF 5 or ZBF 5      | –                  |
| FBS-PV UT 3047358        | D-PT 2,5-PE/3L 3210543       | –                 | –                      | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | UC-TM 5, UCT-TM 5 or ZB 5    | UC-TMF 5, UCT-TMF 5 or ZBF 5      | –                  |
| –                        | D-PTT 2,5/S-2MT-0,8 3210300  | –                 | ATP-STTB 4 3030747     | –                  | –                 | –                          | –                            | UC-TMF 5, UCT-TMF 5 or ZBF 5      | –                  |
| FBS-PV 3032185           | D-PTTB 2,5-2MTB 3210404      | –                 | –                      | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | UC-TM 5, UCT-TM 5 or ZB 5    | –                                 | –                  |
| –                        | D-PTI 2,5/3B 3213959         | –                 | ATP-PTI/3 3213990      | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | –                            | UC-TMF 5, UCT-TMF 5 or ZBF 5      | –                  |
| –                        | –                            | –                 | –                      | –                  | –                 | –                          | –                            | –                                 | –                  |
| –                        | D-STU 2,5-TWIN 3033045       | –                 | ATP-ST-TWIN 3030789    | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | UC-TM 5, UCT-TM 5 or ZB 5    | UC-TMF 5, UCT-TMF 5 or ZBF 5      | STP 5-2-ZB 3037643 |
| –                        | D-MPT 2,5 3248140            | –                 | –                      | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | –                            | UC-TMF 5, UCT-TMF 5 or ZBF 5      | –                  |
| FBS-PV PT 2,5-4L 3012318 | D-PT 2,5-4L/1P 3012301       | –                 | –                      | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | –                            | UC-TMF 5, UCT-TMF 5 or ZBF 5      | –                  |
| FBS-PV PT 2,5-4L 3012318 | D-PT 2,5-4L/2P 3012311       | –                 | –                      | PAI-4-N GY 3032871 | PS-5 3030983      | DP PS-5 3036725            | –                            | UC-TMF 5, UCT-TMF 5 or ZBF 5      | –                  |
| –                        | D-ST 4 3030420               | –                 | ATP-ST 4 3030721       | PAI-4-N GY 3032871 | PS-6 3030996      | DP PS-6 3036738            | UC-TM 6, UCT-TM 6 or ZB 6    | UC-TMF 6, UCT-TMF 6 or ZBF 6      | STP 5-2-ZB 3037643 |
| –                        | D-PT 4-TWIN 3208977          | –                 | ATP-ST-TWIN 3030789    | PAI-4-N GY 3032871 | PS-6 3030996      | DP PS-6 3036738            | UC-TM 6, UCT-TM 6 or ZB 6    | UC-TMF 6, UCT-TMF 6 or ZBF 6      | STP 5-2-ZB 3037643 |
| –                        | D-PT 4-QUATTRO 3208979       | –                 | ATP-ST QUATTRO 3030815 | PAI-4-N GY 3032871 | PS-6 3030996      | DP PS-6 3036738            | UC-TM 6, UCT-TM 6 or ZB 6    | UC-TMF 6, UCT-TMF 6 or ZBF 6      | STP 5-2-ZB 3037643 |
| –                        | –                            | –                 | ATP-ST QUATTRO 3030815 | –                  | –                 | –                          | –                            | UC-TMF 6, UCT-TMF 6 or ZBF 6      | –                  |
| –                        | D-ST 4 3030420               | –                 | ATP-ST 4 3030721       | PAI-4-N GY 3032871 | PS-6 3030996      | DP PS-6 3036738            | UC-TM 6, UCT-TM 6 or ZB 6    | UC-TMF 6, UCT-TMF 6 or ZBF 6      | –                  |
| –                        | D-PTU 4-TWIN 3211863         | –                 | ATP-ST-TWIN 3030789    | PAI-4-N GY 3032871 | PS-6 3030996      | DP PS-6 3036738            | UC-TM 6, UCT-TM 6 or ZB 6    | UC-TMF 6, UCT-TMF 6 or ZBF 6      | STP 5-2-ZB 3037643 |
| –                        | D-PTU 4-MT 3209534           | –                 | ATP-ST QUATTRO 3030815 | PAI-4-N GY 3032871 | PS-6 3030996      | DP PS-6 3036738            | UC-TM 6, UCT-TM 6 or ZB 6    | UC-TMF 6, UCT-TMF 6 or ZBF 6      | –                  |
| –                        | D-ST 4 3030420               | –                 | ATP-ST 4 3030721       | –                  | –                 | –                          | –                            | UC-TMF 6, UCT-TMF 6 or ZBF 6      | –                  |
| –                        | D-PTI 4/3 3214054            | –                 | –                      | PAI-4-N GY 3032871 | PS-6 3030996      | DP PS-6 3036738            | –                            | UC-TMF 6, UCT-TMF 6 or ZBF 6      | –                  |
| FBS-PV 3032185           | D-STTB 4 3030462             | –                 | ATP-STTB 4 3030747     | PAI-4-N GY 3032871 | PS-6 3030996      | DP PS-6 3036738            | –                            | UC-TMF 6, UCT-TMF 6 or ZBF 6      | STP 5-2 0800967    |
| FBS-PV UT 3047358        | D-PT 4-PE/ 3L 3210443        | –                 | –                      | PAI-4-N GY 3032871 | PS-6 3030996      | DP PS-6 3036738            | UC-TM 6, UCT-TM 6 or ZB 6    | UC-TMF 6, UCT-TMF 6 or ZBF 6      | –                  |
| –                        | D-PT 6 3212044               | –                 | ATP-ST 6 3024481       | PAI-4-N GY 3032871 | PS-8 3031005      | DP PS-8 3036741            | UC-TM 8, UCT-TM 8 or ZB 8    | UC-TMF 8, UCT-TMF 8 or ZBF 8      | STP 5-2-ZB 3037643 |
| –                        | D-PT 6-TWIN 3211508          | –                 | –                      | PAI-4-N GY 3032871 | PS-8 3031005      | DP PS-8 3036741            | UC-TM 8, UCT-TM 8 or ZB 8    | UC-TMF 8, UCT-TMF 8 or ZBF 8      | STP 5-2-ZB 3037643 |
| –                        | D-PT 6-QUATTRO 3212963       | –                 | –                      | PAI-4-N GY 3032871 | PS-8 3031005      | DP PS-8 3036741            | UC-TM 8, UCT-TM 8 or ZB 8    | UC-TMF 8, UCT-TMF 8 or ZBF 8      | STP 5-2-ZB 3037643 |
| –                        | D-PTU 6-T 3209533            | –                 | –                      | PAI-4-N GY 3032871 | PS-8 3031005      | DP PS-8 3036741            | UC-TM 8, UCT-TM 8 or ZB 8    | UC-TMF 8, UCT-TMF 8 or ZBF 8      | –                  |
| –                        | D-PT 6-QUATTRO/2P 3061855    | –                 | –                      | PAI-4-N GY 3032871 | PS-8 3031005      | DP PS-8 3036741            | UC-TM 8, UCT-TM 8 or ZB 8    | UC-TMF 8, UCT-TMF 8 or ZBF 8      | –                  |
| –                        | D-PT 10 3212057              | –                 | –                      | –                  | –                 | –                          | UC-TM 10, UCT-TM 10 or ZB 10 | UC-TMF 10, UCT-TMF 10 or ZBF 10   | STP 5-2-ZB 3037643 |
| –                        | D-PT 10-TWIN 3208748         | –                 | –                      | –                  | –                 | –                          | UC-TM 10, UCT-TM 10 or ZB 10 | UC-TMF 10, UCT-TMF 10 or ZBF 10   | STP 5-2-ZB 3037643 |
| –                        | –                            | –                 | –                      | –                  | –                 | –                          | –                            | UC-TMF 10, UCT-TMF 10 or ZBF 10   | –                  |
| –                        | D-PT 16 N 3212138            | –                 | –                      | –                  | –                 | –                          | UC-TM 12, UCT-TM 12 or ZB 12 | UC-TMF 12, UCT-TMF 12 or ZBF 12   | –                  |
| –                        | D-PT 16-TWIN N 3208799       | –                 | –                      | –                  | –                 | –                          | UC-TM 12, UCT-TM 12 or ZB 12 | UC-TMF 12, UCT-TMF 12 or ZBF 12   | –                  |

# CLIP PROJECT – Planning and marking software


CLIP PROJECT combines our proven planning software for terminal strip configuration with a high-performance marking tool. Direct data exchange with all conventional CAE programs, along with the creation of the complete project documentation, are what make this configuration software unique.

And there's more: With CLIP PROJECT you can also create the marking for all of your applications.


Use CLIP PROJECT to develop your DIN rail modules – complete with bridging, marking, and further accessories.




By integrating CLIP PROJECT in EPLAN P8, terminal strips are automatically produced from the circuit diagram in CLIP PROJECT. The product data is written back to the EPLAN parts lists using the two-way interface.



The automatic correction function checks the configured terminal strip and automatically adds any missing accessories. 2D and 3D design data are available with a click of the mouse.



The configured terminal strips can be distributed across several DIN rails in order to determine the exact space requirements for installation.



Complete documentation and an effective 3D preview are available for rapidly and correctly producing the mechanical structure of the terminal strips.




Phoenix Contact provides a terminal strip service. The terminal strips configured to suit your requirements can be ordered using the e-mail function. Phoenix Contact will supply the terminal strips promptly.

# Push-in connection technology – Consistent from the field to the controller

Push-in connection technology from Phoenix Contact allows you to wire your entire application easily and safely.

A complete product range is available for consistent wiring, from field wiring to power and control wiring. You can easily connect sensors and actuators, modular terminal blocks, and interface and automation components without using any tools.

Push-in - the new insertion experience!



**Interface components  
with push-in connection**




**Field cabling  
with push-in connection**



I/O system and controller with push-in connection

Modular terminal blocks with push-in connection



# Push-in connection technology – Reliable and used worldwide

We are at home in electrical engineering and automation in many sectors of industry.

Our products prove themselves daily, in machines and systems across the globe. Reap the benefits of push-in connection technology for your application – consistent from the field to the controller.

DMG MORI SEIKI offers its customers a unique range of services in the field of machine tool manufacturing, through combining innovative technologies and a global, highly qualified sales and service network.

Wired with push-in connection technology from Phoenix Contact.

[www.dmgmori-seiki.com](http://www.dmgmori-seiki.com)




DMG MORI SEIKI



## Push-in Technology

Designed by PHOENIX CONTACT



The TRUMPF Group is the global leader in production, laser, and medical technology. TRUMPF offers its customers both innovative and high-quality products, as well as solutions to their problems – in sheet metal processing, laser-based production processes, electronic applications, and hospital equipment. Wired with push-in connection technology from Phoenix Contact. [www.trumpf.com](http://www.trumpf.com)



Grenzbach's assembly lines for materials, glass, and photovoltaics are used throughout the world wherever high demands are made on automation and material flow control. Fast manufacturing times and rapid startup on site are some of the keys to its success. In doing so, the company puts its trust in push-in connection technology from Phoenix Contact. [www.grenzbach.com](http://www.grenzbach.com)



The Weinig Group AG is the market leader in solid wood processing machines and turn-key production systems for industrial and manual operations. In addition to series production of machines, the company increasingly offers its customers tailored solutions. When it comes to wiring, Weinig puts its trust in push-in connection technology from Phoenix Contact. [www.weinig.com](http://www.weinig.com)



Always up-to-date, always available to you. Here you'll find everything on our products, solutions and service:

[phoenixcontact.com](http://phoenixcontact.com)

## Product range

- Cables and wires
- Connectors
- Controllers
- Electronics housing
- Electronic switchgear and motor control
- Fieldbus components and systems
- Functional safety
- HMIs and industrial PCs
- I/O systems
- Industrial communication technology
- Industrial Ethernet
- Installation and mounting material
- Lighting and signaling
- Marking and labeling
- Measurement and control technology
- Modular terminal blocks
- Monitoring
- PCB terminal blocks and PCB connectors
- Plug-in connectors
- Protective devices
- Relay modules
- Sensor/actuator cabling
- Software
- Surge protection and interference filters
- System cabling for controllers
- Tools
- Wireless data communication

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
32825 Blomberg, Germany  
Phone: +49 (0) 52 35 3-00  
Fax: +49 (0) 52 35 3-4 12 00  
E-mail: [info@phoenixcontact.com](mailto:info@phoenixcontact.com)  
[phoenixcontact.com](http://phoenixcontact.com)



INSPIRING INNOVATIONS

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)