

## 502PTZ Composite - For PTZ Cameras: CCTV + Control + Power



For more Information  
please call

1-800-Belden1



### Description:

(1) coax-20 AWG solid BC cond., gas-injected foam HDPE insul., 95% BC braid shield, PVC jkt., cabled with (1) pair - 18 AWG stranded (19x30) BC cond., PO insul., Beldfoil® shield, PVC jkt., cabled with (2) cond.-18 AWG (7x26) BC cond., PP insul., PVC Jkt.

### Coax

#### Physical Characteristics

##### Conductor

###### AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	Solid	BC - Bare Copper	0.032

##### Insulation

###### Insulation Material:

Insulation Material	Dia. (in.)
Gas-injected FHDPE - Foam High Density Polyethylene	0.145

##### Outer Shield

###### Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95.000

##### Outer Jacket

###### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

###### Outer Jacket Diameter:

Nom. Dia. (in.)
0.227

###### Outer Jacket Color Code Chart:

Number	Color
Video	Black

#### Applicable Specifications and Agency Compliance

##### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU CE Mark: Yes

RG Type: 59/U

##### Flame Test

UL Flame Test: UL1666 Vertical Shaft

##### Suitability

Suitability - Indoor: Yes

#### Electrical Characteristics

##### Nom. Characteristic Impedance:

Impedance (Ohm)
-----------------

## 502PTZ Composite - For PTZ Cameras: CCTV + Control + Power

75

**Nom. Inductance:**

Inductance (µH/ft)
0.097

**Nom. Capacitance Conductor to Shield:**

Capacitance (pF/ft)
16.300

**Nominal Velocity of Propagation:**

VP (%)
83.000

**Nominal Delay:**

Delay (ns/ft)
1.220

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)
10.000

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)
3.500

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.300
5.000	0.650
10.000	0.900
50.000	1.900
100.000	2.600
200.000	3.600
400.000	5.000
700.000	7.000
900.000	8.000
1000.000	8.500

**Max. Operating Voltage - UL:** 300 V RMS

### Twisted Pair

#### Physical Characteristics

##### Conductor

**AWG:**

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	18	19x30	BC - Bare Copper	0.044

##### Insulation

**Insulation Material:**

Insulation Material Dia. (in.)
PO - Polyolefin 0.080

**Twisted Pair Color Code Chart:**

Number	Color
1	Blue and White/Blue

##### Outer Shield

**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000

**Outer Shield Drain Wire AWG:**

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

## Outer Jacket

### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

### Outer Jacket Diameter:

Nom. Dia. (in.)
0.219

### Outer Jacket Color Code Chart:

Number	Color
1	Blue

## Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

## Flame Test

UL Flame Test: UL1666 Vertical Shaft

## Suitability

Suitability - Indoor: Yes

## Electrical Characteristics

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
44.000

### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
26.000

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
6.500

### Max. Operating Voltage - Other:

Voltage
300 V RMSI

### Max. Recommended Current:

Description	Current
Data/Control	5.2 Amps

## Multi Conductor

### Physical Characteristics

#### Conductor

##### AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
2	18	7x26	BC - Bare Copper	0.047

## Insulation

### Insulation Material:

Insulation Material
PP - Polypropylene

### Insulation Color Code Chart:

Number	Color
1	Red
2	Black

## 502PTZ Composite - For PTZ Cameras: CCTV + Control + Power

### Individual Shield

#### Outer Jacket

Outer Jacket Diameter:

Nom. Dia. (in.)
0.158

Outer Jacket Color Code Chart:

Number	Color
1	White

### Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

### Flame Test

UL Flame Test: UL1666 Vertical Shaft

### Suitability

Suitability - Indoor: Yes

### Electrical Characteristics

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
21.500

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
6.500

Max. Operating Voltage - Other:

Voltage
300 V RMS

Max. Recommended Current:

Current
5 Amps per conductor @ 25°C

### Physical Characteristics (Overall)

#### Conductor

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
Unjacketed

#### Overall Cable

Overall Nominal Diameter: 0.451 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -10°C To +75°C

Separation Temperature Range: 0°C To +75°C

Bulk Cable Weight: 74.000 lbs/1000 ft.

Max. Recommended Pulling Tension: 140.000 lbs.

Min. Bend Radius/Minor Axis: 4.500 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

## 502PTZ Composite - For PTZ Cameras: CCTV + Control + Power

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

### Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 602PTZ

### Notes (Overall)

**Notes:** RG59 CCTV + 1 STP18 AWG Control Grade + 2C 18 AWG CMR. Individually jacketed and color coded components, cabled around and each fused to a central binding spline. Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation. Banana Peel® US PATENT 7049523.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
502PTZ 0001000	1,000 FT	89.000 LB	NONE		1 RG59 + 2C18 SH + 2C18
502PTZ 000500	500 FT	45.000 LB	NONE		1 RG59 + 2C18 SH + 2C18

Revision Number: 1    Revision Date: 07-15-2008

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)