

UER

Aluminum Polymer Capacitors

5,000 Hour



FEATURES

High Temperature – Very Low ESR – High Ripple Current – Stable with Temperature – High Frequency

APPLICATIONS

DC-DC Converters – Voltage Regulators – Decoupling

Operating Temperature Range		-55°C to +105°C			
Capacitance Tolerance		+20% at 120 Hz, 20°C			
Surge Voltage	WVDC	2.5	4	10	16
	SVDC	1.15 x rated WVDC			
Dissipation Factor 120 Hz, 20°C		10% MAX			
Leakage Current		2 Minutes			
		0.2CV or 280uA, whichever is greater			
Low Temperature Stability Impedance Ratio (100 kHz)	-55°C/ +20°C	≤1.25			
	+105°C/ +20°C	≤1.25			
Load Life		5000 hours at 105°C with rated WVDC applied			
		Capacitance Change	≤20% of initial measured value		
		Dissipation Factor	≤150% of maximum specified value		
		ESR	≤150% of maximum specified value		
		Leakage Current	≤100% of maximum specified value		
Damp Heat test		1000 hours at 60°C with rated voltage applied at 90-95% R.H.			
		Capacitance Change	≤20% of initial measured value		
		Dissipation Factor	≤150% of maximum specified value		
		ESR	≤150% of maximum specified value		
		Leakage Current	≤100% of maximum specified value		
Surge Voltage test		1000 cycles at 105°C with rated surge voltage applied for 30 seconds through a 1kΩ resistor and discharged for 5 minutes and 30 seconds			
		Capacitance Change	≤20% of initial measured value		
		Dissipation Factor	≤150% of maximum specified value		
		ESR	≤150% of maximum specified value		
		Leakage Current	≤100% of maximum specified value		
Ripple Current Multipliers		Frequency (Hz)			
		120Hz≤f<1kHz	1kHz≤f<10kHz	10kHz≤f<100kHz	100kHz≤f<500kHz
		0.05	0.3	0.7	1.0



D+0.5	5	6.3	8	10
S±0.5	2	2.5	3.5	5.0
d	0.5 L≤7mm 0.6 (L>7mm)	0.45 L≤6mm 0.6 (L>6mm)	0.6	0.6

L₁=L+1.0 mm MAX L<11mm
L₁=L+1.5 mm MAX, L≥11 mm

UER

+105°C 5000 hour Low ESR

WVDC	Capacitance (µF)	IC PART NUMBER	Maximum ESR (Ω) 120 Hz, +20°C	Maximum ESR (mΩ) 100 kHz, +20°C	Leakage Current (µA)	Maximum RMS Ripple Current (mA) 100 kHz, +105°C	Dims DxL (mm)
2.5	470	477UER2R5MEF	0.35	10	280	4500	6.3x8
2.5	820	827UER2R5MEF	0.2	7	410	5600	6.3x8
2.5	820	827UER2R5MFF	0.2	7	410	5600	8x8
4	560	567UER4R0MEF	0.3	7	448	4500	6.3x8
6.3	100	107UER6R3MEW	1.66	30	280	2580	6.3x6
6.3	470	477UER6R3MEF	0.35	10	592	4500	6.3x8
6.3	470	477UER6R3MFF	0.35	8	592	4000	8x8
6.3	560	567UER6R3MEF	0.3	8	706	4700	6.3x8
6.3	560	567UER6R3MFF	0.3	8	706	4800	8x8
10	1200	128UER010MGU	0.14	8	2400	5000	10x12.5
16	100	107UER016MED	1.66	24	320	2490	6.3x5
16	100	107UER016MES	1.66	24	320	2490	6.3x7
16	100	107UER016MEF	1.66	24	320	2820	6.3x8
16	220	227UER016MFH	0.75	15	704	4300	8x11.5
16	270	277UER016MFF	0.61	12	864	5000	8x8
16	270	277UER016MFH	0.61	10	864	5000	8x11.5
16	330	337UER016MFH	0.5	10	1056	5000	8x11.5
16	470	477UER016MFH	0.35	11	1504	5400	8x11.5
16	470	477UER016MGU	0.35	10	1504	5600	10x12.5
16	1000	108UER016MGU	0.17	11	3200	5600	10x12.5

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru