

## Interactive Catalog Supplements Catalog PDFs

If you need detailed product information, or help choosing the right product for your application, see our **Interactive Catalog**. Use the **Interactive Catalog** to access the most complete and up-to-date information available.

The **Interactive Catalog** provides an extensive collection of product specifications, application data, and technical literature that can be searched based on criteria you select.

This PDF catalog information was published in November 2000.



Sensing and Control  
**Interactive  
Catalog...**

**Click this icon to try  
the Interactive Catalog.**

---

### Sensing and Control

Honeywell Inc.

11 West Spring Street


Freeport, IL 61032

[www.honeywell.com/sensing](http://www.honeywell.com/sensing)

# Limit and Enclosed Switches

## Rotary Actuated Switches

HDLS Series



Side Rotary

Top Rotary

Order guides below and on page A35 provide specification and pricing information for side and top rotary switches.

Plug-in body style catalog listings consist of the complete plug-in base receptacle.

Levers are ordered separately. See pages A37-A39 for lever selection.

For rapid response – off the shelf service, all **bold face** listings are normally stocked items.

For low temperature, high temperature or preleading see page A42.

### ASSEMBLED CONDITIONS

Catalog listings in order guide below are factory assembled with:



- Shaft of side rotary heads facing front of switch (label side).
- Head adjusted for both clockwise and counterclockwise operation.
- Light on indicator versions wired to N.O. circuit.

Refer to facing page to specify modifications to these assembled conditions.

### PRELEADED OR CONNECTORIZED VERSIONS

Refer to page A42.

**ORDER GUIDE** (Momentary action. UL listed, CSA certified, CE approved. Levers not included. Order separately pages A37-A39.)

| Circuitry                                                                                              | Electrical Rating | Body** Style                                                | Catalog Listings |                  |              |              |                             |                            |
|--------------------------------------------------------------------------------------------------------|-------------------|-------------------------------------------------------------|------------------|------------------|--------------|--------------|-----------------------------|----------------------------|
|                                                                                                        |                   |                                                             | Standard         | Low Differential | 5° Pretravel | Low Torque   | Low Differential Low Torque | Top Rotary High Overtravel |
| Silver contacts                                                                                        | A                 | Plug-in 1/2" Conduit                                        | <b>LSA1A</b>     | <b>LSP1A</b>     | LSU1A        | <b>LSR1A</b> | <b>LSH1A</b>                | <b>LSB1A</b>               |
| Gold cross point contacts                                                                              | C                 | Plug-in 1/2" Conduit                                        | <b>LSA1J</b>     |                  | LSU1J        | —            | —                           | LSB1J                      |
| Gold plated contacts                                                                                   | C                 |                                                             | LSA1E            | LSP1E            | —            | LSR1E        | LSH1E                       | —                          |
| Silver contacts                                                                                        | A*                | 120 V Ind. lite Plug-In* 1/2" Conduit                       | <b>LSA5A</b>     | <b>LSP5A</b>     | LSU5A        | LSR5A        | <b>LSH5A</b>                | LSB5A                      |
|                                                                                                        | A*                | 240 V Ind. lite Plug-In 1/2" Conduit                        | LSA8A            | LSP8A            | LSU8A        | LSR8A        | LSH8A                       | LSB8A                      |
|                                                                                                        | A*                | 24 V LED lite 1.5mA max. Auto polarity Plug-in 1/2" Conduit | LSA9A            | LSP9A            | LSU9A        | LSR9A        | LSH9A                       | LSB9A                      |
|  SPDT Double Break    | A                 | Non plug-in 1/2" Conduit                                    | <b>LSA3K</b>     | <b>LSP3K</b>     | LSU3K        | <b>LSR3K</b> | <b>LSH3K</b>                | <b>LSB3K</b>               |
| Silver contacts                                                                                        | B                 | Plug-in 3/4" Conduit                                        | <b>LSA2B</b>     | <b>LSP2B</b>     | LSU2B        | LSR2B        | <b>LSH2B</b>                | <b>LSB2B</b>               |
|  DPDT Double Break   | B                 | Plug-in 1/2" Conduit                                        | LSA6B            | LSP6B            | LSU6B        | LSR6B        | LSH6B                       | LSB6B                      |
|                                                                                                        | B                 | 120 V Ind. lite Plug-in 3/4" Conduit                        | LSA2R            | LSP2R            | LSU2R        | LSR2R        | LSH2R                       | LSB2R                      |
|                                                                                                        | B                 | Non plug-in 3/4" Conduit                                    | <b>LSA4L</b>     | <b>LSP4L</b>     | LSU4L        | LSR4L        | LSH4L                       | LSB4L                      |
|                                                                                                        | B                 | Non plug-in 1/2" Conduit                                    | LSA7L            | LSP7L            | LSU7L        | LSR7L        | LSH7L                       | LSB7L                      |
|  SPNC Direct Acting | D                 | Non plug-in 1/2" Conduit                                    | LSA3N            |                  |              | LSR3N        |                             | LSB3N                      |

\*Use at voltage indicated for light. Wired to N.O. circuit.

Upper temperature limit for lighted units is 200°F (93°C).

\*\*Plug-in listings include base receptacle.

### OPERATING CHARACTERISTICS

|                                    |                    |                                |                       |                       |                               |                         |                         |
|------------------------------------|--------------------|--------------------------------|-----------------------|-----------------------|-------------------------------|-------------------------|-------------------------|
| Pretravel (degrees max.)           |                    | 15                             | 9                     | 5                     | 15                            | 9                       | 25                      |
| Differential Travel (degrees max.) | SPDT               | 5                              | 3                     | 3                     | 5                             | 3                       | 10                      |
|                                    | DPDT               | 7                              | 4                     | 4                     | 7                             | 4                       | 12                      |
| Overtravel (degrees min.)          |                    | 60                             | 66                    | 70                    | 60                            | 66                      | 110                     |
| Operating Torque (max.)            | NM = Newton meters | 0,45 Nm<br>4 in. lbs.          | 0,45 Nm<br>4 in. lbs. | 0,45 Nm<br>4 in. lbs. | 0,19 Nm<br>1.7 in. lbs.       | 0,19 Nm<br>1.7 in. lbs. | 0,28 Nm<br>2.5 in. lbs. |
| Operating Temperature Range***     |                    | 10°F to 250°F<br>-12° to 121°C |                       |                       | 30°F to 250°F<br>-1° to 121°C |                         |                         |


\*\*\*Completely fluorocarbon-sealed switches are preferred for use in temperatures above 200°F (93°C). Refer to page A42.

Limit/Enclosed


## Rotary Actuated Switches

### ACTUATION DIRECTION

(Drawings apply to listings on facing page only).



### HEAD ORIENTATION



### ASSEMBLY MODIFICATIONS

#### How to order

Momentary action rotary switches can be furnished in other than the normal assembled conditions described on the facing page. To specify modifications, add the number(s) shown below to the catalog listings. Prices are the same as their counterparts shown in the order guide.

Modification number suffixes are:

- 1 Clockwise operation only
- 2 Counterclockwise operation only
- 3 Shaft to right of switch front
- 4 Shaft to left of switch front
- 5 Shaft to back of switch
- 7 Indicator light wired to N.C. circuit

Examples:

Catalog Listing LSA1A23 is an LSA1A switch adjusted for counterclockwise operation only. The operating shaft is to the right side of the switch when viewing it from the front (label side). No lever.

Catalog Listing LSA8A7 is an LSA8A switch with the 240 volt indicator light wired to the N.C. circuit. No lever.

Switches with assembly modifications are not normally stocked and may extend delivery leadtimes.

### LEVERS

Levers for rotary actuated switches are normally ordered as separate catalog listings. They also may be ordered by including a suffix to the switch catalog listing and adding the lever price. See pages A34-A39.

### SWITCHES FOR SPECIAL APPLICATIONS

HDLS limit switches for special application needs are described on pages A42 and A43. They include: manifold mount, low temperature, complete fluorocarbon-sealed, gravity return, extra low torque and 20 Amp switches.

Adapter plates for interchanging HDLS with LS/200LS limit switches are described on page A49.

### ELECTRICAL RATINGS

10 amps continuous carry (except for electrical rating "C"). Circuits on any one pole must be the same polarity.

#### AC Volts

Pilot duty: 600 VAC, 720VA

| Electrical Rating | Circuitry                                      | VAC                              | Amps at 0.35 Power Factor |       |
|-------------------|------------------------------------------------|----------------------------------|---------------------------|-------|
|                   |                                                |                                  | Make                      | Break |
| A*                | Single-Pole<br>Double-Throw                    | 120                              | 60                        | 6     |
|                   |                                                | 240                              | 30                        | 3     |
|                   |                                                | 480                              | 15                        | 1.5   |
|                   |                                                | 600                              | 12                        | 1.2   |
| B                 | Double-Pole<br>Double-Throw                    | 120                              | 30                        | 3     |
|                   |                                                | 240                              | 15                        | 1.5   |
|                   |                                                | 480                              | 7.5                       | 0.75  |
|                   |                                                | 600                              | 6                         | 0.60  |
| D                 | Single-Pole<br>Single-Throw<br>Normally Closed | 120                              | 60                        | 6     |
|                   |                                                | 240                              | 30                        | 3     |
|                   |                                                | 480                              | 15                        | 1.5   |
|                   |                                                | 600                              | 12                        | 1.2   |
| C**               | Single-Pole<br>Double-Throw                    | 250 VAC or 60 VDC, .050 amp max. |                           |       |

#### DC Volts

Pilot duty: 240 VDC, 30 watts

| Electrical Rating | Circuitry                                      | VDC                              | Make and Break Amps |           |
|-------------------|------------------------------------------------|----------------------------------|---------------------|-----------|
|                   |                                                |                                  | Inductive           | Resistive |
| A*                | Single-Pole<br>Double-Throw                    | 120                              | 0.25                | 0.8       |
|                   |                                                | 240                              | 0.15                | 0.4       |
| B                 | Double-Pole<br>Double-Throw                    | 120                              | 0.25                | 0.8       |
|                   |                                                | 240                              | 0.15                | 0.4       |
| D                 | Single-Pole<br>Single-Throw<br>Normally Closed | 30                               | 4.3                 | 4.3       |
|                   |                                                | 120                              | 1.1                 | 1.1       |
| C**               | Single-Pole<br>Double-Throw                    | 250 VAC or 60 VDC, .050 amp max. |                     |           |

\*For switches with indicator light, use only at voltage stated for indicator light.

\*\*These switches have either gold plated or gold cross point contacts. Cross point contacts improve high reliability of contact make when particle contamination is a problem or low energy loads must be carried.

## Rotary Actuated Switches

## ADDITIONAL CIRCUITRY/ACTION OPTIONS



## ASSEMBLY MODIFICATIONS

Switches in the order guide, below, have the operating shaft facing front. If another orientation is desired, add a number from the drawing to the catalog listing.


To specify the indicator light wired to the N.C. circuit, add **7** to the catalog listing.

## Example:

Catalog Listing **LSN5A37** is an LSN5A switch with the shaft facing right and the indicator light wired to the N.C. circuit.

## HEAD ORIENTATION

(Drawing applies to this page only.)



Lever ordering information is shown on pages A36-A39.

## ORDER GUIDE

Maintained, center neutral, or sequential action. UL listed, CSA certified. Levers not included (see pages A36-A39).

For low temperature, all Viton or preloaded versions see page A42.

| Circuitry                                   | Elec. Rating<br>Page A23 | Body**<br>Style                           | Maintained†<br>360° Alternate<br>Action | 2 Position<br>Standard | Center Neutral<br>(Pole 1 operates CCW<br>Pole 2 operates CW)                                             | Sequential<br>(Pole 1 operates before Pole 2,<br>either CW or CCW or both)                                          |
|---------------------------------------------|--------------------------|-------------------------------------------|-----------------------------------------|------------------------|-----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| <p>SPDT Double Break<br/>Maintained</p>     | A                        | Plug-in<br>1/2" Conduit                   | LSQ300                                  | LSN1A                  | <p>CENTER NEUTRAL<br/>(Momentary)</p> <p>SPDT Double Break<br/>each direction<br/>Electrical rating B</p> | <p>SEQUENCE<br/>(Momentary)</p> <p>(2) SPDT Double Break<br/>with 10° between operation<br/>Electrical rating B</p> |
|                                             | A*                       | 120V Ind. Lite<br>Plug-in<br>1/2" Conduit |                                         | LSN5A                  |                                                                                                           |                                                                                                                     |
|                                             | A*                       | 240V Ind. Lite<br>Plug-in<br>1/2" Conduit |                                         | LSN8A                  |                                                                                                           |                                                                                                                     |
|                                             | A                        | Non plug-in<br>1/2" Conduit               | LSQ310                                  | LSN3K                  |                                                                                                           |                                                                                                                     |
| <p>DPDT Double Break<br/>Maintained</p>     | B                        | Plug-in<br>3/4" Conduit                   |                                         | LSN2B                  | LSM2D                                                                                                     | LSL2C                                                                                                               |
|                                             | B                        | Plug-in<br>1/2" Conduit                   |                                         | LSN6B                  | LSM6D                                                                                                     | LSL6C                                                                                                               |
|                                             | B                        | Non plug-in<br>3/4" Conduit               | LSQ320                                  | LSN4L                  | LSM4N                                                                                                     | LSL4M                                                                                                               |
|                                             | B                        | Non plug-in<br>1/2" Conduit               |                                         | LSN7L                  | LSM7N                                                                                                     | LSL7M                                                                                                               |
| <p>SP Normally Closed<br/>Direct Acting</p> | D                        | Non plug-in<br>1/2" Conduit               |                                         | LSN3N                  |                                                                                                           |                                                                                                                     |

\* Use at voltage indicated for light. Wired to N.O. circuit.  
Upper temperature for lighted units is 200°F (93°C).

\*\* Plug-in listings include base receptacle.

† Total travel is approximately 80° max. Maintained contact switch normally used with LSZ53 yoke actuator.

## OPERATING CHARACTERISTICS

|                                              |                    |                              |                    |                                              |
|----------------------------------------------|--------------------|------------------------------|--------------------|----------------------------------------------|
| Pretravel (degrees max.)                     | SPDT               | 65                           | Not Applicable     | Not Applicable                               |
| Note: Mechanical trip before electrical trip | DPDT               | 65                           | 18                 | 1st Pole 15<br>2nd Pole 10 additional (max.) |
| Differential Travel (degrees max.)           | SPDT               | 40                           | Not Applicable     | Not Applicable                               |
|                                              | DPDT               | 40                           | 10                 | For each pole — 5 degrees                    |
| Overtravel (degrees min.)                    |                    | 20                           | 57                 | 48                                           |
| Operating Torque (max.)                      | Nm = Newton meters | 0,45 Nm<br>4 in. lbs.        | 0,45<br>4 in. lbs. | 0,45<br>4 in. lbs.                           |
| Operating Temperature Range***               |                    | 30°F to 250°F<br>-1 to 121°C |                    | 10°F to 250°F<br>-12 to 121°C                |

\*\*\* Completely fluorocarbon-sealed switches are preferred for temperatures above 200°F (93°C). Refer to page A42.

## Levers for Rotary Actuated Switches

Levers for use with side or top rotary actuated switches are available in a wide choice of sizes and materials, as shown in the order guides on the following pages. Rollers may be on either side of the lever to best match the external actuating mechanism. They permit a wide range of cam tracking possibilities (see drawings below).

**LSZ51** standard rollers and **LSZ55** offset roller levers have a fixed 1.5 inch (38,1 mm) radius.



**LSZ53** yoke roller levers are used with side rotary maintained switches, where a reciprocating actuator operates the switch in one direction and reverses it when moving in the other direction.

**LSZ52** adjustable length roller levers are universally adaptable to many application needs.

**LSZ54** rod levers may be formed by the user. The hub permits adjusting of lever length. Also available in flexible versions.

**LSZ61** is an adjustable loop lever.


For lever order guides, refer to the following pages.



NOTE: Shaft dia. is .29 in.

## Levers for Rotary Actuated Switches




Rollers may be mounted on the front or back side of the lever. (See below).



Levers shown in the order guides are furnished with cap screws which accommodate a  $\frac{9}{64}$ -inch allen wrench.

Teller tab assures proper torque. When it cannot be moved, the lever is tight enough to prevent slippage.

### ORDER GUIDE

| Type                                                                                                                               | Radius (in.) | Roller Mounted On This Side Of Lever | Dia. in. | Width in. | Material                       | Catalog Listings |
|------------------------------------------------------------------------------------------------------------------------------------|--------------|--------------------------------------|----------|-----------|--------------------------------|------------------|
|  LSZ51 Series<br>Std.<br>Roller<br>Lever          | 1.5          | Front                                | .75      | .25       | Nylon                          | LSZ51A           |
|                                                                                                                                    | 1.5          | Front                                | .75      | .25       | Steel                          | LSZ51B           |
|                                                                                                                                    | 1.5          | Back                                 | .75      | .25       | Nylon                          | LSZ51C           |
|                                                                                                                                    | 1.5          | Back                                 | .75      | .25       | Steel                          | LSZ51D           |
|                                                                                                                                    | 1.5          | Front                                | 1.0      | .50       | Nylon                          | LSZ51F           |
|                                                                                                                                    | 1.5          | Front                                | 1.5      | .25       | Nylon                          | LSZ51G           |
|                                                                                                                                    | 1.5          | Back                                 | 1.0      | .50       | Nylon                          | LSZ51J           |
|                                                                                                                                    | 1.5          | Back                                 | .75      | .25       | Ball Bearing                   | LSZ51L           |
|                                                                                                                                    | 1.5          | Back                                 | .75      | 1.30      | Nylon                          | LSZ51M           |
|                                                                                                                                    | 1.5          | Back                                 | .75      | .375      | Stainless                      | LSZ51T           |
|                                                                                                                                    | 1.5          | Front                                | .75      | .50       | Nylon                          | LSZ51P           |
|                                                                                                                                    | 1.5          | Front                                | 1.59     | .25       | Nylon                          | LSZ51R           |
|                                                                                                                                    | 1.5          | —                                    | —        | —         | Less Roller                    | LSZ51            |
|  LSZ53 Series<br>Yoke<br><br>Back view of LSZ53E | 1.5          | Front-Back                           | .75      | .25       | Nylon                          | LSZ53A           |
|                                                                                                                                    | 1.5          | Front-Back                           | .75      | .25       | Steel                          | LSZ53B           |
|                                                                                                                                    | 1.5          | Front-Front                          | .75      | .25       | Steel                          | LSZ53D           |
|                                                                                                                                    | 1.5          | Back-Front                           | .75      | .25       | Nylon                          | LSZ53E           |
|                                                                                                                                    | 1.5          | Back-Back                            | .75      | .25       | Nylon                          | LSZ53S           |
|                                                                                                                                    | 1.5          | Back-Back                            | .75      | .25       | Steel                          | LSZ53P           |
|                                                                                                                                    | 1.5          | Back-Front                           | .75      | .25       | Steel                          | LSZ53U           |
|                                                                                                                                    | 1.5          | Back-Front                           | .75      | 1.25      | Nylon                          | LSZ53M           |
|                                                                                                                                    | 1.5          | —                                    | —        | —         | Less Rollers                   | LSZ53            |
|                                                                                                                                    | 1.5          | —                                    | —        | —         | Less Roller                    | LSZ55            |
|  LSZ55 Series<br>Offset                          | 1.5          | Back                                 | .75      | .25       | Nylon                          | LSZ55A           |
|                                                                                                                                    | 1.5          | Back                                 | .75      | .25       | Steel                          | LSZ55B           |
|                                                                                                                                    | 1.5          | Front                                | .75      | .25       | Nylon                          | LSZ55C           |
|                                                                                                                                    | 1.5          | Front                                | .75      | .25       | Steel                          | LSZ55D           |
|                                                                                                                                    | 1.5          | Front                                | .75      | .50       | Nylon                          | LSZ55E           |
|                                                                                                                                    | 1.5          | Front                                | 1.5      | .25       | Nylon                          | LSZ55K           |
|                                                                                                                                    | 1.5          | Front                                | 1.0      | .50       | Nylon                          | LSZ55F           |
|  LSZ69 Series*                                   |              | —                                    | 6.0      | —         | Stainless (spokes replaceable) | LSZ69CA          |

\*For use with LSQ300 Series. Hub is aluminum. See page A59 for dimensions.

## Levers for Rotary Actuated Switches

### METRIC CONVERSION





|          |   |         |
|----------|---|---------|
| .25 in.  | = | 6,35 mm |
| .5 in.   | = | 12,7 mm |
| .625 in. | = | 15,9 mm |
| .75 in.  | = | 19,1 mm |
| 1.0 in.  | = | 25,4 mm |
| 1.5 in.  | = | 38,1 mm |
| 2.0 in.  | = | 50,8 mm |
| 2.5 in.  | = | 63,5 mm |
| 3.0 in.  | = | 76,2 mm |
| 4.8 in.  | = | 122 mm  |
| 5.0 in.  | = | 127 mm  |
| 6.0 in.  | = | 152 mm  |
| 12.0 in. | = | 305 mm  |

### LOW TORQUE APPLICATION CONSIDERATION

When heavier levers (such as LSZ52 series and LSZ54 series, below), are used with low torque LSH, LSR, LSS and LST switches, it is desirable to mount the switch with the lever down. In this way, gravity will assist in restoring levers to the free position.

Conversely, when these switches are mounted with the lever upright, gravity tends to work to prevent lever return after switching actuation. By counterbalancing the lever or adding an auxiliary extension spring, this problem may be overcome. Contact the 800 number for application assistance.

### ORDER GUIDE


| Type                                                                                                                     | Radius (in.) | Roller Mounted On This Side Of Lever                                                                                           | Dia. in. | Width in. | Material                   | Catalog Listings         |
|--------------------------------------------------------------------------------------------------------------------------|--------------|--------------------------------------------------------------------------------------------------------------------------------|----------|-----------|----------------------------|--------------------------|
|  LSZ52 Series<br>Adjustable Radius       | 1.5-3.5      | Back                                                                                                                           | .75      | .25       | Nylon                      | LSZ52A                   |
|                                                                                                                          | 1.5-3.5      | Back                                                                                                                           | .75      | .25       | Steel                      | LSZ52B                   |
|                                                                                                                          | 1.5-3.5      | Front                                                                                                                          | .75      | .25       | Nylon                      | LSZ52C                   |
|                                                                                                                          | 1.5-3.5      | Front                                                                                                                          | .75      | .25       | Steel                      | LSZ52D                   |
|                                                                                                                          | 1.5-3.5      | Front                                                                                                                          | .75      | 1.30      | Nylon                      | LSZ52E                   |
|                                                                                                                          | 1.5-3.5      | Front                                                                                                                          | 1.0      | .5        | Nylon                      | LSZ52J                   |
|                                                                                                                          | 1.5-3.5      | Front                                                                                                                          | 1.5      | .25       | Nylon                      | LSZ52K                   |
|                                                                                                                          | 1.5-3.5      | Front                                                                                                                          | .75      | .25       | Ball Bearing               | LSZ52L                   |
|                                                                                                                          | 1.5-3.5      | Front                                                                                                                          | 2.0      | .25       | Nylon                      | LSZ52M                   |
|                                                                                                                          | 1.5-3.5      | Front                                                                                                                          | .75      | .5        | Nylon Less Roller Hub Only | LSZ52N<br>LSZ52<br>LSZ54 |
|  LSZ68 Series<br>Spring/Rod           | 12.0         | —                                                                                                                              | .25      | —         | Delrin Rod w/Spring        | LSZ68                    |
|                                                                                                                          | 16.0         | —                                                                                                                              | .25      | —         | Delrin Rod w/Spring        | LSZ617                   |
|  LSZ54 Series<br>Rod                  | 5.5          | —                                                                                                                              | —        | —         | Aluminum                   | LSZ54M                   |
|                                                                                                                          | 13.0         | —                                                                                                                              | —        | —         | Stainless Steel            | LSZ54N                   |
|                                                                                                                          | 20.0         | —                                                                                                                              | —        | —         | Delrin Rod                 | LSZ54P                   |
|                                                                                                                          | 12.0         | —                                                                                                                              | —        | —         | Spring Wire                | LSZ54R                   |
|                                                                                                                          | 4.8          | —                                                                                                                              | —        | —         | Flexible Cable Hub Only    | LSZ54V*<br>LSZ54         |
|  LSZ61 Series<br>Flexible Loop         |              | 6" Flexible Loop/Cap Screw<br>9.5" Flexible Loop/Cap Screw<br><br>(measured from center line of shaft hole to tip of actuator) |          |           | Nylatron<br><br>Hub Only   | LSZ61<br>LSZ618<br>LSZ54 |
|                                                                                                                          |              |                                                                                                                                |          |           |                            |                          |
|  LSZ60 Series<br>One Way Roller Lever |              | Front                                                                                                                          | .75      | .25       | Nylon                      | LSZ60A                   |
|                                                                                                                          |              | Front                                                                                                                          | .75      | .25       | Steel                      | LSZ60B                   |

See page A60 for dimensions

\*Hub not available separately.

## Levers for Rotary Actuated Switches





### FIXED LENGTH LEVERS ORDER GUIDE

| Fixed Length Levers<br>LSZ65 Series                                              | Lever<br>Length (in.)                                                                  | Lever<br>Listing | For a complete listing add your choice of roller suffix |             |              |          |
|----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|------------------|---------------------------------------------------------|-------------|--------------|----------|
|                                                                                  |                                                                                        |                  | Roller<br>Suffix                                        | Dia.<br>in. | Width<br>in. | Material |
|  | .88                                                                                    | LSZ65A           | A                                                       | .75         | .25          | Nylon    |
|                                                                                  | 1.38                                                                                   | LSZ65B           | B                                                       | .75         | .25          | Steel    |
|                                                                                  | 1.25                                                                                   | LSZ65L           |                                                         |             |              |          |
|                                                                                  | 1.50                                                                                   | LSZ65C           | C                                                       | .75         | .50          | Nylon    |
|                                                                                  | 1.75                                                                                   | LSZ65D           | D                                                       | .75         | 1.30         | Nylon    |
|                                                                                  | 2.00                                                                                   | LSZ65E           | E                                                       | 1.00        | .50          | Nylon    |
|                                                                                  | 2.50                                                                                   | LSZ65F           | F                                                       | 1.50        | .25          | Nylon    |
|                                                                                  | 3.00                                                                                   | LSZ65G           |                                                         |             |              |          |
|                                                                                  | 4.00                                                                                   | LSZ65H           |                                                         |             |              |          |
|                                                                                  | 5.00                                                                                   | LSZ65J           |                                                         |             |              |          |
|                                                                                  | 6.00                                                                                   | LSZ65K           |                                                         |             |              |          |
|                                                                                  | Example:<br>LSZ65AB is a .88" long lever with a steel .75" diameter, .25" wide roller. |                  |                                                         |             |              |          |

### RUBBER ROLLER LEVERS

Ideal for elevator or conveyor applications requiring quiet operation or protection of delicate surfaces.

### ORDER GUIDE

| Type                                                                                                                          | Radius<br>(in.)          | Roller<br>Mounted On<br>This Side<br>Of Lever | Dia.<br>in. | Width<br>in. | Material         | Catalog<br>Listing |
|-------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------|-------------|--------------|------------------|--------------------|
| LSZ51 Series<br>Std.<br>Roller<br>Lever<br> | 1.5<br>1.5               | Front<br>Front                                | 1.6<br>2.0  | .5<br>.5     | Rubber<br>Rubber | LSZ51W<br>LSZ51Y   |
| LSZ55 Series<br>Offset<br>                 | 1.5<br>1.5               | Front<br>Front                                | 1.6<br>2.0  | .50<br>.50   | Rubber<br>Rubber | LSZ55W<br>LSZ55Y   |
| LSZ52 Series<br>Adjustable<br>Radius<br>    | 1.5 to 3.5<br>1.5 to 3.5 | Front<br>Front                                | 1.6<br>2.0  | .50<br>.50   | Rubber<br>Rubber | LSZ52W<br>LSZ52Y   |
| LSZ67 Series<br>Conveyor<br>Roller<br>     | —                        | —                                             | 1.5         | 3.8          | Plastic          | LSZ67AA            |

Limit/Enclosed

## Plunger Actuated Switches

### ASSEMBLED CONDITIONS

Catalog listings in order guide below are factory assembled with:

- Side plungers facing front (label side) of switch. Rollers on side plungers are in horizontal position.


- Roller on top plungers are parallel to mounting surface.
- Lights on indicator versions are wired to N.O. circuit.

Refer to facing page to specify modifications to these assembled conditions.



For low temperature, high temperature or preleaded versions see page A42.

### ORDER GUIDE

Momentary action, except for maintained contact LSG version. UL listed, CSA certified.



Circuits on any one pole must be the same polarity.

| Catalog listings in this chart are complete switches.                                                       |                          |                                              | Catalog Listings |        |            |               |        |            |                                       |
|-------------------------------------------------------------------------------------------------------------|--------------------------|----------------------------------------------|------------------|--------|------------|---------------|--------|------------|---------------------------------------|
|                                                                                                             |                          |                                              | Top Plungers     |        |            | Side Plungers |        |            | Maintained<br>(Circuitry Shown Above) |
| Circuitry                                                                                                   | Elec. Rating<br>Page A34 | Body**<br>Style                              | Plain            | Roller | Adjustable | Plain         | Roller | Adjustable |                                       |
| Silver contacts                                                                                             | A                        | Plug-in<br>1/2" Conduit                      | LSC1A            | LSD1A  | LSV1A      | LSE1A         | LSF1A  | LSW1A      | LSG1A                                 |
| Gold cross pt.                                                                                              | C                        | Plug-in<br>1/2" Conduit                      | LSC1J            | LSD1J  | LSV1J      | LSE1J         | LSF1J  | LSW1J      | —                                     |
| Gold plated                                                                                                 | C                        | —                                            | —                | LSD1E  | —          | —             | LSF1E  | LSW1E      | —                                     |
| <br>SPDT<br>Double Break   | A*                       | 120 V. Ind. Lite<br>Plug-in<br>1/2" Conduit* | LSC5A            | LSD5A  | LSV5A      | LSE5A         | LSF5A  | LSW5A      | LSG5A                                 |
|                                                                                                             | A*                       | 240 V. Ind. Lite<br>Plug-in<br>1/2" Conduit* | LSC8A            | LSD8A  | LSV8A      | LSE8A         | LSF8A  | LSW8A      | LSG8A                                 |
|                                                                                                             | A                        | Non plug-in<br>1/2" Conduit                  | LSC3K            | LSD3K  | LSV3K      | LSE3K         | LSF3K  | LSW3K      | LSG3K                                 |
| <br>DPDT<br>Double Break  | B                        | Plug-in<br>3/4" Conduit                      | LSC2B            | LSD2B  | LSV2B      | LSE2B         | LSF2B  | LSW2B      | LSG2B                                 |
|                                                                                                             | B                        | 120 V Ind. Lite<br>Plug-in<br>3/4" Conduit   | LSC2R            | LSD2R  | LSV2R      | LSE2R         | LSF2R  | LSW2R      | LSG2R                                 |
|                                                                                                             | B                        | Plug-in<br>1/2" Conduit                      | LSC6B            | LSD6B  | LSV6B      | LSE6B         | LSF6B  | LSW6B      | LSG6B                                 |
|                                                                                                             | B                        | Non plug-in<br>3/4" Conduit                  | LSC4L            | LSD4L  | LSV4L      | LSE4L         | LSF4L  | LSW4L      | LSG4L                                 |
|                                                                                                             | B                        | Non plug-in<br>1/2" Conduit                  | LSC7L            | LSD7L  | LSV7L      | LSE7L         | LSF7L  | LSW7L      | LSG7L                                 |
| <br>SPNC<br>Direct Acting | D                        | Non plug-in<br>1/2" Conduit                  | —                | —      | —          | LSE3N         | LSF3N  | LSW3N      | LSG3N                                 |

\*Use at voltage indicated for light. Upper operating temperature limit for lighted units is 200°F. Wired to N.O. circuit.

\*\* Plug-in listings include base receptacle.

### OPERATING CHARACTERISTICS

|                                      |                              |                           |                                |                           |                              |                                |                             |
|--------------------------------------|------------------------------|---------------------------|--------------------------------|---------------------------|------------------------------|--------------------------------|-----------------------------|
| mm<br>Pretravel (in. max.)           | 1,78<br>.070                 | 1,78<br>.070              | 1,78<br>.070                   | 2,54<br>.100              | 2,54<br>.100                 | 2,54<br>.100                   | 4,32<br>.170                |
| Differential mm<br>Travel (in. max.) | 0,38<br>.015                 | 0,38<br>.015              | 0,38<br>.015                   | 0,64<br>.025              | 0,64<br>.025                 | 0,64<br>.025                   | 2,29<br>.090                |
|                                      | 0,51<br>.020                 | 0,51<br>.020              | 0,51<br>.020                   | 0,89<br>.035              | 0,89<br>.035                 | 0,89<br>.035                   | 2,29<br>.090                |
| mm<br>Overtravel (in. min.)          | 4,83<br>.190                 | 4,83<br>.190              | 4,83<br>.190                   | 4,83<br>.190              | 4,83<br>.190                 | 4,83<br>.190                   | 2,0<br>.080                 |
| Newton<br>Operating Force (lb. max.) | 17,8<br>4                    | 17,8<br>4                 | 17,8<br>4                      | 26,7<br>6                 | 26,7<br>6                    | 26,7<br>6                      | 44,5<br>10                  |
| Operating Point mm<br>(in.)          | 45,8 ±0,76<br>1.805 ±.030    | 55,9 ±1,02<br>2.200 ±.040 | 53,0 to 59,3<br>2.085 to 2.335 | 33,0 ±0,76<br>1.300 ±.030 | 44,1 ±1,02<br>1.735 ±.040    | 41,0 to 47,4<br>1.615 to 1.865 | 37,6 ±0,76<br>1.480 ±.030   |
| Operating Temperature<br>Range       | 10°F to 200°F<br>-12 to 93°C |                           | 10°F to 200°F<br>-12 to 93°C   |                           | 10°F to 200°F<br>-12 to 93°C |                                | 30°F to 200°F<br>-1 to 93°C |

## Plunger Actuated Switches/Assembly Modifications

## ASSEMBLY MODIFICATIONS

## How to order

To specify other than the normal assembled conditions described on facing page, add the following modification numbers to the catalog listing in the plunger switch order guide.


## Mod.

- 3 Side plunger to right of switch front  
4 Side plunger to left of switch front

- 5 Side plunger to back of switch  
6 Roller on top plungers perpendicular to mounting surface  
7 Light on indicator versions wired to N.C. circuit  
8 Roller on side plungers in vertical position.

Example:

LSF1A3 is an LSF1A with the side roller plunger to the right side.



## Wobble Actuated Switches

Wobble actuated switches have flexible levers which may be operated with any movement, except direct pull.

## ORDER GUIDE

Momentary action. UL listed, CSA certified

|                                                       |                          |                                           | Catalog Listings                                                                  |                                                                                   |                                                                                    |                                                                                     |                                                                                     |
|-------------------------------------------------------|--------------------------|-------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Catalog listings in this chart are complete switches. |                          |                                           |  |  |  |  |  |
| Lever lengths measured from top mounting hole         |                          |                                           | 5.5"                                                                              | 13"                                                                               | 5.5"                                                                               | 5.5"                                                                                | 5.5"                                                                                |
| Circuitry                                             | Elec. Rating<br>Page A34 | Body**<br>Style                           | Delrin Rod                                                                        | Spring Wire                                                                       | Cat*** Whisker                                                                     | Cable                                                                               | Coil Spring                                                                         |
| Silver contacts                                       | A                        | Plug-in<br>1/2" Conduit                   | LSJ1A-7A                                                                          | LSJ1A-7M                                                                          | LSK1A-8A                                                                           | LSJ1A-7N                                                                            | LSK1A-8C                                                                            |
| Gold cross point                                      | C                        | Plug-in<br>1/2" Conduit                   | LSJ1J-7A                                                                          | LSJ1J-7M                                                                          | LSK1J-8A                                                                           | LSJ1J-7N                                                                            | LSK1J-8C                                                                            |
| Gold plated contacts                                  | C                        |                                           | —                                                                                 | LSJ1E-7M                                                                          | —                                                                                  | —                                                                                   | —                                                                                   |
| Silver contacts<br>MOMENTARY                          | A*                       | 120 V. Ind. Lite Plug-in<br>1/2" Conduit* | LSJ5A-7A                                                                          | LSJ5A-7M                                                                          | LSK5A-8A                                                                           | LSJ5A-7N                                                                            | LSK5A-8C                                                                            |
|                                                       | A*                       | 240 V. Ind. Lite Plug-in<br>1/2" Conduit* | LSJ8A-7A                                                                          | LSJ8A-7M                                                                          | LSK8A-8A                                                                           | LSJ8A-7N                                                                            | LSK8A-8C                                                                            |
| SPDT Double Break                                     | A                        | Non plug-in<br>1/2" Conduit               | LSJ3K-7A                                                                          | LSJ3K-7M                                                                          | LSK3K-8A                                                                           | LSJ3K-7N                                                                            | LSK3K-8C                                                                            |
| Silver contacts<br><br>MOMENTARY                      | B                        | Plug-in<br>3/4" Conduit                   | LSJ2B-7A                                                                          | LSJ2B-7M                                                                          | LSK2B-8A                                                                           | LSJ2B-7N                                                                            | LSK2B-8C                                                                            |
|                                                       | B                        | 120 V Ind. Lite Plug-In<br>3/4" Conduit   | LSJ2R-7A                                                                          | LSJ2R-7M                                                                          | LSK2R-8A                                                                           | LSJ2R-7N                                                                            | LSK2R-8C                                                                            |
|                                                       | B                        | Plug-in<br>1/2" Conduit                   | LSJ6B-7A                                                                          | LSJ6B-7M                                                                          | LSK6B-8A                                                                           | LSJ6B-7N                                                                            | LSK6B-8C                                                                            |
|                                                       | B                        | Non plug-in<br>3/4" Conduit               | LSJ4L-7A                                                                          | LSJ4L-7M                                                                          | LSK4L-8A                                                                           | LSJ4L-7N                                                                            | LSK4L-8C                                                                            |
|                                                       | B                        | Non plug-in<br>1/2" Conduit               | LSJ7L-7A                                                                          | LSJ7L-7M                                                                          | LSK7L-8A                                                                           | LSJ7L-7N                                                                            | LSK7L-8C                                                                            |
| DPDT Double Break                                     |                          |                                           |                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |

## OPERATING CHARACTERISTICS

|                                      |                          |           |           |           |           |
|--------------------------------------|--------------------------|-----------|-----------|-----------|-----------|
| mm<br>Pretravel (approx. in. radius) | 25,4<br>1                | 102<br>4  | 51<br>2   | 38<br>1.5 | 51<br>2   |
| Newton<br>Operating Force (oz. max.) | 2,78<br>10               | 1,39<br>5 | 1,39<br>5 | 1,95<br>7 | 1,95<br>7 |
| Operating Temperature Range          | 10°F to 200°F 12 to 93°C |           |           |           |           |

\* Use at voltage indicated for light. Upper operating temperature limit for lighted units is 200°F.

\*\* Plug-in listings include base receptacle.

\*\*\* These cat whiskers have 5 1/2 inch long levers. To specify 7 1/2 inch length, substitute -8B for -8A.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)