

MJE700 THRU MJE703 PNP
MJE800 THRU MJE803 NPN

**COMPLEMENTARY
POWER DARLINGTON TRANSISTORS**



TO-126 CASE



www.centrasemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR MJE700, MJE800 series devices are medium power complementary silicon Darlington transistors designed for audio amplifier applications as complementary output devices.

MARKING: FULL PART NUMBER

	SYMBOL	MJE700	MJE702	UNITS
		MJE701	MJE703	
MAXIMUM RATINGS: ($T_C=25^\circ\text{C}$)		MJE800	MJE802	
		MJE801	MJE803	
Collector-Base Voltage	V_{CBO}	60	80	V
Collector-Emitter Voltage	V_{CEO}	60	80	V
Emitter-Base Voltage	V_{EBO}		5.0	V
Continuous Collector Current	I_C		4.0	A
Continuous Base Current	I_B		100	mA
Power Dissipation	P_D		40	W
Operating and Storage Junction Temperature	T_J, T_{stg}		-65 to +150	$^\circ\text{C}$
Thermal Resistance	θ_{JC}		3.13	$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS: ($T_C=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
I_{CBO}	$V_{CB}=\text{Rated } V_{CBO}$		100	μA
I_{CBO}	$V_{CB}=\text{Rated } V_{CBO}, T_C=100^\circ\text{C}$		500	μA
I_{CEO}	$V_{CE}=\text{Rated } V_{CEO}$		100	μA
I_{EBO}	$V_{EB}=5.0\text{V}$		2.0	mA
BV_{CEO}	$I_C=50\text{mA}$ (MJE702,703,802,803)	80		V
BV_{CEO}	$I_C=50\text{mA}$ (MJE700,701,800,801)	60		V
$V_{CE(\text{SAT})}$	$I_C=1.5\text{A}, I_B=30\text{mA}$ (MJE700,702,800,802)		2.5	V
$V_{CE(\text{SAT})}$	$I_C=2.0\text{A}, I_B=40\text{mA}$ (MJE701,703,801,803)		2.8	V
$V_{CE(\text{SAT})}$	$I_C=4.0\text{A}, I_B=40\text{mA}$		3.0	V
$V_{BE(\text{ON})}$	$V_{CE}=3.0\text{V}, I_C=1.5\text{A}$ (MJE700,702,800,802)		2.5	V
$V_{BE(\text{ON})}$	$V_{CE}=3.0\text{V}, I_C=2.0\text{A}$ (MJE701,703,801,803)		2.5	V
$V_{BE(\text{ON})}$	$V_{CE}=3.0\text{V}, I_C=4.0\text{A}$		3.0	V
h_{FE}	$V_{CE}=3.0\text{V}, I_C=1.5\text{A}$ (MJE700,702,800,802)	750		
h_{FE}	$V_{CE}=3.0\text{V}, I_C=2.0\text{A}$ (MJE701,703,801,803)	750		
h_{FE}	$V_{CE}=3.0\text{V}, I_C=4.0\text{A}$	100		
f_T	$V_{CE}=3.0\text{V}, I_C=1.5\text{A}, f=1.0\text{MHz}$	1.0		MHz

MJE700 THRU MJE703 PNP
MJE800 THRU MJE803 NPN

COMPLEMENTARY
POWER DARLINGTON TRANSISTORS



TO-126 CASE - MECHANICAL OUTLINE



LEAD CODE:

- 1) Emitter
- 2) Collector
- 3) Base

MARKING:

FULL PART NUMBER

SYMBOL	DIMENSIONS			
	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.094	0.110	2.40	2.80
B	0.050		1.27	
C	0.015	0.030	0.38	0.75
D	0.291	0.335	7.40	8.50
E	0.148		3.75	
F	0.118	0.134	3.00	3.40
G	0.413	0.472	10.50	12.00
H	0.618		15.70	
J	0.024	0.035	0.62	0.90
K	0.089		2.25	
L	0.177		4.50	
M	0.045	0.055	1.14	1.40
N	0.083		2.10	

TO-126 (REV:R3)

R2 (23-January 2014)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru