



Main

| | |
|-----------------------------------|---|
| Range of product | 9012G |
| Pressure sensor type | Electromechanical pressure switch |
| Pressure sensor name | 9012G |
| Pressure sensor size | 5600 psi |
| Maximum pressure | 20000 psi |
| Contacts type and composition | NC-NO, SPDT-DB, Form Z, snap action, silver nickel contacts |
| Controlled fluid | Air Non-corrosive liquids Non-corrosive gas Hydraulic oil (-15...250 °F) |
| Fluid connection type | 0.25 inch 18 NPTF conforming to UL 508 |
| Pressure switch type of operation | Regulation between 2 thresholds |
| Scale type | Adjustable differential |
| Local display | Without |

Complementary

| | |
|---|--|
| Range on decreasing pressure | 170...5600 psi |
| Approx adjustable differential at mid range | 289...1260 psi +/- 2.5 % full scale |
| Terminal block type | 4 screw terminals |
| Electrical connection | 1 male connector (mini) 5 pins |
| Terminal identifier | (3)gnd (2-4)NC (1-5)NO |
| Electrical circuit type | Control circuit |
| Local signalling | 1 neon (red) AC/DC at 120 V (voltage limits:105...125 V) |
| [In] rated current | 0.22 A (Ue = 125 V DC) 3 A (Ue = 120 V AC) |
| Setting | Internal |
| Enclosure material | Die cast aluminium alloy 380 |
| Pressure actuator | Piston |
| Height | 6.37 in |
| Depth | 3.11 in |
| Width | 3.5 in |
| Operating position | Any position |
| Materials in contact with fluid | Teflon Viton fluorocarbon 440 stainless steel 303 stainless steel |
| Short-circuit protection | 10 A by gL (cartridge) overload and short-circuit protection |
| Operating rate | <= 120 cyc/mn |
| Mechanical durability | 3000000 cycles |
| Repeat accuracy | 4 % |
| Product weight | 3 lb(US) |

Environment

| | |
|----------------------|---|
| vibration resistance | 2 gn conforming to IEC 68-2-6 (f = 40...150 Hz) |
| shock resistance | 50 gn conforming to IEC 58-2-27 |
| standards | CE UL 508 CSA C22.2 No 14 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---------------------------------------|--|
| product certifications | CE CSA LR25490 class 3211 03 UL listed file E12158 CCN NKPZ and CCN NTHT |
| NEMA degree of protection | NEMA 4/4X/13 conforming to UL 50 |
| ambient air temperature for operation | -10...185 °F |

Offer Sustainability

| | |
|--|--|
| Not Green Premium product | Not Green Premium product |
| Will not be Compliant | Will not be Compliant |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Available | Available |
| WARNING: This product can expose you to chemicals including: | WARNING: This product can expose you to chemicals including: |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to www.p65warnings.ca.gov | For more information go to www.p65warnings.ca.gov |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru