

PRODUCT NO.
73725

PRODUCT NUMBER CODE

73725-X X X X LF

HOUSING COLOR OPTION
0-WHITE
1-BLACK


SENSOR CONTACT OPTION
0-WITH SENSOR CONTACT
1-WITHOUT SENSOR CONTACT

SHIELD PLATING OPTION
1- 1.25μm MINIMUM NICKEL UNDERPLATE &
2.5μm MINIMUM BRIGHT TIN OVER ALL AREA.
(HOLD DOWN STYLE "A")
2- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL;
2.5 μm MINIMUM MATTE TIN PLATED ON
HOLD DOWN AREA ONLY.(HOLD DOWN STYLE "B")
3- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL;
2.5 μm MINIMUM MATTE TIN PLATED ON
HOLD DOWN AREA ONLY.(HOLD DOWN STYLE "A")
4- 1.25μm MINIMUM NICKEL UNDERPLATED &
2.5μm MINIMUM BRIGHT TIN OVER ALL AREA.
(HOLD DOWN STYLE "B")
5- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL;
2.5μm MINIMUM MATTE TIN PLATED ON
HOLD DOWN AREA ONLY (HOLD DOWN STYLE "C")
6- 1.25μm MINIMUM NICKEL ONLY.
(HOLD DOWN STYLE "A")
7- 1.25μm MINIMUM NICKEL UNDERPLATED &
2.5 μm MINIMUM MATTE TIN PLATED OVER ALL.
(HOLD DOWN STYLE "A")
8- 1.25μm MINIMUM NICKEL UNDERPLATED &
2.5 μm MINIMUM MATTE TIN PLATED ALL AREA.
(HOLD DOWN STYLE "B")
9- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL;
2.5 μm MINIMUM MATTE TIN PLATED ON
HOLD DOWN AREA ONLY (HOLD DOWN STYLE "D")
S- 1.25μm MINIMUM NICKEL ONLY.(HOLD DOWN STYLE "A").
HIGH PERFORMANCE MATERIAL
FOR 12,000 DURABILITY CYCLES
A- 1.25μm MINIMUM NICKEL PLATED OVER ALL
2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY
(HOLD DOWN STYLE "F")
B- 1.25μm MINIMUM NICKEL PLATED OVER ALL
2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY
(HOLD DOWN STYLE "F")


TERMINAL OPTION
50u" NI UNDERPLATE; 30u" GXT CONTACT AREA,100u" TIN TAIL AREA;
0- DIM "A": 2.29 (TERMINAL TAIL LENGTH);
1- DIM "A": 3.71 (TERMINAL TAIL LENGTH);

LEAD FREE OPTION
SEE NOTE 9


PACKAGING OPTION
B - TUBE
R - TAPE&REEL



SENSOR CONTACT




WITH SENSOR CONTACT



FRONT OF CONNECTOR

PC BOARD MOUNTING DIMENSIONS FOR 5 PIN



NOTES:

- MATERIAL:
CONTACTS: COPPER ALLOY
SHIELD: COPPER ALLOY
HOUSING: UL 94V-0 THERMOPLASTIC, COLOR: SEE PRODUCT CODE
- PLATING:
CONTACTS: GOLD FLASH OVER PALLADIUM NICKEL (0.76μm MINIMUM)
IN CONTACT AREA; 2.5 μm TIN MINIMUM IN SOLDER TAIL AREA.
1.27 μm MINIMUM NICKEL UNDERPLATE OVER ALL SURFACES.
SHIELD: SEE PRODUCT NUMBER CODE.
(THE PLATING MEASURE POINT ON THE SHIELD HOLD DOWN AREA ONLY).
- DATUMS & BASIC DIMENSIONS TO BE DETERMINED BY CUSTOMER
- RECOMMENDED PCB BOARD THICKNESS IS 1.00 ~ 1.60mm EXCEPT 73725-1191BLF; 73725-1191BLF CAN BE USED FOR THE PCB BOARD THICKNESS 2.30 ~ 2.65mm.
- MAXIMUM PANEL THICKNESS TO BE 2.67mm IF MOUNTED BEHIND PANEL
- METAL SHELL SLIVER 0.20 MAX.
- NI PLATING DOES NOT COMPLY WITH THE USB STANDARDS (TO BE CONTINUED)

mat'l. code				surface123/tolerance			projection		product family		
				ISO 1302	ISO 406	ISO 1101			HPL 511 USB 2.0		
ltr	ecn no	dr	date	tolerances unless otherwise specified			title				
AJ	ELX-N-27708	LZ	2017/08/15	angles	linear		mm		USB UP-RIGHT RECEPT		
AD	ELX-N-012006	A.ZH	06/25/2012	0±2°			scale 1:1				
AE	ELX-N-13463	A.ZH	11/14/2012	dr	PAMP	5/20/97			dwg no sheet 1 of 4 size		
AF	ELX-N-14592	J.HAN	06/10/2013	engr	R Y LIU	5/20/97			73725 A3		
AG	ELX-N-21594	LQ	08/04/2015	chr	R Y LIU	5/20/97					
AH	ELX-N-21919	LQ	08/04/2015	appd	JENN TSAO	5/20/97			type Product Customer Drawing		
sheet	revision										
index	sheet										

PRODUCT NO.
73725

(CONTINUED)

8. P/N'S WITH SUFFIX "LF" ARE LEAD FREE P/N'S



FOR LEAD FREE P/N, THE PRODUCT MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008

FOR THE PRODUCTS WITH THE METAL SHELL PLATING NICKEL AND MATTE SN CAN WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 40 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW PROCESS; FOR THE PRODUCTS WITH METAL SHELL PLATING BRIGHT SN OR SEMI-BRIGHT SN CAN'T WITHSTAND REFLOW AND JUST CAN WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN WAVE SOLDERING PROCESS.



FOR ALL LEAD FREE P/N'S, WITH SUFFIX LF.

12. THE PRODUCT CAN BE USED FOR PIP PROCESS


13. DATUM OF CUSTOMER'S PCB LAYOUT.



PC BOARD MOUNTING DIMENSIONS FOR 4 PIN








WITHOUT SENSOR CONTACT




FOR 73725-X1X0B
HOLD DOWN STYLE "A"

mat'l. code				surface ¹²³ /tolerance			projection		product family		
				ISO 1302 ✓ ISO 406 ISO 1101					HPL 511 USB 2.0		
ltr	ecn	no	dr	date			tolerances unless otherwise specified		title		
AJ							mm		USB UP-RIGHT RECEPT		
				angles			.0±.30				
				linear			.00±.20				
				0°±2'			.000±.10				
				dr			PAMP		5/20/97		
				eng			R Y LIU		5/20/97		
				chr			R Y LIU		5/20/97		
				appd			JENN TSAO		5/20/97		
sheet		revision								dwg no	
index		sheet								sheet2 of 4	
										size	
										A3	
										type	
										Product Customer Drawing	





mat'l. code				surface ¹²³ / tolerance		projection		product family						
				ISO 1302 ✓ ISO 406 ISO 1101				HPL 511 USB 2.0						
ltr	ecn no	dr	date	tolerances unless otherwise specified				title						
AJ				angles		mm		USB UP-RIGHT RECEPT						
				linear		mm								
				0°±2'		scale 1:1								
				.0±.30										
				.00±.20				dwg no						
				.000±.10										
				dr PAMP		5/20/97						sheet3 of 4		size
				eng R Y LIU		5/20/97						73725		A3
				chr R Y LIU		5/20/97		type Product Customer Drawing						
				app JENN TSAO		5/20/97								
sheet index		revision sheet												

PRODUCT NO.
73725



PC BOARD MOUNTING DIMENSIONS FOR 4 PIN



WITHOUT SENSOR CONTACT
FOR 73725-X150B
HOLD DOWN STYLE "C"

mat'l. code				surface ¹²³ / tolerance		projection		product family			
ISO 1302 ✓				ISO 406 ISO 1101				HPL 511 USB 2.0			
ltr	ecn no	dr	date	tolerances unless otherwise specified				title			
AJ				angles	.0±.30			USB UP-RIGHT			
				linear	.00±.20			RECEPT			
				0°±2°	.000±.10			scale 1:1			
				dr	PAMP	5/20/97	Amphenol FCI	dwg no		sheet 4 of 4	size
				engr	R Y LIU	5/20/97		73725			A3
				chr	R Y LIU	5/20/97					
				appd	JENN TSAO	5/20/97		type Product Customer Drawing			
sheet index		revision sheet									

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru