



## A Dimensions: [mm]











Scale - 1:2

## **Additional Features**

Safety key to lock/ unlock	74271

## B Applicable Cable Diameter: [mm]



Scale - 1:2



## **D Electrical Properties:**

Properties	Test conditions		Value	Unit	Tol.
Impedance @ 25 MHz 1 turn	25 MHz	Z	55	Ω	±25%
Impedance @ 100 MHz 1 turn	100 MHz	Z	110	Ω	±25%
Impedance @ 25 MHz 2 turns	25 MHz	Z	190	Ω	typ.
Impedance @ 100 MHz 2 turns	100 MHz	Z	390	Ω	typ.

## **E General information:**

Storage Temperature (before assembly): 0°C to +40°C Operating Temperature: -25°C to +105°C

Test conditions of Electrical Properties: 20°C, 33% RH

if not specified differently

Pro				
] _				
,	SMu	SSt	2013-03-18	6.4
Wüı	SMu	SSt	2013-02-19	6.3
EM0 Max	SSt	SSt	2012-11-28	6.2
746	SSt	SSt	2012-06-27	6.1
Ger Tel.	SMu	SSt	2012-04-30	6.0
ww eiSo	-	SMu	2007-01-25	5.0
8100	CHECKED	BY	DATE	REV

Würth Elektronik eiSos GmbH & Co. KG
EMC & Inductive Solutions
Max-Eyth-Str. 1
74638 Waldenburg
Germany
Tel. +49 (0) 79 42 945 - 0
www.we-online.com
eiSos@we-online.com

DESCRIPTION

# STAR-RING Snap Ferrite with safety key technology

Order.- No.

7427155



SIZE A4


This electronic component has been designed and developed for usage in general electronic equipment only. This product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use.
Moreover Würth Elektronik elSos GmbH & Co KG mouts be informed about the intent of such usage before
the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.



## **D2 General Properties:**

	Properties		Value	Unit	Tol.
Ferrite core	Material		4 W 620		
Ferrite core	Initial permeability	$\mu_{i}$	620		typ.
Ferrite core	Curie temperature	тс	150	°C	typ.
Plastic housing	Colour		Grey		
Plastic housing	Flammability Classification		UL94-V0		
Test cable	Applicable cable		AWG26		
Test cable	Applicable cable length		120	mm	

## **F Typical Impedance Characteristics:**



				Projection -		DESCRIPTION			
6.4	2013-03-18	SSt	SMu	STAR-RING Snap Ferrite with s		ap Ferrite with safety k	(ev		
6.3	2013-02-19	SSt	SMu	Würth Elektronik eiSos GmbH		technology	<b>,</b>	,	
6.2	2012-11-28	SSt	SSt	EMC & Inductive Solutions Max-Eyth-Str. 1		technology			
6.1	2012-06-27	SSt	SSt	74638 Waldenburg		Order No.	COMPLIANT	SI7F	
6.0	2012-04-30	SSt	SMu	Germany Tel. +49 (0) 79 42 945 - 0		7407455	ROHS&REACH	OIZE	
5.0	2007-01-25	SMu	-	www.we-online.com		7427155	I SATA ELEKTRONIK	A4	
REV	DATE	BY	CHECKED	ei303@We-Offilite.com					

## I Cautions and Warnings:

## The following conditions apply to all goods within the product series of WE-STAR RING of Würth Elektronik eiSos GmbH & Co. KG:

#### General:

All recommendations according to the general technical specifications of the data sheet have to be complied with.

The disposal and operation of the product within ambient conditions which probably alloy or harm the component surface has to be avoided.

The packaging of the product is to encase the needed humidity of the plastic housing. To ensure the humidity level, the products have to be stored in this delivered packaging. If not, the products are losing their humidity. In this case you can re-condition the components according to the internal standard WE1581 to ensure the necessary humidity in the plastic.

To ensure the operating mode of the product, the ambient temperature at processing (when the part will be mounted on the cable) has to be in the range of 15 to 25 °C.

Before mounting, the part should be stored for one hour in this condition.

The responsibility for the applicability of customer specific products and the use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply for customer specific products.

Direct mechanical impact to the product and the forcible closing of this shall be prevented as the ferrite material of the ferrite body or the plastic housing could flake or in the worst case it could break.

#### **Product specific:**

Follow all instructions mentioned in the datasheet, especially:

- •The cable diameter must be pointed out, otherwise no warranty will be sustained.
- Violation of the technical product specifications such as exceeding the nominal rated current will result in the loss of warranty.



				Projection !	DESCRIPTION	
6.4	2013-03-18	SSt	SMu		STAR-RING Snap Ferrite with safety ke	.V
6.3	2013-02-19	SSt	SMu	Würth Elektronik eiSos GmbH & Co.		,
6.2	2012-11-28	SSt	SSt	EMC & Inductive Solutions Max-Evth-Str. 1	teciniology	
6.1	2012-06-27	SSt	SSt	74638 Waldenburg	Order No.	SIZE
6.0	2012-04-30	SSt	SMu	Germany Tel. +49 (0) 79 42 945 - 0	ROHS&REACH WORTH ELEKTRONIK	OILL
5.0	2007-01-25	SMu	-	www.we-online.com eiSos@we-online.com	7427155 WÜRTH ELEKTRONIK	A4
REV	DATE	BY	CHECKED	CIOOSSWC OHIIIO.COM		

### **J Important Notes:**

## The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

#### 1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

#### 2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications.

In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component.

Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

#### 3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

#### 4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

#### 5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.



#### 6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered.

The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

#### 7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG.

Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

#### 8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

				Projection		DESCRIPTION		
6.4	2013-03-18	SSt	SMu			STAR-RING Sna	ap Ferrite with safety k	(ev
6.3	2013-02-19	SSt	SMu	Würth Elektronik eiSos Gmbl	H & Co. KG	technology	ap : 011110 111111 04101, 1	,
6.2	2012-11-28	SSt	SSt	EMC & Inductive Solutions Max-Eyth-Str. 1		leciniology		
6.1	2012-06-27	SSt	SSt	74638 Waldenburg		Order No.	COMPLIANT	SIZF
6.0	2012-04-30	SSt	SMu	Germany Tel. +49 (0) 79 42 945 - 0		7407455	ROHS&REACH WURTH ELEKTRONIK	OIZL
5.0	2007-01-25	SMu	-	www.we-online.com eiSos@we-online.com		7427155	2 WOMIN ELEKTRONIK	A4
				eloos@we-offlifie.com				



OOO «ЛайфЭлектроникс" "LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 P/C 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

### Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru