



PNP POWER SILICON TRANSISTOR

Qualified per MIL-PRF-19500/535

Qualified Levels:
JAN, JANTX, and
JANTXV

DESCRIPTION

This high speed transistor is rated at 5 amps and is military qualified up to a JANTXV level. This TO-59 isolated package is available with a 180 degree lead orientation. Microsemi also offers numerous other products to meet higher and lower power voltage regulation applications.

Important: For the latest information, visit our website <http://www.microsemi.com>.

FEATURES

- JEDEC registered 2N5003 and 2N5005.
- Internal metallurgical bond option available.
- JAN, JANTX, and JANTXV, qualification per MIL-PRF-19500/535 available.
- RoHS compliant versions available (commercial grade only).



Marking may vary.

**TO-59 (TO-210AA)
Isolated Package**

APPLICATIONS / BENEFITS

- Fast switching capable - 0.5 μ s rise time.
- High frequency response.
- TO-59 case with Isolated terminals.
- Class 3B to ESD per MIL-STD-750 Method 1020.

MAXIMUM RATINGS

Parameters/Test Conditions	Symbol	Value	Unit
Junction and Storage Temperature	T_J and T_{STG}	-65 to +200	$^{\circ}C$
Thermal Resistance Junction-to-Ambient	$R_{\theta JA}$	88	$^{\circ}C/W$
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	3.0	$^{\circ}C/W$
Collector Current	I_C	5.0	A
	$I_C^{(3)}$	10	
Collector-Emitter Voltage	V_{CEO}	80	V
Collector-Base Voltage	V_{CBO}	100	V
Emitter-Base Voltage	V_{EBO}	5.5	V
Steady-State Power Dissipation	@ $T_A = +25^{\circ}C$ ⁽¹⁾	2.0	W
	@ $T_C = +25^{\circ}C$ ⁽²⁾	58	

- Notes:**
1. Derate linearly 11.4 mW/ $^{\circ}C$ for $T_A > +25^{\circ}C$.
 2. Derate linearly 331 mW/ $^{\circ}C$ for $T_C > +25^{\circ}C$.
 3. This value applies for $PW \leq 8.3$ ms, duty cycle $\leq 1\%$.

MSC – Lawrence

6 Lake Street,
Lawrence, MA 01841
1-800-446-1158
(978) 620-2600
Fax: (978) 689-0803

MSC – Ireland


Gort Road Business Park,
Ennis, Co. Clare, Ireland
Tel: +353 (0) 65 6840044
Fax: +353 (0) 65 6822298

Website:

www.microsemi.com

MECHANICAL and PACKAGING

- CASE: Nickel Plated.
- TERMINALS: Solder Dip over Nickel Plating. RoHS compliant Matte/Tin available on commercial grade only.
- MARKING: Manufacturer's ID, Date Code, Part Number, BeO.
- POLARITY: See Package Outline Drawing on last page.
- See [Package Dimensions](#) on last page.

PART NOMENCLATURE

SYMBOLS & DEFINITIONS

Symbol	Definition
C_{obo}	Common-base open-circuit output capacitance.
I_{CEO}	Collector cutoff current, base open.
I_{CES}	Collector emitter cutoff current, circuit between base and emitter.
I_{EBO}	Emitter cutoff current, collector open.
h_{FE}	Common-emitter static forward current transfer ratio.
V_{CEO}	Collector-emitter voltage, base open.
V_{CBO}	Collector-emitter voltage, emitter open.
V_{EBO}	Emitter-base voltage, collector open.

ELECTRICAL CHARACTERISTICS @ $T_C = 25^\circ\text{C}$ unless otherwise noted.

Characteristic	Symbol	Min.	Max.	Unit
----------------	--------	------	------	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage $I_C = 100\text{ mA}$	$V_{(BR)CEO}$	80		V
Collector-Emitter Cutoff Current $V_{CE} = 40\text{ V}, I_B = 0$	I_{CEO}		50	μA
Collector-Emitter Cutoff Current $V_{CE} = 60\text{ V}, V_{BE} = 0$ $V_{CE} = 100\text{ V}, V_{BE} = 0$	I_{CES}		1.0 1.0	μA mA
Emitter-Base Cutoff Current $V_{BE} = 4.0\text{ V}, I_C = 0$ $V_{BE} = 5.5\text{ V}, I_C = 0$	I_{EBO}		1.0 1.0	μA mA

ON CHARACTERISTICS

Forward-Current Transfer Ratio $I_C = 50\text{ mA}, V_{CE} = 5.0\text{ V}$ $I_C = 2.5\text{ A}, V_{CE} = 5.0\text{ V}$ $I_C = 5.0\text{ A}, V_{CE} = 5.0\text{ V}$ $I_C = 50\text{ mA}, V_{CE} = 5.0\text{ V}$ $I_C = 2.5\text{ A}, V_{CE} = 5.0\text{ V}$ $I_C = 5.0\text{ A}, V_{CE} = 5.0\text{ V}$	2N5003 2N5005	h_{FE}	20 30 20 50 70 40	90 200	
Base-Emitter Voltage Non-saturated $V_{CE} = 5.0\text{ V}, I_C = 2.5\text{ A}$		V_{BE}		1.45	V
Collector-Emitter Saturation Voltage $I_C = 2.5\text{ A}, I_B = 250\text{ mA}$ $I_C = 5.0\text{ A}, I_B = 500\text{ mA}$		$V_{CE(sat)}$		0.75 1.5	V
Base-Emitter Saturation Voltage $I_C = 2.5\text{ A}, I_B = 250\text{ mA}$ $I_C = 5.0\text{ A}, I_B = 500\text{ mA}$		$V_{BE(sat)}$		1.45 2.2	V

DYNAMIC CHARACTERISTICS

Common Emitter Small-Signal Short-Circuit Forward Current Transfer Ratio $I_C = 100\text{ mA}, V_{CE} = 5.0\text{ V}, f = 1\text{ kHz}$	2N5003 2N5005	h_{fe}	20 50		
Magnitude of Common Emitter Small-Signal Short-Circuit Forward Current Transfer Ratio $I_C = 500\text{ mA}, V_{CE} = 5.0\text{ V}, f = 10\text{ MHz}$	2N5003 2N5005	$ h_{fe} $	6.0 7.0		
Output Capacitance $V_{CB} = 10\text{ V}, I_E = 0, f = 1\text{ MHz}$		C_{obo}		250	pF


SWITCHING CHARACTERISTICS

Turn-On Time $I_C = 5\text{ A}; I_{B1} = 500\text{ mA}$		t_{on}		0.5	μs
Storage Time $I_{B2} = -500\text{ mA}$		t_s		1.4	μs
Fall Time $V_{BE(OFF)} = 3.7\text{ V}$		t_f		0.5	μs
Turn-Off Time $R_L = 6\text{ Ohms}$		t_{off}		1.5	μs

ELECTRICAL CHARACTERISTICS @ $T_C = 25^\circ\text{C}$ unless otherwise noted. (continued)
SAFE OPERATING AREA (See Figure below and [MIL-STD-750, Test Method 3053](#))
DC Tests
 $T_C = +25^\circ\text{C}$, $V_{CE} = 0$, $t_P = 1$ second 1 Cycle

Test 1
 $V_{CE} = 12$ V, $I_C = 5$ A

Test 2
 $V_{CE} = 32$ V, $I_C = 1.7$ A

Test 3
 $V_{CE} = 80$ V, $I_C = 100$ mA

Maximum safe operating area


GRAPHS


FIGURE 1
Temperature-Power Derating






FIGURE 2
Thermal Impedance

PACKAGE DIMENSIONS

NOTES:

1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. See NSB Handbook H28, "Screw-Thread Standards for Federal Services".
4. The orientation of the terminals in relation to the hex flats is not controlled.
5. All three terminals.
6. The case temperature may be measured anywhere on the seating plane within .125 inch (3.18 mm) of the stud.
7. Terminal spacing measured at the base seat only.
8. This dimension applies to the location of the center line of the terminals.
9. Terminal - 1, emitter; terminal - 2, base; terminal - 3, collector. Collector lead is isolated from the case.
10. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.

Symbol	Dimension				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A1		.250		6.35	
CD	.330	.360	8.38	9.14	
CD1	.370	.437	9.40	11.10	
CH	.320	.468	8.13	11.89	
HF	.424	.437	10.77	11.10	
HT	.090	.150	2.29	3.81	
OAH	.575	.763	14.61	19.38	5
PS	.185	.215	4.70	5.46	4, 8
PS1	.090	.110	2.29	2.79	4, 8
SL	.400	.455	10.16	11.56	
SU		.078		1.98	7
T	.040	.065	1.02	1.65	
UD	.155	.189	3.94	4.80	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Microchip:](#)

[2N5005](#) [2N5003](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru