



FCIconnect.com

Copyright FCI

D

1		2		3		4		5		6																																																																																																																																																																																																																																																											
 NOTE-1. FOR 14 POSN.HOLE NO.9 IS BLOCKED.						<table border="1"><thead><tr><th rowspan="2">SIZE</th><th colspan="7">DIMENSIONS</th></tr><tr><th>A±0.38</th><th>B±0.12</th><th>C±0.10</th><th>D^{+0.25}₋₀</th><th>E</th><th>F</th><th>G</th></tr></thead><tbody><tr><td>14/15</td><td>30.81</td><td>24.99</td><td>16.96</td><td>16.21</td><td>7.68</td><td>8.19</td><td>2.285</td></tr><tr><td>26</td><td>39.14</td><td>33.32</td><td>25.18</td><td>24.54</td><td>7.02</td><td>8.01</td><td>2.285</td></tr><tr><td>44</td><td>53.03</td><td>47.04</td><td>39.12</td><td>38.25</td><td>7.01</td><td>8.02</td><td>2.285</td></tr><tr><td>62</td><td>69.32</td><td>63.50</td><td>55.68</td><td>54.71</td><td>7.03</td><td>8.21</td><td>2.41</td></tr></tbody></table>						SIZE	DIMENSIONS							A±0.38	B±0.12	C±0.10	D ^{+0.25} ₋₀	E	F	G	14/15	30.81	24.99	16.96	16.21	7.68	8.19	2.285	26	39.14	33.32	25.18	24.54	7.02	8.01	2.285	44	53.03	47.04	39.12	38.25	7.01	8.02	2.285	62	69.32	63.50	55.68	54.71	7.03	8.21	2.41																																																																																																																																																																																																											
						SIZE	DIMENSIONS																																																																																																																																																																																																																																																														
							A±0.38	B±0.12	C±0.10	D ^{+0.25} ₋₀	E	F	G																																																																																																																																																																																																																																																								
						14/15	30.81	24.99	16.96	16.21	7.68	8.19	2.285																																																																																																																																																																																																																																																								
						26	39.14	33.32	25.18	24.54	7.02	8.01	2.285																																																																																																																																																																																																																																																								
44	53.03	47.04	39.12	38.25	7.01	8.02	2.285																																																																																																																																																																																																																																																														
62	69.32	63.50	55.68	54.71	7.03	8.21	2.41																																																																																																																																																																																																																																																														
 FOR 14 & 15 POSN FOR 26,44 & 62 POSN PCB DRILLING DETAILS																																																																																																																																																																																																																																																																					
TECHNICAL SPECIFICATIONS <table><tr><td>MATERIAL</td><td>: STEEL TIN/Zinc Cr 3 PLATED.</td></tr><tr><td>SHELL</td><td>: SELF EXTINGUISHING BLACK POLYESTER UL CLASS 94V0</td></tr><tr><td>INSULATORS</td><td>: THE HOUSING WILL WITHSTAND EXPOSURE TO 260-265°C IF WE USE PROTECTIVE ADHESIVE (type Kapton or Teflon) OR PROTECTIVE METALLIC DEVICE</td></tr><tr><td>CONTACTS</td><td>: COPPER ALLOY</td></tr><tr><td>PLATING</td><td>: GOLD OVER NICKEL</td></tr><tr><td>ACTIVE ZONE</td><td>: SnPb over Ni</td></tr><tr><td>TERMINATION ZONE</td><td>: 2 µ MIN.MATTE TIN TOP OVER</td></tr><tr><td>FOR LEAD FREE PLATING</td><td>: 1.27 µ MIN.NICKEL UNDER PLATE(ON TERMINATION ZONE)</td></tr><tr><td>METAL BRACKET</td><td>: BRASS,TIN /Zinc Cr3 PLATED.</td></tr><tr><td>SCREW LOCK</td><td>: BRASS,TIN /Zinc Cr3 PLATED.</td></tr><tr><td>HARPOON</td><td>: BRASS,TIN PLATED.</td></tr><tr><td>CLINCH NUT</td><td>: BRASS,TIN /Zinc Cr3 PLATED.</td></tr><tr><td>ELECTRICAL DATA</td><td></td></tr><tr><td>MAX.CURRENT RATING</td><td>: 3A</td></tr><tr><td>TEST VOLTAGE</td><td>: 1000V</td></tr><tr><td>RATED VOLTAGE</td><td>: 300V</td></tr><tr><td>CONTACT RESISTANCE</td><td>: <25mΩ</td></tr><tr><td>SHELL RESISTANCE</td><td>: <5mΩ</td></tr><tr><td>INSULATION RESISTANCE</td><td>: >5000MΩ</td></tr><tr><td>ENVIRONMENTAL CHARACTERISTICS.</td><td></td></tr><tr><td>OPERATING TEMPERATURE RANGE</td><td>: -55°C +125°C</td></tr><tr><td>MECHANICAL CHARACTERISTICS</td><td></td></tr><tr><td>MATING/UNMATING CYCLES (Min.)</td><td>: 200 MATINGS FOR <0.40µ GOLD PLATING</td></tr><tr><td></td><td>: 500 MATINGS FOR >0.75µ GOLD PLATING</td></tr><tr><td>INSERTION/EXTRACTION FORCE PER CONTACTS</td><td>: 5 N Max./0.3 N Min.</td></tr></table>						MATERIAL	: STEEL TIN/Zinc Cr 3 PLATED.	SHELL	: SELF EXTINGUISHING BLACK POLYESTER UL CLASS 94V0	INSULATORS	: THE HOUSING WILL WITHSTAND EXPOSURE TO 260-265°C IF WE USE PROTECTIVE ADHESIVE (type Kapton or Teflon) OR PROTECTIVE METALLIC DEVICE	CONTACTS	: COPPER ALLOY	PLATING	: GOLD OVER NICKEL	ACTIVE ZONE	: SnPb over Ni	TERMINATION ZONE	: 2 µ MIN.MATTE TIN TOP OVER	FOR LEAD FREE PLATING	: 1.27 µ MIN.NICKEL UNDER PLATE(ON TERMINATION ZONE)	METAL BRACKET	: BRASS,TIN /Zinc Cr3 PLATED.	SCREW LOCK	: BRASS,TIN /Zinc Cr3 PLATED.	HARPOON	: BRASS,TIN PLATED.	CLINCH NUT	: BRASS,TIN /Zinc Cr3 PLATED.	ELECTRICAL DATA		MAX.CURRENT RATING	: 3A	TEST VOLTAGE	: 1000V	RATED VOLTAGE	: 300V	CONTACT RESISTANCE	: <25mΩ	SHELL RESISTANCE	: <5mΩ	INSULATION RESISTANCE	: >5000MΩ	ENVIRONMENTAL CHARACTERISTICS.		OPERATING TEMPERATURE RANGE	: -55°C +125°C	MECHANICAL CHARACTERISTICS		MATING/UNMATING CYCLES (Min.)	: 200 MATINGS FOR <0.40µ GOLD PLATING		: 500 MATINGS FOR >0.75µ GOLD PLATING	INSERTION/EXTRACTION FORCE PER CONTACTS	: 5 N Max./0.3 N Min.																																																																																																																																																																																																														
MATERIAL	: STEEL TIN/Zinc Cr 3 PLATED.																																																																																																																																																																																																																																																																				
SHELL	: SELF EXTINGUISHING BLACK POLYESTER UL CLASS 94V0																																																																																																																																																																																																																																																																				
INSULATORS	: THE HOUSING WILL WITHSTAND EXPOSURE TO 260-265°C IF WE USE PROTECTIVE ADHESIVE (type Kapton or Teflon) OR PROTECTIVE METALLIC DEVICE																																																																																																																																																																																																																																																																				
CONTACTS	: COPPER ALLOY																																																																																																																																																																																																																																																																				
PLATING	: GOLD OVER NICKEL																																																																																																																																																																																																																																																																				
ACTIVE ZONE	: SnPb over Ni																																																																																																																																																																																																																																																																				
TERMINATION ZONE	: 2 µ MIN.MATTE TIN TOP OVER																																																																																																																																																																																																																																																																				
FOR LEAD FREE PLATING	: 1.27 µ MIN.NICKEL UNDER PLATE(ON TERMINATION ZONE)																																																																																																																																																																																																																																																																				
METAL BRACKET	: BRASS,TIN /Zinc Cr3 PLATED.																																																																																																																																																																																																																																																																				
SCREW LOCK	: BRASS,TIN /Zinc Cr3 PLATED.																																																																																																																																																																																																																																																																				
HARPOON	: BRASS,TIN PLATED.																																																																																																																																																																																																																																																																				
CLINCH NUT	: BRASS,TIN /Zinc Cr3 PLATED.																																																																																																																																																																																																																																																																				
ELECTRICAL DATA																																																																																																																																																																																																																																																																					
MAX.CURRENT RATING	: 3A																																																																																																																																																																																																																																																																				
TEST VOLTAGE	: 1000V																																																																																																																																																																																																																																																																				
RATED VOLTAGE	: 300V																																																																																																																																																																																																																																																																				
CONTACT RESISTANCE	: <25mΩ																																																																																																																																																																																																																																																																				
SHELL RESISTANCE	: <5mΩ																																																																																																																																																																																																																																																																				
INSULATION RESISTANCE	: >5000MΩ																																																																																																																																																																																																																																																																				
ENVIRONMENTAL CHARACTERISTICS.																																																																																																																																																																																																																																																																					
OPERATING TEMPERATURE RANGE	: -55°C +125°C																																																																																																																																																																																																																																																																				
MECHANICAL CHARACTERISTICS																																																																																																																																																																																																																																																																					
MATING/UNMATING CYCLES (Min.)	: 200 MATINGS FOR <0.40µ GOLD PLATING																																																																																																																																																																																																																																																																				
	: 500 MATINGS FOR >0.75µ GOLD PLATING																																																																																																																																																																																																																																																																				
INSERTION/EXTRACTION FORCE PER CONTACTS	: 5 N Max./0.3 N Min.																																																																																																																																																																																																																																																																				
ORDERING INFORMATION <table><tr><td>I</td><td>C</td><td>D</td><td>X</td><td>X</td><td>S</td><td>1</td><td>3</td><td>E</td><td>X</td><td>X</td><td>X</td><td>O</td><td>O</td><td>L</td><td>F</td></tr><tr><td colspan="2">SERIES</td><td colspan="2">NO.OF CONTACTS</td><td colspan="2">TYPE OF CONTACTS</td><td colspan="2">S-SOCKET</td><td colspan="2">TYPE OF TERMINATION</td><td colspan="2">HEIGHT OF TERMINATION</td><td colspan="2">LEAD FREE</td><td colspan="2">MOUNTING OPTIONS</td></tr><tr><td colspan="2">14,15,26,44 & 62</td><td colspan="2">13-ANGLED SPILL</td><td colspan="2">PITCH 2.54 USA</td><td colspan="2">FOOT PRINT 8.89 USA</td><td colspan="2">13-ANGLED SPILL</td><td colspan="2">PITCH 2.54 USA</td><td colspan="2">FOOT PRINT 8.89 USA</td><td colspan="2">PA->STANDARD HOLE</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">PL->THREADED INSERT M3</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">PX->THREADED INSERT UNC 4.40</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">PV->FEMALE SCREW LOCK UNC 4.40</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">GL->HARPOON+INSERTM3+METAL BRACKET</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">GX->HARPOON+INSERT UNC 4.40+METAL BRACKET</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">GV->HARPOON+F.SCREW LOCK UNC 4.40+METAL BRACKET</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">GA->HARPOON+METAL BRACKET+STANDARD HOLE</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">UL->INSERT M3+METAL BRACKET</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">UX->INSERT UNC 4.40+METAL BRACKET</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">UV->F.SCREW LOCK UNC 4.40+METAL BRACKET</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">PLATING</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">4->FLASH Au+SnPb/Sn</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">6->0.76 µAu+SnPb/Sn</td></tr></table>						I	C	D	X	X	S	1	3	E	X	X	X	O	O	L	F	SERIES		NO.OF CONTACTS		TYPE OF CONTACTS		S-SOCKET		TYPE OF TERMINATION		HEIGHT OF TERMINATION		LEAD FREE		MOUNTING OPTIONS		14,15,26,44 & 62		13-ANGLED SPILL		PITCH 2.54 USA		FOOT PRINT 8.89 USA		13-ANGLED SPILL		PITCH 2.54 USA		FOOT PRINT 8.89 USA		PA->STANDARD HOLE																PL->THREADED INSERT M3																PX->THREADED INSERT UNC 4.40																PV->FEMALE SCREW LOCK UNC 4.40																GL->HARPOON+INSERTM3+METAL BRACKET																GX->HARPOON+INSERT UNC 4.40+METAL BRACKET																GV->HARPOON+F.SCREW LOCK UNC 4.40+METAL BRACKET																GA->HARPOON+METAL BRACKET+STANDARD HOLE																UL->INSERT M3+METAL BRACKET																UX->INSERT UNC 4.40+METAL BRACKET																UV->F.SCREW LOCK UNC 4.40+METAL BRACKET																PLATING																4->FLASH Au+SnPb/Sn																6->0.76 µAu+SnPb/Sn	
I	C	D	X	X	S	1	3	E	X	X	X	O	O	L	F																																																																																																																																																																																																																																																						
SERIES		NO.OF CONTACTS		TYPE OF CONTACTS		S-SOCKET		TYPE OF TERMINATION		HEIGHT OF TERMINATION		LEAD FREE		MOUNTING OPTIONS																																																																																																																																																																																																																																																							
14,15,26,44 & 62		13-ANGLED SPILL		PITCH 2.54 USA		FOOT PRINT 8.89 USA		13-ANGLED SPILL		PITCH 2.54 USA		FOOT PRINT 8.89 USA		PA->STANDARD HOLE																																																																																																																																																																																																																																																							
														PL->THREADED INSERT M3																																																																																																																																																																																																																																																							
														PX->THREADED INSERT UNC 4.40																																																																																																																																																																																																																																																							
														PV->FEMALE SCREW LOCK UNC 4.40																																																																																																																																																																																																																																																							
														GL->HARPOON+INSERTM3+METAL BRACKET																																																																																																																																																																																																																																																							
														GX->HARPOON+INSERT UNC 4.40+METAL BRACKET																																																																																																																																																																																																																																																							
														GV->HARPOON+F.SCREW LOCK UNC 4.40+METAL BRACKET																																																																																																																																																																																																																																																							
														GA->HARPOON+METAL BRACKET+STANDARD HOLE																																																																																																																																																																																																																																																							
														UL->INSERT M3+METAL BRACKET																																																																																																																																																																																																																																																							
														UX->INSERT UNC 4.40+METAL BRACKET																																																																																																																																																																																																																																																							
														UV->F.SCREW LOCK UNC 4.40+METAL BRACKET																																																																																																																																																																																																																																																							
														PLATING																																																																																																																																																																																																																																																							
														4->FLASH Au+SnPb/Sn																																																																																																																																																																																																																																																							
														6->0.76 µAu+SnPb/Sn																																																																																																																																																																																																																																																							
"This LF product meets European Union Directives and other country regulations as described in GS-22-008" The housing will withstand exposure to 260°C peak temperature for 3.5 seconds in a wave solder application with a 1.6mm minimum thick circuit board. Packaging as per GS-14-920																																																																																																																																																																																																																																																																					
form: A3																																																																																																																																																																																																																																																																					

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru