


L2 L3 N PE
1 2 3 N 4
5 6 7 8 PE
PE 11 N PE 12 N PE 13 PE
1 2 3 4 5 N PE 6 PE 8 9 PE 11 N PE 12 PE 13

Weidmüller terminal - SAK-series- are proved in millions of applications for more than 50 years.

Available for the two rail systems TS32 and TS35, the SAK terminals are useable for every application and for all cross-sections. SAK terminals fulfill the requirements of EN 60 947-7-1.



Thermosetting plastic or Thermoplastic

Terminal of thermosetting plastic are normally used in applications where high continuous service temperature and high flammability level are necessary. The Weidmüller thermosetting plastic KRG is very resistant against infection through mould and micro-organisms.


The thermoplastic material Polyamide 66 has very good electrical and mechanical properties upto 100 °C. PA66 is flexible and unsusceptible to fracture, even with low temperatures.
Polyamid 66 has improved fire resistance and is self-extinguishing with flammability level V2 according to UL 94.



Thermosetting plastic



Thermoplastic



Cross-connection systems

40% of all terminals are cross-connected for potential branching.

Weidmüller distinguishes between the following cross-connection units for SAK-series:

- type Q pre-assembled cross-connections
- type QL permanent cross-connections
- type VL removeable cross-connection straps
- type QS removeable cross-connection plugs

Cross-connection systems from the SAK and AKZ series, type Q, QL or VL or other freely accessible live components, must be protected with appropriate covers ADP 1 or 4 or TSK 31.5 as long as they are to be inserted safe from contact.



Approvals

The following approvals apply to SAK terminals:

UL	UL-USA
CSA	CSA-Canada
GOST	GOST-Russia
SEV	SEV-Switzerland
KEMA	KEMA-Netherlands
LR	Lloyds Register of Shipping
GL	Germanischer Lloyd
DNV	Det Norske Veritas

SAK portfolio

- Feed-through terminals
- Protective conductor terminals
- Fuse terminals
- Disconnect-test terminals
- Feed-through terminals with tab, solder, WireWrap and Termi Point connections
- Initiator terminals, Actuator terminals
- Stud terminals

Accessories



An extensive assortment of accessories is available for Weidmüller SAK terminals:

- Partitions
- Cover plates
- Small partitions
- Test plugs
- Test adapters
- Marking material
- Cross-connections and
- Covers

Positioning of end plates or partitions between cross-connections

Operating voltage	Terminal width (in mm)					
	≦ 6	≦ 8	10	12	18	22
125 V ~	AP	–	–	–	–	–
250 V ~	AP	–	–	–	–	–
380 V ~	AP	AP	–	–	–	–
440 V ~	TW	AP	AP	AP	AP	–
500 V ~	TW	TW	AP	AP	AP	–
660 V ~	TW	TW	TW	TW	TW	AP
750 V ~	TW	TW	TW	TW	TW	AP



In PA terminals small partitions (TSch) have to be used up to 380 V.

Feed-through terminals

	SAKD 2.5 N SAKD 2.5/10/35	SAK 2.5/35 SAK 2.5/10/35	SAK 2.5 SAK 2.5/10	SAK 4/35 SAK 4/10/35
				
Dimensions/approvals				
Width/length/height (mm) with TS 32 ⊏	5/32.5/43.5		6/36.5/46.5	6.5/40/51.5
Width/length/height (mm) with TS 35 x 7.5 ⊐	5/44/38	6/45/40		6.5/45/44
Insulation stripping length/clamping screw/screwdriver blade	10/M 2.5/3.5 x 0.6	10/M 2.5/3.5 x 0.6	10/M 2.5/3.5 x 0.6	12/M 3/3.5 x 0.6
Rated data according to IEC 60 947-7-1				
Rated voltage/current/cross-section	500 V/24 A/2.5 mm²	800 V/24 A/2.5 mm²	800 V/24 A/2.5 mm² [3]	800 V/32 A/4 mm²
Rated impulse voltage/pollution severity	6 kV/3	8 kV/3	8 kV/3	8 kV/3
Further technical data				
Tightening torque range Nm	0.4…0.6	0.4…0.6	0.4…0.6	0.5…1.0
Torque setting with electric screwdriver type DMS 2	1	1	1	2
Clampable conductor				
Solid H07V-U mm²	0.5…4	0.5…6	0.5…6	0.5…6
Stranded H07V-R mm²	0.5…2.5	0.5…2.5	0.5…2.5	0.5…4
Flexible H07V-K mm²	0.5…4	0.5…4	0.5…4	0.5…4
Flexible H07V-K and ferrule according to DIN 46 228/1 mm²	0.5…2.5	0.5…2.5/4 [3]	0.5…2.5/4 [3]	0.5…4
Plug gauge according to 60 947-7-1 Size	A 2	A 3	A 3	A 4
Continuous current of terminal for conductor size	30 A/4 mm²	32 A/4 mm²	32 A/4 mm²	41 A/6 mm²
Continuous current rating of cross-connection 2…5-pole A	24	32	32	36
Continuous current rating of cross-connection 6…10-pole A	24			
Rated data according to UL/CSA				
Voltage/current/conductor size UL	300 V/20 A/28…12 AWG	600 V/20 A/22…12 AWG	600 V/20 A/22…12 AWG	600 V/20 A/22…12 AWG
Voltage/current/conductor size CSA	300 V/20 A/22…12 AWG	600 V/25 A/26…10 AWG	600 V/25 A/26…10 AWG	600 V/36 A/26…10 AWG
Ordering data Version	⊏ Qty. ⊐ Qty.	⊐ Cat. No. Qty.	⊏ Cat. No. Qty.	⊐ Cat. No. Qty.
KrG		**0380420000** 100	**0279620000** 100	**0443620000** 100
Blue KrG		**0380470000** 100	**0279670000** 100	**0443670000** 100
KrS			**0279630000** 100	
PA	**0215560000** 100 **0268860000** 100	**0380460000** [1] 100	**0279660000** [1][2] 100	**0443660000** [1] 100
Blue PA	**0215580000** 100 **0268880000** 100	**0380480000** [1] 100	**0279680000** [1][2] 100	**0443680000** [1] 100
Orange PA			**1326360000** [1][2] 100	**1323660000** [1] 100
Terminal block with marking PA	**0401060000** 10 **0523160000** 10	**0499460000** [1] 10	**0322560000** [1][2] 10	**0530460000** [1] 10
Terminal block without marking PA	**0401160000** 10	**0499560000** [1] 10	**0322860000** [1][2] 10	**0530360000** [1] 10
End plate (thickness mm)	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
KrG		AP (1.5) **0279520000** 20	AP (1.5) **0279520000** 20	AP (1.5) **0117920000** 20
Blue KrG		AP (1.5) **0279570000** 20	AP (1.5) **0279570000** 20	AP (1.5) **0117970000** 20
KrS		AP (1.5) **0279530000** 20	AP (1.5) **0279530000** 20	AP (1.5) **0117930000** 20
PA	AP (1.5) **0150960000** 20	AP (1.5) **0460560000** 20		AP (1.5) **0117960000** 20
Blue PA	AP (1.5) **0150980000** 20	AP (1.5) **0460580000** 20		AP (1.5) **0117980000** 20
PA			AP (1.5) **0279560000** 20	
Blue PA			AP (1.5) **0279580000** 20	
Partition (thickness mm)				
TW WTW KrG		TW (2.5) **0302820000** 20	TW (2.5) **0302820000** 20	TW (2.5) **0130120000** 20
Blue KrG		TW (2.5) **0302870000** 20	TW (2.5) **0302870000** 20	TW (2.5) **0103170000** 20
KrS		TW (2.5) **0302830000** 20	TW (2.5) **0302830000** 20	TW (2.5) **0130130000** 20
PA	TW (1.5) **0191860000** 20	TW (1.5) **0302860000** 20	TW (1.5) **0302860000** 20	TW (1.5) **0130160000** 20
Blue PA	TW (1.5) **0191880000** 20	TW (1.5) **0302880000** 20	TW (1.5) **0302880000** 20	TW (1.5) **0130180000** 20
HP	TW (1.5) **0307500000** 20	TW (1.0) **0297100000** 20	TW (1.0) **0297100000** 20	TW (1.0) **0197100000** 20
Small partition				
TSch 1		TSch 1 **0319160000** 100	TSch 1 **0319160000** 100	TSch 1 **0319160000** 100
	TSch 3 **0366860000** 100			
Cross-connection				
Q 4 2-pole	Q 2 **0367800000** 50	Q 2 **0337000000** 50	Q 2 **0337000000** 50	Q 2 **0336700000** 50
3-pole	Q 3 **0367900000** 50	Q 3 **0337100000** 50	Q 3 **0337100000** 50	Q 3 **0336800000** 50
4-pole	Q 4 **0368000000** 50	Q 4 **0337200000** 50	Q 4 **0337200000** 50	Q 4 **0336900000** 50
10-pole	Q 10 **0368100000** 20	Q 10 **0368700000** 20	Q 10 **0368700000** 20	Q 10 **0368800000** 20
Cover plates				
		AD 4 **0303400000** 50	AD 4 **0303400000** 50	AD 4 **0285300000** 50
		BSKM3x22 **0128900000** 100	BSKM3x22 **0128900000** 100	BSKM3x22 **0128900000** 100
Switchable cross-connection link				
VL 2 BS VH				VL 2 **0197000000** 100
				VH **0285100000** 50
				BS **0292500000** 100
Marking tags **Print**				
1 2 3 4 5 6 DEK Standard	DEK 5 see “Accessories”	DEK 6 see “Accessories”	DEK 6 see “Accessories”	DEK 6.5 see “Accessories”
Mounting rails, end brackets, further marking material see “Accessories”				

[1] Contact-proof with ADP 4 cover profile (see section “Accessories”)
[2] Not suitable for SST 3 safety pin
[3] Cat. No. **0279660000**, **0279680000**, **0380460000** and **0380480000**, 41 A for 6 mm²

Feed-through terminals

		SAK 4 SAK 4/10	DK 4 Q* DKB4 Q*/10*	DK 4 DK4/35
				
Dimensions/approvals		LR DNV		
Width/length/height (mm)	with TS 32	6.5/40/51.5	6/54/60	6/54/60
Width/length/height (mm)	with TS 35 x 7.5		6/54/60.5	6/54/60.5
Insulation stripping length/clamping screw/screwdriver blade			9/M 3/3.5 x 0.6	9/M 3/3.5 x 0.6
Rated data according to IEC 60 947-7-1				
Rated voltage/current/cross-section		800 V/32 A/4 mm²	500 V/2 x 32 A/4 mm²	500 V/2 x 32 A/4 mm²
Rated impulse voltage/pollution severity		8 kV/3	6 kV/3	6 kV/3
Further technical data				
Tightening torque range	Nm	0.5…1.0	0.5…1.0	0.5…1.0
Torque setting with electric screwdriver type DMS 2		2	2	2
Clampable conductor				
Solid H07V-U	mm²	0.5…6	0.5…4	0.5…4
Stranded H07V-R	mm²	0.5…4	0.5…4	0.5…4
Flexible H07V-K	mm²	0.5…4	0.5…4	0.5…4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm²			
With/without plastic insulating collar	mm²	0.5…4	0.5…4	0.5…4
Plug gauge according to 60 947-7-1	Size	A 4	A 3	A 3
Continuous current of terminal for conductor size		41 A/6 mm²	32 A/4 mm²	32 A/4 mm²
Continuous current rating of cross-connection 2…5-pole	A	36	32	32
Continuous current rating of cross-connection 6…10-pole	A		32	32
Technical data				
Voltage/current/conductor size	UL	600 V/20 A/22…12 AWG	300 V/27 A/22…12 AWG	300 V/27 A/22…12 AWG
Voltage/current/conductor size	CSA	600 V/36 A/26…10 AWG	300 V/10 A/26…12 AWG	300 V/10 A/26…12 AWG
Ordering data	Version	Cat. No. Qty.	Qty. Qty.	Qty. Qty.
	KrG	**0128320000** 100		
	Blue KrG	**0128370000** 100		
	KrS	**0128330000** 100		
	PA	**0128360000**[1)2)] 100	**0590060000**[*1)] 100 **0590160000**[1)] 100	**0355460000** 100 **0527660000** 100
	Blue PA	**0128380000**[1)2)] 100	**0590080000**[*1)] 100 **0590180000**[1)] 100	**0355480000** 100 **0527680000** 100
	Orange PA	**0105060000**[1)2)] 100		
	Terminal block with marking PA	**0322660000**[1)2)] 10	**1323860000**[*1)] 10	
	Terminal block without marking PA	**0308860000**[1)2)] 10		
End plate (thickness mm)		Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
	KrG	AP (1.5) **0117920000** 20		
	Blue KrG	AP (1.5) **0117970000** 20		
	KrS	AP (1.5) **0117930000** 20		
	PA	AP (1.5) **0117960000** 20	AP (1.5) **1397160000** 20	AP (1.5) **1397160000** 20
	Blue PA	AP (1.5) **0117980000** 20	AP (1.5) **1397180000** 20	AP (1.5) **1397180000** 20
	PA			
	Blue PA			
Partition (thickness mm)				
TW  WTW 	KrG	TW (2.5) **0130120000** 20		
	Blue KrG	TW (2.5) **0103170000** 20		
	KrS	TW (2.5) **0130130000** 20		
	PA	TW (1.5) **0130160000** 20	WTW (Ex) **1058800000** 20	WTW (Ex) **1058800000** 20
	Blue PA	TW (1.5) **0130180000** 20		
	HP	TW (1.0) **0197100000** 20		
Small partition				
TSch 6 		TSch 1 **0319160000** 100	TSch 6 **0190260000** 100	TSch 6 **0190260000** 100
Cross-connection				
Q 4  QB 4 	2-pole	Q 2 **0336700000** 50	Q 2 **0336400000** 50	Q 2 **0336400000** 50
	3-pole	Q 3 **0336800000** 50	Q 3 **0336500000** 50	Q 3 **0336500000** 50
	4-pole	Q 4 **0336900000** 50	Q 4 **0336600000** 50	Q 4 **0336600000** 50
	10-pole	Q 10 **0368800000** 20	Q 10 **0368600000** 20	Q 10 **0368600000** 20
	2-pole		QB 2 **0482700000**** 100	QB 2 **0482700000**** 100
	3-pole		QB 3 **0482800000**** 50	QB 3 **0482800000**** 50
	4-pole		QB 4 **0482900000**** 50	QB 4 **0482900000**** 50
Switchable cross-connection link				
VL 2  BS  VH 		VL 2 **0197000000** 100	VL 2 **0446700000** 50	VL 2 **0446700000** 50
		VH **0285100000** 50	VH **1056500000** 100	VH **1056500000** 100
		BS **0292500000** 100	BS **0343100000** 100	BS **0343100000** 100
Marking tags	**Print**			
	DEK Standard	DEK6.5 see “Accessories”	DEK6 see “Accessories”	DEK6 see “Accessories”
Mounting rails, end brackets, further marking material see “Accessories”				



* Accepts LS 2.8 shield lugs Cat. No. **1056400000**

** 2.5 mm² conductor connection when using QB


[1)] Contact-proof cross-connec. with ADP 4 over profile (see “Accessories”)

[2)] Not suitable for fuse pin SST 3

Feed-through terminals

	DK4 QV* DK4 QV/35*	SAK 6 N SAK 6/10/35	SAK 10 SAK 10/10/35	SAK 16 SAK 16/35
				
Dimensions/approvals				
Width/length/height (mm) with TS 32 ⊏	6/54/60	8/40/51.5	10/40/51.5	12/50/57.5
Width/length/height (mm) with TS 35 x 7.5 ⊐	6/54/60.5	8/45/44	10/45/44	12/50/50
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 3/3.5 x 0.6	12 mm/M 3.5/4.0 x 0.8	12 mm/M 4/5.5 x 1.0	15 mm/M 4/5.5 x 1.0
Rated data according to IEC 60 947-7-1				
Rated voltage/current/cross-section	500 V/32 A/4 mm²	800 V/41 A/6 mm²	800 V/57 A/10 mm²	1000 V/76 A/16 mm²
Rated impulse voltage/pollution severity	6 kV/3	8 kV/3	8 kV/3	8 kV/3
Further technical data				
Tightening torque range Nm	0.5…1.0	0.8…1.6	1.2...2.0[3]	1.2…2.4
Torque setting with electric screwdriver type DMS 2	2	3	4	4
Clampable conductor				
Solid H07V-U mm²	0.5…4	0.5…10	1.5…10	2.5…10
Stranded H07V-R mm²	0.5…4	0.5…6	2.5…16	4…16[2]
Flexible H07V-K mm²	0.5…4	0.5…10	1.5…10	4…16
Flexible H07V-K and ferrule according to DIN 46 228/1 mm²				
With/without plastic insulating collar mm²	0.5…4	0.5…6	1.5…10	4…16
Plug gauge according to 60 947-7-1 Size	A 3	A 5	B 6	B 6
Continuous current of terminal for conductor size	32 A/4 mm²		76 A/16 mm²	
Continuous current rating of cross-connection 2…5-pole A	32	41	57	76
Continuous current rating of cross-connection 6…10-pole A	32			
Rated data according to UL/CSA				
Voltage/current/conductor size UL	300 V/27 A/22…12 AWG	600 V/40 A/22…8 AWG	600 V/60 A/14…6 AWG[3]	600 V/80 A/12…4 AWG
Voltage/current/conductor size CSA	300 V/10 A/26…12 AWG	600 V/47 A/20…8 AWG	600 V/65 A/14…6 AWG[3]	600 V/87 A/10…4 AWG

Ordering data Version	⊏ Qty.	⊐ Qty.	⊏ Qty.	⊐ Qty.	⊏ Qty.	⊐ Qty.
KrG			**0193220000** 100	**0380520000** 100	**0110020000** 100	**0443720000** 100	**0271020000** 50	**0380620000** 50
Blue KrG				**0380570000** 100	**0110070000** 100	**0443770000** 100		
KrS			**0193230000** 100		**0110030000** 100		**0271030000** 50	
PA	**0590260000**[*1)] 100	**0363660000**[*1)] 100	**0193260000**[1)] 100	**0380560000**[1)] 100	**0110060000**[1)] 100	**0443760000**[1)] 100	**0271060000**[1)] 50	**0380660000**[1)] 50
Blue PA	**0590280000**[*1)] 100	**0363680000**[*1)] 100	**0193280000**[1)] 100	**0380580000**[1)] 100	**0110080000**[1)] 100	**0443780000**[1)] 100	**0271080000**[1)] 50	**0380680000**[1)] 50
Orange PA								
Terminal block with marking			**0322760000**[1)] 10			**0553860000**[1)] 10		
Terminal block without marking			**0308960000**[1)] 10		**0353160000**[1)] 10			

End plate (thickness mm)	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat No.	Qty.
AP  KrG				AP (1.5)	**0117920000**	20	AP (1.5)	**0117920000**	20	AP (3.0)	**0271120000**	20
Blue KrG				AP (1.5)	**0117970000**	20	AP (1.5)	**0117970000**	20			
KrS				AP (1.5)	**0117930000**	20	AP (1.5)	**0117930000**	20	AP (3.0)	**0271130000**	20
PA	AP (1.5)	**1397160000**	20	AP (1.5)	**0117960000**	20	AP (1.5)	**0117960000**	20	AP (1.5)	**0271160000**	20
Blue PA	AP (1.5)	**1397180000**	20	AP (1.5)	**0117980000**	20	AP (1.5)	**0117980000**	20	AP (1.5)	**0271180000**	20
Partition (thickness mm)												
TW  WTW  Small partition  KrG				TW (1.5)	**0130120000**	20	TW (1.5)	**0130120000**	20	TW (3.0)	**0281120000**	20
Blue KrG							TW (1.5)	**0130170000**	20			
KrS				TW (1.5)	**0130130000**	20	TW (1.5)	**0130130000**	20	TW (3.0)	**0281130000**	20
PA	WTW (Ex)	**1058800000**	20	TW (1.5)	**0130160000**	20	TW (1.5)	**0130160000**	20	TW (1.5)	**0303660000**	10
Blue PA				TW (1.5)	**0130180000**	20	TW (1.5)	**0130180000**	20	TW (1.5)	**0303680000**	10
	TW (2.0)	**0607000000**	20	TW (1.5)	**0197100000**	20	TW (1.5)	**0197100000**	20	TW (2.0)	**0607000000**	20
TSch 6	TSch 6	**0190260000**	100	TSch 1	**0319160000**	100	TSch 1	**0319160000**	100	TSch 1	**0319160000**	100
Cross-connection												
Q 4  QB 4  2-pole	Q 2	**0336400000**	50	Q 2	**0456700000**	50	Q 2	**0457100000**	50	Q 2	**0457500000**	50
3-pole	Q 3	**0336500000**	50	Q 3	**0456800000**	50	Q 3	**0457200000**	50	Q 3	**0457600000**	50
4-pole	Q 4	**0336600000**	50	Q 4	**0456900000**	50	Q 4	**0457300000**	50	Q 4	**0457700000**	50
10-pole	Q 10	**0368600000**	20	Q 10	**0457000000**	20	Q 10	**0457400000**	20	Q 10	**0457800000**	20
	QB 2	**0482700000****	100									
	QB 3	**0482800000****	50									
	QB 4	**0482900000****	50									
Cover												
	AD 4	**0303400000**	50	AD 4	**0196600000**	50	AD 4	**0178600000**	50	AD 4	**0518200000**	50
	BSK M 2.5 x18	**0303300000**	100	BSKM3x22	**0128900000**	100	BSKM3x22	**0128900000**	100	BSKM3x22	**0128900000**	100
Switchable cross-connection link												
VL 2  BS  VH 	VL 2	**04467000000**	50	VL 2	**0194700000**	50	VL 2	**0135900000**	50	VL 2	**0135800000**	50
	VH	**10565000000**	100	VH	**0285100000**	50	VH	**0285100000**	50	VH	**0285100000**	50
	BS	**03431000000**	100	BS	**0292500000**	100	BS	**0292500000**	100	BS	**0292500000**	100
Marking tags		**Print**										
 DEK	DEK 6	see "Accessories"		DEK 8	see "Accessories"		DEK 5	see "Accessories"		DEK 5	see "Accessories"	
Mounting rails, end brackets, further marking material see "Accessories"												

* Accepts LS 2.8 shield lugs Cat. No.**1056400000**
** 2.5 mm² conductor connection when using QB

[1)] Contact-proof with ADP 4 cover profile (see section "Accessories")

[2)] Tightening torque for 16 mm² stranded: 2 Nm

[3)] Tightening torque for 16 mm² and AWG6: 2 Nm

Feed-through terminals



	SAK 35 N SAK 35 N/35	SAK 35 SAK 35/35	SAK 70 SAK 70/35	SAK 95 SAK 95/35
				
Dimensions/approvals	DNV	LR DNV	LR DNV	DNV
Width/length/height (mm) with TS 32	16/58/67.5	18/58/60	22/75/79.5	28/83.5/100.5
Width/length/height (mm) with TS 35 x 7.5	16/63/60	18/58/60	22/75/87	28/83.5/96.5
Insulation stripping length/clamping screw/screwdriver blade	18 mm/M 6/6.5 x 1.2	20 mm/M 6/6.5 x 1.2	24 mm/M 8/S 6 D911	30 mm/M 10/S 8 D6911
Rated data according to IEC 60 947-7-1				
Rated voltage/current/cross-section	1000 V/125 A/35 mm²	800 V/125 A/35 mm²	1000 V/192 A/70 mm²	1000 V/232 A/95 mm²
Rated impulse voltage/pollution severity	8 kV/3	8 kV/3	8 kV/3	8 kV/3
Further technical data				
Tightening torque range Nm	4.0…5.0/4.0…6.0***	4.0…5.0/4.0…6.0***	6.0…12.0	10.0…20.0
Torque setting with electric screwdriver type DMS 2				
Clampable conductor			Strips	Strips
Solid H07V-U mm²	2.5…16	6…16	16 3x9x0.8	10…16 3x9x0.8
Stranded H07V-R mm²	2.5…50	16…50	16…70 [1] 6x9x0.8	10…120 [2] 6x9x0.8
Flexible H07V-K mm²	2.5…35	10…35	16…70 [1] 6x13x0.5	10…95 [2] 6x13x0.5
Flexible H07V-K and ferrule according to DIN 46 228/1 mm²	2.5…35	10…35	16…35	10…35 6x16x0.8
Plug gauge according to 60 947-7-1 Size	B 8	B 9	B 11	B 12
Continuous current of terminal for conductor size	125 A/35 mm²	125 A/35 mm²	192 A/70 mm²	232 A/95 mm²
Continuous current rating of cross-connection 2…5-pole A	65	99	180	180
Continuous current rating of cross-connection 6…10-pole A	65	99		
Rated data according to UL/CSA				
Voltage/current/conductor size UL	600 V/100 A/12…2 AWG	600 V/100 A/6…2 AWG	600 V/145 A/4…2/0 AWG	600 V/190 A/6…3/0 AWG
Voltage/current/conductor size CSA	600 V/120 A/12…2 AWG	600 V/145 A/6…2 AWG	600 V/150 A/4…2/0 AWG	600 V/260 A/6…3/0 AWG
Ordering data Version	Qty. Qty.	Qty. Qty.	VPE Qty.	Qty. Qty.
KrG	**0550620000** 20 **0608220000** 20	**0303520000** 20		
Hexagon socket KrG	**0555720000** 20 **0608320000** 20	**0476520000** 20	**0340820000** 10	**0550520000** 10 **0662220000** 10
Hexagon socket Blue KrG	**0608370000** 20		**0340870000** 10	
KrS	**0550630000** 20	**0303530000** 20		
Hexagon socket KrS	**0555730000** 20		**0340830000** 10	
PA	**0550660000** 20 **0608260000** 20	**0303560000** 20 **0380760000** 20		
Hexagon socket PA	**0555760000** 20 **0608360000** 20	**0476560000** 20 **0582460000** 20	**0139160000** 10	
Blue PA		**0303580000** 20 **0380780000** 20		
End plate (thickness mm)	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
KrG	AP (3.0) **0303620000** 10	AP (3.0) **0303620000** 10	AP (4.0) **0340920000** 10	AP (3.0) **0550920000** 10
Blue KrG	AP (3.0) **0303670000** 10	AP (3.0) **0303670000** 10		AP (3.0) **0550970000** 10
KrS	AP (3.0) **0303630000** 10	AP (3.0) **0303630000** 10	AP (4.0) **0340930000** 10	
PA	AP (1.5) **0303660000** 10	AP (1.5) **0303660000** 10	AP (2.0) **0340960000** 10	
Blue PA	AP (3.0) **0303680000** 10	AP (3.0) **0303680000** 10		
Orange PA				
Partition (thickness mm)				
KrG	TW (3.0) **0304320000** 10	TW (3.0) **0304320000** 10		
Blue KrG				
KrS	TW (3.0) **0304330000** 10	TW (3.0) **0304330000** 10		
PA	TW (1.5) **0304360000** 10	TW (1.5) **0304360000** 10		
Blue PA				
Cross-connection				
QL 3 VH BS SS 2-pole	QL 2 **0564900000** 50	QL 2 **0123600000** 20	QL 2 **0345300000** 20	QL 2 **0551200000** 10
3-pole	QL 3 **0565000000** 50	QL 3 **0123700000** 20	QL 3 **0167000000** 20	QL 3 **0407600000** 10
4-pole	QL 4 **0565100000** 50	QL 4 **0123800000** 20		QL 4 **0407700000** 10
10-pole	QL 10 **0565200000** 20	QL 10 **0338600000** 20		
	VH 17 **0267000000** 50	VH 17 **0267000000** 50	VH 30.5 **0345500000** 20	VH 35 **0551100000** 10
	BS M 4x30 **0267100000** 50	BS M 4x30 **0267100000** 50	BS M 5x45 **0345600000** 20	BS M 5x50 **0630200000** 20
	SS M 4 **0136400000** 100	SS M 4 **0136400000** 100	SS M 5 **0346100000** 100	
Switchable cross-connection link				
VL 2 BS VH		VL 2 **0124000000** 50		
		VH 24.5 **0298700000** 50		
		BS M 4x35 **0298900000** 50		
Cover / test plug				
	AD 4 **0576700000** 50	AD 4 **0178700000** 20	AD 3 **0344300000** 10	ADP 3 **0485400000** 20
	BSK M 4x32 **0129100000** 50	BSK M 4x32 **0129100000** 50	BSK M 5x45 **0344400000** 50	
PS 4	PS 4 **0299600000** 20	PS 4 **0299600000** 20	PS 4 **0299600000** 20	PS 4 **0299600000** 20
Marking tags **Print**				
1 2 3 4 5 6 DEK Standard	DEK 5 see "Accessories"	DEK 5 see "Accessories"	DEK 5 see "Accessories"	DEK 5 see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"				

*** For hexagon socket

[1] 12 Nm for 70 mm²

[2] 20 Nm for 95 mm² and 120 mm²

Feed-through terminals (spring-loaded)

		RSF 3 RSF 3/35	RSF 1		RSF 2 Disconnect test terminal
					
Dimensions/approvals					
Width/length/height (mm)	with TS 32	8/50/60	11/50/60		11/77/72.5
Width/length/height (mm)	with TS 35 x 7.5	8/50/53			
Insulation stripping length/clamping screw/screwdriver blade		12 mm	12 mm		12 mm
Rated data					
Rated voltage/-current		630 V/32 A	500 V/57 A		500/41 A
Rated cross-section	mm²	4	10		6
Rated impulse voltage VDE 0110/1.89/pollution severity		6 kV/3	6 kV /3		6 kV/3
Further technical data					
Tightening torque range	Nm	0.5…1.0			
Torque setting with electric screwdriver type DMS 2		2			
Clampable conductor					
Solid H07V-U	mm²	0.5…4	0.5…10		0.75...16
Stranded H07V-R	mm²	0.5…4	0.5…10		0.75...10
Rated data according to UL/CSA					
Voltage/current/conductor size	UL				
Voltage/current/conductor size	CSA				

Ordering data	**Version**		Qty.		Qty.		Qty.		Qty.		Qty.
	PA	**0497560000**	50	**9501160000**	50						
	KrG	**0497520000**	50			**0270320000**	50			**0623320000***	20 **0623120000**** 20

End plate/partition/small partition		Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
AP TW TSch 1	PA	AP (3)	**0270460000**	10						
	KrG				AP (3)	**0270420000**	10	AP (3.0)	**0301420000**	10
	PA	TW (1.5)	**3877960000**	10						
	HP	TW (2)	**3833500000**	20	TW (2)	**3833500000**	20			
	HP	TW (0.5)	**0474700000**	20	TW (0.5)	**0474700000**	20			
	PA	TSch 1	**0319160000**	100						

Cross-connection										
QL VH SS	2-pole	QL 2	**0194300000**	50	QL 2	**0194300000**	50			
	3-pole	QL 3	**0194400000**	50	QL 3	**0194400000**	50	QL 2	**0267400000**	50
	4-pole	QL 4	**0194500000**	50	QL 4	**0194500000**	50	QL 3	**0267500000**	50
	10-pole	QL 10	**0338300000**	10	QL 10	**0338300000**	10	QL 4	**0267600000**	50
		VH 13.5	**0248500000**	100	VH 17.5	**0285200000**	50	QL 10	**0341700000**	20
BS M 3 x ...		BS M 3x20	**0303000000**	100	BS M 3x25	**0292500000**	100	BS M 4x6	**0149700000**	100
					SS	**0164400000**	50	SB 14	**0135300000**	100
					QS 4	**0369760000**	10			
Switchable cross-connection link										
VH 21		VH 2	**0194700000**	50	VH 2	**0528400000**	50			
		VH 21	**0309600000**	100	VH 27	**0309400000**	50			
		BS M 3x20	**0296200000**	50	BS M 3x25	**0309800000**	50			
		SS	**0164400000**	50	SS	**0164400000**	50			
Dummy plug										
made from plastic, to keep the place of an extracted plug								BST 1	**3878060000**	20
Test plug/socket										
PS		PS 2.3	**0180400000**	50	PS 2.4	**0299600000**	20	PS 4	**0299600000**	20
		StB 14	**0168600000**	50	StB 18	**0286500000**	20	StB 17	**0147100000**	50
StB Plug-testsocket (QL cannot be used)										
Cover plate										
		ADP 2	**0485300000**	1	ADP 2	**0485300000**	1			

Marking tags	**Print**									
1 2 3 4 5 6	Standard	DEK	see “Accessories”		DEK	see “Accessories”				


* with disconnector (73 mm height)
** Disconnector with handle (86 mm height)

Feed-through terminals for thermocouples

Busbars made from thermocouple materials according to DIN IEC 584

Weidmüller's **thermocouple-treminals** are specially designed for transmitting the smallest voltages in temperature measuring circuits. Special busbars ensure that no false signals occur in the terminal when temperature differences exist in the positive and negative path.
This high measuring precision is necessary for, e.g. test beds, air craft engines, for complicated chemical processes, controls, etc.

I. Configuration of a temperature measuring circuit



1 Thermocouple (sensor)
2 Thermocouple terminals
3 Compensation conductor
4 Reference point
5 Supply conductors (to and from)
6 Measuring device


The thermocouple terminals displayed in this measurement circuit are used to thermoelectrically transmit thermal e.m.f. of the thermocouple to the reference point and indicating device via the thermocouple.

II. Symbols
Thermocouples according to IEC 584 DIN 43710

	Terminal	Busbar material trade name
a) Type J		
Fe (positive leg)		Iron
CuNi (negative leg)		Constantan
b) Type T		
Cu (positive leg)		Copper
CuNi (negative leg)		Constantan
c) Type K		
NiCr (positive leg)		Chromel
Ni (negative leg)		Alumel

		SAK 2.5 TC	DK 4 Q/TC
Dimensions/approvals			
Width/length/height (mm)	with TS 32 ⊏	6/36.5/49.5	6/54/59.5
Width/length/height (mm)	with TS 35 x 7.5 ⊐		6/54/60.5
Insulation stripping length/clamping screw/screwdriver blade		10 mm/M 2.5/3.5 x 0.6	9 mm/M 3/3.5 x 0.6
Technical data/VDE			
Rated voltage/current/cross-section		–/–/2.5 mm²	–/–/4 mm²
Tightening torque range	Nm	0.4…0.6	0.5…1





Ordering data	Version	Type	⊏ Cat. No.	Qty.	⊐	⊏	Qty.
	NiCr		**0107260000**	100			
	Ni		**0107160000**	100			
	CuNi		**0189860000**	100			
	Fe		**0190060000**	100			
	Cu		**0189960000**	100			
	NiCr/Ni	K			**1284160000**	**1338260000**	100
	Cu/CuNi	T			**1285660000**	**1338160000**	100
	Fe/CuNi	J			**1284060000**	**1338060000**	100

End plate (thickness mm)	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
KrG						
Blue KrG						
KrS						
PA	AP (1.5)	**0279560000**	20	AP (1.5)	**1397160000**	20
Blue PA						
Orange PA						



Partition (thickness mm)						
KrG						
Blue KrG						
KrS						
PA	TW (1.5)	**0302860000**	20			
WEM				WTW (Ex)e	**1058800000**	20
for TS 32 HP				TW HP (2.0)	**0607000000**	20



Marking tags		**Print**				
1 2 3 4 5 6	DEK	Standard	DEK 6	see "Accessories"	DEK 6	see "Accessories"


Mounting rails, end brackets, further marking material see "Accessories"

SAK-series


The Weidmüller SAKG range offers the following connection variants:

- clamping yoke/flat lug as a combination, Version I.
- flat lug, Version II.
  Two types of threading are provided here.
  a) screw set with lock nut
  b) with thread in busbar
- clamping yoke connection, Version III.
  The stripped conductor can be connected without further preparation.


Versions




Version I



Version II
without thread



Version II G
with thread




Version III

Cables with cable lugs are connected to SAKG terminals of Version I and to SS stud terminals.


Fitting instructions for SAKG terminals

When tightening the clamping screw, it is recommended that the conductor be held against the direction of tightening to prevent deformation of the mounting rail and so as not to place the terminal foot under undue torsional forces.



Cover

To ensure shock protection following connections of **conductors, AH** covers can be clipped onto the terminal.

Terminals/Accessories		SAKG 28 I	SAKG 28 II
			
Dimensions/approvals			DNV
Width/length/height (mm)	with TS 32 ⊏	28/70/63.5	28/70/53
Width/length/height (mm)	with TS 35 ⊐		
Insulation stripping length/clamping screw/screwdriver blade		15 mm/M 6/–	–/M 6/–
Rated data according to IEC 60 947-7-1			
Rated voltage/current/cross-section		1000 V*/125 A/35 mm²	1000 V*/125 A/35 mm²
Rated impulse voltage/pollution severity		8 kV/3	8 kV/3
Further technical data			
Tightening torque range	Nm	3…6	3…6
Torque setting with electric screwdriver type DMS 2			
Clampable conductor			
Solid H07V-U	mm²	6…35	
Stranded H07V-R	mm²	6…35	
Flexible H07V-K	mm²	10…35	
Flexible H07V-K and ferrule according to DIN 46 228/1	mm²	6…35	
Plug gauge according to 60 947-7-1	Size	B 9	
Continuous current of terminal for conductor size		125 A/35 mm²	125 A/35 mm²
Continuous current rating of cross-connection 2…5-pole	A	(QL 2) 125	(QL 2) 125
Continuous current rating of cross-connection 6…10-pole	A		
Rated data according to UL/CSA			
Voltage/current/conductor size	UL	600 V/95 A/2 AWG	600 V/115 A/2 AWG
Voltage/current/conductor size	CSA	600 V/110 A/6…1 AWG	600 V/110 A/6…1 AWG
Ordering data	Type	⊏ Cat. No. Qty.	⊏ Cat. No. Qty.
	KrG	**0170020000** 10	**0170320000** 10
End plate, hard paper		⊏ Cat. No. Qty.	⊏ Cat. No. Qty.
 **0205100000**		EP 1 (2) **0205100000** 10	EP 1 (2) **0205100000** 10
0205200000	tropic-proof	EP 1 (2) **0205200000** 10	EP 1 (2) **0205200000** 10
		⊐ Cat. No. Qty.	⊐ Cat. No. Qty.
 **0180700000, 0205300000**			
0180800000, 0205400000	tropic-proof		
Partition, hard paper (thickness in mm)		⊏ Qty.	⊏ Qty.
 **0151400000**		TW 1 (2) **0151400000** 10	TW 1 (2) **0151400000** 10
0164600000	tropic-proof	TW 1 (2) **0164600000** 10	TW 1 (2) **0164600000** 10
 **0177100000**	B/L/H (incl. TS 32) mm	2/120/75.5	2/120/75.5
0179900000	B/L/H (incl. TS 35) mm		
Cross-connection			
	2-pole	QL 2 **0193900000** 5	QL 2 **0193900000** 5
	3-pole	QL 3 **0407600000** 5	QL 3 **0407600000** 5
	4-pole	QL 4 **0407700000** 5	QL 4 **0407700000** 5
Cover			
		AH 28 **0326660000** 5	AH 28 **0326660000** 5
Marking tags	**Print**		
	DEK Standard	DEK 5 see "Accessories"	DEK 5 see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"			

During conductor connection, observe clearance and creepage distances. Insert partitions if necessary.

SAKG 28 II G



28/70/53

-/M 6/-

1000 V*/125 A/35 mm²
8 kV/3

3…6

125 A/35 mm²
(QL 2) 125

600 V/110 A/6…1 AWG

	Cat. No.	Qty.
	0185020000	10

	Cat. No.	Qty.
EP 1 (2)	**0205100000**	10
EP 1 (2)	**0205200000**	10

	Cat. No.	Qty.

		Qty.
TW 1 (2)	**0151400000**	10
TW 1 (2)	**0164600000**	10

2/120/75.5

QL 2	**0193900000**	5
QL 3	**0407600000**	5
QL 4	**0407700000**	5

AH 28	**0326660000**	5

DEK 5	see “Accessories”

SAKG 28 III



28/70/63.5

15 mm/M 6/-

1000 V*/125 A/35 mm²
8 kV/3

3…6

6…35
6…35
10…35
6…35
B 9

600 V/95 A/2 AWG
600 V/135 A/8…2 AWG

	Cat. No.	Qty.
	0170820000	10

	Cat. No.	Qty.
EP 1 (2)	**0205100000**	10
EP 1 (2)	**0205200000**	10

	Cat. No.	Qty.

		Qty.
TW 1 (2)	**0151400000**	10
TW 1 (2)	**0164600000**	10

2/120/75.5

AH 28	**0326660000**	5

DEK 5	see “Accessories”

SAKG 32 I
SAKG 32/35 I



32/87/84
32/87/84.5
26 mm/M 8/-

1000 V*/150 A/50 mm²
8 kV/3

6…12

10…70
10…70
10…70
10…35
B 11
150 A/50 mm²
(QL 2) 150

600 V/165 A/3 AWG
600 V/170 A/1…2/0 AWG

	Cat. No.	Qty.		Qty.
	0286620000		**0637120000**	10

	Cat. No.	Qty.
EP 1 (2)	**0205300000**	10
EP 1 (2)	**0205400000**	10

	Cat. No.	Qty.
EP 2/35 (2)	**0180700000**	10
EP 2/35 (2)	**0180800000**	10

	+	Qty.
TW 2 (2)	**0177100000**	10
TW 2 (2)	**0179900000**	10

2/160/90.5
2/160/90.5

QL 2	**0194000000**	5
QL 3	**0441500000**	5
QL 4	**0441600000**	5

AH 32	**0326760000**	5

DEK 5	see “Accessories”

SAKG 32 II
SAKG 32/35 II



32/80/53
32/80/51
-/M 8/-

1000 V*/150 A/50 mm²
8 kV/3

6…12

150 A/50 mm²
(QL 2) 150

600 V/200 A/3 AWG
600 V/170 A/1…2/0 AWG

	Qty.		Qty.
0170420000	10	**0637320000**	10

	Cat. No.	Qty.
EP 1 (2)	**0205100000**	10
EP 1 (2)	**0205200000**	10

	Cat. No.	Qty.
EP 1/35 (2)	**0180700000**	10
EP 1/35 (2)	**0180600000**	10

	+	Qty.
TW 1 (2)	**0151400000**	10
TW 1 (2)	**0164600000**	10

2/120**/75.5
2/120**/75.5

QL 2	**0194000000**	5
QL 3	**0441500000**	5
QL 4	**0441600000**	5

AH 32	**0326760000**	5

DEK 5	see “Accessories”

SAKG 32 II G
SAKG 32/35 II G



32/80/53
32/80/53
-/M 8/-

1000 V*/150 A/50 mm²
8 kV/3

6…12

150 A/50 mm²
(QL 2) 150

600 V/170 A/1…2/0 AWG

	Qty.		Qty.
0185120000	10	**0637420000**	10

	Cat. No.	Qty.
EP 1 (2)	**0205100000**	10
EP 1 (2)	**0205200000**	10

	Cat. No.	Qty.
EP 1/35 (2)	**0180700000**	10
EP 1/35 (2)	**0180600000**	10

	+	Qty.
TW 1 (2)	**0151400000**	10
TW 1 (2)	**0164600000**	10

2/120**/75.5
2/120**/75.5

QL 2	**0194000000**	5
QL 3	**0441500000**	5
QL 4	**0441600000**	5

AH 32	**0326760000**	5

DEK 5	see “Accessories”

SAKG 32 III
SAKG 32/35 III



32/94/84
32/94/84.5
26 mm/M 8/-

1000 V*/150 A/50 mm²
8 kV/3

6…12

10…70
10…70
10…70
10…35
B 11
150 A/50 mm²

600 V/165 A/3 AWG
600 V/185 A/1…2/0 AWG

	Qty.		Qty.
0286720000	10	**0637220000**	10

	Cat. No.	Qty.
EP 2 (2)	**0205300000**	10
EP 2 (2)	**0205400000**	10

	Cat. No.	Qty.
EP 2/35 (2)	**0180700000**	10
EP 2/35 (2)	**0180800000**	10

	+	Qty.
TW 2 (2)	**0177100000**	10
TW 2 (2)	**0179900000**	10


2/160/90.5
2/160/90.5

AH 32	**0326760000**	5

DEK 5	see “Accessories”

* During conductor connection, observe clearance and creepage distances. Insert partitions if nececssary
** For Cat. No. **0180600000** and **0180700000:** length = 160 mm.

Feed-through terminals

		SAKG 70 II G SAKG 70/35 II G	SAKG 40 I SAKG 40/35 I	SAKG 40 II SAKG 40/35 II	SAKG 40 II G SAKG 40/35 II G
					
Dimensions/approvals		DNV		DNV	
Width/length/height (mm)	with TS 32 ⊏⎓	32/84/54	40/95/84	40/90/53	40/90/55
Width/length/height (mm)	with TS 35 x 7.5 ⎓⊐	32/84/53	46/95/85.5	46/90/53	46/90/55
Insulation stripping length/clamping screw/screwdriver blade		–/M 8/–	27 mm/M 10/–	–/M 10/–	–/M 10/–
Rated data according to IEC 60 947-7-1					
Rated voltage/current/cross-section		1000 V*/192 A/70 mm²	1000 V*/232 A/95 mm²	1000 V*/232 A/95 mm²	1000 V*/232 A/95 mm²
Rated impulse voltage/pollution severity		8 kV/3	8 kV/3	8 kV/3	8 kV/3
Further technical data					
Tightening torque range	Nm	6…12	10...20	10…20	10…20
Torque setting with electric screwdriver type DMS 2					
Clampable conductor					
Solid H07V-U	mm²		10…95		
Stranded H07V-R	mm²		10…95		
Flexible H07V-K	mm²		10…95		
Flexible H07V-K and ferrule according to DIN 46 228/1	mm²		10…35		
Plug gauge according to 60 947-7-1	Size		B 12		
Continuous current of terminal for conductor size		192 A/90 mm²	232 A/95 mm²	232 A/95 mm²	232 A/95 mm²
Continuous current rating of cross-connection 2…5-pole	A	(QL 2) 192	(QL 2) 232	(QL 2) 232	(QL 2) 232
Continuous current rating of cross-connection 6…10-pole	A				
Rated data according to UL/CSA					
Voltage/current/conductor size	UL		600 V/195 A/4/0 AWG	600 V/230 A/4/0 AWG	600 V/230 A/4/0 AWG
Voltage/current/conductor size	CSA	600 V/200 A/2/0…4/0 AWG	600 V/250 A/2/0…4/0AWG	600 V/250 A/2/0…4/0 AWG	600 V/250 A/2/0…4/0 AWG
Ordering data	Version	⊏⎓ Qty. ⎓⊐ Qty.	⊏⎓ Qty. ⎓⊐ Qty.	⊏⎓ Qty. ⎓⊐ Qty.	⊏⎓ Qty. ⎓⊐ Qty.
	KrG	**0150420000** 10 **0636620000** 10	**0286820000** 10 **0637520000** 5	**0170520000** 10 **0637720000** 5	**0185220000** 10 **0637820000** 5
End plate, hard paper (thickness mm)		⊏⎓ Cat. No. Qty.	⊏⎓ Cat. No. Qty.	⊏⎓ Cat. No. Qty.	⊏⎓ Cat. No. Qty.
0205100000, 0180500000		EP 1 (2) **0205100000** 10	EP 2 (2) **0205300000** 10	EP 2 (2) **0205300000** 10	EP 2 (2) **0205300000** 10
0205200000, 0180600000	tropic-proof	EP 1 (2) **0205200000** 10	EP 2 (2) **0205400000** 10	EP 2 (2) **0205400000** 10	EP 2 (2) **0205400000** 10
		⎓⊐ Cat. No. Qty.	⎓⊐ Cat. No. Qty.	⎓⊐ Cat. No. Qty.	⎓⊐ Cat. No. Qty.
0180700000, 0205300000		EP 1/35 (2) **0180500000** 10	EP 2/35 (2) **0180700000** 10	EP 2/35 (2) **0180700000** 10	EP 2/35 (2) **0180700000** 10
0180800000, 0205400000	tropic-proof	EP 1/35 (2) **0180600000** 10	EP 2/35 (2) **0180800000** 10	EP 2/35 (2) **0180800000** 10	EP 2/35 (2) **0180800000** 10
Partition, hard paper (thickness mm)		⊏⎓+⎓⊐ Qty.	⊏⎓+⎓⊐ Qty.	⊏⎓+⎓⊐ Qty.	⊏⎓+⎓⊐ Qty.
0151400000		TW 1 (2) **0151400000** 10	TW 2 (2) **0177100000** 10	TW 2 (2) **0177100000** 10	TW 2 (2) **0177100000** 10
0164600000	tropic-proof	TW 1 (2) **0164600000** 10	TW 2 (2) **0179900000** 10	TW 2 (2) **0179900000** 10	TW 2 (2) **0179900000** 10
0177100000	B/L/H (incl. TS 32) mm	2/120/75.5	2/160/90.5	2/160/90.5	2/160/90.5
0179900000	B/L/H (incl. TS 35) mm	2/120/75.5	2/160/90.5	2/160/90.5	2/160/90.5
Cross-connection		⊏⎓+⎓⊐ Qty.	⊏⎓ Qty. ⎓⊐ Qty.	⊏⎓ Qty. ⎓⊐ Qty.	⊏⎓ Qty. ⎓⊐ Qty.
	2-pole, QL 2	**0194000000** 10	**0194100000** 10 **0211400000** 10	**0194100000** 10 **0211400000** 10	**0194100000** 10 **0211400000** 10
	3-pole, QL 3	**0441500000** 10	**0263500000** 10 **0444900000** 10	**0263500000** 10 **0444900000** 10	**0263500000** 10 **0444900000** 10
	4-pole, QL 4	**0441600000** 10	**0409800000** 10 **0445000000** 10	**0409800000** 10 **0445000000** 10	**0409800000** 10 **0445000000** 10
Cover					
		AH 32 **0326760000** 5	AH 40 **0326860000** 5	AH 40 **0326860000** 5	AH 40 **0326860000** 5
Marking tags		**Print**			
1 2 3 4 5 6	DEK	Standard DEK 5 see "Accessories"	DEK 5 see "Accessories"	DEK 5 see "Accessories"	DEK 5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

*During conductor connection, observe clearance and creepage distances. Insert partitions if necessary.

SAKG 40 III
SAKG 40/35 III



40/100/84	
46/100/85.5	
27 mm/M 10/–	
1000 V*/232 A/95 mm²	
8 kV/3	
10…20	
10…95	
10…95	
10…95	
10…35	
B 12	
232 A/95 mm²	
600 V/195 A/4/0 AWG	
600 V/230 A/2/0…4/0 AWG	

	Qty.		Qty.
0286920000	10	**0637620000**	5

	Cat. No.	Qty.
EP 2 (2)	**0205300000**	10
EP 2 (2)	**0205400000**	10

	Cat. No.	Qty.
EP 2/35 (2)	**0180700000**	10
EP 2/35 (2)	**0180800000**	10

	+	Qty.
TW 2 (2)	**0177100000**	10
TW 2 (2)	**0179900000**	10

2/160/90.5
2/160/90.5

AH 40 **0326860000** 5

DEK 5 see “Accessories”

SAKG 46 II
SAKG 46/35 II



46/106/55	
46/106/54.5	
–/M 12/–	
1000 V*/309 A/150 mm²	
8 kV/3	
14…31	
309 A/150 mm²	
600 V/285 A/4/0 AWG	
600 V/365 A/300 MCM	

	Qty.		Qty.
0170620000	10	**0637920000**	5

	Cat. No.	Qty.
EP 2 (2)	**0205300000**	10
EP 2 (2)	**0205400000**	10

	Cat. No.	Qty.
EP 2/35 (2)	**0180700000**	10
EP 2/35 (2)	**0180800000**	10

	+	Qty.
TW 2 (2)	**0177100000**	10
TW 2 (2)	**0179900000**	10

2/160/90.5
2/160/90.5

QL 2	**0247000000**	5
QL 3	**0444400000**	5
QL 4	**0444500000**	5

AH 46 **0326960000** 5

DEK 5 see “Accessories”

SAKG 46 II G
SAKG 46/35 II G



DNV	
46/106/57.5	
46/106/57	
–/M 12/–	
1000 V*/309 A/150 mm²	
8 kV/3	
14…31	
309 A/150 mm²	
(QL 2) 309	
600 V/285 A/4/0 AWG	
600 V/365 A/300 MCM	

	Qty.		Qty.
0185320000	10	**0638020000**	5

	Cat. No.	Qty.
EP 2 (2)	**0205300000**	10
EP 2 (2)	**0205400000**	10

	Cat. No.	Qty.
EP 2/35 (2)	**0180700000**	10
EP 2/35 (2)	**0180800000**	10

	+	Qty.
TW 2 (2)	**0177100000**	10
TW 2 (2)	**0179900000**	10


2/160/90.5
2/160/90.5

QL 2	**0247000000**	5
QL 3	**0444400000**	5
QL 4	**0444500000**	5

AH 46 **0326960000** 5

DEK 5 see “Accessories”

SAKG 54 II
SAKG 54/35 II



54/122/57	
54/122/57	
–/M 16/–	
1000 V*/415 A/240 mm²	
8 kV/3	
25…60	
415 A/240 mm²	
(QL 2) 415	
600 V/380 A/500 MCM	
600 V/600 A/300…500 MCM	

	Qty.		Qty.
0170720000	10	**0638120000**	5

	Cat. No.	Qty.
EP 2 (2)	**0205300000**	10
EP 2 (2)	**0205400000**	10

	Cat. No.	Qty.
EP 2/35 (2)	**0180700000**	10
EP 2/35 (2)	**0180800000**	10


	+	Qty.
TW 2 (2)	**0177100000**	10
TW 2 (2)	**0179900000**	10

2/160/90.5
2/160/90.5

QL 2	**0264400000**	5
QL 3	**0408000000**	5
QL 4	**0247400000**	5

DEK 5 see “Accessories”

SAKG 54 II G
SAKG 54/35 II G



DNV	
54/122/60	
54/122/60	
–/M 16/–	
1000 V*/415 A/240 mm²	
8 kV/3	
25…60	
415 A/240 mm²	
(QL 2) 415	
600 V/380 A/500 MCM	
600 V/600 A/300…500 MCM	

	Qty.		Qty.
0185420000	10	**0638220000**	5

	Cat. No.	Qty.
EP 2 (2)	**0205300000**	10
EP 2 (2)	**0205400000**	10

	Cat. No.	Qty.
EP 2/35 (2)	**0180700000**	10
EP 2/35 (2)	**0180800000**	10

	+	Qty.
TW 2 (2)	**0177100000**	10
TW 2 (2)	**0179900000**	10

2/160/90.5
2/160/90.5

QL 2	**0264400000**	5
QL 3	**0408000000**	5
QL 4	**0247400000**	5

DEK 5 see “Accessories”

SAKG 46/I AL
SAKG 46/II AL



46/112/74	
23 mm/M 12/M 14/-	
1000 V*/309 A/150 mm²	
8 kV/3	
14…31/25…40	
50…240	
35…185	

	Qty.		Qty.
1287920000**	5		

	Cat. No.	Qty.
EP 2 (2)	**0205300000**	10
EP 2 (2)	**0205400000**	10

	Cat. No.	Qty.
EP 2/35 (2)	**0180700000**	10

		Qty.
TW 2 (2)	**0177100000**	10
TW 2 (2)	**0179900000**	10

2/160/90.5
2/160/90.5

QL 2	**0194000000**	5
QL 3	**0441500000**	5
QL 4	**0441600000**	5





AH 46 **0326960000** 5

DEK 5 see “Accessories”

* During conductor connection, observe clearance and creepage distances. Insert partitions if necessary.
** Suitable for connection of 1 aluminium conductor of max 185 mm²

*** Suitable for connection of 2 aluminium conductors of max. 185 mm²

Stud terminals

		SS 6 SS 6/35	KST 5 KST 5/35	KST 6 KST 6/35	KST 8 KST 8/35
					
Dimensions/approvals					
Width/length/height (mm)	with TS 32 ⊏	18/40/62	24/60/55	24/60/62	24/60/72
Width/length/height (mm)	with TS 35 x 7.5 ⊐	18/49.5/54.5	24/62.5/49.5	24/62.5/54.5	24/62.5/64.5
Insulation stripping length/clamping screw/screwdriver blade		–/M 6/–	–/M 5/–	–/M 6/–	–/M 8/–
Rated data					
Rated voltage/current/cross-section		1000 V[1])/76 A/16 mm²	1000 V[1])/57 A/10 mm²	1000 V[1])/76 A/16 mm²	1000 V[1])/125 A/35 mm²
Rated impulse voltage/pollution severity		6 kV/3	8 kV/3	8 kV/3	8 kV/3
Further technical data					
Tightening torque range	Nm	3…6	2…4	3…6	6…12
Torque setting with electric screwdriver type DMS 2					
Clampable conductor					
Solid H07V-U	mm²				
Stranded H07V-R	mm²				
Flexible H07V-K	mm²				
Flexible H07V-K and ferrule according to DIN 46 228/1	mm²				
Plug gauge according to 60 947-7-1	Size				
Continuous current of terminal for conductor size		82 A/16 mm²	65 A/10 mm²	82 A/16 mm²	135 A/35 mm²
Continuous current rating of cross-connection 2…5-pole	A			200	200
Continuous current rating of cross-connection 6…10-pole	A				
Rated data according to UL/CSA					
Voltage/current/conductor size	UL	600 V/85 A/12…4 AWG	600 V/50 A/12…6 AWG	600 V/65 A/12…6 AWG	600 V/115 A/12…2 AWG
Voltage/current/conductor size	CSA	600 V/65 A/6 AWG			
Ordering data	Version	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.
	KrG	**0498220000** 25 **0649820000** 25			
	PA		**9503370000** 25		**9501320000** 25
	PPO				
	KrG				
for TS 35 x 7.5	PA		**9508230000** 25	**9506940000** 25	**9506950000** 25
for TS 35 x 15/2.3	PA		**9528300000** 25	**9528310000** 25	**9528320000** 25
Partition, (thickness mm)		Cat. No. Qty.	⊏ + ⊐	⊏ + ⊐	⊏ + ⊐
	PA	TW SS6 (TS32) **0455860000** 10			
	Hard paper	TW HGW (2) (TS 35) **0607100000** 20			
	HM		TW right **1718530000** 10	TW right **1718530000** 10	TW right **1718530000** 10
	HM		TW left [2]) **1752800000** 10	TW left **1752800000** 10	TW left **1752800000** 10
Width/length/height (incl. TS 32) mm		2/129/93	2/160/83.5	2/160/83.5	2/160/83.5
Width/length/height (incl. TS 35) mm		2/70/62.5	2/160/78.5	2/160/78.5	2/160/78.5
Cross-connection					
	2-pole	QL 2 **0284300000** 20	QL 2 **9503390000** 1	QL 2 **9501350000** 5	QL 2 **9501360000** 1
	3-pole	QL 3 **0279000000** 20			
Marking tags	**Print**				
	DEK Standard	DEK 5 see “Accessories”	DEK 5 see “Accessories”	DEK 5 see “Accessories”	DEK 5 see “Accessories”
Mounting rails, end brackets, further marking material see “Accessories”					


* Depends on cable lug

[1]) with partition

[2]) Left AP is required only once at beginning of terminal strip


Stud terminals

KST 10
KST 10/35




34/60/82	
34/62.5/74.5	
–/M 10/–	
1000 V[1])/192 A/70 mm²	
8 kV/3	
10…20	
207 A/70 mm²	
200	
600 V/175 A/12…2/0	
Qty.	Qty.
9501330000 20	
	9506960000 20
	9528330000 20
+	
TW right	**1718530000** 10
TW left	**1752800000** 10
2/160/83.5	
2/160/78.5	
QL 2	**9501370000** 1
DEK 5	see “Accessories”

KST 12
KST 12/35



34/60/82	
34/62.5/74.5	
–/M 12/–	
1000 V[1])/232 A/95 mm²	
8 kV/3	
14…31	
250 A/95 mm²	
200	
600 V/200 A/12…3/0	
Qty.	Qty.
	9506970000 20
	9528340000 20
+	
TW right	**1718530000** 10
TW left	**1752800000** 10
2/160/83.5	
2/160/78.5	
QL 2	**9501380000** 1
DEK 5	see “Accessories”

PE terminals

		EK 2.5 N EK 2.5/35	EK 4 EK 4/35	EK 6/35	EK 10 EK 10/35
					
Dimensions/approvals					
Width/length/height (mm)	with TS 32 ⊏⎓	6/36.5/49.5	8/40/51.5		10/40/51.5
Width/length/height (mm)	with TS 35 x 7.5 ⊐⎓	6/56/40	6.5/56/44	8/56/44	10/56/44
Insulation stripping length/clamping screw/screwdriver blade		10 mm/M 2.5/3.5 x 0.6	12 mm/M 3/3.5 x 0.6	12 mm/M 3.5/4.0/0.8	12 mm/M 4/5.5 x 1.0
Rated data according to IEC 60 947-7-2					
Rated voltage/current with PEN/cross-section		–/–/2.5 mm²	–/–/4 mm²	–/–/6 mm²	–/–/10 mm²
Rated voltage/rated impulse voltage acc. to VDE 0110/1.89/ pollution severity					
Further technical data					
Tightening torque range	Nm	0.4…0.8/0.5…1.0*	0.5…1.0/0.5…1.0*	1.2…1.6/0.5…1.0*	1.2…2.4/0.5…1.0*
Clampable conductor					
Solid H07V-U	mm²	0.5…4	0.5…6	0.5…10	0.5…10
Stranded H07V-R	mm²	0.5…2.5	0.5…4	1.5…6	1.5…6
Flexible H07V-K	mm²	0.5…4	0.5…4	0.5…10	0.5…10
Fexible H07V-K and ferrule DIN 46 228/1	mm²	0.5…2.5	0.5…4	0.5…6	0.5…10
Cable AWG	Nr.	22…14	22…10	20…8	20….8
Plug gauge according to 60 947-7-1	Size	A 3	A 4	A 5	B 6
Ordering data	Version	⊏⎓ Qty. ⊐⎓ Qty.	⊏⎓ Qty. ⊐⎓ Qty.	⊐⎓ Qty.	⊏⎓ Qty. ⊐⎓ Qty.
	Green/yellow PA	**0474360000** 100 **0661060000** 100	**0354560000** 100 **0661160000** 100	**0661260000** 100	**0354660000** 80 **0661360000** 100
	Blank				
	Two clamping yokes blank				
	Hexagon socket blank				
Support block		Type / Cat. No. / Qty.	Type / Cat. No. / Qty.	Type / Cat No. / Qty.	Type / Cat. No. / Qty.
 For insulation of mounting rails in insulated-earth installations		SH 2 **0494920000** 10	SH 2 **0494920000** 10	SH 2 **0494920000** 10	SH 2 **0494920000** 10
SK - key, 8mm					
Marking tags	**Print**				
	DEK Standard	DEK 6 see “Accessories”	DEK 6.5 see “Accessories”	DEK 8 see “Accessories”	DEK 5 see “Accessories”
Mounting rails, end brackets, further marking material see “Accessories”					

* For centre screw

PE terminals

EK 16
EK 16/35



12/50/57.5
12/56/50
16 mm/M 4/5.5 x 1.0

–/–/16 mm²

1.2…2.4/0.8…1.0*

2.5…16
2.5…16
2.5…16
4…16
12…6
B 6

	Qty.		Qty.
0374660000	50	**0190160000**	50

Type	Cat. No.	Qty.
SH 2	**0494920000**	10

DEK 5 see “Accessories”

EK 35**
EK 35/35



18/58/67.5
16/58/60
20 mm/M 6/6.5 x 1.2

–/–/35 mm²

2.5…5.0/ **

6…16
16…50
10…35
10…35
10…2
B 9

	Qty.		Qty.
0354760000	20	**0661460000**	20

Type	Cat. No.	Qty.
SH 2	**0494920000**	10

DEK 5 see “Accessories”

EK 2



10/52/38

14 mm/M 4/–

–/–/10

1.2…2.4/2.0…4.0*

1.5…10
1.5…10
1.5…10
1.5…10
16…8
B 6

	Qty.
0323100000	20

Type	Cat. No.	Qty.

SAKE 35



14/46/39

16 mm/M 6/–

–/–/35 mm²


2.5…5.0/2.0…4.0*

6…35
6…35
6…16
10…35
8…2
B 8

	Qty.	Qty.
0144400000	20	

Type	Cat. No.	Qty.
SH 2	**0494920000**	10

SAKE 70



18/94/59.5

25 mm/M 8/–

–/–/70 mm²

6.0…12/2.0…4.0*

10…70
10…70
10…70
10…70
6…0
B 10

	Qty.		Qty.
0213200000	20		
		1338300000	10

Type	Cat. No.	Qty.
SH 2	**0494920000**	10

EK 95/35



25/76/100/92
25/76/100/92
27 mm/M 10/–

–/–/95 mm²

10.0…20.0/1.2…2.4*



10…120
10…95
10…95
10…95
6…4/0
B 12

		Qty.
	0535300000	10
	0535400000	10

0235000000

** ADm f. EK 35/35 = 1.2 - 2.4 Nm
ADm f. EK 35 = 0.8 - 1.6 Nm


Fuse terminals

	ASK 1[1]) ASK 1/35[1])	KDKS 1[1]) KDKS 1/35[1])	SAKS 1 SAKS 1/35	SAKS 1/G25 SAKS 1/35/G25
				
Dimensions/approvals			DNV	DNV
Width/length/height (mm) with TS 32 ⊏	8/58/45.5	8/73.5/59,8	13/54/61	13/54/61
Width/length/height (mm) with TS 35 x 7.5 ⊐	8/58/44	8/73.5/55,7	13/54/54	13/54/54
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6	12 mm/M 4/5.5 x 1.0	12 mm/M 4/5.5 x 1.0
Rated data/feed through-terminal base				
Rated voltage/current/cross-section	500 V/6.3 A[2])/4 mm²	500 V/6.3 A/4 mm²	500 V/6.3 A[3])/10 mm²	500 V/6.3 A[3])/10 mm²
Rated impulse voltage/pollution severity	6 kV/3	6 kV/3	6 kV/3	6 kV/3
Further technical data				
Tightening torque range Nm	0.5…1.0	0.5…1.0	1.2…2.4	1.2…2.4
Torque setting with electric screwdriver type DMS 2	2	2	4	4
Clampable conductor				
Solid H07V-U mm²	0.5…4	0.5…4	0.5…16	0.5…16
Stranded H07V-R mm²	1.5…4		1.5…10	1.5…10
Flexible H07V-K mm²	0.5…4	0.5…4	0.5…10	0.5…10
Flexible H07V-K and ferrule according to DIN 46 228/1 mm²	0.5…4	0.5…4	0.5…10	0.5…10
Plug gauge according to 60 947-7-1 Size	A 3	A 4	B 6	B 6
Continuous current rating of cross-connection 2…5-pole A	(QB 2…4) 10	(QB 2…4) 10	(QL 2…5) 47	(QL 2…5) 47
Continuous current rating of cross-connection 6…10-pole A			(QL 6…10) 36	(QL 6…10) 36
Rated data according to UL/CSA				
Voltage/current/conductor size UL	300 V/6.3 A/12 max. AWG	300 V/15 A/12 max. AWG	300 V/6.3 A/22…10 AWG	
Voltage/current/conductor size CSA	300 V/6.3 A/26…12 AWG		600 V/10 A/26…10 AWG	600 V/10 A/26…10 AW
Ordering data Version	⊏+⊐ Cat.No. Qty.	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.
PA	**0474560000** 100	**9503300000** 50 **9503310000** 50		
KrG			**0191220000** 20 **0501620000** 20	**0191120000** 20 **0501520000** 20
Beige Wemid				**0501500000** 20
End plate/partition (thickness mm)	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
	AP (1.5) **0380360000** 20	AP 1 KDKS **9503330000** 25	AP (2.5) **0191320000** 20	AP (2.5) **0191320000** 20
		Wemid **9532470000** 25	Wemid beige **0191300000** 20	Wemid-beige **0191300000**
		for ⊏ TW (2.0)	for ⊏ TW (2.0)	for ⊏ TW (2.0)
		0607000000 20	**0607000000** 20	**0607000000** 20
G-fuse inserts	5 x 20 mm	5 x 20 mm	5 x 20 mm	5 x 25 mm
Acc. to IEC 60127-2 (VDE 0820 T.2 Bl 1) rated current (A): 0.10 fast	**0430300000** 10	**0430300000** 10	**0430300000** 10	0.25 (m) **0546900000** 10
Rated voltage 250 V 0.20 fast	**0430400000** 10	**0430400000** 10	**0430400000** 10	0.5 (m) **0510300000** 10
Fast switching capacity 1500 A 0.25 fast	**0430500000** 10	**0430500000** 10	**0430500000** 10	0.8 (m) **0646400000** 10
(at 250 V, 50 Hz, cos φ = 0.7) 0.50 fast	**0430600000** 10	**0430600000** 10	**0430600000** 10	1 (m) **0265800000** 10
1.0 fast	**0430700000** 10	**0430700000** 10	**0430700000** 10	10 (m) **0193100000** 10
1.6 fast	**0430800000** 10	**0430800000** 10	**0430800000** 10	2 (f) **0192700000** 10
2.0 fast	**0430900000** 10	**0430900000** 10	**0430900000** 10	4 (f) **0192800000** 10
2.5 fast	**0431000000** 10	**0431000000** 10	**0431000000** 10	6.3 (f) **0192900000** 10
3.15 fast				
4.0 fast				
5.0 fast				
6.3 fast				
Contact sleeve	**0553300000** 100	**0553300000** 100		
Screw cap/disconnector lever (spare)				
	TH **0377060000** 100	TH **0377060000** 100	SK (5 x 20) **0282100000** 20	SK (5 x 25) **0282000000** 20
Red pull lever	SIHA **1593020000** 100	SIHA **1593020000** 100		
Marking tags Print				
 DEK Standard	DEK 8 see “Accessories”	DEK 8 see “Accessories”	DEK 5 see “Accessories”	DEK 5 see “Accessories”
Mounting rails, end brackets, further marking material see “Accessories”				

[1]) Multipole interruptable with group marking carrier
Sch2 2-pole Cat. No. **1359500000**, 1000 mm Cat. No. **0337400000**

Fuse terminals

KSKM 1
KSKM 1/35



13/69/62
13/69/63
12 mm/–/–

250 V/6.3 A[1])/10 mm²

0.5…16

0.5…10

B 6

600 V/10 A/22…8 AWG

Qty.	Qty.
9509570000 20	**9509600000** 20


Type	Cat. No.	Qty.
AP (3)	**9509630000**	20

5 x 20 mm

0.10 (f)	**0430300000**	10
0.20 (f)	**0430400000**	10
0.25 (f)	**0430500000**	10
0.50 (f)	**0430600000**	10
1.00 (f)	**0430700000**	10
1.60 (f)	**0430800000**	10
2.00 (f)	**0430900000**	10
2.50 (f)	**0431000000**	10
3.15 fast	**0431100000**	10
4.0 fast	**0431200000**	10
5.0 fast	**0431300000**	10
6.3 fast	**0431400000**	10
5 x 20 SBL	**0446100000**	40

DEK 5 see “Accessories”

KSKM 2
KSKM 2/35



13/69/62
13/69/63
12 mm/–/–

250 V/13 A[2])/10 mm²

0.5…16

0.5…10

B 6

600 V/15 A/22…8 AWG

Qty.	Qty.
9509580000 20	**9509610000** 20

Type	Cat. No.	Qty.
AP (3)	**9509630000**	20

1 x 1/4”

1 x 1/4” SBL	**0446200000**	40

DEK 5 see “Accessories”

KSKM 3
KSKM 3/35



13/69/62
13/69/63
12 mm/–/–

440 V/10 A/10 mm²

0.5…16

0.5…10

B 6

600 V/15 A/22…8 AWG

Qty.	Qty.
	9509620000 20

Type	Cat. No.	Qty.
AP (3)	**9509630000**	20


1 1/4 x 1/4”

E 2 A	**0294500000**	10
E 3 A	**0295700000**	10
E 5 A	**0294600000**	10
E 7 A	**0295800000**	10
E 10 A	**0293900000**	10
1 1/4 x 1/4” SBL	**0446300000**	40

DEK 5 see “Accessories”

[1]) Max. fuse rating according to DIN 41 660, IEC 127 CEE4 Type 1
[2]) Fuse according to BS 1362

Fuse terminals

		SAKS 3 SAKS 3/35	SAKS 4 SAKS 4/35	SAKS 5 SAKS 5/35	SAKS 2 SAKS 2/35
					
Dimensions/approvals					
Width/length/height (mm)	with TS 32 ⊏	13/54/61	24/75/73	28/80/80.5	28/80/81.5
Width/length/height (mm)	with TS 35 x 7.5 ⊐	13/54/55	24/75/66	28/80/66	28/80/75
Insulation stripping length/clamping screw/screwdriver blade		12 mm/M 4/5.5 x 1	14 mm/M 4/5.5 x 1	13 mm/M 4/5.5 x 1	12 mm/M 4/5.5 x 1
Rated data/feed through-terminal base					
Rated voltage/current/cross-section		500 V/10 A/10 mm²	400 V**/16 A/10 mm²	400 V/63 A***/16 mm²	500 V/10 (25) A***/10 mm²
Rated impulse voltage/pollution severity		6 kV/3	6 kV/3	6 kV/3	6 kV/3
Further technical data					
Tightening torque range	Nm	1.2…2.4	1.2…2.4	1.2…2.4	1.2…2.4
Torque setting with electric screwdriver type DMS 2		4	4	4	4
Clampable conductor					
Solid H07V-U	mm²	0.5…16	0.5…16	1.5…16	0.5…16
Stranded H07V-R	mm²	1.5…10	1.5…10	1.5…16	0.5…10
Flexible H07V-K	mm²	0.5…10	0.5…10	1.5…16	0.5…10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm²	0.5…10	0.5…10	1.5…16	0.5…10
Plug gauge according to 60 947-7-1	Size	B 6	B 6	B 7	B 6
Continuous current rating of cross-connection 2…5-pole	A	(QL 2…5) 47	(QL 2…5) 47	(QL 2…5) 47	(QL 2…5) 47
Continuous current rating of cross-connection 6…10-pole	A	(QL 6…10) 36	(QL 6…10) 36	(QL 6…10) 36	(QL 6…10) 36
Rated data according to UL/CSA					
Voltage/current/conductor size	UL	300 V/10 A/22…10 AWG			
Voltage/current/conductor size	CSA	600 V/10 A/22…10 AWG	600 V/30 A/22…8 AWG	600 V/63 A/14…6 AWG	600 V/25 A/22…8 AWG
Ordering data	Version	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.
	KrG	**0248920000**[3] 20 **0667520000**[3] 20	**0321320000** 20 **0501820000** 20	**0359420000** 20 **0502120000** 20	**0206820000** 20 **1368720000** 20
	KrG	**0297520000**[4] 20 **0328920000**[4] 20			
End plate/partition (thickness mm)		Type / Cat. No. / Qty.	Neozed D 01 Type / Cat. No. / Qty.	Neozed D 02 Type / Cat. No. / Qty.	Diazed E 16 Type / Cat. No. / Qty.
	PA	AP (2.5) **0191320000**	TW HP (2.0) **0607000000*** 20	TW HP (2.0) **0607000000*** 20	TW HP (2.0) **0607000000*** 20
	HP	for ⊏			
		TW (2.0) **0607000000**			
Cross-connection					
 QL SS			QL 2 **0328000000** 20 QL 3 **0328100000** 20 QL 4 **0328200000** 20 QL 10 **0339000000** 20	QL 2 **0207800000** 20 QL 3 **0207900000** 20 QL 4 **0208000000** 20 QL 10 **0338900000** 20	QL 2 **0207800000** 20 QL 3 **0207900000** 20 QL 4 **0208000000** 20 QL 10 **0338900000** 20
Fixing screws for cross-connections			SS M 4 **0136400000** 100 BS M 4x9 **0103300000** 100	SS M 4 **0136400000** 100 BS M 4x9 **0103300000** 100	SS M 4 **0136400000** 100 BS M 4x9 **0103300000** 100
Fuse inserts		Fuse insert	Gauge ring	Gauge ring	Gauge ring
			Amp. Colour Cat. No. Qty.	Amp. Colour Cat. No. Qty.	Amp. Colour Cat. No. Qty.
1 1/4" x 1/4"	Nominal current (A): 0.5 fast	E 0.5 A **0533800000**	P 14/2 pink **0138000000** 50		
	1.0 fast	E 1 A **0525500000**	P 14/4 brown **0138100000** 50		P 16/10 red **0208900000** 100
	2.0 fast	E 2 A **0294500000**	P 14/6 green **0328600000** 50		P 16/16 grey **0209000000** 100
	3.0 fast	E 3 A **0295700000**	P 14/10 red **0328700000** 50	P 18/20 Blue **0361800000** 50	P 16/20 Blue **0209100000** 100
	5.0 fast	E 5 A **0294600000**		P 18/25 yellow **0361900000** 50	
	7.0 fast	E 7 A **0295800000**		P 18/35 black **0362000000** 50	
	10.0 fast	E 10 A **0293900000**		P 18/50 white **0362100000** 50	
G fuse inserts 5 x 30 mm (500 V~/0.032…6.3 A). Available from Wickmann-Werke GmbH, Annastr. 113, 58453 Witten, Germany, Phone ++492302/6620					
D fuse inserts			Rated voltage 400 V	Rated voltage 400 V	Rated voltage 500 V
			E 14/2 **0137400000** 10	E 18/20 **0361300000** 10	E 10 A **0208500000** 25
			E 14/4 **0137500000** 10	E 18/25 **0361400000** 10	E 16 A **0208600000** 25
			E 14/6 **0328300000** 10	E 18/35 **0361500000** 10	E 20 A **0208700000** 25
			E 14/10 **0328400000** 10	E 18/50 **0361600000** 10	E 25 A **0208800000** 25
			E 14/16 **0328500000** 10	E 18/63 **0361700000** 10	
Screw cap (spare)					
	red	SK (5 x 30) **0282000000** 20	SK **0339410000** 20	SK **0359310000** 20	SK **0284110000** 20
	black	SK (1/4" x 1 1/4) **0428900000** 20			
Marking tags	**Print**				
1 2 3 4 5 6	DEK Standard	DEK 5 see "Accessories"	DEK 5 see "Accessories"	DEK 5 see "Accessories"	DEK 5 see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"					

*only for TS 32

** Also for 440 V~ with neozed marina fuse
*** Current for overload up to 10 A, for short circuit up to 25 A

[3]) For fuse inserts 1 1/4 x 1/4" DEF 63
[4]) For fuse inserts 5 x 30

Fuse terminals

SAKS 4 USA



24/75/73	
24/75/66	
14 mm/M 4/5.5 x 1	
400 V/30 A/10 mm²	
6 kV/3	
1.2…2.4	
4	
0.5…16	
1.5…10	
0.5…10	
0.5…10	
B 6	
(QL 2…5) 47	
(QL 6…10) 36	
600 V/30 A/20…8 AWG	
600 V/30 A/22…8 AWG	
⌙ Qty. ⌐ Qty.	
0162220000 20	**0178220000** 20
10.3 x 38,1	
Type Cat. No. Qty.	
TW HP (2.0) **0607000000*** 20	
QL 2 **0328000000** 20	
QL 3 **0328100000** 20	
QL 4 **0328200000** 20	
QL 10 **0339000000** 20	
SS M 4 **0136400000** 100	
BS M 4 x 9 **0103300000** 100	


Fuse terminals

with fault indicator



SAKS 1


Fuse insert 5 x 20/5 x 25



Warning:
In the event of a faulty fuse, the connection system is live!

SAKS 4


Fuse insert E14/D 01
(e.g. Neozed D 01)



Warning:
In the event of a faulty fuse, the connection system is live!

SAKS 6


Fuse insert 11/4" x 1/4"
acc. to DEF 63



Warning:
In the event of a faulty fuse, the connection system is live!

SAKS 7

Fuse insert 5 x 20/5 x 25



Warning:
In the event of a faulty fuse, the connection system is live!

Dimensions/approvals					
Width/length/height (mm)	with TS 32 ⊏⊐				
Width/length/height (mm)	with TS 35 x 7.5 ⊐⊏				
Terminal width (+ 0.2 assembly tolerance)	mm	13	24	12	12
Insulation stripping length/clamping screw/screwdriver blade		12	14	12	12
Connection data					
Screw connection, solid		0.5…16 mm²	0.5…16 mm²	0.5…16 mm²	0.5…16 mm²
Screw connection, flexible		0.5…10 mm²	0.5…10 mm²	0.5…10 mm²	0.5…10 mm²
Conductor cross-section		AWG 20…8	AWG 20…7	AWG 20…8	AWG 20…8
Further technical data					
Tightening torque range	Nm	1.2…2.4	1.2…2.4	1.2…2.4	1.2…2.4
Torque setting with electric screwdriver type DMS 2		4	4	4	4
VDE rated data					
Voltage/current		–/10 A	–/16 A	500 V~/10 A	500 V~/10 A
LED-current (24…60 V)		≤ 5 mA		10 A	10 A
LED-current (115…230 V)				≤ 1 mA	≤ 1 mA
Incandescent lamp-current		≤ 50 mA			
Neon lamp-current		≤ 0.5 mA	≤ 1 mA	≤ 1 mA	≤ 1 mA
Cross-section		10 mm²	10 mm²	10 mm²	10 mm²

Ordering data		Voltage	⊏⊐ Qty. ⊐⊏ Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
Fuse insert			SAKS 1 LD	SAKS 4	SAKS 6 KrG **0531820000** 40	SAKS 7 KrG
5 x 20	LED	24 V–	**0371420000** 10 **0225820000** 10	TS 32 Neon lamp	for 1¼" x ¼" acc. to DEF 63	for 5 x 25 **0576120000** 40
Acc. to IEC 60127-2 (VDE 0820 T.2 BI 1)		24 V~	**1111220000** 10 **1111320000** 10	Voltage		SAKS 7 KrG
without indicator		48 V–		115 V≂ **0101820000** 10		for 5 x 20 **0573120000** 40
		48 V~	**0214020000** 10	480 V≂ **0102120000** 10	exchangable neon lamps	exchangable neon lamps
			SAKS 1 GL		(please order separately)	(please order separately)
	Incandescent lamp	24 V≂	**0173220000** 10			
		48 V≂	**0378920000** 10			
			SAKS 1 GL			
	Neon lamp	115 V≂	**0385320000** 10 **8068330000** 10			
		230 V≂	**0306120000** 10 **0199920000** 10			
Fuse insert			SAK 1 LD			
5 x 25	LED	24 V–	on demand			
Acc. to DIN 41576			SAKS GL			
without indicator	Incandescent lamp	48 V≂	on demand			
			SAKS 1 GL			
	Neon lamp	115 V≂				
		230 V≂	**0309320000** 10 **0198620000** 10			

Accessories		Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
Mounting rail		TS 32 **0122800000**	TS 32 **0122800000**	TS 32 **0122800000**	TS 32 **0122800000**
		TS 35x7.5 **0383400000**			
		TS 35x15 **0498000000**			
End brackets (thickness mm)	for TS 32 ⊏⊐	EWK 1 (8.5) **0206160000** 50	EWK 1 (8.5) **0206160000** 50	EWK 1 (8.5) **0206160000** 50	EWK 1 (8.5) **0206160000** 50
	for TS 35 ⊐⊏	EW 35 (8.5) **0383560000** 50			
End plate (thickness mm)		AP KrG (3) **0191320000** 20		AP KrG **0146720000** 20	AP KrG (3) **0146720000** 20
Cross-connection				QL 2 **0191400000** 50	QL 2 **0207800000** 20
Type 'QL'				QL 3 **0191500000** 50	QL 3 **0207900000** 20
Cross-connection				QL 4 **0191600000** 20	QL 4 **0208000000** 20
Type 'QB'				QL 10 **0338800000** 20	QL 10 **0338900000** 20
Fixing screw (fits QL)				BSM 3x6 m.SS **0346200000** 100	BSM 4x9 m.SS **0133300000** 100
Screw cap (spare)		SK (5 x 20) **0282100000** 20			
		SK (5 x 25) **0282000000** 100			
Neon lamp				Neon lamp 230 V~ **0550300000**	Neon lamp 230 V~ **0550300000**
				Neon lamp 115 V~ **0550200000**	Neon lamp 115 V~ **0550200000**

Fuse inserts and gauge rings for Weidmüller fuse terminals

Fuse inserts

for terminal type	Size (mm)	Rated voltage (V)	Rated current (A)		Type	Cat. No.	Qty.
	G fuse inserts 5 x 20 **without** indicator acc. to IEC 60127-2 (VDE 0820 T.2 Bl 1)						
SAKS 1			0.1	(F)	G 20/0.10A/F	**0430300000**	10
SAKS 7	5 x 20		0.2	(F)	G 20/0.20A/F	**0430400000**	10
ASK 1	Breaking capacity 1500 A		0.25	(F)	G 20/0.25A/F	**0430500000**	10
WSI 6	(at 250 V, 50 Hz, cos φ 0.7)		0.5	(F)	G 20/0.50A/F	**0430600000**	10
			0.63	(F)	G 20/0.63A/F	**0439000000**	10
			1.0	(F)	G 20/1.00A/F	**0430700000**	10
		250	1.6	(F)	G 20/1.60A/F	**0430800000**	10
			2.0	(F)	G 20/2.00A/F	**0430900000**	10
			2.5	(F)	G 20/2.50A/F	**0431000000**	10
			3.15	(F)	G 20/3.15A/F	**0431100000**	10
			4.0	(F)	G 20/4.00A/F	**0431200000**	10
			5.0	(F)	G 20/5.00A/F	**0431300000**	10
			6.3	(F)	G 20/6.30A/F	**0431400000**	10
	G fuse inserts 5 x 25 **with** indicator acc. to DIN 41576[1])						
SAKS 1							
SAKS 7	5 x 25 m. K.[1])		0.25	(M)	G 25/0.25A/M	**0546900000**	10
WSI 6	Breaking capacity 80 A		0.5	(M)	G 25/0.50A/M	**0510300000**	10
	(at 250 V, 50 Hz, cos φ = 1)		0.8	(M)	G 25/0.80A/M	**0646400000**	10
		250	1	(M)	G 25/1.00A/M	**0265800000**	10
			10	(M)[5])	G 25/10.0A/M	**0193100000**	10
			2	(F)	G 25/2.00A/F	**0192700000**	10
			4	(F)	G 25/4.00A/F	**0192800000**	10
			6.3	(F)	G 25/6.30A/F	**0192900000**	10
	Fuse inserts 1¼" x ¼" **without** indicator acc. to BS 88						
SAKS 3[2])	33 kA Breaking capacity 33 kA fast						
SAKS 6	E 0.5 A		0.5		GZ 0.5A/F	**0533800000**	10
	E 1 A		1		GZ 1.0A/F	**0525500000**	10
	E 2 A	440	2		GZ 2.0A	**0294500000**	10
	E 3 A		3		GZ 3.0A	**0295700000**	10
	E 5 A		5		GZ 5.0A	**0294600000**	10
	E 7 A		7		GZ 7.0A	**0295800000**	10
	E 10 A		10		GZ 10.0A	**0293900000**	10
	D fuse inserts E 16 **with** indicator acc. to DIN 49360 (diazed)						
SAKS 2	E 10 A		10		E 16/10A RT	**0208500000**	25
	E 16 A	500	16		E 16/16A GR	**0208600000**	25
	E 20 A		20		E 16/20A BL	**0208700000**	25
	E 25 A		25		E 16/25A GE	**0208800000**	25
	D fuse inserts E 14 Size D 01 and E 18 size D 02 **with** indicator acc. to DIN 49522 (neozed)[3])						
SAKS 4[4])	E 14/2		2		E 14/2A RS	**0137400000**	10
	E 14/4		4		E 14/4A BR	**0137500000**	10
	E 14/6	400	6		E 14/6A GN	**0328300000**	10
	E 14/10		10		E 14/10A RT	**0328400000**	10
	E 14/16		16		E 14/16A GR	**0328500000**	10
	E 18/20		20		E 18/20A BL	**0361300000**	10
SAKS 5	E 18/25		25		E 18/25A GE	**0361400000**	10
	E 18/35	400	35		E 18/35A SW	**0361500000**	10
	E 18/50		50		E 18/50A WS	**0361600000**	10
	E 18/63		63		E 18/63A KU	**0361700000**	10

(F) = fast

(M) = miedium-delayed action

Note: [1]) The SIBA company also supplies 5 x 25 G fuse inserts with indicators in a shipbuilding model for 450 V AC.

[2]) 5 x 30 (500 V AC) fuse inserts for SAKS 3 are available from the WICKMANN company

[3]) The LINDNER company also supplies neozed fuse cartridges in an additional shipbuilding mode for 440 V AC.





[4]) Fuse cartridges with the dimensions 1"x¼" ≙ 25.4x6.35 mm and 13/32"x1½" ≙ 10.3x38.1 mm ar not included in product line.

[5]) Only for SAKS 1 and SAKS 7.

Gauge rings

For terminal type	Gauge ring type	Amp.	Colour	Type	Cat. No.	Qty.
SAKS 4 and 4/35	P 14/2	2	Pink	P 14/2D01 RS	**0138000000**	50
	P 14/4	4	Brown	P 14/4D01 BR	**0138100000**	50
	P 14/6	6	Green	P 14/6D01 GN	**0328600000**	50
	P 14/1	10	Red	P 14/10D01 RT	**0328700000**	50
SAKS 5 and 5/35	P 18/20	20	Blue	P 18/20D02 BL	**0361800000**	50
	P 18/25	25	Yellow	P 18/25D02 GE	**0361900000**	50
	P 18/35	35	Black	P 18/35D02 SW	**0362000000**	50
	P 18/50	50	White	P 18/50D02 WS	**0362100000**	50
SAKS 2 and 2/35	P 16/10	10	Red	P 16/10 RT	**0208900000**	100
	P 16/16	16	Grey	P 16/16 GR	**0209000000**	100
	P 16/20	20	Blue	P 16/20 BL	**0209100000**	100

Disconnect test terminals

		SAKR SAKR/35	SAKR-D SAKR-D/35	DKT 4 DKT 4/35	DKT 4 V DKT 4 V/35
					
Dimensions/approvals					
Width/length/height (mm)	with TS 32 ⊏	6.5/42/40.5/54.5 (opened)	6.5/42/40.5/57 (with DLS 2)	6/65/56.5/70 (opened)	6/65/56.5/70 (opened)
Width/length/height (mm)	with TS 35 x 7.5 ⊐	6.5/46/38/52	6.5/46/38/54.5	6/65/56.5/70	6/65/56.5/70
Insulation stripping length/clamping screw/screwdriver blade		8 mm/M 3/3.5 x 0.6	8 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6
Rated data					
Rated voltage/current/cross-section		400 V[6])/10 A/4 mm²	400 V/10 A/4 mm²	400V/10 A/4 mm²	400 V/10 A/4 mm²
Rated impulse voltage/pollution severity		6 kV/3	6 kV/3	6 kV/3	6 kV/3
Further technical data					
Tightening torque range	Nm	0.5…1.0/0.5 StB	0.5…1.0/0.5 StB	0.5…1.0/0.5 StB	0.5…1.0/0.5 StB
Torque setting with electric screwdriver type DMS 2		2/1	2/1	2/1	2/1
Clampable conductor					
Solid H07V-U	mm²	0.5…4	0.5…4	0.5…4	0.5…4
Stranded H07V-R	mm²	1.5…4	1.5…4	1.5…4	1.5…4
Flexible H07V-K	mm²	0.5…4	0.5…4	0.5…4	0.5…4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm²				
With/without plastic insulating collar	mm²	0.5…4	0.5…4	0.5…4	0.5…4
Plug gauge according to 60 947-7-1	Size	A 3	A 3	A 3	A 3
Continuous current rating of cross-connection 2…5-pole	A	(QB 2…25) 10	(QB 2…25) 10	(QB 2…4) 10	(QB 2…4) 10
Continuous current rating of cross-connection 6…10-pole	A				
Rated data according to UL/CSA					
Voltage/current/conductor size	UL	300 V/10 A/26…12 AWG	300 V/10 A/26…12 AWG	300 V/10 A/22…12 AWG	300 V/10 A/22…12 AWG
Voltage/current/conductor size	CSA	300 V/10 A/26…12 AWG	300 V/10 A/22…12 AWG	300 V/10 A/26…12 AWG	300 V/10 A/26…12 AWG
Ordering data	Type	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.
	KrG	**0412120000** 100			
	PA	**0412160000** 100 **0172160000** 100	**0412960000**[1]) 100 **0299960000**[1]) 50	**0687360000** 50 **0687460000** 50	
	Without diode PA		**0413060000**[2]) 50 **0185760000**[2]) 50		
	With diode PA		**0263660000**[3]) 50 **0299560000**[3]) 50		
	Blue PA	**0412180000** 100 **0172180000** 100			
	Orange PA	**1461960000** 100			
With 2 StB[5])	KrG	**0412220000** 100			
With 2 StB[5])	PA	**0412260000** 100 **0183360000** 100	**0546460000**[1]) 100	**0327860000** 50 **0327960000** 50	**1304860000** 50 **1304960000** 50
With 2 StB[5])	without diode PA		**0413160000**[2]) 50		
With 2 StB[5])	Blue	**0412280000** 100 **0183380000** 100			
End plate (thickness mm)		Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
	KrG	AP (1.5) **0211320000** 20			
	PA	AP (1.5) **0211360000** 20	AP (1.5) **0211360000** 20	AP (1.5) **0687560000** 20	AP (1.5) **0687560000** 20
	Blue PA	AP (1.5) **0211380000** 20			
Partition (thickness mm)					
		TW HP (1.0) **0297100000** 20	TW HP (1.0) **0297100000** 20	TW HP (2.0) **0607000000** 20	TW HP (2.0) **0607000000** 20
Cross-connection					
QB 4 	2-pole	QB 2[4]) **0482700000** 100	QB 2[4]) **0482700000** 100	QB 2[4]) **0482700000** 100	QB 2[4]) **0482700000** 100
	3-pole	QB 3[4]) **0482800000** 50	QB 3[4]) **0482800000** 50	QB 3[4]) **0482800000** 50	QB 3[4]) **0482800000** 50
	4-pole	QB 4[4]) **0482900000** 50	QB 4[4]) **0482900000** 50	QB 4[4]) **0482900000** 50	QB 4[4]) **0482900000** 50
	25-pole	QB 25 blank[4]) **0134000000** 20	QB 25 blank[4]) **0134000000** 20		
Contact sleeve (spare)					
					
Test plug					
		PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20
Diode plug (spare)					
without diode			DLS 2 **0321060000** 50		
with diode 1N4007			DLS 2 +▷|– **0630160000** 50		
with diode 1N4007			DLS 2 –◁|+ **0547760000** 50		
with jumper			DLS 2 **0547660000** 25		
Marking tags	**Print**				
	DEK Standard	DEK 6.5 see “Accessories”	DEK 6.5 see “Accessories”	DEK 6 see “Accessories”	DEK 6 see “Accessories”
Mounting rails, end brackets, further marking material see “Accessories”					

[1]) without DLS
[2]) with DLS empty
[3]) with DLS 1N4007
[4]) When using QB the rated cross-current reduces to max. 2.5 mm²
[5]) With DKT 4 only on upper terminal level
[6]) As disconnect test terminal rated voltage 250 V

Disconnect test terminals


ASK 1
ASK 1/35



8/58/49	
8/58/44	
9 mm/M 3/3.5 x 0.6	
500 V/19 A/4 mm²	
6 kV/3	
0.5…1.0	
2	
0.5…4	
1.5…4	
0.5…4	
0.5…4	
A 3	
(QB 2…4) 10	
300 V/15 A/12 max. AWG	
300 V/6.3 A/26…12 AWG	
	⊏ + ⊐ Qty.
	0456360000 100
	0105260000 100


Type	Cat. No.	Qty.
AP (1.5)	**0380360000**	20
TW HP (2.0)	**0607000000**	20
QB 2[4])	**0461100000**	100
QB 3[4])	**0461200000**	50
QB 4[4])	**0461300000**	50
multipole interruptable with group marking carrier SchS 2; 2-pole (Cat. No. **1359500000**) 1000 mm (Cat. No. **0337400000**)		
K sleeve	**0553300000**	100
DEK 5 FW	see “Accessories”	

Feed-through terminals with tab connection

	AST 1 AST1/35	AST 3 AST 3/35	AST 4 AST 4/35	AST 5 AST 5/35
	6.3 2.8	6.3 2.8	6.3 2.8	6.3 2.8
				
Dimensions/approvals	DNV	DNV		DNV
Width/length/height (mm) with TS 32	6.5/58/53.5	6.5/40/47.5	6.5/40/47.5	6.5/58/53.5
Width/length/height (mm) with TS 35 x 7.5	6.5/58/46	6.5/44/40	6.5/44/40	6.5/58/46
Insulation stripping length/clamping screw/screwdriver blade			9 mm/M 2.5/3.5 x 0.6	12 mm/M 3/3.5 x 0.6
Rated data				
Rated voltage/-current	500 V[1])/-	500 V[1])/-	500 V[1])/-	500 V[1])/-
Rated cross-section for clamping yokes	-	-	2.5 mm²	4 mm²
Rated cross-section tab 6.3/2.8 mm	2.5/1.0 mm²	2.5/1.0 mm²	2.5/1.0 mm²	2.5/1.0 mm²
Rated Voltage VDE 0110/1.89/pollution severty	6 kV/3	6 kV/3	6 kV/3	6 kV/3
Further technical data				
Tightening torque range Nm			0.4…0.7	0.5…1.0
Torque setting with electric screwdriver type DMS 2			1	2
Clampable conductor				
Solid H07V-U mm²			0.5…4	0.5…6
Stranded H07V-R mm²			1.5…2.5	1.5…4
Flexible H07V-K mm²			0.5…2.5	0.5…4
Flexible H07V-K and ferrule according to DIN 46 228/1 mm²			0.5…2.5	0.5…4
Plug gauge according to 60 947-7-1 Size			A 3	A 4
Continuous current of terminal for conductor size				
Continuous current rating of cross-connection 2…5-pole A	(QL 2…10) 20	(QL 2…10) 20	(QL 2…10) 20	(QL 2…10) 20
Continuous current rating of cross-connection 6…10-pole A				
Rated data according to UL/CSA				
Voltage/current/conductor size UL	300 V/13 A/–	300 V/13 A/–	300 V/13 A/22…12 AWG	300 V/13 A/22…12 AWG
Voltage/current/conductor size CSA	300 V/16 A/–	300 V/16 A/–	300 V/16 A/24…12 AWG	300 V/16 A/24…12 AWG
Ordering data **Version**	⌐ Qty. ⌐ Qty.	⌐ Qty. ⌐ Qty.	⌐ Qty. ⌐ Qty.	⌐ Qty. ⌐ Qty.
Slotted KrG	**0478220000** 50	**0442420000** 100	**0439120000** 100	**0479220000** 50
Slotted blue KrG		**0442470000** 100		
Slotted PA	**0478260000**[2]) 50 **0699660000**[2]) 50	**0460360000**[2]) 100	**0460460000** 100	**0479260000** 50 **0664960000** 50
Unslotted KrG	**0266320000** 50	**0298020000** 100	**0321220000** 100	**0334520000** 50
Unslotted blue KrG			**0321270000** 100	
Unslotted PA	**0266360000**[2]) 50 **0664860000**[2]) 50	**0236760000**[2]) 100 **0479360000**[2]) 10	**0479460000** 100	**0334560000** 50 **0699760000** 50
End plate/partition/small partition (thickness mm)	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
AP TW TSCH 1 KrG	AP (3.0) **0266420000** 20	AP (3.0) **0298120000** 20	AP (3.0) **0298120000** 20	AP (3.0) **0266420000** 20
Blue KrG				
PA	AP (1.5) **0266460000** 20	AP (1.5) **0460560000** 20	AP (1.5) **0460560000** 20	AP (1.5) **0266460000** 20
PA		TW (1.5) **0130160000** 20	TW (1.5) **0130160000** 20	
HP	TW (0.5) **0474700000** 20	TW (1.0) **0297100000** 20	TW (1.0) **0297100000** 20	TW (1.0) **0474700000** 20
HP	TW (2.0) **0607000000** 20			TW (2.0) **0607000000** 20
Only for PA	TSch 1 **0319160000** 100	TSch 1 **0319160000** 100	TSch 1 **0319160000** 100	TSch 1 **0319160000** 100
Cross-connection				
Q4 2-pole	Q 2 **0336700000** 50	Q 2 **0336700000** 50	Q 2 **0336700000** 50	Q 2 **0336700000** 50
3-pole	Q 3 **0336800000** 50	Q 3 **0336800000** 50	Q 3 **0336800000** 50	Q 3 **0336800000** 50
4-pole	Q 4 **0336900000** 50	Q 4 **0336900000** 50	Q 4 **0336900000** 50	Q 4 **0336900000** 50
10-pole	Q 10 **0368800000** 20	Q 10 **0368800000** 20	Q 10 **0368800000** 20	Q 10 **0368800000** 20
25-pole				
Plug adapter				
2-pole		STA 2.5/2 **0165860000** 100	STA 2.5/2 **0165860000** 100	
3-pole		STA 2.5/3 **0165960000** 50	STA 2.5/3 **0165960000** 50	
4-pole		STA 2.5/4 **0190360000** 50	STA 2.5/4 **0190360000** 50	
Clips into PA version 5-pole		STA 2.5/5 **0166060000** 50	STA 2.5/5 **0166060000** 50	
of AST3 and AST4 only 8-pole		STA 2.5/8 **0166160000** 50	STA 2.5/8 **0166160000** 50	
Test plug/socket				
Plug-test socket without using QL for TS 32	StB 14 **0168600000** 50	StB 14 **0168600000** 50	StB 14 **0168600000** 50	StB 14 **0168600000** 50
PS				
StB	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20
Insulation sleeve				
	IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 100
	IH 6.3 **0386260000** 100	IH 6.3 **0386260000** 100	IH 6.3 **0386260000** 100	IH 6.3 **0386260000** 100
Marking tags **Print**				
1 2 3 4 5 6 DEK Standard	DEK 6.5 see "Accessories"	DEK 6 see "Accessories"	DEK 6 see "Accessories"	DEK 6.5 see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"				

[1]) with insulation sleeve
[2]) shock proof with ADP 4 cover profiles ADP4 (see section "Accessories")

Feed-through terminals with tab connection

		SAK 4 S SAK 4 S/35	SAK 4 SS SAK 4 SS/35	SAKR F SAKR F/35
		6.3 2.8	6.3 2.8	2.8
				
Dimensions/approvals				
Width/length/height (mm)	with TS 32 ⊏	6.5/40/51.5	6.5/40/51.5	6.5/42/40.5/54.5 (opened)
Width/length/height (mm)	with TS 35 x 7.5 ⊐	6.5/40/49.5	6.5/40/49.5	6.5/42/40.5/32.5
Insulation stripping length/clamping screw/screwdriver blade		12 mm/M 3/3.5 x 0.6		8 mm/M 3/3.5 x 0.6
Rated data				
Rated voltage/-current		500 V[1])/16 A	500 V[1])/16 A	250 V[1])/10 A
Rated cross-section for clamping yokes		4 mm²	-	4 mm²
Rated cross-section tab	6.3/2.8 mm	2.5/1.0 mm²	2.5/1.0 mm²	-/1.0 mm²
Rated Voltage VDE 0110/1.89/pollution severty		6 kV/3	6 kV/3	6 kV/3
Further technical data				
Tightening torque range	Nm	0.5…1.0		0.5…1.0
Torque setting with electric screwdriver type DMS 2		2		1
Clampable conductor				
Solid H07V-U	mm²	0.33…6		0.5…4
Stranded H07V-R	mm²	1.5…4		1.5…4
Flexible H07V-K	mm²	0.5…4		0.5…4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm²	0.5…4		0.5…2.5
Plug gauge according to 60 947-7-1	Size	A 4		A 3
Continuous current of terminal for conductor size				
Continuous current rating of cross-connection 2 pole	A	(QL 2…10) 36 A at 6 mm²	(QL 2…10) 36 A at 6 mm²	(QB 2…25) 10
Continuous current rating of cross-connection multipole	A			
Rated data according to UL/CSA				
Voltage/current/conductor size	UL	300 V/13 A/26…12 AWG	300 V/13 A/18…14 AWG	300 V/10 A/22…12 AWG
Voltage/current/conductor size	CSA	300 V/13 A/26…12 AWG	300 V/13 A/18…14 AWG	300 V/10 A/26…12 AWG
Ordering data	**Version**	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.	⊏ Qty. ⊐ Qty.
	Slotted KrG	**0401220000** 100	**0479620000** 10	
	Slotted blue KrG			
	Slotted PA	**0401260000** 100 **0630360000** 100	**0479660000** 100 **0630460000** 100	**0663660000** 100 **63828700000** 100
	Unslotted KrG		**0352920000** 10	with 1 StB 6
End plate/partition/small partition (thickness mm)		Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
AP TW TSch 1	KrG	AP (1.5) **0117920000** 20	AP (1.5) **0117920000** 20	
	Blue KrG		AP (1.5) **0117970000** 20	
	PA	AP (1.5) **0117960000** 20	AP (1.5) **0117960000** 20	AP (1.5) **0211360000** 20
	PA	AP (1.5) **0130160000** 20	TW (1.5) **0130160000** 20	
	HP	TW (1.0) **0297100000** 20	TW (1.0) **0297100000** 20	TW (1.0) **0297100000** 20
Cross-connection				
QL QB 4	2-pole	QL 2 **0130600000** 100	QL 2 **0130600000** 100	QB 2* **0482700000** 100
	3-pole	QL 3 **0130700000** 100	QL 3 **0130700000** 100	QB 3* **0482800000** 50
	4-pole	QL 4 **0130800000** 50	QL 4 **0130800000** 50	QB 4* **0482900000** 50
	10-pole	QL 10 **0338200000** 20	QL 10 **0338200000** 20	
	25-pole			QB 25 blank* **0134000000** 20
BS M 3 x 4.5 BS M 3 x 24		BS M 3x4.5 **1593210000** 100	BS M 3x4.5 **1593210000** 100	
				
Test plug/socket				
PS				PS 2.3 **0180400000** 20
				
Insulation sleeve				
		IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 200
		IH 6.3 **0386260000** 100	IH 6.3 **0386260000** 100	
Marking tags	**Print**			
	DEK Standard	DEK 6.5 see "Accessories"	DEK 6.5 see "Accessories"	DEK 6.5 see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"				

[1]) With insulation sleeve

*The conductor cross-section for the screw connection is reduced to 2.5 mm² when QB is used

Feed-through terminals with tab connection

		DK 4 SS/35	DK 4 SS/35 only 2.8	DK 4 S DK 4 S/35	DK 4 S only 2.8 DK 4 S/35 only 2.8
					
Dimensions/approvals					
Width/length/height (mm)	with TS 32 ⊏⎽			6/54/59.5	6/54/59.5
Width/length/height (mm)	with TS 35 x 7.5 ⎽⊐	6/54/60.5	6/54/60.5	6/54/60.5	6/54/60.5
Insulation stripping length/clamping screw/screwdriver blade				9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6
Rated data					
Rated voltage/-current		400 V[1])/2 x 16 A	400 V[1])/2x10	400 V[1])/2 x 10	400 V[1])/2 x 10
Rated cross-section for clamping yokes		-	-	4 mm²	4 mm²
Rated cross-section tab	6.3/2.8 mm	2.5/1.0 mm²	1.0 mm²	1.0 mm²	1.0 mm²
Rated Voltage VDE 0110/1.89/pollution severty		8 kV/3	4 kV/3	6 kV/3	6 kV/3
Further technical data					
Tightening torque range	Nm			0.5…1.0	0.5…1.0
Torque setting with electric screwdriver type DMS 2				2	2
Clampable conductor					
Solid H07V-U	mm²			0.5…4	0.5…4
Stranded H07V-R	mm²			1.5…4	1.5…4
Flexible H07V-K	mm²			0.5…4	0.5…4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm²				
With/without plastic insulation collar				0.5…4	0.5…4
Plug gauge according to 60 947-7-1	Size			A 3	A 3
Continuous current of terminal for conductor size					
Continuous current rating of cross-connection 2 pole	A	(QL 2…10) 20	(QL 2…10) 20	(QL 2…10) 20	(QL 2…10) 20
Continuous current rating of cross-connection multipole	A				
Rated data according to UL/CSA					
Voltage/current/conductor size	UL	300 V/10 A/22…12 AWG	300 V/10 A/22…12 AWG	300 V/10 A/22…12 AWG	300 V/10 A/22…12 AWG
Voltage/current/conductor size	CSA	300 V/10 A/22…12 AWG	300 V/10 A/22…12 AWG	300 V/10 A/22…12 AWG	300 V/10 A/22…12 AWG
Ordering data	Version	⎽⊐ Cat. No. Qty.	⎽⊐ Cat. No. Qty.	⊏⎽ Qty. ⎽⊐ Qty.	⊏⎽ Qty. ⎽⊐ Qty.
	PA	**0217160000** 100	**0297060000** 100	**0631260000** 100 **0686660000** 100	**0631160000** 100 **0686560000** 100
End plate (thickness mm)		Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
 PA		AP (1.5) **0631360000** 20	AP (1.5) **0631360000** 20	AP (1.5) **0631360000** 20	AP (1.5) **0631360000** 20
Partition					
 for TS 32 HP				TW HP (2.0) **0607000000** 20	TW HP (2.0) **0607000000** 20
Small partition					
 TSch 6		TSch 6 **0190260000** 100	TSch 6 **0190260000** 100	TSch 6 **0190260000** 100	TSch 6 **0190260000** 100
Cross-connection					
 Q 3	2-pole	Q 2 **0336400000** 50	Q 2 **0336400000** 50	Q 2 **0336400000** 50	Q 2 **0336400000** 50
	3-pole	Q 3 **0336500000** 50	Q 3 **0336500000** 50	Q 3 **0336500000** 50	Q 3 **0336500000** 50
	4-pole	Q 4 **0336600000** 50	Q 4 **0336600000** 50	Q 4 **0336600000** 50	Q 4 **0336600000** 50
	10-pole	Q 10 **0368600000** 20	Q 10 **0368600000** 20	Q 10 **0368600000** 20	Q 10 **0368600000** 20
Test plug/socket					
 StB	Plug test socket without using QL	StB 8.5 **0215700000** 50	StB 8.5 **0215700000** 50	StB 8.5 **0215700000** 50	StB 8.5 **0215700000** 50
	Plug test socket for use with QL				
 PS		PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20
Insulation sleeve					
		IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 100	PS 2.3 **0180400000** 20
		IH 6.3 **0386260000** 100		IH 6.3 **0386260000** 100	IH 2.8 **0386060000** 100
Marking tags	**Print**				
 DEK	Standard	DEK 6 see "Accessories"	DEK 6 see "Accessories"	DEK 6 see "Accessories"	DEK 6 see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"					

[1]) With insulation sleeve

Feed-through terminals for wrap termination

DIN 41 611, Part 2 and for spring-clip termination DIN 41 611, Part 4

SAK 2.5 T
Pin 1 x 1



SAK 2.5 T
Pin 0.8 x 1.6



SAK 2.5 T
Pin 0.8 x 2.4



Dimensions/approvals								
Width/length/height (mm)	with TS 32 ⊏		6/36.5/47.5/67			6/36.5/47.5/62		
Insulation stripping length/clamping screw/screwdriver blade			12 mm/M 2.5/3.5 x 0.6			12 mm/M 2.5/3.5 x 0.6		
Rated data								
Rated voltage/current/cross-section			250 V/8 A/2.5 mm²			250 V/10 A/2.5 mm²		
Rated impulse voltage VDE 0110/1.89/pollution severity			4 kV/3			4 kV/3		
Further technical data								
Tightening torque range		Nm	0.4…0.7			0.4…0.7		
Torque setting with electric screwdriver type DMS 2			1			1		
Clampable conductor								
Solid H07V-U		mm²	0.5…6			0.5…6		
Stranded H07V-R		mm²	0.5…2.5			0.5…2.5		
Flexible H07V-K		mm²	0.5…4			0.5…4		
Flexible H07V-K and ferrule according to DIN 46 228/1		mm²	0.5…2.5			0.5…2.5		
Plug gauge according to IEC 60 947-1		Size	A 3			A 3		
Continuous current of terminal for conductor size								
Continuous current rating of cross-connection 2-pole		A	(Q 2…10) 24			(Q 2…10) 24		
Continuous current rating of cross-connection multipole		A						
Rated data according to UL/CSA								
Voltage/current/conductor size		UL						
Voltage/current/conductor size		CSA	300 V/10 A/22…12 AWG			300 V/10 A/22…12 AWG		
Ordering data	Pin	Version	⊏	Cat. No.	Qty.	⊏	Cat. No.	Qty.
Horizontal assembly	Right	KrG		**0108520000**	100			
Vertical assembly	Horizontal right	KrG					**0485920000**	100
	Vertical left	KrG					**0478820000**	100
	Vertical right	KrG						
	2x vertical	KrG						
	Right	PA		**0108560000**[1]	100			
End plate (thickness mm)			Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
		KrG	AP (1.5)	**0279520000**	20	AP (1.5)	**0279520000**	20
		PA	AP (1.5)	**0279560000**	20	AP (1.5)	**0279560000**	20
Partition (thickness mm)								
		KrG	TW (2.5)	**0302820000**	20	TW (2.5)	**0302820000**	20
		PA	TW (1.5)	**0302860000**	20	TW (1.5)	**0302860000**	20
		HP	TW (0.5)	**0197100000**	20	TW (0.5)	**0197100000**	20
		HP	TW (2.0)	**0607000000**	20	TW (2.0)	**0607000000**	20
Small partition								
			TSch 1	**0319160000**	100	TSch 1	**0319160000**	100
Cross-connection								
	2-pole		Q 2	**0337000000**	50	Q 2	**0337000000**	50
	3-pole		Q 3	**0337100000**	50	Q 3	**0337100000**	50
	4-pole		Q 4	**0337200000**	50	Q 4	**0337200000**	50
	10-pole		Q 10	**0368700000**	20	Q 10	**0368700000**	20
Test plug/socket								
	Plug-test socket without using QL		StB 8.5 (ø 2.3)	**0280600000**	50	StB 8.5 (ø 2.3)	**0280600000**	50
PS	StB		PS 2.3	**0180400000**	20	PS 2.3	**0180400000**	20
Marking tags		**Print**						
1 2 3 4 5 6	DEK	Standard	DEK 6	see "Accessories"		DEK 6	see "Accessories"	

Mounting rails, end brackets, further marking material see "Accessories"		

[1]) Shock-proof with ADP4 cover profile (see section "Accessories")

** Not for Type 2 x vertical"

SAK-series

Disconnect terminals for wrap connection acc. to DIN 41 611, Part 2 and for spring-clip connection acc. to DIN 41 611, Part 4

DK 4 T
Pin 1 x 1



DK 4 T
Pin 0.8 x 1.6



DK 4 T
Pin 0.8 x 2.4



SAKRT
Pin 1 x 1/0.8 x 2.4 and 0.8 x 1.6




Dimensions											
Width/length/height (mm)	with TS 32 ⊏		6/50/58.5/75.5			6/50/60.5/77.5			6/50/67.5/84.5			6/42/40.5/54.5		
Insulation stripping length/clamping screw/screwdriver blade			9 mm/M 3/3.5 x 0.6			9 mm/M 3/3.5 x 0.6			9 mm/M 3/3.5 x 0.6			8 mm/M 3/3.5 x 0.6		
Rated data														
Rated voltage/current/cross-section			250 V/8 A/4 mm²			250 V/10 A/4 mm²			250 V/10 A/4 mm²			250 V/6/8 A/4 mm²		
Rated impulse voltage VDE 0110/1.89/pollution severity			4 kV/3			4 kV/3			4 kV/3			4 kV/3		
Further technical data														
Tightening torque range		Nm	0.5…1.0			0.5…1.0			0.5…1.0			0.5…1.0		
Torque setting with electric screwdriver type DMS 2			1			1			1			2		
Clampable conductor														
Solid H07V-U		mm²	0.5…4			0.5…4			0.5…4			0.5…4		
Stranded H07V-R		mm²	1.5…4			1.5…4			1.5…4			1.5…4		
Flexible H07V-K		mm²	0.5…4			0.5…4			0.5…4			0.5…4		
Flexible H07V-K and ferrule according to DIN 46 228/1														
With/without plastic insulating collar		mm²	0.5…4			0.5…4			0.5…4			0.5…4		
Plug gauge according to IEC 60 947-1		Size	A3			A3			A3			A3		
Continuous current of terminal block for conductor size														
Continuous current rating of cross-connection 2-pole		A	(Q 2…10) 32			(Q 2…10) 32			(Q 2…10) 32			(QB 2…10) 10		
Continuous current rating of cross-connection multipole		A												
Rated data according to UL/CSA														
Voltage/current/conductor size		UL	–			–			–			–		
Voltage/current/conductor size		CSA	–			–			–			–		
Ordering data	Pin	Type	⊏	Cat. No.	Qty.	⊏	Cat. No.	Qty.	⊏	Cat. No.	Qty.	⊏	Cat. No.	Qty.
	Right	PA		**0536560000**	50									
	Links	PA										1 x 1	**0587460000**	100
	Horizontal right	PA					**0370460000**[1]	50						
Horizontal assembly / Vertical assembly	Vertical right	PA					**0370360000**[1]			**0527760000**[1]	50	0.8 x 2.4	**0545060000**	100
	Vertical right	Blue PA												
	Vertical	PA												
	Vertical left	PA										0.8 x 1.6	**0469360000**	100
DK 4 QT				**1398460000**[1]	50									
bridgeable on both levels	Right	PA												
End plate/partition (thickness mm)			Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
		PA	AP (1.5)	**0359260000**	20	AP (1.5)	**0359260000**	20	AP (1.5)	**0359260000**	20	AP (1.5)	**0211360000**	20
			AP (DK4 QT)	**1397160000**	20									
		Blue PA	AP (1.5)	**0359280000**	20	AP (1.5)	**0359280000**	20						
			TW (2.0)	**0607000000**	20	TW (2.0)	**0607000000**	20	TW (2.0)	**0607000000**	20	TW (2.0)	**0607000000**	20
Small partition														
TSch 4			TSch 4	**0363360000**	100	TSch 4	**0363360000**	100	TSch 4	**0363360000**	100			
Cross-connection/covers														
Q 3 / QB 4	2-pole		Q 2	**0336400000**	50	Q 2	**0336400000**	50	Q 2	**0336400000**	50			
	3-pole		Q 3	**0336500000**	50	Q 3	**0336500000**	50	Q 3	**0336500000**	50			
	4-pole		Q 4	**0336600000**	50	Q 4	**0336600000**	50	Q 4	**0336600000**	50			
	10-pole		Q 10	**0368600000**	20	Q 10	**0368600000**	20	Q 10	**0368600000**	20			
			QB 2*	**0482700000**	100	QB 2*	**0482700000**	100	QB 2*	**0482700000**	100	QB 2*	**0482700000**	100
			QB 3*	**0482800000**	50	QB 3*	**0482800000**	50	QB 3*	**0482800000**	50	QB 3*	**0482800000**	50
			QB 4*	**0482900000**	50	QB 4*	**0482900000**	50	QB 4*	**0482900000**	50	QB 4*	**0482900000**	50
	25-pole											QB 25 blank*	**0134000000**	20
Test plug/socket														
Plug-test socket without using QL			StB 8.5 (ø 23)	**0215700000**	50	StB 8.5 (ø 23)	**0215700000**	50	StB 8.5 (ø 2.3)	**0215700000**	50			
StB														
PS			PS 2.3	**0180400000**	20	PS 2.3	**0180400000**	20	PS 2.3	**0180400000**	20			
1 2 3 4 5 6		FW/FS	dekafix 6	see "Accessories"		dekafix 6	see "Accessories"		dekafix 6	see "Accessories"				
Mounting rails, end brackets, further marking material see "Accessories"														

* The conductor cross-section for the screw connection is reduced to 2.5 mm² when QB is used.
** Only to be used with PA-version

[1]) Shock-proof with ADP4 cover profile (see section "Accessories")

Feed-through terminals and disconnect test terminals

with solder connection

	SAK 2.5/M.LS	SAK 2.5 L SAK 2.5 L/35	SAK 2.5 LL SAK 2.5 LL/35	SAKR L SAKR L/35
	With screen lug			Disconnect terminal
				
Dimensions/approvals				
Width/length/height (mm) with TS 32	6/60/46.5	6/44.5/46.5	6/55/46.5	6.5/50/40.5/54.5 (opened)
Width/length/height (mm) with TS 35 x 7.5		6/44.5/40	6/55/40	6.5/50/38/52
Insulation stripping length/clamping screw/screwdriver blade	12 mm/M 2.5/3.5 x 0.6	12 mm/M 2.5/3.5 x 0.6		8 mm/M 3/3.5 x 0.6
Rated data				
Rated voltage/current/cross-section	250 V/20 A/2.5/1.5 mm²	250 V/20 A/2.5/1.5 mm²	250 V/20 A/1.5 mm²	250 V/10 A/4/1.5 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity	4 kV/3	4 kV/3	4 kV/3	4 kV/3
Further technical data				
Tightening torque range Nm	0.4…0.7	0.4…0.7		0.5…1.0
Torque setting with electric screwdriver type DMS 2	1	1		2/1
Clampable conductor				
Solid H07V-U mm²	0.5…6	0.5…6		0.5…4
Stranded H07V-R mm²	0.5…2.5	0.5…2.5		0.5…4
Flexible H07V-K mm²	0.5…4	0.5…4		0.5…4
Flexible H07V-K and ferrule according to DIN 46 228/1 mm²	0.5…2.5	0.5…2.5		0.5…4
Plug gauge according to 60 947-7-1 Size	A 3	A 3		A 3
Continuous current of terminal block for conductor size				
Continuous current rating of cross-connection 2-pole A	(Q 2…10) 24	(Q 2…10) 24	(Q 2…10) 24	(QB 2…25) 10
Continuous current rating of cross-connection multipole A				
Rated data according to UL/CSA				
Voltage/current/conductor size UL				300 V/10 A/22…12 AWG
Voltage/current/conductor size CSA	300 V/10 A/22…12 AWG	300 V/10 A/22…12 AWG	300 V/10 A/26…12 AWG	300 V/10 A/22…12 AWG
Ordering data Type	Cat. No. Qty.	Qty. Qty.	Qty. Qty.	Qty.
KrG	**0309120000** 100	**0351420000** 100	**0323620000** 100	
Blue KrG		**0351470000** 100	**0323670000** 100	
KrS				
PA		**0351460000**[2] 100 **0495060000**[2] 100	**0323660000**[2] 100 **0567260000**[2] 100	**0412360000** 100
Blue PA				**0412380000** 100
KrG		**0544120000*** 100		
PA		**0544160000***[2] 100		**0412460000*** 100
Blue PA				**0412480000*** 100
End plate/partition (thickness mm)	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
KrG	AP (1.5) **0309220000** 20	AP (1.5) **0309220000** 20	AP (1.5) **0309220000** 20	
Blue KrG	AP (1.5) **0309270000** 20	AP (1.5) **0309270000** 20	AP (1.5) **0309270000** 20	
PA		AP (1.5) **0279560000** 20	AP (1.5) **0279560000** 20	AP (1.5) **0211360000**[1] 20
Blue PA				AP (1.5) **0211380000** 20
PA	TW (1.5) **0302860000** 20	TW (1.5) **0302860000** 20	TW (1.5) **0302860000** 20	
HP	TW (1.0) **0297100000** 20	TW (1.0) **0297100000** 20	TW (1.0) **0297100000** 20	
HP	TW (2.0) **0607000000** 20	TW (2.0) **0607000000** 20	TW (2.0) **0607020000** 20	TW (2.0) **0607000000** 20
Small partition	TSch 1 **0319160000** 100	TSch 1 **0319160000** 100	TSch 1 **0319160000** 100	
Cross-connection				
2-pole	Q 2 **0337000000** 50	Q 2 **0337000000** 50	Q 2 **0337000000** 50	QB 2** **0482700000** 100
3-pole	Q 3 **0337100000** 50	Q 3 **0337100000** 50	Q 3 **0337100000** 50	QB 3** **0482800000** 50
4-pole	Q 4 **0337200000** 50	Q 4 **0337200000** 50	Q 4 **0337200000** 50	QB 4** **0482900000** 50
10-pole	Q 10 **0368700000** 20	Q 10 **0368700000** 20	Q 10 **0368700000** 20	
25-pole				QB 25 blank** **0134000000** 20
Test plug/socket				
Plug-test socket without using QL		StB 8.5 (ø23) **0280600000** 50	StB 8.5 (ø23) **0280600000** 50	
StB Plug-test-socket for use with QL		StB 29.5 (ø4) **0133400000** 50	StB 29.5 (ø4) **0133400000** 50	
		PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20
PS		PS 4 **0299600000** 20	PS 4 **0299600000** 20	
Cover				
	AD 4 **0303400000** 50	AD 4 **0303400000** 50	AD 4 **0303400000** 50	
	BSK M3 x 22 **0128900000** 100	BSK M3 x 22 **0128900000** 100	BSK M3 x 22 **0128900000** 100	
Marking tags **Print**				
DEK Standard	DEK 6 see "Accessories"	DEK 6 see "Accessories"	DEK 6 see "Accessories"	DEK 6.5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

* Soldering lug on left-hand side


** The conductor cross-section for the screw connection is reduced to 2.5 mm² when QB is used.

[1] For TS 32 and TS 35

[2] Contact-proof cross-connection with ADP 4 cover profile (see "Accessories")

SAK-series

Disconnect test terminals with solder connections

		SAKR L With 2 StB 6	SAKR LL	SAKR LL With 2 StB 6
				
Dimensions/approvals				
Width/length/height (mm)	with TS 32 ⊏⊐	6.5/50/40.5/54.5 (opened)	6.5/58/40.5/54.5 (opened)	6.5/58/40.5/54.5 (opened)
Width/length/height (mm)	with TS 35 x 7.5 ⊐⊏			
Insulation stripping length/clamping screw/screwdriver blade		8 mm/M 3/3.5 x 0.6		–/–/3.5 x 0.6
Rated data				
Rated voltage/current/cross-section		250 V/10 A/4/1.5 mm²	250 V/10 A/1.5 mm²	250 V/10 A/1.5 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity		4 kV/3	4 kV/3	4 kV/3
Further technical data				
Tightening torque range	Nm	0.5…1.0		
Torque setting with electric screwdriver type DMS 2		1		
Clampable conductor				
Solid H07V-U	mm²	0.5…4		
Stranded H07V-R	mm²	1.5…4		
Flexible H07V-K	mm²	0.5…4		
Flexible H07V-K and ferrule according to DIN 46228/1				
With/without plastic insulating collar	mm²	0.5…4		
Plug gauge according to 60 947-7-1	Size	A 3		
Continuous current of terminal block for conductor size				
Continuous current rating of cross-connection 2 pole	A	(QB 2…25) 10		
Continuous current rating of cross-connection multipole	A			
Rated data according to UL/CSA				
Voltage/current/conductor size	UL			
Voltage/current/conductor size	CSA		300 V/10 A/22…12 AWG	


Ordering data	Type	⊏⊐ Qty.	⊐⊏ Qty.	⊏⊐ Qty.	⊏⊐ Qty.	⊐⊏ Qty.
	KrG					
	Blue KrG					
	KrS					
	PA	**0518160000*** 100	**0183560000** 100	**0464460000** 100		**0294260000** 100
	Blue PA					
	KrG					
	KrS					
	PA	**0572660000** 100				
	Blue PA					

End plate/partition (thickness mm)	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
AP TW									
 									
KrG				AP (1.5)	**0211320000**	20	AP (1.5)	**0211320000**	20
Blue KrG									
PA	AP (1.5)	**0211360000**	20	AP (1.5)	**0211360000**	20	AP (1.5)	**0211360000**	20
Blue PA	AP (1.5)	**0211380000**	20	AP (1.5)	**0211380000**	20	AP (1.5)	**0211380000**	20
PA									
HP	TW (0.5)	**0474700000**	20	TW (0.5)	**0474700000**	20	TW (0.5)	**0474700000**	20
HP	TW (2.0)	**0607000000**	20	TW (2.0)	**0607000000**	20	TW (2.0)	**0607000000**	20

Small partition									
									

Cross-connection									
 QB 3 	QB 4	QB 2**	**0482700000**	100					
	2-pole	QB 3**	**0482800000**	50					
	3-pole	QB 4**	**0482900000**	50					
	4-pole								
	10-pole	QB 25 blank**	**0134000000**	20					
	25-pole								

Test plug/socket									
 PS		PS 2.3	**0180400000**	20			PS 2.3	**0180400000**	20

Marking tags		**Print**							
	DEK	Standard	DEK 6.5	see "Accessories"		DEK 6.5	see "Accessories"		DEK 6.5	see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"






* Soldering lug on left-hand side
** The conductor cross-section for the screw connection is reduced to 2.5 mm² when QB is used.

Disconnect test terminals with solder connections

	TAL	TAL	SAKK 4	SAKK 10
	2 solder connections	4 solder connections	Ceramic feed-through terminals for use in high temperature ranges up to max. 210°C	
				
Dimensions/approvals				
Width/length/height (mm) with TS 32 ⊏	4/48/36/50 (opened)	4/54/36/50 (opened)	8/40/53	11.5/40/53
Width/length/height (mm) with TS 35 x 7.5 ⊐				
Insulation stripping length/clamping screw/screwdriver blade			12 mm/M3/3.5 x 0.6	12 mm/M 4/5.5 x 1.0
Rated data			**IEC 60 947-7-1**	**IEC 60 947-7-1**
Rated voltage/current/cross-section	63 V/10 A/1.5 mm²	63 V/10 A/1.5 mm²	800 V/32 A/4 mm²	800 V/57 A/10 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity	1.5 kV/3	1.5 kV/3		
Further technical data				
Tightening torque range Nm			0.5…1	1.2…2
Torque setting with electric screwdriver type DMS 2				
Clampable conductor				
Solid H07V-U mm²			0.5...6 mm²	2.5...16 mm²
Stranded H07V-R mm²			0.5...4 mm²	2.5...10 mm²
Flexible H07V-K mm²				
Flexible H07V-K and ferrule according to DIN 46 228/1 mm²				
Plug gauge according to 60 947-7-1 Size			A 4	B 6
Continuous current of terminal block for conductor size			35 A/6 mm²	63 A/16 mm²
Continuous current rating of cross-connection 2 pole A			36	47
Continuous current rating of cross-connection multipole A			36	36
Rated data according to UL/CSA				
Voltage/current/conductor size UL				
Voltage/current/conductor size CSA				
Ordering data Type	⊏ Cat. No. Qty.	⊏ Cat. No. Qty.	⊏ Cat. No. Qty.	⊏ Cat. No. Qty.
KrG				
Blue KrG				
KrS				
PA	**0212060000** 100	**0304960000** 100		
Blue PA				
KrG				
KrS				
PA				
Blue PA				
Ceramic			SAKK 4 **1598080000** 50	SAKK 10 **1598090000** 50
End plate/partition (thickness mm)	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
AP TW KrG			AP/SAKK4/10 **9502630000** 10	AP/SAKK4/10 **9502630000** 10
Blue KrG				
PA	AP (1.5) **0212260000** 20	AP (1.5) **0212260000** 20		
Blue PA				
PA				
Small partition				
Cross-connection			Type Cat. No. Qty.	Type Cat. No. Qty.
Q 3 QB 4 2-pole			QL 2 **9509420000** 100	QL 2 **9509470000** 100
3-pole			QL 3 **9509430000** 100	QL 3 **9509480000** 50
4-pole			QL 4 **9509440000** 50	QL 4 **9509490000** 50
10-pole			QL 10 **9509450000** 20	QL 10 **9509500000** 20
25-pole			VH 13.5 **0248500000** 100	VH 12.5 **9509510000** 50
			BS (M3 X 20) **0303000000** 100	BS (M3 X 20) **0303000000** 100
Additional accessories				
			SST **0152700000**	SST **0152700000**
			MEW 1/32 **0445600000**	MEW 1/32 **0445600000**
			EK 2 **0323100000**	EK 2 **0323100000**
Marking tags	**Print**			
1 2 3 4 5 6 DEK	Standard On demand	On demand		

Mounting rails, end brackets, further marking material see “Accessories”


Feed-through terminals for initiators and actuators

	DLI 2.5	DLI 2.5 LD PNP	DLI 2.5 LD NPN	DLD 2.5
				
Dimensions/approvals				
Width/length/height (mm) with TS 35 x 7.5	6/65/49	6/65/49	6/65/49	6/82/49
Insulation stripping length/clamping screw/screwdriver blade	7 mm/M 2.5/3.5 x 0.6	7 mm/M 2.5/3.5 x 0.6	7 mm/M 2.5/3.5 x 0.6	7 mm/M 2.5/3.5 x 0.6
Rated data according to IEC 60 947-7-1				
Rated voltage/current/cross-section	250 V/20 A/2.5 mm²	5–30 V-/20 A/2.5 mm²	5–30 V-/20 A/2.5 mm²	250 V/24 A/2.5 mm²
Rated impulse voltage/pollution severity	4 kV/3	0.8 kV/3	0.8 kV/3	4 kV/3
Further technical data				
Tightening torque range Nm	0.4…0.6	0.4…0.6	0.4…0.6	0.4…0.6
Torque setting with electric screwdriver type DMS 2	1	1	1	1
Clampable conductor				
Solid H07V-U mm²	0.5…4	0.5…4	0.5…4	0.5…4
Stranded H07V-R mm²	0.5…2.5	0.5…2.5	0.5…2.5	0.5…2.5
Flexible H07V-K mm²	0.5…4	0.5…4	0.5…4	0.5…4
Flexible H07V-K and ferrule according to DIN 46228/1 mm²	0.5…2.5	0.5…2.5	0.5…2.5	0.5…2.5
Plug gauge according to 60 947-7-1 Size	A 3	A 3	A 3	A 3
Continuous current of terminal for conductor size	20 A/2.5 mm²	20 A/2.5 mm²	20 A/2.5 mm²	
Continuous current rating of cross-connection 2…5-pole A	(Q 2…10) 20	(Q 2…10) 20	(Q 2…10) 20	(Q 2…10) 20
Continuous current rating of cross-connection 6…10-pole A				
Rated data according to UL/CSA				
Voltage/current/conductor size UL	300 V/10 A/26…12 AWG	300 V/10 A/26…12 AWG	300 V/10 A/26…12 AWG	300 V/10 A/26…12 AWG
Voltage/current/conductor size CSA	300 V/10 A/26…12 AWG			300 V/10 A/26…12 AWG
Ordering data	Cat. No. Qty.	Cat. No. Qty.	Best.-Nr . Qty.	Cat. No. Qty.
Standard	**1313360000** 100			**1317060000** 50
with diode 1N4007				
with LED red (5…30 V)		**1578510000** 100	**1578550000** 100	
with LED green (5…30 V)		**1578520000** 100	**1578560000** 100	
with LED and diode 1N4007				
with LED and diode 1N4007				
Block of 10[1]	(w/o) **1411360000** 10	(LED red) **1578530000** 10		
Block of 10[1]	(with dekafix) **1579070000** 10	(LED green) **1578540000** 10		
Fuse inserts				
End plate/Small partition	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
AP-DLI AP-DLD Part-AP TSch 1	AP **1313260000** 20	AP **1313260000** 20	AP **1313260000** 20	AP **1317660000** 20
 (thickness 1.5 mm)				AP (Part-AP) **1381860000** 20
	TSch 1 **0319160000** 100	TSch 1 **0319160000** 100	TSch 1 **0319160000** 100	TSch 1 **0319160000** 100
Test plug/plug socket				
 StB 8.5  PS	StB 8.5*(ø23) **0215700000** 50			StB 8.5*(ø23) **0215700000** 50
	PS 2.3 **0180400000** 20			PS 2.3 **0180400000** 20
Cross-connection				
Q 3   	Q 2 **1312500000** 50	Q 2 **1312500000** 50	Q 2 **1312500000** 50	Q 2 **1312500000** 50
	Q 3 **1312600000** 50	Q 3 **1312600000** 50	Q 3 **1312600000** 50	Q 3 **1312600000** 50
	Q 4 **1312700000** 50	Q 4 **1312700000** 50	Q 4 **1312700000** 50	Q 4 **1312700000** 50
	Q 10 **1313100000** 20	Q 10 **1313100000** 20	Q 10 **1313100000** 20	Q 10 **1313100000** 20
	Q 20 **1399800000** 20	Q 20 **1399800000** 20	Q 20 **1399800000** 20	Q 20 **1399800000** 20
	QL 2 **0297200000** 100	QL 2 **0297200000** 100	QL 2 **0297200000** 100	QL 2 **0297200000** 100
	VH 4.2 **1345800000** 100	VH 4.2 **1345800000** 100	VH 4.2 **1345800000** 100	VH 4.2 **1345800000** 100
	VQB1.5/50 BL **1633280000** 5	VQB1.5/50 BL **1633280000** 5	VQB1.5/50 BL **1633280000** 5	VQB1.5/50 BL **1633280000** 5
	VQB1.5/50 RT **1633290000** 5	VQB1.5/50 RT **1633290000** 5	VQB1.5/50 RT **1633290000** 5	VQB1.5/50 RT **1633290000** 5
	VQB1.5/50 SW **1635120000** 5	VQB1.5/50 SW **1635120000** 5	VQB1.5/50 SW **1635120000** 5	VQB1.5/50 SW **1635120000** 5
VQB  Snap fit, external cross-connection VQB 1.5.				
For cross-connections for more than 20 terminals, replace VH with VH 4.2 (134580) without internal thread				
Group marking				
WT 4 	WT 4 **1341060000** 100	WT 4 **1341060000** 100	WT 4 **1341060000** 100	WT 4 **1341060000** 100
	SF 10 **0332400000** 1000	SF 10 **0332400000** 1000	SF 10 **0332400000** 1000	SF 10 **0332400000** 1000
	SG 10 **0332500000** 1000	SG 10 **0332500000** 1000	SG 10 **0332500000** 1000	SG 10 **0332500000** 1000
Cover				
HP 4 	ADP **0485400000** 20	ADP **0485400000** 20	ADP **0485400000** 20	ADP **0485400000** 20
	HP 4 **0485860000** 20	HP 4 **0485860000** 20	HP 4 **0485860000** 20	HP 4 **0485860000** 20
Marking tags Print				
 DEK Standard	DEK 6 see “Accessories”	DEK 6 see “Accessories”	DEK 6 see “Accessories”	DEK 6 see “Accessories”
Mounting rails, end brackets, further marking material see “Accessories”				

[1]) DLI 2.5/35/10 = Block of 10 with built-in cross-connections * only in upper busbar

Feed-through terminals for initiators and actuators

DLA 2.5




	6/65/49
	7 mm/M 2.5/3.5 x 0.6
	250 V**/17.5 A/2.5 mm²
	4 kV/3
	0.4…0.6
	1
	0.5…4
	0.5…2.5
	0.5…4
	0.5…2.5
	A 3
	20 A/2.5 mm²
	(Q 2…20) 20
	300 V/10 A/26…12 AWG
	300 V/10 A/26…12 AWG

	Cat. No.	Qty.
	1565970000	100
(w. dekafix)	**1578380000**	10
(w/o dekafix)	**1578390000**	10

Type	Cat. No.	Qty.
AP	**1313260000**	20
TSch 1	**0319160000**	100
StB 8.5*(ø23)	**0215700000**	50
PS 2.3	**0180400000**	20
Q 2	**1312500000**	50
Q 3	**1312600000**	50
Q 4	**1312700000**	50
Q 10	**1313100000**	20
Q 20	**1399800000**	20
QL 2	**0297200000**	100
VH 4.2	**1345800000**	100
VQB 1.5/50 BL	**1633280000**	5
VQB 1.5/50 RT	**1633290000**	5
VQB 1.5/50 SW	**1635120000**	5
WT 4	**1341060000**	100
SF 10	**0332400000**	1000
SG 10	**0332500000**	1000
ADP	**0485400000**	20
HP 4	**0485860000**	20
DEK 6	see “Accessories”	

DLA 2.5/D




	6/65/49
	7 mm/M 2.5/3.5 x 0.6
	250 V**/17.5 A/2.5 mm²
	4 kV/3
	0.4…0.6
	1
	0.5…4
	0.5…2.5
	0.5…4
	0.5…2.5
	A 3
	20 A/2.5 mm²
	(Q 2…20) 20
	300 V/10 A/26…12 AWG
	300 V/10 A/26…12 AWG

	Cat. No.	Qty.
	1578400000	100

Type	Cat. No.	Qty.
AP	**1313260000**	20
TSch 1	**0319160000**	100
Q 2	**1312500000**	50
Q 3	**1312600000**	50
Q 4	**1312700000**	50
Q 10	**1313100000**	20
Q 20	**1399800000**	20
QL 2	**0297200000**	100
VH 4.2	**1345800000**	100
VQB 1.5/50 BL	**1633280000**	5
VQB 1.5/50 RT	**1633290000**	5
VQB 1.5/50 SW	**1635120000**	5
WT 4	**1341060000**	100
SF 10	**0332400000**	1000
SG 10	**0332500000**	1000
ADP	**0485400000**	20
HP 4	**0485860000**	20
DEK 6	see “Accessories”	

DLA 2.5/LD




	6/65/49
	7 mm/M 2.5/3.5 x 0.6
	5–30 V/17.5 A/2.5 mm²
	0.8 kV/3
	0.4…0.6
	1
	0.5…4
	0.5…2.5
	0.5…4
	0.5…2.5
	A 3
	20 A/2.5 mm²
	(Q 2…20) 20
	300 V/10 A/26…12 AWG
	5–30 V/10 A/26…12 AWG

	Cat. No.	Qty.
	1578430000	100
	1578440000	100

Type	Cat. No.	Qty.
AP	**1313260000**	20
TSch 1	**0319160000**	100
Q 2	**1312500000**	50
Q 3	**1312600000**	50
Q 4	**1312700000**	50
Q 10	**1313100000**	20
Q 20	**1399800000**	20
QL 2	**0297200000**	100
VH 4.2	**1345800000**	100
VQB 1.5/50 BL	**1633280000**	5
VQB 1.5/50 RT	**1633290000**	5
VQB 1.5/50 SW	**1635120000**	5
WT 4	**1341060000**	100
SF 10	**0332400000**	1000
SG 10	**0332500000**	1000
ADP	**0485400000**	20
HP 4	**0485860000**	20
DEK 6	see “Accessories”	

DLA 2.5/LD/D




	6/65/49
	7 mm/M 2.5/3.5 x 0.6
	5–30 V/17.5 A/2.5 mm²
	0.8 kV/3
	0.4…0.6
	1
	0.5…4
	0.5…2.5
	0.5…4
	0.5…2.5
	A 3
	20 A/2.5 mm²
	(Q 2…20) 20
	300 V/10 A/26…12 AWG
	5–30 V/10 A/26…12 AWG

	Cat. No.	Qty.
(LED red)	**1578470000**	100
(LED green)	**1578480000**	100
(LED red)	**1578490000**	10
(LED green)	**1578500000**	10

Type	Cat. No.	Qty.
AP	**1313260000**	20
TSch 1	**0319160000**	100
Q 2	**1312500000**	50
Q 3	**1312600000**	50
Q 4	**1312700000**	50
Q 10	**1313100000**	20
Q 20	**1399800000**	20
QL 2	**0297200000**	100
VH 4.2	**1345800000**	100
VQB 1.5/50 BL	**1633280000**	5
VQB 1.5/50 RT	**1633290000**	5
VQB 1.5/50 SW	**1635120000**	5
WT 4	**1341060000**	100
SF 10	**0332400000**	1000
SG 10	**0332500000**	1000
ADP	**0485400000**	20
HP 4	**0485860000**	20
DEK 6	see “Accessories”	

DLD 2.5/PE




	6/74.5/49
	7 mm/M 2.5/3.5 x 0.6
	250 V**/17.5 A/2.5 mm²
	4 kV/3
	0.4…0.6
	1
	0.5…4
	0.5…2.5
	0.5…4
	0.5…2.5
	A 3
	20 A/2.5 mm²
	(Q 2…20) 20
	300 V/10 A/26…12 AWG
	300 V/10 A/26…12 AWG

	Cat. No.	Qty.
	1595950000	100

Type	Cat. No.	Qty.
AP	**1595960000**	20
AP (Part-AP)	**1595970000**	
TSch 1	**0319160000**	100
StB 8.5*(ø23)	**0215700000**	50
PS 2.3	**0180400000**	20
Q 2	**1312500000**	50
Q 3	**1312600000**	50
Q 4	**1312700000**	50
Q 10	**1313100000**	20
Q 20	**1399800000**	20
QL 2	**0297200000**	100
VH 4.2	**1345800000**	100
VQB 1.5/50 BL	**1633280000**	5
VQB 1.5/50 RT	**1633290000**	5
VQB 1.5/50 SW	**1635120000**	5
WT 4	**1341060000**	100
SF 10	**0332400000**	1000
SG 10	**0332500000**	1000
ADP	**0485400000**	20
HP 4	**0485860000**	20
DEK 6	see “Accessories”	

KDKS1/PE



	8/91/65
	8 mm/M 3[2]/M 2.5[3]/3.5 x 0.6
	500 V/6.3 A/4 mm²
	6 kV/3
	0.5…1[2]/0.4…0.7[3]
	2/1***
	0.5…4
	0.5…4
	0.5…4
	A 4 [2]/ A 3[3]
	-/-/22...12 AWG

	Cat. No.	Qty.
	9528110000	50
not combine with DLI / DLA		
Wemid	**9532450000**	50




5 x 20 without core indicator

Type	Cat. No.	Qty.
AP	**9503330000**	50
AP Wemid	**9532470000**	50
QB 2	**0461100000**	50
QB 3	**0461200000**	50
QB 4	**0461300000**	50

** If the cross-connection runs via the PE connection of the DLA, or if a pole is generally skipped, the rated voltage is reduced to 30 V~

[2] A4 clamping position = max 4 mm² ... [3] A3 clamping position = max 2.5 mm² ... ferrule with/without plastic insulating collar

Feed-through terminals for initiators and motors

		VLI 1.5	VLI 1.5PE	MAK 2.5
				
Dimensions/approvals				
Width/length/height (mm)	with TS 35 x 7.5 ⊓	6/79/64	6/69/63	6/88/64
Insulation stripping length/clamping screw/screwdriver blade		8 mm/M 2.5/3.5 x 0.6	8 mm/M 2.5/3.5 x 0.6	8 mm/M 2.5/3.5 x 0.6
Rated data according to IEC 60 947-7-1				
Rated voltage/current/cross-section		250 V/17.5 A/1.5 mm²	250 V/17.5 A/1.5 mm²	500 V (L-L)/250 V (L-PE) 24 A/2.5 mm²
Rated impulse voltage/pollution severity		4 kV/3	4 kV/3	6 kV/3
Further technical data				
Tightening torque range	Nm	0.4…0.6**	0.4…0.6	0.4…0.6
Torque setting with electric screwdriver type DMS 2		1	1	1
Clampable conductor				
Solid H07V-U	mm²	0.5…4.0	0.5…4.0	0.5…4.0
Stranded H07V-R	mm²	0.5…2.5	0.5…2.5	0.5…2.5
Flexible H07V-K	mm²	0.5…4	0.5…4	1.5…4
Flexible H07V-K and ferrule DIN 46 228/1	mm²	0.5…2.5	0.5…2.5	0.5…2.5
Flexible H07V-K and ferrule with plastic insul. collar	mm²	0.5…2.5	0.5…2.5	0.5…2.5
Plug gauge according to 60 947-7-1	Size	A3	A3	A3
Continuous current of terminal for conductor size		24 A/2.5 mm²	24 A/2.5 mm²	24 A/4 mm²
Continuous current rating of cross-connection, multipole	A	24	24	24
Rated data according to UL/CSA				
Voltage/current/conductor size	UL	300 V/10 A/26…12 AWG	300 V/10 A/26…12 AWG	300 V/10 A/26…12 AWG
Voltage/current/conductor size	CSA	300 V/10 A/26…12 AWG	300 V/10 A/26…12 AWG	300 V/10 A/26…12 AWG
Ordering data	Version	⊓ Cat. No. Qty.	⊓ Cat. No. Qty.	⊓ Cat. No. Qty.
	PA	**1633250000** 50	**1633310000** 50	**1615270000** 50
				⊐ **1631650000** 50
End plate/partition		Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
End plate		AP VLI1.5 **1633260000** 20	AP VLI1.5/PE **1633320000** 20	AP MAK2.5 **1615280000** 20
Partial end plate for VLI1.5 – MAK2.5 combination		TEAP 2 MAK2.5 **1633330000** 20		TEAP 2 MAK2.5 **1633330000** 20
Partial end plate for VLI1.5 – VLI1.5PE combination		TEAP VLI1.5 **1633270000** 20	TEAP VLI1.5 **1633270000** 20	
Partial end plate for VLI1.5PE – MAK2.5 combination			TEAP 1 MAK2.5 **1633340000** 20	TEAP 1 MAK2.5 **1633340000** 20
Cross-connection				
VQB 50-pole, snap-fit, external cross-connection		VQB1.5/50BL* **1633280000** 5 VQB1.5/50RT* **1633290000** 5 VQB1.5/50SW* **1635120000** 5	VQB1.5/50BL* **1633280000** 5 VQB1.5/50RT* **1633290000** 5 VQB1.5/50SW* **1635120000** 5	VQB1.5/50BL* **1633280000** 5 VQB1.5/50RT* **1633290000** 5 VQB1.5/50SW* **1635120000** 5
 QB 25-pole external cross-connection				QB 25 SW* **0520000000** 20 QB 25 RT* **0520060000** 20 QB 25 BL* **0520080000** 20
Group marking				
		T 5 **0348500000** 100	T 5 **0348500000** 100	T 5 **0348500000** 100
Tag carrier		SF 10 **0332400000** 1000	SF 10 **0332400000** 1000	SF 10 **0332400000** 1000
for S 10 tags		SG 10 **0332500000** 1000	SG 10 **0332500000** 1000	SG 10 **0332500000** 1000
Marking tags	**Print**			
	DEK Standard	DEK 5 see “Accessories”	DEK 5 see “Accessories”	DEK 5 see “Accessories”
Mounting rails, end brackets, further marking material see “Accessories”				

* When using cross-connection bridges, the connected cross-section is reduced by one level
** 0.4…0.45 for lower connection level

Disconnect test terminal against induced high voltage

Measures to minimize risks of electric voltage peaks in control systems of power plants and transforming stations:

- Insulation between installation and control cable by pulling disconnect plugs.
- Grounding of control cable is possible on an appropriate location of the workplace.
- Easy connection of electric isolation of counting, control and communication circuits.


Electricity Supply Industry Standard ESI 12-4 1973

The Electricity Supply Industry Standard ESI 12-4 1973 defines a detailed specification of control and protection equipment. The main functions of thiese installations are as follows:

- Insulation of the control cables located in front of ground or installation lines with increased potential, which is required to prevent unintentional contact of service staff with live parts.
- Separation of control cables from local control circuits.
- Application also includes test connections for auxiliary control circuits and / or local control circuits.
- Grounding of control cables and / or auxiliary control circuits.
- Bundled disconnection of all auxiliary control circuits from potential earth.
- A test voltage can be applied using the screening connection of the control cable, which is normally routed on the enclosure, with the help of an appropriate separation. This permits to check whether the screening line is correctly functioning. For this test, an insulated feed-through plate is required.

ESI 12-4:

"Terminating Equipment for Pilot Cables subject to Induced Transient Voltages exceeding 650 V rms".

		PPT/35	SAKH 6
			
Dimensions/approvals			
Width/length/height (mm)	with TS 35 x 7.5 ⊔	15/138/79	
Insulation stripping length/clamping screw/screwdriver blade		12 mm	12 mm
Rated data according to IEC 60 947-7-1			
Rated voltage/current		15 kV ac (ESI 12-4)**/30 A	1 kV ac / 1.5 kV dc / 47 A
Rated impulse voltage/pollution severity			>15 kV (from terminal to terminal)
Clampable conductor			
Solid H07V-U	mm²	0.5...10	0.5... 6
Stranded H07V-R	mm²	0.5...10*	0.5... 6
Ordering data	Version	⊔ Cat. No. Qty.	⊔ Cat. No. Qty.
	EP	PPT/35 **3835020000** 10	SAKH 6 **0126600000** 50
		incl. disconnect plug and displacement tool (if min. 10 items are ordered)	
End plate			
	EP	AP/PPT (3) **3835120000** 10	AP **0131700000** 20
Disconnect plug			
		TST/PPT **3835360000** 10	
Displacement tool			
	PA	PH/PPT **3835260000** 10	
		The disconnect plug may only be removed with the displacement tool.	
Test plug/socket			
		PS (4) **0299600000** 20	
		StB 17 **0147100000** 50	
Insulated mounting rail			
	PVC 35 x 1.5 mm	TSK 35 **0514300000** 1	
Marking tags	**Print**		
	DEK Standard	DEK 5 see “Accessories”	DEK 5 see “Accessories”

Mounting rails, end brackets, further marking material see “Accessories”

* Also two push-on tabs are possible
** mounted on an insulated mounting rail

Rail mounting TS 15

Feed-through terminals
Protective conductor terminals
Fuse terminals
Disconnect test terminals

AKZ 1.5
AKZ 1.5/10



AKZ 2.5



AKZ 4
AKZ 4/10
AKZ 4 Wemid



AKZ 4 for test adapter
AKZ 4/10 for test adapter



		AKZ 1.5 / AKZ 1.5/10	AKZ 2.5	AKZ 4 / AKZ 4/10 / AKZ 4 Wemid	AKZ 4 for test adapter / AKZ 4/10 for test adapter
Max. technical data		21.5 A / 2.5 mm²	26 A / 4 mm²	38.5 A / 6 mm²	38.5 A / 6 mm²
Dimensions/approvals					
Width/length/height (mm)	with TS 15 ⊔	5/25/25	5/25.5/28	6/27/30	60/27/30
Insulation stripping length/clamping screw/screwdriver blade		7 mm/M 2.5/3.0 x 0.5	7 mm/M 2.5/3.0 x 0.5	8 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6
Rated data VDE 0611 Part 1/8.92/IEC 60 947-7-1					
Rated voltage/current/cross-section		250 V/17.5 A/1.5 mm²	250 V/24 A/2.5 mm²	400 V/32 A/4 mm²	500 V/32 A/4 mm²
Rated impulse voltage / pollution severity		4 kV/3	4 kV/3	6 kV/3	6 kV/3
Further technical data					
Tightening torque range	Nm	0.4…0.6	0.4…0.6	0.5…1.0	0.5…1.0
Torque setting with electric screwdriver type DMS 2		1	1	2	2
Clampable conductor					
Solid H07V-U	mm²	0.5…2.5	0.5…4	0.5…6	0.5…6
Stranded H07V-R	mm²	1.5	1.5…2.5	1.5…4	1.5…4
Flexible H07V-K	mm²	0.5…1.5	0.5…4	0.5…4	0.5…4
Flexible H07V-K and ferrule DIN 46 228/1	mm²	0.5…1.5	0.5…2.5	0.5…4	0.5…4
Flexible H07V-K and ferrule with plastic insul. collar	mm²	0.5…1.5	0.5…2.5	0.5…4	0.5…4
Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1	Size	0.2…2.5 / A 1	0.13…4.0 / A 3	0.2…6.0 / A 3	0.2…6.0 / A 3
Continuous current rating of cross-connection 2-pole	A	24	24	32	32
Continuous current rating of cross-connection multipole	A	24	24	32	32
Rated data according to UL/CSA					
Voltage/current/conductor size	UL	150 V/15 A/22…14 AWG	300 V/10 A/26…12 AWG	300 V/27A/22…12 AWG	300V/27 A/22…12 AWG
Voltage/current/conductor size	CSA	300 V/10 A/24…16 AWG	300 V/10 A/26…12 AWG	300 V/10 A/24…12 AWG	300 V/10 A/24…12 AWG

Ordering data	Type	⊔ TS 15	Cat. No.	Qty.	⊔ TS 15	Cat. No.	Qty.	⊔ TS 15	Cat. No.	Qty.	⊔ TS 15	Cat. No.	Qty.
	KrG								**0294320000**	100			
	PA		**0340460000**	100	(with pin)	**0697160000**	100		**0294360000**	100	for test adapter	**1538260000**	100
	Blue PA		**0340480000**	100	(with pin)	**0697180000**	100		**0294380000**	100			
	PA	(10pol./no mk.)	**0358060000**	10	(without pin)	**0175960000**	100	(10pol./no mk.)	**0359560000**	10	w.mk./f.test ad.	**1489360000**	10
	PA	(10pol./w.mk.)	**0358160000**	10	AKZ 2.5 w. AP	**0385860000**	50	(10pol./w.mk.)	**0359660000**	10			
								AKZ 4 Wemid	**9537110000**	100	ATA 1,10-pole	**1633240000**	5

End plate (thickness mm)	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
KrG							AP (1.5)	**0294420000**	20			
Wemid							AP (1.5)	**9537910000**	20			
PA	AP (1.5)	**0340560000**	50	AP (2.5)	**0697360000**	50	AP (1.5)	**0294460000**	20	AP (1.5)	**0294460000**	20
Blue PA				AP (2.5)	**0697380000**	50	AP (1.5)	**0294480000**	20			
Partition (thickness mm)												
KrG							TW (2.0)	**0118900000**	20			
PA				TW (1.5)	**0318560000**	20	TW (0.5)	**0348260000**	50	TW (0.5)	**0348260000**	50
Blue PA				TW (1.5)	**0318580000**	20						
Small partition												
PA							TSch 4	**0363360000**	100	TSch 4	**0363360000**	100
Cross-connection												
	Q 2	**0368200000**	50	Q 2	**0368200000**	50	Q 2	**0336400000**	50	Q 2	**0336400000**	50
	Q 3	**0368300000**	50	Q 3	**0368300000**	50	Q 3	**0336500000**	50	Q 3	**0336500000**	50
	Q 4	**0368400000**	50	Q 4	**0368400000**	50	Q 4	**0336600000**	50	Q 4	**0336600000**	50
	Q 5	**0660300000**	20	Q 5	**0660300000**	20						
	Q 10	**0368500000**	20	Q 10	**0368500000**	20	Q 10	**0368600000**	20	Q 10	**0368600000**	20
Switchable cross-connection link												
							VL 2	**0446700000**	50	VL 2	**0446700000**	50
							VH 10	**0446600000**	50	VH 10	**0446600000**	50
							BS M 2.5x14	**0266800000**	100	BS M 2.5x14	**0266800000**	100
Cover/Profiled material for covers for finger-safety*												
				Marking tags can be snapped on via cross-connection			AD 4	**0303400000**	50	AD 4	**0303400000**	50
							BSK M 2.5x18	**0303300000**	100	BSK M 2.5x18	**0303300000**	100
							ADP 4[1]	**1378160000**	10	ADP 4[1]	**1378160000**	10
Test plug/socket												
StB	Plug test socket	StB 8.5	**0215700000**	50	StB 8.5	**0215700000**	50	StB 8.5	**0215700000**	50	StB 8.5	**0215700000**	50
PS	can be used without QL												
K sleeve		PS 2.3	**0180400000**	20	PS 2.3	**0180400000**	20	PS 2.3	**0180400000**	20	PS 2.3	**0180400000**	20
Marking tags	**Print**												
1 2 3 4 5 6	DEK Standard	DEK 5	see "Accessories"		DEK 5	see "Accessories"		DEK 6	see "Accessories"		DEK 6	see "Accessories"	

Mounting rails, end brackets, further marking material see "Accessories"

* not for terminals made from PA

[1]) Length: 300 mm

Rail mounting TS 15

AK 4
AK 4/10



38.5 A / 6 mm²

60/32/34

9 mm/M 3/3.5 x 0.6

690 V/32 A/4 mm²

8 kV/3

0.5…1.0

2

0.5…6
1.5…4
0.5…4
0.5…4
0.5…4
0.2…6.0 / A 3

20
20

TS 15	Cat. No.	Qty.
	0489560000	100
(10pol./no mk.)	**0366560000**	10
(10pol./w.mk.)	**0469560000**	10

Type	Cat. No.	Qty.
BB 3 (8.0)	**0366660000**	50
combined AP + end brackets		
TW/AP (1.5)	**1331760000**	20
TSch 4	**0363360000**	100
Q 2	**0369000000**	50
Q 3	**0369100000**	50
Q 4	**0369200000**	50
Q 10	**0369300000**	20
AD 4	**0303400000**	50
BSK M 2.5x18	**0303300000**	100
StB 8.5	**0215700000**	50
PS 2.3	**0180400000**	20
DEK 6	see “Accessories”	

AKE 2.5



5/28/27

7 mm/M 2.5/3.0 x 0.5

IEC 60 947-7-2

–/–/2.5 mm²

4 kV/3

0.4…0.6

1

0.5…4
1.5…2.5
0.5…4
0.5…2.5
0.5…2.5
0.13…4.0 / A 3

–/–/26…12 AWG
–/–/26…12 AWG

TS 15	Cat. No.	Qty.
	1303360000 (green/yellow)	100

Type	Cat. No.	Qty.
DEK 5	see “Accessories”	

AKE 4



9 mm/M 3/3.5 x 0.6

IEC 60 947-7-2

–/–/4 mm²

8 kV/3

0.5…1.0

2

0.5…6
1.5…4
0.5…4
0.5…2.5
0.5…2.5
0.13…4.0 / A 3

–/–/22…12 AWG
–/–/26…12 AWG

TS 15	Cat. No.	Qty.
	0380260000 (green/yellow)	100

Type	Cat. No.	Qty.
DEK 6.5	see “Accessories”	

AKE 4 MS



7/27.5/30

9 mm/M 3/3.5 x 0.6

–/–/4 mm²

0.8…1.6

3

0.5…4
1.5…4
0.5…4
0.5…4
0.5…4
0.5…4.0 / A 3

–/–/22…14 AWG

TS 15	Cat. No.	Qty.
	0211200000	50

[1]) The conductor cross-section is reduced to max. 2.5 mm² when QB is used.

ASK 1

Fuse terminal



8/58/34

9 mm/M 3/3.5 x 0.6

500 V/6.3 A*/4 mm²

6 kV/3

0.5…1.0

2

0.5…4
1.5…4
0.5…4
0.5…2.5
0.5…2.5
0.13…4.0 / A 3

(QB 2…4) 10

300 V/10 A/22…12 AWG
300 V/6.3 A/26…12 AWG

TS 15	Cat. No.	Qty.
	0376860000	100
5 x 20 without indicator		

Type	Cat. No.	Qty.
AP (1.5)	**0380360000**	20
QB 2[1]) insul.	**0461100000**	50
QB 3[1]) insul.	**0461200000**	50
QB 4[1]) insul.	**0461300000**	50
3-pole ganging with tag bar SchS 2, snapped onto three disconnect levers (Cat. No. **0337400000**)		
K sleeve	**0553300000**	100
DEK 6.5	see “Accessories”	

* With contact sleeve 19 A

SAKR

Isolating blade terminal with 2 sockets or
with 2 clamping screws



6.5/42/45

8 mm/M 3/3.5 x 0.6

400 V[2])/10 A/4 mm²

6 kV/3

0.5…1.0

2

0.5…4
1.5…4
0.5…4
0.5…4
0.5…4
0.13…4.0 / A 3

(QB 2…4) 10

TS 15	Cat. No.	Qty.
with 2 StB	**0412860000**	100
w. clamp.screw	**0412760000**	100

Type	Cat. No.	Qty.
AP (1.5)	**0211360000**	20
QB 2[1]) insul.	**0482700000**	50
QB 3[1]) insul.	**0482800000**	50
QB 4[1]) insul.	**0482900000**	50
QB 25[1]) blank	**0134000000**	20
PS 2.3	**0180400000**	20
DEK 6.5	see “Accessories”	

[2]) As disconnect test terminal: rated voltage 250 V

Feed-through terminals for TS 15

Tab connection
Solder connection

	AKZ 4 SS	AKZ 4 SS	AKZ 4 S	AKZ 4 SF
				
Dimensions/approvals				
Width/length/height (mm) with TS 15	6/28.5/30.5	6/28.5/30.5	6/27/30	6/27/30
Insulation stripping length/clamping screw/screwdriver blade			9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6
Rated data				
Rated voltage*/current/cross-section	400 V/8 A/2.5/1 mm²	400 V/8 A/1 mm²	400 V/8 A/4/1 mm²	400 V/8 A/4/1 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity	6 kV/3	6 kV/3	6 kV/3	6 kV/3
Further technical data				
Tightening torque range Nm			0.5…1.0	0.5…1.0
Torque setting with electric screwdriver type DMS 2			2	2
Clampable conductor				
Solid H07V-U mm²			0.5…4	0.5…4
Stranded H07V-R mm²			1.5…4	1.5…4
Flexible H07V-K mm²	Tab connec. 6.3 and 2.8 mm	Tab connection 2.8 mm	0.5…4	0.5…4
Flexible H07V-K and ferrule DIN 46 228/1 mm²			0.5…4	0.5…4
Flexible H07V-K and ferrule with plastic insul. collar mm²			0.5…4	0.5…4
Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1 Size			0.2...4/A 3	0.2...4/A 3
Continuous current rating of cross-connection 2-pole A	20	20	20	20
Continuous current rating of cross-connection multipole A	20	20	20	20
Rated data according to UL/CSA				
Voltage/current/conductor size UL	150 V/10 A/22…12 AWG	150 V/10 A/22…12 AWG	150 V/20 A/22…12 AWG	
Voltage/current/conductor size CSA	300 V/10 A/24…12 AWG	300 V/10 A/24…12 AWG	300 V/10 A/24…12 AWG	300 V/10 A/24…12 AWG
Ordering data Type	TS 15 Cat. No. Qty.	TS 15 Cat. No. Qty.	TS 15 Cat. No. Qty.	TS 15 Cat. No. Qty.
KrG				
PA	**0324560000** 100	**0362460000** 100	**0324460000** 100	**0158760000** 100
Blue PA				
PA				
End plate (thickness mm)	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
PA	AP (1.5) **0294460000** 20	AP (1.5) **0294460000** 20	AP (1.5) **0294460000** 20	AP (1.5) **0294460000** 20
PA				
Blue PA				
HP				
HP				
BB				
Partition (thickness mm)				
PA	TW (0.5) **0348260000** 50	TW (0.5) **0348260000** 50	TW (0.5) **0348260000** 50	TW (0.5) **0348260000** 50
HP				
HP				
Small partition				
Cross-connection				
	Q 2 **0369000000** 50	Q 2 **0369000000** 50	Q 2 **0336400000** 50	Q 2 **0336400000** 50
	Q 3 **0369100000** 50	Q 3 **0369100000** 50	Q 3 **0336500000** 50	Q 3 **0336500000** 50
	Q 4 **0369200000** 50	Q 4 **0369200000** 50	Q 4 **0336600000** 50	Q 4 **0336600000** 50
	Q 10 **0369300000** 20	Q 10 **0369300000** 20	Q 10 **0368600000** 20	Q 10 **0368600000** 20
Switchable cross-connection link				
			VL 2 **0446700000** 50	VL 2 **0446700000** 50
			VH 10 **0446600000** 50	VH 10 **0446600000** 50
VL BS VH			BS M 2.5x14 **0266800000** 100	BS M 2.5x14 **0266800000** 100
Test plug/socket				
StB Plug test socket ø 2.3	StB 8.5 **0215700000** 50	StB 8.5 **0215700000** 50	StB 8.5 **0215700000** 50	StB 8.5 **0215700000** 50
PS	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20
Cover				
Insulation sleeves				
	IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 100
	IH 6.3 **0386260000** 100			IH 6.3 **0386260000** 100
Marking tags **Print**				
1 2 3 4 5 6 DEK Standard	DEK 6 see "Accessories"	DEK 6 see "Accessories"	DEK 6 see "Accessories"	DEK 6 see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"				

* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

Feed-through terminals for TS 15

AL 1





6.5/32/21	
400 V/16 A/1 mm²	
6 kV/3	
0.5…1	
0.5…1	
TS 15	Cat. No. Qty.
	0137320000 100

Type	Cat. No.	Qty.
EP (1.0)	**0164100000**	100
EP (1.0 tropi. pr.)	**0164500000**	100
TW (0.5)	**0166800000**	50

Feed-through terminals for TS 15

Solder connection
Spring-clip connection
acc. to DIN 41611 Part 4
Wrap connection
acc. to DIN/IEC 352 Part 1

	AKZ 1.5 T	AKZ 1.5 T	AKZ 1.5 T	AKZ 2.5 K
				
		* 035786 = 45 mm		
Dimensions/approvals				
Width/length/height (mm) with TS 15	5/25/45	5/25/39.5	5/28/44	5/26/46.7
Pin size	0.8 x 1.6	1 x 1	0.8 x 1.6	0.8 x 1.6
Insulation stripping length/clamping screw/screwdriver blade	7 mm/M 2.5/3.0 x 0.5	7 mm/M 2.5/3.0 x 0.5	7 mm/M 2.5/3.0 x 0.5	7 mm/M 2.5/3.0 x 0.5
Rated data				
Rated voltage/current/cross-section	125 V/8 A/1.5 mm²	125 V/8 A/1.5 mm²	125 V/8 A/1.5 mm²	125 V/10 A/2.5 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity	2.5 kV/3	2.5 kV/3	2.5 kV/3	2.5 kV/3
Further technical data				
Tightening torque range Nm	0.4…0.7	0.4…0.7	0.4…0.7	0.4…0.6
Torque setting with electric screwdriver type DMS 2	1	1	1	1
Clampable conductor				
Solid H07V-U mm²	0.5…2.5	0.5…2.5	0.5…2.5	0.5…4
Stranded H07V-R mm²	1.5	1.5	1.5	1.5…2.5
Flexible H07V-K mm²	0.5…1.5	0.5…1.5	0.5…1.5	0.5…2.5
Flexible H07V-K and ferrule DIN 46 228/1 mm²	0.5…1.5	0.5…1.5	0.5…1.5	0.5…2.5
Flexible H07V-K and ferrule with plastic insul. collar mm²	0.5…1.5	0.5…1.5	0.5…1.5	0.5…2.5
Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1 Size	0.13...2.5 / A1	0.13...2.5 / A1	0.13...2.5 / A1	0.13...4.0 / A3
Continuous current rating of cross-connection 2-pole A	24	24	24	24
Continuous current rating of cross-connection multipole A	24	24	24	24
Rated data according to UL/CSA				
Voltage/current/conductor size UL	300 V/10 A/26…14 AWG	300 V/10 A/26…14 AWG	300 V/10 A/26…14 AWG	300 V/10 A/26…14 AWG
Voltage/current/conductor size CSA	300 V/10 A/24…16 AWG		300 V/10 A/24…16 AWG	300 V/10 A/26…10 AWG
Ordering data **Pin versions**	Type / Cat. No. / Qty.	Type / Cat. No. / Qty.	Type / Cat. No. / Qty.	Type / Cat. No. / Qty.
0.6 x 0.6	AKZ 1.5 T **0442560000** 100	AKZ 1.5 T **0483660000** 100	AKZ 1.5 T **0400460000** 100	AKZ 2.5 K **0696260000** 100
1.0 x 1.0	AKZ 1.5 T **0357960000** 100	AKZ 1.5 T **0357860000** 100	AKZ 1.5 T **0400360000** 100	
0.8 x 1.6 horizont.	AKZ 1.5 W **0329460000** 100			
0.8 x 1.6 vertical				
Mounting, horizontal / Mounting, vertical 0.8 x 2.4 horizontal				
0.8 x 2.4 vertical				
End plate (thickness mm)				
PA	AP (1.5) **0340560000** 50	AP (1.5) **0340560000** 50	AP (1.5) **0340560000** 50	AP (2.5) **0697260000** 50
Partition (thickness mm)				
PA				TW (1.5) **0318560000** 20
Small partition				
Cross-connection				
2-pole	Q 2 **0368200000** 50	Q 2 **0368200000** 50	Q 2 **0368200000** 50	Q 2 **0368200000** 50
3-pole	Q 3 **0368300000** 50	Q 3 **0368300000** 50	Q 3 **0368300000** 50	Q 3 **0368300000** 50
4-pole	Q 4 **0368400000** 50	Q 4 **0368400000** 50	Q 4 **0368400000** 50	Q 4 **0368400000** 50
10-pole	Q 10 **0368500000** 20	Q 10 **0368500000** 20	Q 10 **0368500000** 20	Q 10 **0368500000** 20
Q 3				
Switchable cross-connection link				
VL / BS / VH				
Test plug/socket				
StB Plug test socket ø 2.3	StB 8.5 **0215700000** 50	StB 8.5 **0215700000** 50	StB 8.5 **0215700000** 50	StB 8.5 **0215700000** 50
PS	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20
Marking tags **Print**				
1 2 3 4 5 6 DEK Standard	DEK 5 see “Accessories”	DEK 5 see “Accessories”	DEK 5 see “Accessories”	DEK 5 see “Accessories”
Mounting rails, end brackets, further marking material see “Accessories”				

Feed-through terminals for TS 15


AKZ 2.5 K



5/26/46.7	
0.8 x 1.6	
7 mm/M 2.5/3.0 x 0.5	
250 V/8 A/2.5 mm²	
4 kV/3	
0.4…0.6	
1	
0.5…4	
1.5…2.5	
0.5…2.5	
0.5…2.5	
0.5…2.5	
0.13...4.0 / A3	
24	
24	
300 V/10 A/26…14 AWG	
300 V/10 A/26…10 AWG	

Type	Cat. No.	Qty.
AKZ 2.5 K	**0695460000**	100
AKZ 2.5 K	**0695660000**	100
AP (2.5)	**0697260000**	50
TW (1.5)	**0318560000**	20
Q 2	**0368200000**	50
Q 3	**0368300000**	50
Q 4	**0368400000**	50
Q 10	**0368500000**	20
StB 8.5	**0215700000**	50
PS 2.3	**0180400000**	20
DEK 5	see “Accessories”	

AKZ 2.5 K



5/47.5/27	
0.8 x 1.6	
7 mm/M 2.5/3.0 x 0.5	
250 V/8 A/2.5 mm²	
4 kV/3	
0.4…0.6	
1	
0.5…4	
1.5…2.5	
0.5…2.5	
0.5…2.5	
0.5…2.5	
0.13...4.0 / A3	
24	
24	
300 V/10 A/26…14 AWG	
300 V/10 A/26…10 AWG	

Type	Cat. No.	Qty.
AKZ 2.5 K	**0695960000**	100
AKZ 2.5 K	**0696160000**	100
AP (2.5)	**0697260000**	50
TW (1.5)	**0318560000**	20
Q 2	**0368200000**	50
Q 3	**0368300000**	50
Q 4	**0368400000**	50
Q 10	**0368500000**	20
StB 8.5	**0215700000**	50
PS 2.3	**0180400000**	20
DEK 5	see “Accessories”	

AKZ 4 T



6/27/48.5	
1 x 1	
9 mm/M 3/3.5 x 0.6	
250 V/10 A/4 mm²	
4 kV/3	
0.5…1.0	
2	
0.5…4	
1.5…4	
0.5…4	
0.5…4	
0.5…4	
0.13...4.0 / A3	
20	
20	
300 V/10 A/26…14 AWG	
300 V/10 A/24…12 AWG	

Type	Cat. No.	Qty.
AKZ 4 T	**0445860000**	100
AP (1.5)	**0294460000**	20
TW (1.5)	**0348260000**	50
TSch 4	**0363360000**	100
Q 2	**0336400000**	50
Q 3	**0336500000**	50
Q 4	**0336600000**	50
Q 10	**0368600000**	20
VL 2	**0446700000**	50
VH 10	**0446600000**	50
BS M 2.5 x 14	**0266800000**	100
StB 8.5	**0215700000**	50
PS 2.3	**0180400000**	20
DEK 6	see “Accessories”	

AKZ 4 T



6/27/50.5	
0.8 x 1.6	
9 mm/M 3/3.5 x 0.6	
250 V/10 A/4 mm²	
4 kV/3	
0.5…1.0	
2	
0.5…4	
1.5…4	
0.5…4	
0.5…4	
0.5…4	
0.13...4.0 / A3	
20	
20	
300 V/10 A/26…14 AWG	
300 V/10 A/24…12 AWG	

Type	Cat. No.	Qty.
AKZ 4 T	**0344160000**	100
AKZ 4 T	**0344060000**	100
AP (1.5)	**0294460000**	20
TW (1.5)	**0348260000**	50
TSch 4	**0363360000**	100
Q 2	**0336400000**	50
Q 3	**0336500000**	50
Q 4	**0336600000**	50
Q 10	**0368600000**	20
VL 2	**0446700000**	50
VH 10	**0446600000**	50
BS M 2.5 x 14	**0266800000**	100
StB 8.5	**0215700000**	50
PS 2.3	**0180400000**	20
DEK 6	see “Accessories”	

AKZ 4 T



6/27/57,8	
0.8 x 2.4	
9 mm/M 3/3.5 x 0.6	
250 V/10 A/4 mm²	
4 kV/3	
0.5…1.0	
2	
0.5…4	
1.5…4	
0.5…4	
0.5…4	
0.5…4	
0.13...4.0 / A3	
20	
20	
300 V/10 A/26…14 AWG	
300 V/10 A/24…12 AWG	

Type	Cat. No.	Qty.
AKZ 4 T	**0366460000**	100
AKZ 4 T	**0461660000**	100
AP (1.5)	**0294460000**	20
TW (1.5)	**0348260000**	50
TSch 4	**0363360000**	100
Q 2	**0336400000**	50
Q 3	**0336500000**	50
Q 4	**0336600000**	50
Q 10	**0368600000**	20
VL 2	**0446700000**	50
VH 10	**0446600000**	50
BS M 2.5 x 14	**0266800000**	100
StB 8.5	**0215700000**	50
PS 2.3	**0180400000**	20
DEK 6	see “Accessories”	

AKZ 4 ST



6/27/50.2	
0.8 x 1.6	
–	
250 V/10 A/2.5 mm²	
4 kV/3	
0.5...2.5 / -	
20	
20	
300 V/10 A/24…12 AWG	

Type	Cat. No.	Qty.
AKZ 4 ST	**0439260000**	100
AP (1.5)	**0294460000**	20
TW (1.5)	**0348260000**	50
Q 2	**0369000000**	50
Q 3	**0369100000**	50
Q 4	**0369200000**	50
Q 10	**0369300000**	20
StB 8.5	**0215700000**	50
PS 2.3	**0180400000**	20
DEK 6	see “Accessories”	

Feed-through terminals for TS 15

for temperature measuring circuits


AKZ 4/TC



Weidmüller's thermocouple terminals are specially designed for transmitting the smallest voltages in temperature measuring circuits. Special busbars ensure that no false signals occur in the terminal when temperature differences exist in the positive and negative path. This high measuring precision is necessary for, e.g. test beds for aircraft engines, for complicated chemical processes, control systems, etc.

- Busbar material corresponds to thermal and compensating conductors
- Clear thermocouple marking
- 2-pole blocks per thermocouple
- Row width 14 mm, incl. end plate

Configuration of a temperature measuring circuit



1 Thermocouple (sensor)
2 Thermocouple terminals
3 Compensating conductor
4 Reference point
5 Supply conductors (to and from)
6 Measuring device

The thermocouple terminals displayed in this measurement circuit are used to thermo-electrically transmit thermal e.m.f. of the thermocouple to the reference point and indicating device. Thermocouple terminals are required for the construction of temperature measuring circuits.


Dimensions				
Width/length/height (mm)			with TS 15 ⊔	14/27/30
Insulation stripping length/clamping screw/screwdriver blade				9 mm/M 3/3.5 x 0.6
Rated data				
Rated voltage/current/cross-section				–/–/4 mm²
Further technical data				
Tightening torque range			Nm	0.5…1
Torque setting with electric screwdriver type DMS 2				2
Clampable conductor				
Solid H07V-U			mm²	0.5…4
Stranded H07V-R			mm²	1.5…4
Flexible H07V-K			mm²	0.5…4
Flexible H07V-K and ferrule DIN 46 228/1			mm²	0.5…2.5
Flexible H07V-K and ferrule with plastic insul. collar			mm²	0.5…2.5
Plug gauge acc. to IEC 60 947-1			Size	A 3
Continuous current of terminal for conductor size				
Continuous current rating of cross-connection 2-pole			A	
Continuous current rating of cross-connection multipole			A	

Ordering data	Version		⊔ TS 15	Cat. No.	Qty.
for thermocouples		Type J	Fe – CuNi	**1627010000**	20
Acc. to IEC 584	Type T	Cu – CuNi		**on demand**	
(DIN 43710)	Type K	NiCr – Ni		**1677130000**	20
	Type E	NiCr – CuNi		**on demand**	

End plate			Cat. No.	Qty.
	AP (thickness 1.5 mm)	PA	**0294460000**	20

Partition				
	TW (thickness 0.5 mm)	PA	**0348260000**	50


Thermocouple, type J	
Thermocouple acc. to IEC 584 (DIN 43 710)	
	Busbar
	Constantan (CuNi)
	Iron (Fe)

Marking tags	**Print**			
	Material V0	DEK 5/6	**1789590000**	500


Mounting rails, end brackets, further marking material see "Accessories"


Multipole terminal blocks


Screw connection




		MK 2/12	MK 10/14	MK 3/12	MK 4/16
Dimensions/approvals					
Width/length/height (mm)		86/15/15	88.5/13.5/12	110/15/16.1	103/17/16
Insulation stripping length/clamping screw/screwdriver blade		5 mm/M 2.5/3.5 x 0.6	6 mm/M 2.5/3.5 x 0.6	5 mm/M 2.5/3.5 x 0.6	5 mm/M 2.5/3.5 x 0.6
Rated data according to IEC 60 947-7-1					
Rated voltage/current/cross-section		125 V/24 A/2.5 mm²	125 V/24 A/2.5 mm²	400 V/24 A/2.5 mm²	400 V/24 A/2.5 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity		2.5 kV/3	2.5 kV/3	6 kV/3	6 kV/3
Further technical data					
Tightening torque range	Nm	0.4…0.45	0.4…0.45	0.4…0.45	0.4…0.45
Torque setting with electric screwdriver type DMS 2		1	1	1	1
Clampable conductor					
Solid H07V-U	mm²	0.5…4	0.5…4	0.5…4	0.5…4
Stranded H07V-R	mm²	1.5…2.5	1.5…2.5	1.5…2.5	1.5…2.5
Flexible H07V-K	mm²	0.5…2.5	0.5…2.5	0.5…2.5	0.5…2.5
Flexible H07V-K and ferrule DIN 46 228/1	mm²	0.5…1.5	0.5…1.5	0.5…1.5	0.5…1.5
Flexible H07V-K and ferrule with plastic insul. collar	mm²	0.5…1.5	0.5…1.5	0.5…1.5	0.5…1.5
Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1	Size	0.2…4.0 / A 2	0.2…4.0 / A 2	0.2…4.0 / A 2	0.2…4.0 / A 2
Continuous current rating of cross-connection 2-pole	A				
Continuous current rating of cross-connection multipole	A				
Rated data according to UL/CSA					
Voltage/current/conductor size	UL	300 V/10 A/24…12 AWG	150 V/25 A/22…12 AWG	300 V/25 A/22…12 AWG	150 V/20 A/22…12 AWG
Voltage/current/conductor size	CSA	300 V/10 A/24…12 AWG	300 V/10 A/24…12 AWG	300 V/25 A/22…12 AWG	150 V/15 A/22…12 AWG
Ordering data	Version	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
	2-pole			MK 3/2 KrG **0273820000** 100	
	3-pole			MK 3/3 KrG **0273920000** 50	
	4-pole			MK 3/4 KrG **0274020000** 50	
	4-pole				
	6-pole			MK 3/6 KrG **0274220000** 50	
	6-pole				
	8-pole			MK 3/8 KrG **0274420000** 25	
	8-pole				
	10-pole			MK 3/10 KrG **0274620000** 20	
	12-pole	MK 2/12 PA **0241260000** 50		MK 3/12 KrG **0243520000** 20	
	12-pole				
	14-pole		MK 10/14 PA **0370160000** 20		
	16-pole		other numbers on request		MK 4/16 KrG **0244220000** 20









The MK 10/14 can be mounted with glue or with M 3 x 12* screws through the empty terminal point aperture

*DIN EN ISO 1207

Soldering strip/expansion rivet					
		MF 2/12 **0241760000** 50			
		SN **0200100000** 500			
Marking strips					
	printed	BSTb 28/12 **0245700000** 50		BSTb 28/12 **0245900000** 50	BSTb 28/16 **0262200000** 50
	1 ...	bottom		BSTb 28/8 **0290200000** 50	bottom
		BSTb 28/12 **0278500000** 50		BSTb 28/6 **0290000000** 50	BSTb 28/16 **0278700000** 50
		top		BSTb 28/4 **0289800000** 50	top
	unprinted	BSTo 28/12 **0245600000** 50		BSTo 28/12 **0245800000** 50	BSTo 28/16 **0262100000** 50
				BSTo 28/8 **0284700000** 50	
				BSTo 28/6 **0289500000** 50	
				BSTo 28/4 **0289300000** 50	
				Printed on top on request	

Multipole terminal blocks

Screw/tab connection

	MK 5/2	KS 2…10	BK 2…12	MK 6/2…6/6
				
Dimensions/approvals				
Width/length/height (mm)	40/18/15.5	see table below	see table below	see table below
Insulation stripping length/clamping screw/screwdriver blade	5 mm/M 2.5/3.5 x 0.6	8 mm/M 3/4.0 x 0.8	8 mm/M 3/4.0 x 0.8	9 mm/M 4/4.0 x 0.8
Rated data according to IEC 60 947-7-1				
Rated voltage/current/cross-section	500 V/24 A/2.5 mm²	500 V/24 A/2.5 mm²	400 V/32 A/4 mm²	690 V/41 A/6 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity	6 kV/3	6 kV/3	6 kV/3	8 kV/3
Further technical data				
Tightening torque range Nm	0.4…0.45	0.5…0.7	0.5…0.7	1.2…2.0
Torque setting with electric screwdriver type DMS 2	1	2	2	4
Clampable conductor				
Solid H07V-U mm²	0.5…4	0.5…4	0.5…4	0.5…6
Stranded H07V-R mm²	1.5…2.5	1.5…2.5	1.5…4	1.5…6
Flexible H07V-K mm²	0.5…2.5	0.5…2.5	0.5…4	0.5…6
Flexible H07V-K and ferrule DIN 46 228/1 mm²	0.5…1.5	0.5…1.5	0.5…4	0.5…4
Flexible H07V-K and ferrule with plastic insul. collar mm²	0.5…1.5	0.5…1.2	0.5…4	0.5…4
Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1 Size	0.2…4.0 / A 2	0.2…4.0 / A 2	0.33…4.0 / A 3	0.33…6.0 / A 3
Rated data according to UL/CSA				
Voltage/current/conductor size UL		300 V/20 A/22…12 AWG	300 V/10 A/22…12 AWG	300 V/30 A/22…10 AWG
Voltage/current/conductor size CSA		300 V/25 A/24…12 AWG	300 V/10 A/22…12 AWG	300 V/40 A/22…10 AWG

Ordering data — **Versions**

Versions	MK 5/2	KS 2…10	BK 2…12	MK 6/2…6/6
2-pole	Type Cat. No. Qty. MK 5/2 KrG **0243820000** 100	Type Cat. No. Qty. KS 2 KrG²) **0134420000** 100	Type Cat. No. Qty. BK 2 KrG **0624720000** 50	Type Cat. No. Qty. MK 6/2 KrG **0620420000** 50
3-pole			BK 3 KrG **0624920000** 50	MK 6/3 KrG **0620320000** 50
4-pole		KS 4 KrG²) **0140320000** 50	BK 4 KrG **0625120000** 50	MK 6/4 KrG **0620220000** 20
4-pole				
6-pole		KS 6 KrG²) **0140620000** 50	BK 6 KrG **0625220000** 50	MK 6/6 KrG **0620120000** 20
6-pole				
8-pole				
8-pole				
10-pole		KS 10 KrG²) **0141620000** 20		
12-pole	Cover	Cover	BK 12 KrG **0625320000** 50	
12-pole	D2 (for MK 5/2) **0244060000** 50	D 2 (for KS 2) **0134500000** 100 D 4 (for KS 4) **0140500000** 50 D 6 (for KS 6) **0140800000** 50 D10 (for KS 10) **0141800000** 20		


Cover D 2 (for MK 5/2)




Cover D 4 (for KS 4)





Cover



Marking tag cover







Dimensions		
Type	a	b
KS 2	42	32
KS 4	66	56
KS 6	90	80
KS 10	138	128

Dimensions		
Type	a	b
BK 2	20	–
BK 3	31	11
BK 4	38	18
BK 6	52	32
BK 12	92	72.5

Dimens. Length/attach.dim.	
Type	KRG
MK 6/2	23.5
MK 6/3	36.5 13
MK 6/4	49.5 26
MK 6/6	75.5 52

Expansion rivet

SN	**0200100000** 500

Marking strips



	ELSb 2	BSTb 28/2	BSTb 17/6
printed	ELSb 2 **0143200000** 50	BSTb 28/2 **0203600000** 50	BSTb 17/6 **0304600000** 50
1 …	ELSb 4 **0143300000** 50	BSTb 28/3 **0203800000** 50	
	ELSb 6 **0143400000** 50	BSTb 28/4 **0197300000** 50	
	ELSb 10 **0143500000** 50	BSTb 28/6 **0197500000** 50	
		BSTb 28/12 **0198800000** 50	
unprinted	ELSo 2 **0142800000** 50	BSTo 28/2 **0203500000** 50	
	ELSo 4 **0142900000** 50	BSTo 28/3 **0203700000** 50	
	ELSo 6 **0143000000** 50	BSTo 28/4 **0197200000** 50	
	ELSo 10 **0143100000** 50	BSTo 28/6 **0197400000** 50	
		BSTo 28/12 **0198700000** 50	

Mounting rails, end brackets, further marking material see “Accessories”

[1]) Projecting length = 1 mm. To be considered for the last terminal in a row! Printed on top on request


[2]) Please order cover and marking strips separately.


Multipole terminal blocks

		MF 1/6...1/12	SLS 2/2
			
			SLS 2/4
			
Max. technical data			
Dimensions/approvals		cULus CSA	cULus CSA
Width/length/height (mm)		see below	see below
Insulation stripping length/clamping screw/screwdriver blade			8 mm/M 3.5/4.0 x 0.8
Rated data according to IEC 60 947-7-1			
Rated voltage*/current/cross-section		400 V*/16 A/2.5/1 mm²	400 V*/16 A/4 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity		6 kV/3	6 kV/3
Further technical data			
Tightening torque range	Nm		0.8…1.6
Torque setting with electric screwdriver type DMS 2			3
Clampable conductor			
Solid H07V-U	mm²		0.5…4
Stranded H07V-R	mm²		1.5…4
Flexible H07V-K	mm²		0.5…4
Flexible H07V-K and ferrule DIN 46 228/1	mm²		0.5…4
Flexible H07V-K and ferrule with plastic insul. collar	mm²		0.5…4
Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1	Size		0.33...4.0 / A 3
Rated data according to UL/CSA			
Voltage/current/conductor size	UL	300 V/10 A/24…12 AWG	
Voltage/current/conductor size	CSA	300 V/10 A/22…10 AWG	300 V/10 A/22…10 AWG

Ordering data


	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
PA	MF 1/6 KrG[2]	**0479720000**	100	SLS 2/2 KrG	**0213420000**	100
	MF 1/6 KrG[3]	**0480020000**	100			
	MF 1/8 KrG[2]	**0479820000**	50	SLS 2/4 KrG	**0240420000**	50
	MF 1/8 KrG[3]	**0480120000**	50	SLS 2/4 KrG	**0480320000**	50
	MF 1/12 KrG[2]	**0479920000**	50	Slotted		
	MF1/12 KrG[3]	**0480220000**	50			





Dimensions

Type	a	b	c	d
MF 1/6	52	34	9.5	6.5
MF 1/8	68	50	9.5	6.5
MF 1/12	113+0.5	102	8	7.5



Expansion rivet/insulation sleeve

	IH	IH 2.8	**0386060000**	100	IH 2.8	**0386060000** 100
		IH 6.3	**0386260000**	100	IH 6.3	**0386260000** 100
		SN	**0200100000**	500		

Cover/marking strips

BSTb 10/6	**0240900000**	50	
BSTb 10/8	**0241100000**	50	
BSTb 10/12	**0209500000**	50	
BSTo 10/6	**0240800000**	50	
BSTo 10/8	**0241000000**	50	
BSTo 10/12	**0209400000**	100	




Mounting rails, end brackets, further marking material see “Accessories”

* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

[2]) Single tab
[3]) Double tab

Multipole terminal blocks

Screw, solder, tab connection

	MKL 2/12	MF 2/12	MKL 3/12	MKL 4/16
	 	 0241860000  0241760000	  0243620000  0249920000	  0262020000  0244320000
Dimensions/approvals				
Width/length/height (mm)	88/23/15	75/24/6	110/23/16	103/24/16.5
Insulation stripping length/clamping screw/screwdriver blade	5 mm/M 2.5/3.5 x 0.6	5 mm	5mm/M 2.5/3.5 x 0.6	5mm/M 2.5/3.5 x 0.6
Rated data				
Rated voltage*/current/cross-section	125 V/20 A/2.5/1.5/1 mm²	63 V/17.5 A/1.5/1 mm²	400 V*/20 A/2.5/1.5/1 mm²	400 V/20 A/2.5/1.5/1 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity	2.5 kV/3	1.5 kV/3	6 kV/3	6 kV/3
Further technical data				
Tightening torque range Nm	0.4…0.45		0.4…0.45	0.4…0.45
Torque setting with electric screwdriver type DMS 2	1		1	1
Clampable conductor				
Solid H07V-U mm²	0.5…2.5		0.5…4	0.5…4
Stranded H07V-R mm²	1.5…2.5		1.5…2.5	1.5…2.5
Flexible H07V-K mm²	0.5…2.5		0.5…2.5	0.5…2.5
Flexible H07V-K and ferrule DIN 46 228/1 mm²	0.5…2.5		0.5…1.5	0.5…1.5
Flexible H07V-K and ferrule with plastic insul. collar mm²	0.5…2.5		0.5…1.5	0.5…1.5
Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1 Size	0.2...2.5 / A 2		0.33...4.0 / A 2	0.33...4.0 / A 2
Rated data according to UL/CSA				
Voltage/current/conductor size UL			300 V/25 A/22...12 AWG	300 V/25 A/22...12 AWG
Voltage/current/conductor size CSA			300 V/25 A/22…12 AWG	150 V/15 A/22…12 AWG
Ordering data **Versions**	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat.No. Qty.	Type Cat. No. Qty.
Horizontal 2-pole			MKL 3/2 KrG **0274920000**** 100	
Other number of poles on demand 4-pole			MKL 3/4 KrG **0275120000**** 100	
6-pole			MKL 3/6 KrG **0275320000**** 50	
12-pole	MKL 2/12 PA **0241360000** 50		MKL 3/12 KrG **0243620000**** 20	
16-pole				MKL 4/16 KrG **0262020000**[1] 20
Vertical 2-pole			MKL 3/2 KrG **0276020000*** 100	
Other number of poles on demand 4-pole				
6-pole			MKL 3/6 KrG **0276420000*** 50	
12-pole			MKL 3/12 KrG **0249920000*** 20	
16-pole				MKL 4/16 KrG **0244320000** 20
double-sided 2.8 x 0.8		MF 2/12 PA **0241860000** 50		
single-sided 0.8 x 1.6/2.8 x 0.8		MF 2/12 PA **0241760000** 50		
Expansion rivet/insulation sleeve				
	SN **0200100000** 500			
IH		IH 2.8 **0386060000** 100		
Marking strips				
printed	BSTb 28/12 **0245700000** 50		BSTb 28/4 **0289800000** 50	BSTb 28/16 **0262200000** 50
1 … bottom			BSTb 28/6 **0290000000** 50	bottom
top	**0278500000** 50		BSTb 28/12 **0245900000** 50	top
unprinted	BSTo 28/12 **0245600000** 50		BSTo 28/4 **0289300000** 50	BSTo 28/16 **0262100000** 50
			BSTo 28/6 **0289500000** 50	
			BSTo 28/12 **0245800000** 50	
Mounting rails, end brackets, further marking material see “Accessories”				

* For terminals directly mounted next to each other, the rated voltage is reduced to 250 V.


** Rated voltage 250 V. For terminals directly mounted next to each other, the rated voltage is reduced to 125 V.

* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

[1]) Rated voltage 250 V

Multipole terminal blocks

Screw, solder, tab connection
Modular design







		AKB 4	AKZ 2.5	ASK 1
Max. technical data		32 A / 4 mm²	26 A / 2.5 mm²	
Dimensions/approvals				
Width/length/height (mm)		6/27/23	5/25.5/26.5	8/58/30.5
		–	–	–
Insulation stripping length/clamping screw/screwdriver blade		9 mm/M 3/3.5 x 0.6	7 mm/M 2.5/3 x 0.5	9 mm/M 3/3.5 x 0.6
Rated data according to IEC 60 947-7-1				
Rated voltage/current/cross-section		400 V/32 A/4 mm²	250 V/24 A/2.5 mm²	500 V/6.3 A*/4 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity		6 kV/3	4 kV/3	6 kV/3
Further technical data				
Tightening torque range	Nm	0.5…1.0	0.4…0.6	0.5…1.0
Torque setting with electric screwdriver type DMS 2		2	1	2
Clampable conductor				
Solid H07V-U	mm²	0.5…6	0.5…4	0.5…4
Stranded H07V-R	mm²	1.5…4	1.5…2.5	1.5…4
Flexible H07V-K	mm²	0.5…4	0.5…2.5	0.5…4
Flexible H07V-K and ferrule DIN 46 228/1	mm²	0.5…4	0.5…2.5	0.5…2.5
Flexible H07V-K and ferrule with plastic insul. collar	mm²	0.5…4	0.5…2.5	0.5…2.5
Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1	Size	0.33...4.0 / A3	0.13...4.0 / A3	0.13...4.0 / A3
Continuous current rating of cross-connection 2-pole	A	32	24	(QB 2…4) 10
Continuous current rating of cross-connection multipole	A	32	24	
Rated data according to UL/CSA				
Voltage/current/conductor size	UL	300/250 V/27 A/22…12 AWG	300 V/10 A/22…12 AWG	300 V/10 A/22…12 AWG
Voltage/current/conductor size	CSA	300 V/10 A/22…12 AWG	300 V/10 A/26…10 AWG	300 V/6.3 A/26…12 AWG
Ordering data		Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
	PA	AKB 4 PA **0321560000** 100	AKZ 2.5 **0697160000** 100	ASK 1 PA **0376960000** 100
	Blue PA	**0321580000** 100	AKZ 2.5 **0697180000** 100	
		Direct mounting with BB 1 please order separately	Direct mounting with BB 4 please order separately	(for G fuse inserts 5x 20 without indicator)
End plate/attachment bracket (thickness mm)				
AP	PA	BB 1 (7) **0320560000** 50	BB 4 (7.5) **0697560000** 50	
		BS M 3 x 15 **0359000000** 100		
	Blue PA		AP (2.5) **0697360000** 50	AP (1.5) **0380360000** 20
			AP (2.5) **0697380000** 50	
Partition (thickness mm)		TW PA (0.5) **0348260000** 50		
Small partition		TSch 4 **0363360000** 100		
Cross-connection				
Q 3 / QB 4		Q 2 **0336400000** 50	Q 2 **0368200000** 50	QB 2[1] **0461100000** 50
		Q 3 **0336500000** 50	Q 3 **0368300000** 50	QB 3[1] **0461200000** 50
		Q 4 **0336600000** 50	Q 4 **0368400000** 50	QB 4[1] **0461300000** 50
		Q 10 **0368600000** 20	Q 10 **0368500000** 20	
Switchable cross-connection link				
VL		VL 2 **0446700000** 50		
		VH 10 **0446600000** 50		For fixing the screws of ASK 1 please use M 3 x ... DIN EN. ISO 1207 or M 3 x ... DIN EN, ISO 1580
BS		BS M 2.5 x 14 **0266800000** 100		
VH				
Test plug/socket				
PS		StB 8.5 **0215700000** 50	StB 8.5 **0215700000** 50	
StB		PS 2.3 **0180400000** 20	PS 2.3 **0180400000** 20	
Cover/contact sleeve				
		AD 4 **0303400000** 50		
K sleeve		BSK M 2.5 x 18 **0303300000** 100		K sleeve **0553300000** 100
Marking tags		**Print**		
1 2 3 4 5 6	DEK	Standard DEK 6 see "Accessories"	DEK 5 see "Accessories"	DEK 6.5 see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"				

[1] The conductor cross-section is reduced to max. 2.5 mm² when QB is used.

* With contact sleeve 19 A

Feed-through terminals

Screw connection
Solder connection
Tab connection
Spring-clip connection
acc. to DIN 41 611 Part 4
Wrap connection
acc. to DIN/IEC 352 Part 1

	AKA 2.5	ADK 1	ADK 1 F ADK 3 F	ADK 1 S
				
Dimensions/approvals				
Width/length/height with Pins (mm)	6/20/31	6/22/36.5	6/22/36.5	6/22/36.5
Length solder tag/pin (mm)	7,8	8,4	8.5/7.5	8,4
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 2.5/3.5 x 0.6	9 mm/M 3.5/3.5 x 0.6	11 mm/M 2.5/3.5 x 0.6	–
Rated data				
Rated voltage*/current/cross-section	400 V/20 A/2.5/1.5 mm²	400 V/16 A/4/1.5 mm²	400 V/20 A/2.5/1.5 mm²	400 V/16 A/2.5/1.5/1 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity	6 kV/3	6 kV/3	6 kV/3	6 kV/3
Further technical data				
Tightening torque range Nm	0.4	0.5…1.0	0.4…0.6	–
Torque setting with electric screwdriver type DMS 2	1	2	1	–
Clampable conductor				
Solid H07V-U mm²	0.5…2.5	0.5…4	0.5…2.5	
Stranded H07V-R mm²	1.5…2.5	1.5…4	1.5…2.5	
Flexible H07V-K mm²	0.5…2.5	0.5…4	0.5…2.5	
Flexible H07V-K and ferrule DIN 46 228/1 mm²	0.5…1.5	0.5…2.5	0.5…1.5	
Flexible H07V-K and ferrule with plastic insul. collar mm²	0.5…1.5	0.5…2.5	0.5…1.5	
Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1 Size	0.13...2.5 / A2	0.13...2.5 / A3	0.13...2.5 / A2	0.5...2.5 / -
Continuous current rating of cross-connection 2-pole A				
Continuous current rating of cross-connection multipole A	10	10		
Rated data according to UL/CSA				
Voltage/current/conductor size UL	300 V/20 A/26...12 AWG	300 V/10 A/26...12 AWG	300 V/20 A/26...14 AWG	300 V/18 A/12 AWG max.
Voltage/current/conductor size CSA	300 V/10 A/24…12 AWG	300 V/15 A/26…12 AWG	300 V/15 A/22…14 AWG	300 V/3 A/–
Ordering data Version for plate thickn. mm	Cat. No. **1.5** Qty.	**1.5** Qty. **2.5** Qty.	**1.5** Qty. **2.5** Qty.	**1.5** Qty. **2.5** Qty.
PA		**0303860000** 100 **0301060000** 100	**0476060000** 100 **0478660000** 100	
KrG	**0300720000** 100			
Pin 1.0x1.0				
Pin 0.8x1.6				
FS 1x6.3 slotted/0.8x2.8				**0476160000** 100 **0478560000** 100
12-pole PA				
End plate (thickness mm)	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
KrG	AP (3) **0162520000** 100			
PA		AP (3) **0476260000** 50	AP (3) **0476260000** 50	AP (3) **0476260000** 50
EP			AP (3) **0360000000** 20	
Spacer (thickness mm)				
KrG	ZP (1.5) **0240720000** 50			
KrG	ZP (2.5) **0288520000** 20			
Partition (thickness mm)				
TW		TW (0.5) **0442300000** 50	TW (0.5) **0442300000** 50	TW (0.5) **0442300000** 50
Test plug/socket				
StB Plug test socket ø 2.3		PS 2.3 **0180400000** 20		
PS				
Fuse pin/insulation sleeve/expansion rivet				
	SST 1.2 **0306600000**	SST 1.2 **0306600000**	SST 1.2 **0306600000**	SST 1.2 **030660**
		IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 100	IH 2.8 **0386060000** 100
IH				IH 6.3 **0386260000** 100
Marking tags **Print**				
1 2 3 4 5 6 DEK Standard	DEK 6 see “Accessories”	DEK 6 see “Accessories”	DEK 6 see “Accessories”	DEK 6 see “Accessories”
Mounting rails, end brackets, further marking material see “Accessories”				

* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

ADK 1 T



6/22/50.5	
19.5…21.9	
9 mm/M 3/3.5 x 0.6	
400 V/8 A/4 mm²	
6 kV/3	
0.5…1.0	
2	
0.5…4	
1.5…4	
0.5…4	
0.5…2.5	
0.5…2.5	
0.13...4.0 / A3	
10	
300/250 V/10 A/26...12 AWG	
300 V/15 A/26…12 AWG	
1.5 Qty.	**2.5** Qty.
	0372260000 100
0366360000 100	

Type	Cat. No.	Qty.
AP (3)	**0476260000**	50
TW (0.5)	**0442300000**	50
PS 2.3	**0180400000**	20
SST 1.2	**0306600000**	
DEK 6	see “Accessories”	

AKZ 2.5 K



0109160000 solder tag

5/26/45.5	
22.4…23.6	
7 mm/M 2.5/3.0 x 0.5	
250 V/8 A/2.5 mm²	
4 kV/3	
0.4…0.6	
1	
0.5…2.5	
1.5…2.5	
0.5…2.5	
0.5…2.5	
0.5…2.5	
0.13...2.5 / A2	
10	
300/250 V/10 A/22...12 AWG	
300 V/10 A/26…10 AWG	
Cat. No.	Qty.
0109160000 solder tag	100
0108960000	100

Type	Cat. No.	Qty.
AP (3)	**0697260000**	50
TW (1.5)	**0318560000**	20
PS 2.3	**0180400000**	20
StB 8.5	**0215700000**	50
IH 2.8	**0386060000**	100
DEK 5	see “Accessories”	


ADK 1 FT



6/22/52	
24	
11 mm/M 2.5/3.5 x 0.6	
250 V/10 A/2.5 mm²	
4 kV/3	
0.4…0.6	
1	
0.5…2.5	
1.5…2.5	
0.5…2.5	
0.5…1.5	
0.5…1.5	
0.33...2.5 / A2	
300 V/3 A/22…14 AWG	
Cat. No. **1.5**	Qty.
0176960000	100

Type	Cat. No.	Qty.
AP (3)	**0476260000**	50
TW (0.5)	**0442300000**	50
SST 1.2	**0306600000**	
DEK 6	see “Accessories”	



MK 2/12



86/15/23	
8	
5	
63 V/20 A/2.5/1.5 mm²	
1.5 kV/3	
0.4…0.45	
1	
0.5…2.5	
1.5…2.5	
0.5…2.5	
0.5…2.5	
0.5…2.5	
0.2...2.5 / A2	
300 V/10 A/24…12 AWG	
300 V/10 A/24…12 AWG	
Cat. No.	Qty.
0241460000	50

Type	Cat. No.	Qty.
SN	**0200100000**	500
BSTb 28/12	**024570…**	50
BSTo 28/12	**024560…**	50

Rack-mounted interface systems

		TOP 1.5 F/32	SP 10 FF[2] SP 10 LF[3]	SP 60 FF[2] SP 60 LF[3]	SP 90 FF[2] SP 90 LF[3]
					
Dimensions					
Width/length/height (mm)		40.2/110.6/29.5	42/46.5/170/28	40/45.5/162.5/110	40/45.5/228.5/110
Hole spacing/mounting dimensions	mm	101.6/20.3	147	151/90	217/90
Insulation stripping length/clamping screw/screwdriver blade		10 mm/M 2.5/3.5 x 0.6			
Rated data					
Rated voltage*/current/cross-section		250* V/6 A/1.5/1 mm²	1000* V/16 A/2.5/1.5 mm²	400* V/16 A/2.5/1.5 mm²	400* V/16 A/2.5/1.5 mm²
Rated impulse voltage VDE 0110/1.89/pollution severity		4 kV/3	6 kV/3	6 kV/3	6 kV/3
Further technical data					
Tightening torque range	Nm	0.4…0.7			
Torque setting with electric screwdriver type DMS 2		1			
Clampable conductor					
Solid H07V-U	mm²	0.5…2.5			
Stranded H07V-R	mm²	1.5			
Flexible H07V-K	mm²	0.5…1.5			
Flexible H07V-K and ferrule DIN 46 228/1	mm²	0.5…1.5			
Flexible H07V-K and ferrule with plastic insul. collar	mm²	0.5…1.5			
Plug gauge acc. to IEC 60 947-1	Size	A1			

Ordering data	Version	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
Pin 1.0 x 1.0	PA	TOP 1.5 F/32	**0443160000**[1]	5									
Pin 0.8 x 2.8 (push-on), unprinted	PA												
Pin 0.8 x 2.8 (push-on), printed, 1…32	PA												
Pin 0.8 x 2.8 (push-on), printed, 1…32, blue	PA												
6 x plug (6.3 x 0.8)	KrG				SP 10 FF	**0456220000**	10	SP 60 FF[4]	**0340320000**	1	SP 90 FF**	**0248120000**	1
6 x plug (6.3 x 0.8), blue	KrG							SP 60 FF[4]	**0340370000**	1			
6 x plug (6.3 x 0.8), bzw. 12 x 2.8 x 0.8 slotted	KrG										SP 90 FF**	**0608920000**	1
6 x plug (6.3 x 0.8), bzw. 12 x 2.8 x 0.8 slotted, blue	KrG												
3 x plug (6.3 x 0.8) /1 x solder per pole	KrG							SP 60 LF[4]	**0343720000**	1	SP 90 LF**	**0248220000**	1
3 x plug (6.3 x 0.8) /1 x solder per pole, blue	KrG							SP 60 LF[4]	**0343770000**	1			
3 x plug (6.3 x 0.8 bzw. 6 x 2.8 x 0.8)/1 x solder	KrG							SP 60 LF[5]	**0124520000**	1			
3 x plug (6.3 x 0.8 bzw. 6 x 2.8 x 0.8)/1 x solder, blue	KrG							SP 60 LF[5]	**0124570000**	1	printed:		
2 x direct connection, 1 x Pin 0.8 x 1.6	PA										** A...F / 1...15		
								printed:					
								[4] A...F / 1...10					
								[5] 00...50 / 1...10					

Insulation sleeves	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
	IH 2.8	**0386060000**	100	IH 2.8	**0386060000**	100	IH 2.8	**0386060000**	100	IH 2.8	**0386060000**	100
				IH 6.3	**0386260000**	100	IH 6.3	**0386260000**	100	IH 6.3	**0386260000**	100

Marking tags	**Print**					
dekafix	for group markers		FW 5	see “Accessories”		

Mounting rails, end brackets, further marking material see “Accessories”


* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

[1] Rated voltage 125 V

[2] FF = Tab- Tab
[3] LF = Solder - Tab

Rack-mounted interface systems

RV 8/8 long



RV 8/8 short



RV 8/9 long



RV 8/9 short



Technical data acc. to VDE

125 V/–/–

Pin versions (intern)	Type	Cat. No.	Qty.
0.8 x 2.4/1 x 1		**0468860000**	1
0.8 x 2.4/0.8 x 2.4		**0468960000**	1

Plug adapter	Type	Cat. No.	Qty.
1-pole	DSA 1	**0576060000**	50

for connection of solid and flexible conductors from 0.75 to 1.5 mm² directly on to the pins of the interface system.

125 V/–/–

Type	Cat. No.	Qty.
	0467160000	1
	0467260000	1

Type	Cat. No.	Qty.
DSA 1	**0576060000**	50

105 V/–/–

Type	Cat. No.	Qty.
	0498960000	1
	0499060000	1

with shield pins

Type	Cat. No.	Qty.
DSA 1	**0576060000**	50

125 V/–/–

Type	Cat. No.	Qty.
	0444060000	1
	0545960000	1

with shield pins

Type	Cat. No.	Qty.
DSA 1	**0576060000**	50

RV 8/20 short




Technical data acc. to VDE

125 V~/–/–

Pin versions (internal)	Cat. No.	Qty.
0.8 x 2.4/1 x 1		
0.8 x 2.4/0.8 x 2.4	**0544460000**	1


Additional versions on request


RV 8/56 short



125 V~/–/–

Cat. No.	Qty.
0462260000	1
0533060000	4





Type	Size A in mm	Size B in mm
RV 8/8 K	81	40.64
RV 8/9 K	89	40.64
RV 8/8 L	93	40.64
RV 8/9 L	100	40.64
RV 8/20 K	187,62/31.5	63
RV 8/56 K	460/31.5	63

(K = short/L = long)

Cat. No.	RV	a	b	c
0468860000	8/8 L	26	20	200
0468960000	8/8 L	26	26	206
0467160000	8/8 K	26	20	84
0467260000	8/8 K	26	26	89
0119360000	8/20 K	26	20	84
0544460000	8/20 K	26	26	89
0462260000	8/56 K	26	20	84
0533060000	8/56 K	26	26	89

Mounting rails, end brackets, further marking material see “Accessories”

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru