



Customer drawing

Nb OF CONTACTS	Dimension				
	A	B	C	D	E
9	30.84	24.99	16.92	11.09	19.28
15	39.24	33.32	24.70	19.39	27.51
25	53.04	47.04	38.96	33.24	41.30
37	69.32	63.50	55.42	49.86	57.71

REVISONS			
SYM	EDN	DESCRIPTION	DATE
1			06/10/09

D-SUB TECHNICAL DATA

- SHELL : Steel 100u"min tin over 50u" min nickel
- BODY : Glass filled thermoplastic.
- CONTACTS : Brass
- Flame retardant to UL94 V-0 Color Black
- Gold flash over 50u" min nickel on mating area.
- 100u" min tin over 50u" min nickel on solder area
- SCREWLOCK :Steel,100u" min nickel plated.
- REAR NUT : Brass,100u" min nickel plated.
- ELECTRICAL: Voltage rating : 250 V Rms to 50 Hz
- Current rating : 3A
- Withstanding Voltage >1000 V Rms to 50 Hz for one minute
- Insulation resistance >5000 M Ohms
- Contact resistance 20 mOhms max.
- CLIMATIC : Temperature range -55 °C up to 125°C
- MARKING : Amphenol...(Series No.)
- Commercial reference
- Manufacturing date

PRODUCT CODE

L 717 SD X H XX P VF

L: RoHS Compliance

717: tinned shell +
dimples for plug

SD: standard density

Shell Size: E,A,B,C

VF=Front
screwlock 4-40

Contact type:
P=pin

Configuration: 09,15,25,37

H=Rear insert #4-40

UNLESS OTHERWISE SPECIFIED		TOLERANCES		APPROVAL		DATE	
U.S.		METRIC		DRAWN		Checked and/or	
.X		+/-		0.50		06/10/09	
.XX		+/-		0.30		1st using	
.XXX		+/-		0.20		06/10/09	
ANGLES		+/-		2°		CHECKED	
FOR MATERIALS AND FINISHES				DRAWING FILE :			
SEE NOTES				REMOVE SHARP EDGES			
DIMENSIONS				ANGLE OF PROJECTION			
TOLERANCE		TOLERANCE		TOLERANCE		TOLERANCE	
NONE		NONE		NONE		NONE	

TITLE			
Amphenol			
Stamped and Formed contacts, SD series			

SIZE		DRAWING NO.		REV.	
A4		C L77SDXXXXP F		1	
SCALE		NONE		SHEET 1 OF 1	

Amphenol

Stamped and Formed contacts, SD series

SIZE	DRAWING NO.	REV.
A4	C L717SDXHXXPVF	1
SCALE	NONE	SHEET 1 OF 1

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru