

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0744410001

Status:


Active

Overview:

sfp_sfp_host_connectors

Description:

0.80mm (.031") Pitch SFP, SFP Plus (SFP+) Host Connector, Z-Axis Pluggable, Right Angle, SMT, 20 Circuits, 0.38µm (15µ") Gold (Au)



Documents:	
3D Model	Product Specification PS-74441-001 (PDF)
Application Specification (PDF)	RoHS Certificate of Compliance (PDF)
Drawing (PDF)	

Agency Certification	
CSA	LR19980
UL	E29179
General	
Product Family	I/O Connectors
Series	74441
Application	Module-to-Board
Component Type	Receptacle
Overview	sfp_sfp_host_connectors
Product Name	Z-Axis Pluggable
Type	N/A
Physical	
Boot Color	N/A
Circuits (Loaded)	20
Circuits (maximum)	20
Circuits Detail	20
Color - Resin	Black
Durability (mating cycles max)	200
Flammability	94V-0
Gender	Receptacle
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Rows	2
Orientation	Right Angle
PCB Locator	Yes
PCB Retention	Yes
Packaging Type	Embossed Tape on Reel
Panel Mount	No
Pitch - Mating Interface (in)	0.031 In
Pitch - Mating Interface (mm)	0.80 mm
Pitch - Term. Interface (in)	0.031 In
Pitch - Term. Interface (mm)	0.80 mm
Plating min: Mating (µin)	15.2
Plating min: Mating (µm)	0.38
Plating min: Termination (µin)	101.6
Plating min: Termination (µm)	2.54
Polarized to Mating Part	Yes
Polarized to PCB	No
Ports	1

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Halogen-Free

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

74441Series

Mates With

SFP Modules

Use With

EMI Shield, [73927](#) SFP Cage, [86025](#) LC Duplex Cable Assembly, Guide Frame, [73939](#) HSSDC2 Cable Assembly

Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-40°C to +85°C
Termination Interface: Style	Surface Mount
Waterproof / Dustproof	No
Wire Size AWG	N/A

Electrical

Current - Maximum per Contact	0.5A
Grounding to Panel	Yes
Shielded	No
Voltage - Maximum	30V AC (RMS)/DC

Solder Process Data

Duration at Max. Process Temperature (seconds)	40
Lead-free Process Capability	Reflow Capable (SMT only)
Max. Cycles at Max. Process Temperature	3
Process Temperature max. C	260

Material Info

Reference - Drawing Numbers

Application Specification	AS-74441-001
Product Specification	PS-74441-001
Sales Drawing	SD-74441-001, SD-74441-004
Test Summary	TS-74441-002, TS-74441-004, TS-74441-010

SALES ASSEMBLY DRAWINGS FOR SMALL FORM-FACTOR AND Z AXIS PLUGGABLE CONNECTORS

CKT SIZE	PART NUMBER	TOOLED	DESCRIPTION	"A"	"B"	"C"	"D"	MULTI-SOURCE AGREEMENT	CONNECTOR DRAWING	CIRCUIT BOARD DRAWING
20	74441-0001	YES	PLATED PER NOTE 2	1.10/.043	11.00/.433	9.40/.370	9.60/.378	SFP	PAGE 2	PAGE 3
	74441-0004	NO*	PLATED PER NOTE 2	0.76/.030						
	74441-0010	YES	PLATED PER NOTE 3	1.10/.043						
	74441-0014	NO*	PLATED PER NOTE 3	0.76/.030						
	74441-0021	YES	PLATED PER NOTE 4	1.10/.043						
	74441-0031	YES	PLATED PER NOTE 5	1.10/.043						
30	74441-0041	YES	PLATED PER NOTE 6	1.10/.043						
	74441-0007	YES	PLATED PER NOTE 2	1.10/.043	15.00/.591	13.40/.528	13.60/.535	XFP	PAGE 2	PAGE 4
	74441-0017	YES	PLATED PER NOTE 3	1.10/.043						
40	74441-0027	YES	PLATED PER NOTE 4	1.10/.043						
	74441-0005	YES	PLATED PER NOTE 2	1.10/.043	19.00/.748	17.40/.685	17.60/.693		PAGE 2	PAGE 5
	74441-0015	YES	PLATED PER NOTE 3	1.10/.043						
50	74441-0025	YES	PLATED PER NOTE 4	1.10/.043						
	74441-0008	YES	PLATED PER NOTE 2	1.10/.043	23.00/.906	21.40/.843	21.60/.850		PAGE 2	PAGE 6
	74441-0018	YES	PLATED PER NOTE 3	1.10/.043						
	74441-0028	YES	PLATED PER NOTE 4	1.10/.043						
70	74441-0038	YES	PLATED PER NOTE 5	1.10/.043						
	74441-0003	YES	PLATED PER NOTE 2	1.10/.043	31.00/1.220	29.40/1.157	29.60/1.165	XENPAK XPAK X2	PAGE 2	PAGE 7
	74441-0013	YES	PLATED PER NOTE 3	1.10/.043						
	74441-0023	YES	PLATED PER NOTE 4	1.10/.043						
	74441-0033	YES	PLATED PER NOTE 5	1.10/.043						

NOTES

1. MATERIAL:

HOUSING - HIGH TEMPERATURE THERMOPLASTIC GLASS FILLED, UL 94V-0, BLACK
TERMINALS - COPPER ALLOY

2. PLATING:

CONTACT AREA - 0.38 μ m MIN GOLD OVER 2.54 μ m MIN NICKEL
SOLDER FOOT AREA - 2.54 - 5.09 μ m TIN OVER 2.54 μ m MIN NICKEL.

3. PLATING:

CONTACT AREA - 0.76 μ m MIN GOLD OVER 2.54 μ m NICKEL
SOLDER AREA - 2.54 -5.09 μ m TIN OVER 2.54 μ m MIN NICKEL

4. PLATING:

CONTACT AREA - 0.76 μ m MIN GOLD OVER 2.54 μ m NICKEL; LUBRICATED
SOLDER AREA: GOLD FLASH OVER 2.54 μ m MIN NICKEL.

5. PLATING:

CONTACT AREA - 0.76 μ m MIN GOLD OVER 2.54 μ m NICKEL,
SOLDER AREA: GOLD FLASH OVER 2.54 μ m MIN NICKEL.

6. PLATING:


CONTACT AREA - 0.38 μ m MIN GOLD OVER 2.54 μ m NICKEL,
SOLDER AREA: GOLD FLASH OVER 2.54 μ m MIN NICKEL.

7. TERMINAL SOLDER FEET TO BE COPLANAR WITHIN 0.10/.004 FOR 20, 30 AND 40 CIRCUIT CONNECTORS
TERMINAL SOLDER FEET TO BE COPLANAR WITHIN 0.15/.006 FOR 70 CIRCUIT CONNECTOR

8. * CONTACT PLANT FOR MORE INFORMATION

9. DATE CODE: 4 DIGIT (3 DIGIT DATE, 1 DIGIT YEAR)





10. CIRCUIT 1 IDENTIFIER LOCATED ON ALL PART NUMBERS





ADD -0041 EC NO: UCP2009-1455 DRAWN BY: DRWN:MS BARRA CHKD:BSMART APPR:SMILLER REV T	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE MM/IN		SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
			mm	INCH	DRAWN BY DATE	TITLE		
			4 PLACES ± ---	± ---	HAVERY 00/04/06	SALES ASSEMBLY Z AXIS PLUGGABLE PCB CONNECTOR		
			3 PLACES ± ---	± ---	CHECKED BY DATE	MOLEX INCORPORATED		
REV T	DESCRIPTION	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	2 PLACES ± 0.13	± .005	APPROVED BY DATE	DOCUMENT NO.	SHEET NO. 1 OF 7	
			1 PLACE ± 0.25	± .010	MBANAKIS 00/04/06	SD-74441-001		
			ANGULAR ± 1/2°		SEE TABLE			
			SIZE C		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

13 12 11 10 9 8 7 6 5 4 3 2 1

CIRCUIT 1
IDENTIFIER





SECTION A1-A1
SCALE 12:1



SECTION B1-B1
SCALE 12:1



SEE SHEET 1 EC NO: UCP2009-1455 DRAWN BY: DRWN:MS BARRA CHKD:BSMART APPR:SMILLER REV: T	DESCRIPTION 2009/01/15 2009/01/15 2009/01/16	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 6:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
				mm	INCH	DRAWN BY HAVERY	DATE 00/04/06	TITLE SALES ASSEMBLY Z AXIS PLUGGABLE PCB CONNECTOR			
			4 PLACES	± ---	± ---	CHECKED BY KSWEENEY	DATE 00/04/06				
			3 PLACES	± ---	± ---	APPROVED BY MBANAKIS	DATE 00/04/06				
			2 PLACES	± 0.13	± .005	MATERIAL NO.		DOCUMENT NO.		SHEET NO. 2 OF 7	
			1 PLACE	± 0.25	± .010	SEE TABLE		SD-74441-001			
			ANGULAR ±1/2°								
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS								
						THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					

12 11 10 9 8 7 6 5 4 3 2 1





20 CIRCUIT MOTHER BOARD RECOMMENDED PCB LAYOUT

SEE SHEET 1 EC NO: UCP2009-1455 DRAWN BY: IBARRA CHKD BY: SMART APPR: MILLER 2009/01/15 2009/01/15 2009/01/16	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 8:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION			
					DRAWN BY HAVERY		DATE 00/04/06	TITLE SALES ASSEMBLY Z AXIS PLUGGABLE PCB CONNECTOR				
					CHECKED BY KSWEENEY		DATE 00/04/06	MOLEX INCORPORATED				
					APPROVED BY MBANAKIS		DATE 00/04/06					
					MATERIAL NO.		DOCUMENT NO.		SHEET NO.			
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE		SD-74441-001		3 OF 7			
					SIZE C		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					



30 CIRCUIT MOTHER BOARD
RECOMMENDED PCB LAYOUT


SEE SHEET 1 EC NO: UCP2009-1455 T DRWN:MSIBARRA 2009/01/15 CHKD:BSMART 2009/01/15 APPR:SMILLER 2009/01/16	REV	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 6:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION			
						DRAWN BY HAVERY		DATE 00/04/06			TITLE SALES ASSEMBLY Z AXIS PLUGGABLE PCB CONNECTOR		
						CHECKED BY KSWEENEY		DATE 00/04/06					
						APPROVED BY MBANAKIS		DATE 00/04/06			MOLEX INCORPORATED		
						MATERIAL NO.		DOCUMENT NO.					
						DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE			SD-74441-001		SHEET NO. 4 OF 7
						SIZE C		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					



DETAIL C
SCALE 24:1

40 CIRCUIT MOTHER BOARD RECOMMENDED PCB LAYOUT

SEE SHEET 1 EC NO: UCP2009-1455 DRWN:MSIBARRA 2009/01/15 CHKD:BSMART 2009/01/15 APPR:SMILLER 2009/01/16	DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)			DIMENSION STYLE MM/IN		SCALE 6:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
				mm	INCH	DRAWN BY HAVERY	DATE 00/04/06	TITLE SALES ASSEMBLY Z AXIS PLUGGABLE PCB CONNECTOR		
			4 PLACES	± .---	± .---	CHECKED BY KSWEENEY	DATE 00/04/06			
			3 PLACES	± .---	± .---	APPROVED BY MBANAKIS	DATE 00/04/06	MOLEX INCORPORATED		
			2 PLACES	± 0.13	± .005	MATERIAL NO.	DOCUMENT NO.			
			1 PLACE	± 0.25	± .010	SEE TABLE		SD-74441-001	SHEET NO. 5 OF 7	
			ANGULAR ±1/2°							
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS							
						THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				





13	12	11	10	9	8	7	6	5	4	3	2	1
CKT SIZE	PART NUMBER	DESCRIPTION			"A"	"B"	"C"	"D"				
20	74441-9001	PLATED PER NOTE 2			1.10/.043	11.00/.433	9.40/.378	9.60/.378				
20	74441-9010	PLATED PER NOTE 3			1.10/.043	11.00/.433	9.40/.378	9.60/.378				
30	74441-9007	PLATED PER NOTE 2			1.10/.043	15.00/.591	13.40/.528	13.60/.535				
40	74441-9005	PLATED PER NOTE 2			1.10/.043	19.00/.748	17.40/.685	17.60/.693				
70	74441-9003	PLATED PER NOTE 2			1.10/.043	31.00/1.220	29.40/1.517	29.60/1.165				


NOTES

- MATERIAL:
HOUSING - HIGH TEMPERATURE THERMOPLASTIC GLASS FILLED, UL 94V-0, BLACK
TERMINALS - COPPER ALLOY
- PLATING:
CONTACT AREA - 0.38 μ m MIN GOLD OVER 2.54 μ m MIN NICKEL
SOLDER FOOT AREA - 2.54 - 5.09 μ m TIN OVER 2.54 μ m MIN NICKEL.
- PLATING:
CONTACT AREA - 0.76 μ m MIN GOLD OVER 2.54 μ m NICKEL
SOLDER AREA - 2.54 -5.09 μ m TIN OVER 2.54 μ m MIN NICKEL
- PLATING:
CONTACT AREA - 0.76 μ m MIN GOLD OVER 2.54 μ m NICKEL, LUBRICATED
SOLDER AREA: GOLD FLASH OVER 2.54 μ m MIN NICKEL.
- PLATING:
CONTACT AREA - 0.76 μ m MIN GOLD OVER 2.54 μ m NICKEL,
SOLDER AREA: GOLD FLASH OVER 2.54 μ m MIN NICKEL.
- TERMINAL SOLDER FEET TO BE COPLANAR WITHIN 0.10/.004 FOR 20, 30 AND 40 CIRCUIT CONNECTORS
TERMINAL SOLDER FEET TO BE COPLANAR WITHIN 0.15/.006 FOR 70 CIRCUIT CONNECTOR
- * CONTACT PLANT FOR MORE INFORMATION
- DATE CODE: 4 DIGIT (3 DIGIT DATE, 1 DIGIT YEAR)
- CIRCUIT 1 IDENTIFIER LOCATED ON ALL PART NUMBERS

CIRCUIT 1
IDENTIFIER




SECTION A1-A1



SECTION B1-B1



INITIAL RELEASE EC NO: UCP2010-0714 DRWN:MS IBARRA 2009/09/16 CHKD:BBARKER 2009/09/24 APPR:SMILLER 2009/09/24 A	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 6:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION				
				mm	INCH	DRAWN BY MS IBARRA	DATE 2009/09/16	TITLE SALES ASSEMBLY- LEADFREE Z AXIS PLUGGABLE PCB CONNECTOR					
			4 PLACES	±---	±---	CHECKED BY BBARKER	DATE 2009/09/16						
			3 PLACES	±---	±---	APPROVED BY SMILLER		DATE 2009/09/16	MOLEX INCORPORATED SD-74441-004				
			2 PLACES	±---	±---								
			1 PLACE	±---	±---								
	ANGULAR ±1/2°			MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-74441-004		SHEET NO. 1 OF 6					
REV	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE C THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										

SALES ASSEMBLY DRAWINGS FOR SMALL FORM-FACTOR AND Z AXIS PLUGGABLE CONNECTORS





CIRCUIT SIZE	MSA	CONNECTOR DRAWING	CIRCUIT BOARD DRAWING
20	SFP	PAGE 2	PAGE 3
30	XFP	PAGE 2	PAGE 4
40		PAGE 2	PAGE 5
70	XENPAK XPAK X2	PAGE 2	PAGE 6

INITIAL RELEASE EC NO: UCP2010-0714 2009/09/16 DRWN:MSIBARRA CHKD:BBARKER APPR:SMILLER 2009/09/16 2009/09/16 2009/09/16	DESCRIPTION REV A	QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)			DIMENSION STYLE MM/IN		SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION				
						DRAWN BY MSIBARRA DATE 2009/09/16		TITLE SALES ASSEMBLY- LEADFREE Z AXIS PLUGGABLE PCB CONNECTOR MOLEX INCORPORATED						
						CHECKED BY BBARKER DATE 2009/09/16								
						APPROVED BY SMILLER DATE 2009/09/16								
						MATERIAL NO.					DOCUMENT NO.		SHEET NO.	
						SIZE C								
						SEE TABLE		SD-74441-004			2 OF 6			
			</											



20 CIRCUIT MOTHER BOARD RECOMMENDED PCB LAYOUT



INITIAL RELEASE EC NO: UCP2010-0714 DRAWN:MSIBARRA 2009/09/16 CHKD:BBARKER 2009/09/16 APPR:SMILLER 2009/09/16 A	DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 8:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
				mm	INCH	DRAWN BY MSIBARRA	DATE 2009/09/16	TITLE SALES ASSEMBLY- LEADFREE Z AXIS PLUGGABLE PCB CONNECTOR	MOLEX MOLEX INCORPORATED	SHEET NO. 3 OF 6
			4 PLACES	± ---	± ---	CHECKED BY BBARKER	DATE 2009/09/16			
			3 PLACES	± ---	± ---					
			2 PLACES	± ---	± ---	APPROVED BY SMILLER	DATE 2009/09/16			
			1 PLACE	± ---	± ---	MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-74441-004		
			ANGULAR ±1/2°		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE C	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX. INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		



DETAIL B
SCALE 24:1

30 CIRCUIT MOTHER BOARD RECOMMENDED PCB LAYOUT

INITIAL RELEASE EC NO: UCP2010-0714 2009/09/16 DRWN:MSIBARRA 2009/09/24 CHKD:BBARKER 2009/09/24 APPR:SMILLER		DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 6:1	DESIGN UNITS METRIC	 THIRD ANGLE PROJECTION	TITLE SALES ASSEMBLY- LEADFREE Z AXIS PLUGGABLE PCB CONNECTOR MOLEX MOLEX INCORPORATED			
				mm INCH		DRAWN BY DATE MSIBARRA 2009/09/16		APPROVED BY DATE SMILLER 2009/09/16				DOCUMENT NO. SD-74441-004		SHEET NO. 4 OF 6
				4 PLACES ± --- ± ---		CHECKED BY DATE BBARKER 2009/09/16								
				3 PLACES ± --- ± ---		2 PLACES ± --- ± ---								
A		REV		2 PLACES ± --- ± ---		1 PLACE ± --- ± ---		ANGULAR ±1/2°		SIZE C	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				SEE TABLE										



DETAIL C
SCALE 24:1

40 CIRCUIT MOTHER BOARD RECOMMENDED PCB LAYOUT

INITIAL RELEASE EC NO: UCP2010-0714 DRAWN BY: MS IBARRA 2009/09/16 CHKD BY: BBARKER 2009/09/24 APPR: SMILLER 2009/09/24 A	DESCRIPTION	QUALITY SYMBOLS F=0 E=0 F=0	GENERAL TOLERANCES (UNLESS SPECIFIED)			DIMENSION STYLE MM/IN		SCALE 6:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
				mm	INCH	DRAWN BY MS IBARRA	DATE 2009/09/16	TITLE SALES ASSEMBLY- LEADFREE Z AXIS PLUGGABLE PCB CONNECTOR			
			4 PLACES	± ---	± ---	CHECKED BY BBARKER	DATE 2009/09/16				
			3 PLACES	± ---	± ---	APPROVED BY SMILLER	DATE 2009/09/16				
			2 PLACES	± ---	± ---	MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-74441-004	SHEET NO. 5 OF 6		
	1 PLACE	± ---	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS							
	ANGULAR ±1/2°										
	REV	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru