




NOTES:

1. PERFORM CONTINUITY & HI-POT TESTING.
2. PACKAGE IN HEAT SEALED POLY BAG. TAG IN BAG WITH "AMPHENOL CONNEX, 135101-R2-XX.XX AND DATE CODE".
3. CABLE SHOULD HAVE TOLERANCE OF ± 0.25" UPTO 12 INCH LENGTH.  
± 0.50" FOR LONGER CABLES.

| 135101-R2-XX.XX   |     | REVISIONS      |           |     |      |
|-------------------|-----|----------------|-----------|-----|------|
| DRAWING NO.       | REV | DESCRIPTION    | DATE      | ECO | APPR |
| THIRD ANGLE PROJ. | A   | RELEASE TO MFG | 19-Mar-10 | --  | CL   |



| LENGTH TABLE    |              |
|-----------------|--------------|
| PART NUMBER     | LENGTH (IN.) |
| 135101-R2-03.00 | 3.00         |
| 135101-R2-04.00 | 4.00         |
| 135101-R2-05.00 | 5.00         |
| 135101-R2-06.00 | 6.00         |
| 135101-R2-07.00 | 7.00         |
| 135101-R2-08.00 | 8.00         |
| 135101-R2-09.00 | 9.00         |
| 135101-R2-10.00 | 10.00        |
| 135101-R2-11.00 | 11.00        |
| 135101-R2-12.00 | 12.00        |
| 135101-R2-18.00 | 18.00        |
| 135101-R2-24.00 | 24.00        |

DESIGN REQUIREMENTS:

- ☐ FREQUENCY \_\_\_\_\_ TO \_\_\_\_\_ GHz    ☒ CONTINUITY
- ☐ VSWR \_\_\_\_\_ : 1 MAX    ☒ HI-POT : 1000 VRMS
- ☐ INS. LOSS \_\_\_\_\_ dB MAX    ☐ OTHER

| 009-881-396 | A/R | 2    | CONFORMABLE 0.141" CABLE |        |
|-------------|-----|------|--------------------------|--------|
| 132102      | 2   | 1    | SMA STR PLUG             |        |
| PART NUMBER | QTY | ITEM | DESCRIPTION              | FINISH |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |           |                                                         |                   |                                                                                               |          |                    |        |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|---------------------------------------------------------|-------------------|-----------------------------------------------------------------------------------------------|----------|--------------------|--------|
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:<br>2 PLACE DECIMAL    3 PLACE DECIMAL    ANGLES<br>±.015 (0,381 mm)    ±.005 (0,127 mm)    ± 1°                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | MATERIAL  | DRAWN<br>CLEMENT                                        | DATE<br>19-Mar-10 | TITLE<br>SMA STR PLUG TO<br>SMA STR PLUG, USING<br>0.141" CONFORMABLE CABLE,<br>XX.XX" LENGTH |          | Amphenol<br>Connex |        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | REFERENCE | ENGINEER<br>CLEMENT                                     | DATE<br>19-Mar-10 |                                                                                               |          |                    |        |
| NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data. |           | APPROVED                                                | DATE              | SCALE: 2:31                                                                                   |          | SHEET              | 1 OF 1 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |           | CAD FILE<br>Root folder:\Cable assembly\135101-R2-XX.XX | DWG SIZE<br>B     | DRAWING NO.<br>135101-R2-XX.XX                                                                | REV<br>A |                    |        |

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)