

FEATURES

- Rugged vitreous enamel coating withstands high humidity and temperature cycling.
- Durable construction, recommended for industrial applications where reliability is paramount.
- All-welded construction.
- Flame resistant lead free vitreous enamel coating.
- RoHS compliant; Add "E" suffix to part number to specify.

SPECIFICATIONS

Material

Coating: Conformal lead free vitreous enamel.

Core: Ceramic.

Terminals: Solder-coated axial.
RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu

Derating

Linearly from
100% @ +25°C to
0% @ +350°C.

Electrical

Tolerance: ±5% standard.
Other tolerances available.

Power rating: Based on 25°C free air rating (other wattages available).

Overload:

Under 7 watts: 5 times rated wattage for 5 seconds.
7 watts and over: 10 times rated wattage for 5 seconds.

Temperature coefficient:

1 to 9.99 ohms: ±50 ppm/°C
10 ohms and over: ±30 ppm/°C



20 Series

Vitreous Enamel Conformal Axial Terminal Wirewound, 5% Tolerance Standard



Series	Wattage	Ohms	Dimensions (in./mm max.)		Max. Volt. **	Lead ga.
			Length*	Diam.*		
21	1	1.0-3.0K	0.421 / 10.7	0.156 / 4.0	75	24
22	2	1.0-3.0K	0.421 / 10.7	0.219 / 5.6	65	20
23	3	0.1-10K	0.515 / 13.1	0.220 / 5.6	135	20
25	5	0.1-28K	1.015 / 25.8	0.276 / 7.0	330	20
27	7	0.1-25K	1.265 / 32.1	0.394 / 10.0	450	20
20	10	0.1-100K	1.859 / 47.2	0.394 / 10.0	720	20

12.5 watt size available on special order

*For units below 1Ω, add 15% to body diameter, 10% to body length.

**Maximum Voltage is based on Ohm's Law $[V = \sqrt{P \cdot R}]$ as limited by the resistance value of specified product

ORDERING INFORMATION

RoHS Compliant			
21JR10E			
20 Series	Wattage	Tolerance	Resistance Value
Vitreous Enamel	1 = 1W	J = 5%	R10 = 0.10Ω
Axial Lead	2		1R0 = 1.0Ω
Wirewound	3		10R = 10.0Ω
	5		250 = 250Ω
	7		1K0 = 1,000Ω
	0 = 10W		4K5 = 4,500Ω
			50K = 50,000Ω

Check product availability at ohmite.com

The 20 Series axial terminal resistors are both durable and economical. They have all the electrical attributes of the more expensive 90 Series resistors, including all-welded construction. They offer the durability of a lead free conformal vitreous enamel coating and are ideal for computer, communications and industrial applications in which cost, quality, and reliability are key considerations.

STANDARD PART NUMBERS FOR 20 SERIES

Ohmic value	Part No. Prefix Suffix	Wattage						Ohmic value	Part No. Prefix Suffix	Wattage						Ohmic value	Part No. Prefix Suffix	Wattage					
		1	2	3	5	7	10			1	2	3	5	7	10			1	2	3	5	7	10
0.10 — R10				✓	✓		✓	62 — 62R	✱	✱	✓	✓	✓	✱	✓	1,800 — 1K8		✓	✓	✓	✱	✱	✱
0.13 — R13				✓	✓		✓	68 — 68R	✓	✓	✓	✓	✓	✱	✓	2,000 — 2K0	✱	✓	✓	✓	✱	✱	✓
0.15 — R15				✓	✓		✓	75 — 75R	✓	✓	✓	✓	✓	✱	✓	2,200 — 2K2	✓	✓	✓	✓	✱	✓	✓
0.20 — R20				✓	✓		✓	82 — 82R	✓	✓	✓	✓	✓	✱	✓	2,500 — 2K5	✓	✓	✓	✓	✱	✓	✓
0.25 — R25				✓	✓		✓	100 — 100	✓	✱	✓	✓	✓	✓	✓	2,700 — 2K7	✓	✓	✓	✓	✱	✓	✓
0.30 — R30				✓	✓		✓	120 — 120	✓	✓	✓	✓	✓	✱	✓	3,000 — 3K0	✓	✓	✓	✓	✱	✓	✓
0.33 — R33				✓	✓		✓	125 — 125	✱	✱	✓	✓	✓	✱	✓	3,300 — 3K3				✓	✱	✱	✓
0.50 — R50				✓	✓		✓	150 — 150	✓	✓	✓	✓	✓	✱	✓	3,500 — 3K5				✓	✱	✱	✓
0.75 — R75				✓	✓		✓	180 — 180	✓	✓	✓	✓	✓	✱	✓	3,900 — 3K9				✓	✱	✱	✓
1 — 1R0	✓	✓	✓	✓	✓	✓	✓	200 — 200	✓	✓	✓	✓	✓	✓	✓	4,000 — 4K0				✓	✱	✱	✓
1.5 — 1R5	✓	✓	✓	✓	✓	✓	✓	220 — 220	✱	✓	✓	✓	✓	✱	✓	4,500 — 4K5				✓	✱	✱	✓
2 — 2R0	✓	✓	✓	✓	✓	✱	✓	225 — 225	✱	✱	✓	✓	✓	✱	✓	4,700 — 4K7				✓	✓	✱	✓
2.2 — 2R2	✓	✓	✓	✓	✓	✱	✓	250 — 250	✓	✓	✓	✓	✓	✱	✓	5,000 — 5K0				✓	✓	✓	✓
3 — 3R0	✓	✓	✓	✓	✓	✓	✓	270 — 270	✓	✓	✓	✓	✓	✱	✓	6,000 — 6K0				✓	✓	✓	✓
4 — 4R0	✓	✱	✓	✓	✓	✱	✓	300 — 300	✓	✓	✓	✓	✓	✱	✓	6,800 — 6K8				✓	✓	✱	✓
5 — 5R0	✓	✓	✓	✓	✓	✓	✓	330 — 330	✓	✓	✓	✓	✓	✓	✓	7,000 — 7K0				✓	✓	✱	✓
7.5 — 7R5	✓	✓	✓	✓	✓	✱	✓	350 — 350	✱	✓	✓	✓	✓	✱	✓	7,500 — 7K5				✓	✓	✓	✓
10 — 10R	✓	✓	✓	✓	✓	✱	✓	390 — 390	✓	✓	✓	✓	✓	✱	✓	8,000 — 8K0				✓	✓	✓	✓
12 — 12R	✱	✱	✓	✓	✓	✱	✓	400 — 400	✱	✱	✓	✓	✓	✓	✓	9,000 — 9K0				✓	✱	✱	✓
15 — 15R	✓	✱	✓	✓	✓	✓	✓	450 — 450	✱	✱	✓	✓	✓	✱	✓	10,000 — 10K				✓	✓	✱	✓
18 — 18R	✓	✱	✓	✓	✓	✓	✓	470 — 470	✓	✓	✓	✓	✓	✱	✓	12,000 — 12K				✓	✱	✓	✓
20 — 20R	✓	✓	✓	✓	✓	✱	✓	500 — 500	✓	✓	✓	✓	✓	✓	✓	13,000 — 13K					✓	✓	✓
22 — 22R	✓	✓	✓	✓	✓	✱	✓	560 — 560	✓	✓	✓	✓	✓	✱	✓	15,000 — 15K					✓	✱	✓
25 — 25R	✱	✓	✓	✓	✓	✱	✓	600 — 600	✓	✓	✓	✓	✓	✓	✓	17,000 — 17K					✓	✱	✓
27 — 27R	✓	✓	✓	✓	✓	✱	✓	680 — 680	✓	✱	✓	✓	✓	✓	✓	20,000 — 20K				✓	✓	✓	✓
30 — 30R	✓	✓	✓	✓	✓	✱	✓	750 — 750	✓	✓	✓	✓	✓	✱	✓	22,000 — 22K				✓	✓	✱	✓
33 — 33R	✓	✓	✓	✓	✓	✓	✓	800 — 800	✓	✓	✓	✓	✓	✱	✓	25,000 — 25K					✓	✱	✓
35 — 35R	✱	✱	✱	✓	✓	✱	✓	820 — 820	✓	✓	✓	✓	✓	✓	✓	30,000 — 30K						✓	✓
39 — 39R	✓	✓	✓	✓	✓	✱	✓	900 — 900	✱	✓	✓	✓	✓	✓	✓	33,000 — 33K						✓	✓
40 — 40R	✓	✱	✓	✓	✓	✱	✓	1,000 — 1K0	✓	✓	✓	✓	✓	✓	✓	35,000 — 35K						✓	✓
47 — 47R	✓	✓	✓	✓	✓	✱	✓	1,100 — 1K1	✱	✱	✓	✓	✓	✱	✓	40,000 — 40K							✓
50 — 50R	✓	✓	✓	✓	✓	✓	✓	1,200 — 1K2	✓	✓	✓	✓	✓	✓	✓	50,000 — 50K							✓
56 — 56R	✱	✓	✓	✓	✓	✱	✓	1,500 — 1K5	✓	✓	✓	✓	✓	✓	✓								✓

✓ = Standard values
✱ = Non-standard values subject to minimum handling charge per item

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru