

### LSP05 Module Series



#### Description

The Littelfuse LSP05 thermally protected Surge Protective Device is a self-protected device which is specially designed to be used in outdoor and commercial LED lighting fixtures for transient overvoltage protection. It is constructed with Littelfuse thermally protected varistor technology. Its built-in thermal disconnect function provides additional protection to prevent catastrophic failure and fire hazard even under the extreme circumstances of varistor end-of-life or sustaining over voltage conditions. The LSP05 SPD facilitates customer's product compliance to IEEE C62.41.2 Location Category C Low and US Dept of Energy MSSLC Model Spec.

#### Features

- Maximum Discharge Current, 10kA, 8/20us
- Meets ANSI C136.2/ IEEE C62.41.2 Location Category C Low Exposure
- Parallel connected SPD device
- Thermally protected Varistor technology
- IP66 Water-proof and Dust-proof
- Indication wire lead options for Parallel connected modules
- CE Compliance IEC61643-11 Class II/ EN61643-11 Type 2
- Compact form factor (48x48x30mm) with mounting tabs
- 240Vac and 277Vac voltage ratings are CE compliant and available for Class I and Class II installation based on IEC protection classes

#### Agency Approvals

| Agency  | Standard           | Agency File Number |
|---|--------------------|--------------------|
|  | UL1449 3rd Edition | E320116            |

#### Applications

- Outdoor and Commercial LED Lighting
- Roadway lighting
- Traffic lighting
- Digital signage
- Wash wall lighting
- Parking garage/lot lighting
- Flood lighting
- Tunnel lighting
- Street lighting

#### Additional Information



Datasheet



Resources



Samples

#### Notes:

1. These parts are in compliance with IEC61643-11 Class II (Low Voltage System) and EN61643-11 Type 2 (Low Voltage System).
2. Tested for temporary overvoltage from low-voltage system faults per IEC 61643-11

#### Absolute Maximum Ratings

• For ratings of individual members of a series, see Device Ratings and Specifications chart

|  | LSP05 Series | Units      |
|--|--------------|------------|
| <b>Continous:</b>  |              |            |
| <b>Steady State Applied Voltage:</b>                             |              |            |
| Max AC Voltage Range ( $V_{M(ACRMS)}$ )                          | 150 to 510   | V          |
| <b>Transient:</b>  |              |            |
| Maximum Discharge Current 8/20 $\mu$ s Waveform ( $I_{max}$ )    | 10,000       | A          |
| Nominal Discharge Current 8/20 $\mu$ s Waveform ( $I_n$ )        | 5,000        | A          |
| Operating Ambient Temperature Range ( $T_A$ )                    | -45 to +85   | °C         |
| Storage Temperature Range ( $T_{STG}$ )                          | -45 to +125  | °C         |
| Isolation Voltage Capability (When the thermal disconnect opens) | 600          | V          |
| Insulation Resistance  | >1,000       | M $\Omega$ |

**CAUTION:** Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

## LSP05 Series Device Ratings & Specifications

| Part Number | Operating Voltage (VAC) | MCOV/Uc (VAC) | Maximum Discharge Current (Imax)(A) <sup>2</sup> | Nominal Discharge Current (In)(A) <sup>1</sup> | MLV (V) <sup>3</sup>             | Up (V) <sup>4</sup> |
|-------------|-------------------------|---------------|--|--|----------------------------------|---------------------|
| LSP05120P   | 120                     | 150           | 10,000   | 5,000  | L-N:680<br>L-G:680<br>N-G:630    | 800                 |
| LSP05240P   | 240                     | 275           | 10,000   | 5,000  | L-N:1100<br>L-G:1100<br>N-G:1100 | 1200                |
| LSP05277P   | 277                     | 320           | 10,000   | 5,000  | L-N:1270<br>L-G:1270<br>N-G:1220 | 1400                |
| LSP05347P   | 347                     | 420           | 10,000   | 5,000  | L-N:1600<br>L-G:1600<br>N-G:1580 | 1700                |
| LSP05480P   | 480                     | 510           | 10,000   | 5,000  | L-N:1780<br>L-G:1780<br>N-G:1730 | 1900                |
| LSP05240LLP | L-L:240                 | L-L:275       | 10,000   | 5,000  | L-L:1100                         | L-L:1200            |
|             | L-N/G:120               | L-N/G:150     |  |  | L-N/G:680                        | L-N/G:800           |
| LSP05480LLP | L-L:480                 | L-L:510       | 10,000   | 5,000  | L-L:1780                         | L-L:1900            |
|             | L-N/G:277               | L-N/G:320     |  |  | L-N/G:1270                       | L-N/G:1400          |

Notes:

- Nominal Discharge Current (In)(A): The nominal discharge current is a measure of the SPDs endurance capability; 15 impulses of discharge current uses the 8/20us current waveform.
- Maximum Discharge Current (Imax)(A): The maximum discharge current is a measure of the SPDs maximum capability; single impulse of discharge current uses the 8/20us current waveform.
- MLV – UL1449 Measured limiting voltage; the highest value of residual voltage measurements during the application of impulses of 8/20us nominal discharge current (In); an average voltage value of 15 impulses
- Up – IEC 61643-11 Voltage protection level; the highest value of residual voltage measurements during the application of impulses of 8/20us nominal discharge current (In); a rounding voltage value of maximum measurement.

## Dimensions



Notes:

- Black: Line; White: Neutral; Green: Ground  
(P/N with suffix X3333/X3316: Brown: Line; Blue: Neutral; Green-Yellow stripe: Ground)
- Black: R1; Red: R2; Blue: R3
- Wire Gauge: AWG14 wire Line in, AWG22 Wire for indication; Wire Length: 100mm or customized

**Application/Installation Schematic**



Notes:  
1. LED indicator and associated circuitry are not included in the module.



**Part Numbering System**



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)