



### Main

|                               |                      |
|-------------------------------|----------------------|
| Range of product              | Harmony XB7          |
| Product or component type     | Pilot light          |
| Device short name             | XB7                  |
| Mounting diameter             | 0.87 in (22 mm)      |
| Sale per indivisible quantity | 10                   |
| Shape of signaling unit head  | Round                |
| Cap/operator or lens colour   | Green                |
| Light source                  | LED                  |
| Bulb base                     | Integral LED         |
| [Us] rated supply voltage     | 24 V AC/DC, 50/60 Hz |
| Device presentation           | Monolithic product   |

### Complementary

|                                        |                                                                                                                                                                                                                                                                                  |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Height                                 | 1.14 in (29 mm)                                                                                                                                                                                                                                                                  |
| Width                                  | 1.14 in (29 mm)                                                                                                                                                                                                                                                                  |
| Depth                                  | 2.13 in (54 mm)                                                                                                                                                                                                                                                                  |
| Terminals description ISO n°1          | (X1-X2)PL                                                                                                                                                                                                                                                                        |
| Product weight                         | 0.04 lb(US) (0.02 kg)                                                                                                                                                                                                                                                            |
| Device mounting                        | Fixing hole: Ø 0.89 in (22.5 mm) (22.3 +0.4/0) conforming to EN/IEC 60947-5-1                                                                                                                                                                                                    |
| Fixing center                          | >= 30 x 40 mm on support panel, metal, thickness: 0.04...0.24 in (1...6 mm)<br>>= 30 x 40 mm on support panel, plastic, thickness: 0.08...0.24 in (2...6 mm)                                                                                                                     |
| Fixing mode                            | Fixing nut beneath head recommended torque: 2...2.4 N.m                                                                                                                                                                                                                          |
| Connections - terminals                | Screw clamp terminals: <= 2 x 1.5 mm² with cable end conforming to EN/IEC 60947-1<br>Screw clamp terminals: 1 x 0.22...2 x 2.5 mm² without cable end conforming to EN/IEC 60947-1                                                                                                |
| Tightening torque                      | 7.08...10.62 lbf.in (0.8...1.2 N.m) conforming to EN 60947-1                                                                                                                                                                                                                     |
| Shape of screw head                    | Cross head compatible with JIS No 1 screwdriver<br>Cross head compatible with Philips no 1 screwdriver<br>Cross head compatible with pozidriv No 1 screwdriver<br>Slotted head compatible with flat Ø 4 mm screwdriver<br>Slotted head compatible with flat Ø 5.5 mm screwdriver |
| [Ui] rated insulation voltage          | 250 V (degree of pollution: 3) conforming to EN/IEC 60947-1                                                                                                                                                                                                                      |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN/IEC 60947-1                                                                                                                                                                                                                                                |
| Signalling type                        | Steady                                                                                                                                                                                                                                                                           |
| Supply voltage limits                  | 19.2...30 V DC<br>21.6...26.4 V AC                                                                                                                                                                                                                                               |
| Current consumption                    | 20...27 mA                                                                                                                                                                                                                                                                       |
| Service life                           | 70000 h at rated voltage and 25 °C                                                                                                                                                                                                                                               |

### Environment

|                                       |                                                                                       |
|---------------------------------------|---------------------------------------------------------------------------------------|
| protective treatment                  | TH                                                                                    |
| ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                            |
| ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                            |
| overvoltage category                  | Class II conforming to IEC 60536                                                      |
| IP degree of protection               | IP20 (rear face) conforming to IEC 60529<br>IP65 (front face) conforming to IEC 60529 |
| NEMA degree of protection             | NEMA 12 conforming to UL 50 E<br>NEMA 4 conforming to UL 50 E                         |
| standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>JIS C 4520                                      |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                               |                                                                                   |
|-------------------------------|-----------------------------------------------------------------------------------|
| vibration resistance          | 5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6                                 |
| shock resistance              | 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27 |
| electromagnetic compatibility | Disturbing field emission, class B conforming to EN 55011                         |

### Offer Sustainability


|                                                                                                                                  |                                                                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| WARNING: This product can expose you to chemicals including:                                                                     | WARNING: This product can expose you to chemicals including:                                                                     |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

### Pilot Light with Screw Terminal


#### Dimensions



e Support panel thickness: 1 to 6 mm/0.4 to 0.24 in. (metal), 2 to 6 mm/0.8 to 0.24 in. (plastic).


### Mounting

#### Diameter of Finished Fixing Holes




- (1) Minimum value.
- (2) 40 mm/1.58 in. for Emergency switching off pushbutton only.
- (3) Standard value: Ø 22.3 (0; + 0.4) mm/Ø 0.88 (0; + 0.02) in.

### Faston Clip Connection




### “U” Type Tag Connection

$\frac{\text{mm}}{\text{in.}}$



- (1) 6.5 mm/0.26 in. recommended, 7 mm/0.28 in. max.
- (2) M3 screw clamp terminal.

## Wiring Diagram



- (1) LED

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)