





RECESSED MOUNTING CONFIGURATION




RECOMMENDED PCB LAYOUT
COMPONENT SIDE VIEW










MOUNTING PANEL CUTOUT
(INTERNAL SIDE)



NOTE:
1. MATERIAL:
   HOUSING:NYLON GLASS-FIBER REINFORCED, UL94-V0,COLOR:BLACK.
   TERMINAL:PHOSPHOR BRONZE.
   METAL SHELL:FRONT SHELL:SUS 304
   BACK SHELL:BRASS
2. PLATING:
   TERMINAL:
   CONTACT AREA:SEE TABLE
   SOLDER TAIL:TIN PLATED(Sn)ALLOY.THICKNESS=75 MICROINCH MIN.
   UNDERPLATE:NICKEL(Ni),THICKNESS=50 MICROINCH MIN.
   SURFACE APPERANCE:BRIGHT.
   METAL SHELL:
   TIN PLATED (Sn) AT SOLDER AREA
   THICKNESS=100 MICROINCH MINIMUM.
   UNDER PLATE:NICKEL (Ni),(SOLDERING AVAILABLE)
   THICKNESS=50 MICROINCH MINIMUM.
   SURFACE APPEARANCE:BRIGHT.
3. RECOMMENDED PCB THICKESS:1.20±0.05MM
4. PROUDCT SPECIFICATION:REFER TO PS-67998-002
5. TEST SUMMARY:REFER TO TS-67298-007
6. PACKAGING SPECIFICATION:
   REFER TO PK-67298-003 FOR TRAY.
   REFER TO PK-67298-004 FOR TAPE & REEL.
7. LEAD FREE AND ROHS COMPLIANCE PRODUCT
8. FOR IR REFLOW PROCESS
9. WEEK CODE XXXXX
   YEAR, WEEK, FACTORY

PART NUMBER LEGEND

P/N	CONTACT PLATING	PACKAGE
67298-2090	GOLD FLASH	TRAY
67298-2091	30 MICROINCH GOLD	TRAY
67298-2190	GOLD FLASH	TAPE & REEL
67298-2191	30 MICROINCH GOLD	TAPE & REEL

L/F FOR 67298
EC NO: SH2005-0297 2005/05/06
DRWN: JCHEN12 2005/05/10
CH'KD: 2005/05/10
APPR: WWSCHANG
DESCRIPTION
REV B

QUALITY SYMBOLS
▼=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± 0.25	± ---
1 PLACE	± 0.25	± ---
ANGULAR ± 3 °		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE:
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: IVY-LIN DATE: 05/04/18
CHECKED BY: ALLEN DATE: 05/04/18
APPROVED BY: WWSCHANG DATE: 05/04/18
MATERIAL NO.: SEE TABLE

TITLE: USB DUAL STACKED A CONNECTOR (LEAD FREE VERSION)
MOLEX INCORPORATED
DOCUMENT NO.: SD-67298-007
SHEET NO.: 1 OF 1
SIZE: A4

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru