COMPACT POWER RELAY

1 POLE X 2—12A (28VDC) (FOR 24V BATTERY AUTOMOTIVE APPLICATIONS)

FBR572, 582 SERIES

■ FEATURES

- Two independent relays mounted in a single package (43% of the volume of the two FRL-270 relays)
- High current contact capacity (carrying current: 40 A/2 minutes, 30 A/1 hour)
- Suitable for controlling 24 V motors in trucks and other large vehicles
- High heat resistance and extended operating voltage
- Two types of contact gap (FBR572: 0.8 mm, FBR582: 1.4 mm)

■ ORDERING INFORMATION

[Example] FBR572 (a) N (b) D24 (c) – W (d) ** (e)

(a)	Series Name	FBR572: FBR572 Series relay (contact gap 0.8 mm) FBR582: FBR582 Series relay (contact gap 1.4 mm)
(b)	Structure	N : Plastic sealed type
(c)	Nominal Voltage	D24 : 24 VDC
(d)	Contact Material	W : Silver-tin oxide indium Y : Silver-tin oxide N : Silver copper nickel
(e)	Custom Designation	To be assigned custom specification

■ SPECIFICATIONS

Item			FBR570 Series	FBR580 Series
Contact	Arrangement		1 form C × 2 (SPDT ×2)	
	Material		Silver-tin oxide indium (–W type) Silver copper nickel (–N type)	Silver-tin oxide indium (–W type) Silver-tin oxide (–Y type)
	Voltage Drop (Resistance)		Maximum 100 mV (at 12 VDC 2 A)	
	Ratings		28 VDC 12 A (locked motor load) 28 VDC inrush 15 A, break 2.5 A (motor free load)	
	Maximum Carrying Current		40 A/2 minutes, 30 A/ 1 hour (25°C, 100% rated coil voltage)	
	Maximum Inrush Current (Reference)		–W,–Y type: 60 A –N type: 40 A	
	Max. Switching Current (Reference)		12 A 28 VDC	14 A 32 VDC
	Minimum Switching Load*1 (Reference)		–W, –Y Type: 6 VDC 1 A –N Type: 6 VDC 2 A	
Coil	Operating Temperature		–40°C to +85°C (no frost)	
	Storage Temperature		–40°C to +100°C (no frost)	
Time Value	Operate (at nominal voltage)		Maximum 10 ms	
	Release (at nominal voltage)		Maximum 5 ms	
Life	Mechanical		1×10^7 operations minimum	1×10^6 operations minimum
	Electrical		1×10^5 operations minimum (locked motor load) 5×10^5 operations minimum (motor free load)	1×10^5 operations minimum (locked motor load)
Other	Vibration Resistance		10 to 55 Hz (double amplitude of 1.5 mm)	
	Shock Resistance	Misoperation	100 m/s^2	
		Endurance	1,000 m/s^2	
	Weight		Approximately 18 g	

*1 Values when switching a resistive load at normal room temperature and humidity, and in a clean environment.
The minimum switching load varies with the switching frequency and operating environment.

■ COIL DATA CHART

ORDERING CODE	Rated coil voltage	Coil resistance (±10%)	Must operate voltage	Thermal resistance
FBR572ND24-W FBR572ND24-N	24 VDC	384 Ω	14.4 VDC (at 20°C)	67°C/W
FBR582ND24-W FBR582ND24-Y		170 Ω	18.0 VDC (at 85°C)	56°C/W

■ SUITABLE APPLICATIONS

Application	Normal load current		Life x 10^3	Recommended model (example)
Power Windows	10 to 12 A (switching at motor locking)		100	FBR572ND24-W
Automatic Door Lock	5 A/2 door (switching at motor locking)		100	FBR572ND24-W
Intermittent Wipers	INRUSH 15 to 30 A BREAK 2 to 8 (motor free)	Current wave 	300	FBR572ND24-W
				FBR572ND24-N

■ CHARACTERISTIC DATA

1. MAXIMUM BREAK CAPACITY



• Test circuit



2. LIFE TEST (EXAMPLE)

[FBR572 type]

• Test item
28 VDC-12 A
Motor lock
100,000 operations minimum
(FBR572 □-W type)

• Test circuit



• Current wave form



• Shift of pick-up drop-out voltage



• Shift of contact resistance

(measured at 6 V-1 A)



[FBR582 type]

• Test item
28 VDC-12 A
Motor lock
100,000 operations minimum
(FBR582□ -W type)

• Test circuit



• Current wave form



• Shift of pick-up drop-out voltage



• Shift of contact resistance

(measured at 6 V-1 A)



3. OPERATING COIL VOLTAGE RANGE

[FBR572 type]



[FBR582 type]



4. VIBRATION RESISTANCE CHARACTERISTICS



5. SHOCK RESISTANCE CHARACTERISTICS



■ REFERENCE DATA

[FBR572 type]



[FBR582 type]



■ DIMENSIONS

[FBR572 type]

● Dimensions



● PC board mounting hole layout (BOTTOM VIEW)



● Schematic
(BOTTOM VIEW)



● Tube carrier



20pieces/tube

Unit: mm

■ DIMENSIONS

[FBR582 type]

● Dimension



● PC board mounting hole layout (BOTTOM VIEW)



● Schematic
(BOTTOM VIEW)



● Tube carrier



20pieces/tube

Unit: mm

Fujitsu Components International Headquarter Offices

Japan
Fujitsu Component Limited
Gotanda-Chuo Building
3-5, Higashigotanda 2-chome, Shinagawa-ku
Tokyo 141, Japan
Tel: (81-3) 5449-7010
Fax: (81-3) 5449-2626
Email: promothq@ft.ed.fujitsu.com
Web: www.fcl.fujitsu.com

North and South America
Fujitsu Components America, Inc.
250 E. Caribbean Drive
Sunnyvale, CA 94089 U.S.A.
Tel: (1-408) 745-4900
Fax: (1-408) 745-4970
Email: marcom@fcai.fujitsu.com
Web: www.fcai.fujitsu.com

Europe
Fujitsu Components Europe B.V.
Diamantlaan 25
2132 WV Hoofddorp
Netherlands
Tel: (31-23) 5560910
Fax: (31-23) 5560950
Email: info@fceu.fujitsu.com
Web: www.fceu.fujitsu.com

Asia Pacific
Fujitsu Components Asia Ltd.
102E Pasir Panjang Road
#04-01 Citilink Warehouse Complex
Singapore 118529
Tel: (65) 6375-8560
Fax: (65) 6273-3021
Email: fcal@fcal.fujitsu.com
www.fcal.fujitsu.com

© 2005 Fujitsu Components America, Inc. All company and product names are trademarks or registered trademarks of their respective owners. Rev. 02/25/2005.

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru