

f	0	0	0	0	0	0	0	0	0	0	0				0	0	0	0	0	0	0	0	0	0	0	0
e	A	7	7	7	7	7	7	7	7	7	7				7	7	7	7	7	7	7	7	7	7	7	7
d	7	7	7	7	7	7	7	7	7	7	7				7	7	7	7	7	7	7	7	7	7	7	7
c	7	7	7	7	7	7	7	7	7	7	7				7	7	7	7	7	7	7	7	7	7	7	7
b	7	7	7	7	7	7	7	7	7	7	7				7	7	7	7	7	7	7	7	7	7	7	7
a	A	7	7	7	7	7	7	7	7	7	7				7	7	7	7	7	7	7	7	7	7	7	7
z	0	0	0	0	0	0	0	0	0	0	0				0	0	0	0	0	0	0	0	0	0	0	0
P	0	0				1				1				2				2								
O	1	5				0				5				0				5								

Technical drawings of the connector showing side and top views with dimensions and notes.

Side View (Left):

- Overall height: $13.45^{+0.15}_{-0.10}$
- Base height: $3.00^{+0}_{-0.10}$
- Top flange width: 15.40 ± 0.50
- Internal feature width: 11.70 ± 0.10 (NOTE 3)
- Pin pitch: 2.00 ± 0.05 (10x)
- Pin height: 2.00 ± 0.05 (4x)
- NOTE 6 points to the top flange.

Top View (Right):

- Overall width: 50.0 MAX
- Pin pitch: 2.00 ± 0.05 (10x)
- Pin height: 2.00 ± 0.05 (10x)
- NOTE 5 points to the top flange.

Technical drawing showing two views of a connector assembly, labeled 7 and A.

View 7 (top) shows a side profile of the connector. The dimensions are:

- 8.20 (distance from the left end to the center of the connector)
- 13.00 (distance from the center of the connector to the right end)

View A (bottom) shows a side profile of the connector. The dimensions are:

- 9.70 (distance from the left end to the center of the connector)
- 13.00 (distance from the center of the connector to the right end)

A vertical line indicates the SEATING PLANE FOR CONNECTOR, which is the center of the connector.

PLATING CODE (DIGIT 13 AND 14)
(REF DRW NO. BS,C , 201844 , 003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001

[illegible]

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru