

# Fluke 971

## Temperature Humidity Meter

### Technical Data



Quickly take accurate humidity and temperature readings in the air. Temperature and humidity are two important factors in maintaining optimal comfort levels and good indoor air quality. The Fluke 971 is

invaluable for facility maintenance and utility technicians, HVAC-service contractors, and specialists who assess indoor air quality (IAQ). Lightweight, rugged, and easy to hold, the Fluke 971 is the perfect tool for monitoring problem areas.

#### The Fluke 971 has:

- Backlit dual display of humidity and temperature
- 99 record storage capacity
- Ergonomic design with belt clip and protective holster
- Quick-response capacitance sensor with twist-open protective cover

#### General Features

- Compact and lightweight (190 g/6.7 oz)
- Temperature range from -20 °C to 60 °C (-4 °F to 140 °F)
- Measures dew point and wet bulb
- Relative humidity from 5 % to 95 %
- Min/Max/Avg data hold
- Low battery indicator

#### Specifications

|                                      |   |
|--------------------------------------|---|
| <b>Temperature range</b>             | -20 °C to 60 °C (-4 °F to 140 °F)                         |
| <b>Temperature accuracy</b>          |   |
| 0 °C to 45 °C                        | ± 0.5 °C  |
| -20 °C to 0 °C and 45 °C to 60 °C    | ± 1.0 °C  |
| 32 °F to 113 °F                      | ± 1.0 °F  |
| -4 °F to 32 °F and 113 °F to 140 °F  | ± 2.0 °F  |
| <b>Resolution</b>                    | 0.1 °C / 0.1 °F   |
| <b>Temperature update rate</b>       | 500 ms  |
| <b>Temperature sensor type</b>       | NTC   |
| <b>Relative humidity range</b>       | 5 % to 95 % R.H.  |
| <b>Relative humidity accuracy</b>    |   |
| 10 % to 90 % R.H. @ 23 °C (73.4 °F)  | ± 2.5 % R.H.  |
| <10 %, > 90 % R.H. @ 23 °C (73.4 °F) | ± 5.0 % R.H.  |
| <b>Resolution</b>                    | 0.1 % R.H.  |
| <b>Response time (humidity)</b>      | For 90 % of total range - 60 sec. with 1 m/s air movement |
| <b>Humidity sensor</b>               | Electronic capacitance polymer film sensor                |
| <b>Data storage</b>                  | 99 points   |

**Specifications** cont.

|                              |   |
|------------------------------|---|
| <b>Operating temperature</b> |   |
| Temperature                  | -20 °C to 60 °C (-4 °F to 140 °F)                                       |
| Humidity                     | 0 °C to 55 °C (32 °F to 131 °F)   |
| <b>Storage temperature</b>   | -20 °C to 60 °C (-4 °F to 140 °F) at < 80 % R.H. (with battery removed) |
| <b>Weight</b>                | 190 g (6.7 oz)  |
| <b>Dimensions (HxWxD)</b>    | 194 mm x 60 mm x 34 mm (7.6 in x 2.4 in x 1.3 in)                       |
| <b>Battery type</b>          | 4 AAA alkaline batteries  |
| <b>Battery life</b>          | 200 Hours   |
| <b>Safety approval</b>       | Electromagnetic compatibility: Complies with EN 61326-1                 |
| <b>Warranty</b>              | 12 months   |

\* Humidity sensor hysteresis (excursion of 10 % to 90 % to 10 % R.H.): ± 1 % R.H. with 1 m/s air movement  
 \* Temperature coefficient: 0.1 times the applicable accuracy specification per °C from 0 °C to 18 °C and 28 °C to 50 °C (32 °F to 64 °F and 83 °F to 122 °F)

**Other IAQ Tools from Fluke**

**Fluke 983 Particle Counter**

- Simultaneous display of six size channels on a bright, backlit LCD
- 5000 sample record capacity
- Logged samples include date, time, particle counts, sample volume, temperature and relative humidity
- Rechargeable NiMH battery providing up to 8 hours continuous operation
- Selectable sample time, count data, programmable delay
- Built-in relative humidity and temperature sensors



**CO-210 Carbon Monoxide Probe**

- Use as an accessory to a digital multimeter with DC millivolt inputs
- Displays CO level readings from 0 to 999 ppm, with a resolution of 1 ppm and accuracy of ± 3 %.
- Also used as a standalone device with an LED indicator and beeper that triggers with increasing frequency as CO levels rise.



**CO-205 Aspirator Kit**

The CO-205 flue gas sampling accessory kit contains all the components necessary to provide a clean sample for the Fluke family of gas measuring devices. The CO-205 accessory kit includes:

- Stainless steel sampling tube
- Industrial-grade hand operated aspirator to draw flue sample
- Easily replaceable particulate filter
- Specially designed nose cap for connection to the Fluke CO-210/CO-220.



**CO-220 Carbon Monoxide Meter**

- Standalone CO meter that does not require a digital multimeter
- Large backlit LCD displays CO levels from 0 to 1000 ppm.
- Beeper triggers with increasing frequency as CO levels rise.
- MAX hold function stores and displays the maximum CO level.
- Automatic sensor zeroing and self-test upon startup.



**Fluke.** *Keeping your world up and running.*

**Fluke Corporation**  
 PO Box 9090, Everett, WA USA 98206  
 Fluke Europe B.V.  
 PO Box 1186, 5602 BD  
 Eindhoven, The Netherlands  
 For more information call:  
 In the U.S.A. (800) 443-5853 or  
 Fax (425) 446-5116  
 In Europe/M-East/Africa (31 40) 2 675 200 or  
 Fax (31 40) 2 675 222  
 In Canada (800) 36-FLUKE or  
 Fax (905) 890-6866  
 From other countries +1 (425) 446-5500 or  
 Fax +1 (425) 446-5116  
 Web access: <http://www.fluke.com>

©2005 Fluke Corporation. All rights reserved.  
 Printed in U.S.A. 11/2005 2457037 D-EN-N Rev C

**Ordering Information**

- Fluke-971** Temperature Humidity Meter
- Fluke-983** Particle Counter
- Fluke-CO-205** Aspirator Kit
- Fluke-CO-210** Carbon Monoxide Probe
- Fluke-CO-220** Carbon Monoxide Meter

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)