

# Type 930C, Metallized Polypropylene Capacitors for DC Filtering

## Low Dissipation, General Purpose



Type 930C metallized polypropylene capacitors are designed for general purpose filtering applications. Their stability and low loss characteristics make them an excellent choice for blocking, filtering, bypassing, coupling and decoupling applications. This Series is UL recognized for construction only under UL File Number E128034(N).

### Highlights


- Low dissipation factor
- Self healing
- UL recognized

### Specifications

|                                               |                                                                                             |
|-----------------------------------------------|---------------------------------------------------------------------------------------------|
| Capacitance Range                             | 0.22 to 10.0 $\mu$ F                                                                        |
| Capacitance Tolerance                         | $\pm 10\%$ (K) Standard; $\pm 5\%$ (J) Optional                                             |
| Rated Voltage                                 | 100 to 630 Vdc (70 to 250 Vac, 60 Hz)                                                       |
| Operating Temperature Range with Ripple       | -55 °C to 105 °C*<br>*Full rated voltage at 85 °C - derated linearly to 50% rated at 105 °C |
| Maximum rms Current                           | Check tables for values                                                                     |
| Insulation Resistance                         | 200,000 M $\Omega$ x $\mu$ F                                                                |
| Test Voltage between Terminals @ 25 °C        | 200% rated DC voltage for 60 s                                                              |
| Test Voltage between Terminals & Case @ 25 °C | 3 kVac @ 50/60 Hz for 60 s                                                                  |
| Life Test                                     | 1,000 h @ 85 °C, 125% rated DC voltage                                                      |
| Life Expectancy                               | 60,000 h @ rated Vdc, 70 °C<br>30,000 h @ rated Vac, 70 °C                                  |
| RoHS Compliant                                |                                                                                             |


### Dimensions

#### Construction Diagram



#### Construction Details

|                   |                           |
|-------------------|---------------------------|
| Case Material     | UL510 Polyester Tape Wrap |
| Resin Material    | UL94V-0 Epoxy Fill        |
| Terminal Material | Tin Plated Copper         |



# Type 930C, Metallized Polypropylene Capacitors for DC Filtering

## Low Dissipation, General Purpose

### Part Numbering System

|        |                      |                                                          |                                           |                                      |                     |                          |
|--------|----------------------|----------------------------------------------------------|-------------------------------------------|--------------------------------------|---------------------|--------------------------|
| 930    | C                    | 1                                                        | P                                         | 22                                   | K                   | -F                       |
| Series | Termination Code     | Voltage Code                                             | Capacitance Decimal Point                 | Capacitance Significant Figures (μF) | Tolerance Code      | RoHS Compliant Indicator |
| 930    | C = Bare Copper Wire | 1 = 100 Vdc<br>2 = 250 Vdc<br>4 = 400 Vdc<br>6 = 630 Vdc | S = 0.0<br>P = 0.<br>W = No decimal point |                                      | K = ±10%<br>J = ±5% |                          |

### Ratings

**NOTE:** Other ratings, sizes and performance specifications are available. Contact us.

| Cap.<br>(μF)      | Catalog<br>Part Number | D<br>mm | L<br>mm | ESR<br>20-100 kHz<br>(mΩ) | dV/dt<br>(V/μs) | Max. Ripple Current (A) 20 kHz |       |                  |       |       |       |       |
|-------------------|------------------------|---------|---------|---------------------------|-----------------|--------------------------------|-------|------------------|-------|-------|-------|-------|
|                   |                        |         |         |                           |                 | 25 °C                          | 35 °C | Case Temperature |       |       |       |       |
|                   |                        |         |         |                           |                 |                                |       | 45 °C            | 55 °C | 65 °C | 75 °C | 85 °C |
| 100 Vdc (70 Vac)  |                        |         |         |                           |                 |                                |       |                  |       |       |       |       |
| .22               | 930C1P22K-F            | 7.0     | 19.0    | ---                       | 25              | 2.3                            | 2.3   | 2.3              | 2.3   | 2.3   | 1.8   | 1.0   |
| .27               | 930C1P27K-F            | 7.6     | 19.0    | ---                       | 25              | 2.6                            | 2.6   | 2.6              | 2.6   | 2.4   | 1.9   | 1.1   |
| .33               | 930C1P33K-F            | 8.2     | 19.0    | ---                       | 25              | 2.8                            | 2.8   | 2.8              | 2.8   | 2.6   | 2.2   | 1.2   |
| .39               | 930C1P39K-F            | 8.8     | 19.0    | ---                       | 25              | 3.1                            | 3.1   | 3.1              | 3.1   | 2.9   | 2.3   | 1.3   |
| .47               | 930C1P47K-F            | 9.5     | 19.0    | 37                        | 25              | 3.7                            | 3.4   | 3.1              | 2.8   | 2.5   | 2.0   | 1.4   |
| .56               | 930C1P56K-F            | 8.2     | 25.4    | 35                        | 14              | 3.9                            | 3.6   | 3.3              | 2.9   | 2.6   | 2.1   | 1.5   |
| .68               | 930C1P68K-F            | 8.8     | 25.4    | 33                        | 14              | 4.1                            | 3.8   | 3.5              | 3.1   | 2.8   | 2.2   | 1.6   |
| .82               | 930C1P82K-F            | 9.6     | 25.4    | 31                        | 14              | 4.3                            | 4.0   | 3.6              | 3.2   | 2.9   | 2.3   | 1.7   |
| 1.00              | 930C1W1K-F             | 10.7    | 25.4    | 26                        | 14              | 5.5                            | 5.1   | 4.7              | 4.2   | 3.6   | 2.8   | 2.6   |
| 1.20              | 930C1W1P2K-F           | 11.5    | 25.4    | 24                        | 14              | 5.7                            | 5.3   | 4.9              | 4.4   | 3.8   | 3.0   | 2.8   |
| 1.50              | 930C1W1P5K-F           | 12.7    | 25.4    | 20                        | 14              | 6.1                            | 5.5   | 5.1              | 4.6   | 4.0   | 3.2   | 3.1   |
| 1.80              | 930C1W1P8K-F           | 13.7    | 25.4    | 19                        | 14              | 6.3                            | 5.7   | 5.3              | 4.8   | 4.1   | 3.4   | 3.0   |
| 2.00              | 930C1W2K-F             | 12.3    | 31.7    | 18                        | 10              | 6.5                            | 6.0   | 5.5              | 4.9   | 4.2   | 3.5   | 3.2   |
| 2.20              | 930C1W2P2K-F           | 12.9    | 31.7    | 18                        | 10              | 6.8                            | 6.3   | 5.7              | 2.1   | 4.4   | 3.6   | 3.3   |
| 2.70              | 930C1W2P7K-F           | 14.1    | 31.7    | 17                        | 10              | 7.1                            | 6.5   | 6.0              | 5.3   | 4.6   | 3.7   | 3.4   |
| 3.00              | 930C1W3K-F             | 14.8    | 31.7    | 16                        | 10              | 7.3                            | 6.7   | 6.2              | 5.5   | 4.8   | 3.9   | 3.5   |
| 3.30              | 930C1W3P3K-F           | 15.4    | 31.7    | 16                        | 10              | 7.4                            | 6.8   | 6.4              | 5.6   | 4.9   | 4.0   | 3.6   |
| 3.90              | 930C1W3P9K-F           | 16.6    | 31.7    | 15                        | 10              | 7.6                            | 6.9   | 6.6              | 5.8   | 5.1   | 4.1   | 3.7   |
| 4.00              | 930C1W4K-F             | 13.6    | 44.4    | 15                        | 6               | 7.8                            | 7.0   | 6.7              | 5.9   | 5.2   | 4.2   | 3.8   |
| 4.70              | 930C1W4P7K-F           | 14.7    | 44.4    | 15                        | 6               | 8.1                            | 7.4   | 6.8              | 6.0   | 5.3   | 4.3   | 3.9   |
| 5.00              | 930C1W5K-F             | 15.1    | 44.4    | 14                        | 6               | 8.3                            | 7.6   | 7.0              | 6.2   | 5.4   | 4.4   | 4.0   |
| 5.60              | 930C1W5P6K-F           | 15.8    | 44.4    | 14                        | 6               | 8.4                            | 7.7   | 7.1              | 6.4   | 5.5   | 4.5   | 4.1   |
| 6.00              | 930C1W6K-F             | 16.4    | 44.4    | 14                        | 6               | 8.5                            | 7.8   | 7.2              | 6.5   | 5.6   | 4.6   | 4.2   |
| 6.80              | 930C1W6P8K-F           | 17.3    | 44.4    | 13                        | 6               | 8.5                            | 8.0   | 7.4              | 6.7   | 5.7   | 4.7   | 4.3   |
| 8.00              | 930C1W8K-F             | 18.7    | 44.4    | 13                        | 6               | 8.6                            | 8.3   | 7.7              | 6.8   | 6.0   | 4.8   | 4.4   |
| 8.20              | 930C1W8P2K-F           | 18.9    | 44.4    | 13                        | 6               | 8.8                            | 8.6   | 8.0              | 7.0   | 6.1   | 4.9   | 4.5   |
| 10.00             | 930C1W10K-F            | 20.7    | 44.4    | 12                        | 6               | 9.0                            | 9.0   | 8.5              | 7.6   | 6.6   | 5.4   | 4.9   |
| 250 Vdc (175 Vac) |                        |         |         |                           |                 |                                |       |                  |       |       |       |       |
| .10               | 930C2P1K-F             | 8.0     | 19.0    | ---                       | 37              | 1.5                            | 1.5   | 1.5              | 1.5   | 1.5   | 1.5   | .09   |
| .12               | 930C2P12K-F            | 8.0     | 19.0    | ---                       | 37              | 1.9                            | 1.9   | 1.9              | 1.9   | 1.9   | 1.7   | 1.0   |
| .15               | 930C2P15K-F            | 8.5     | 19.0    | ---                       | 37              | 2.3                            | 2.3   | 2.3              | 2.3   | 2.3   | 1.9   | 1.1   |
| .18               | 930C2P18K-F            | 9.0     | 19.0    | ---                       | 37              | 2.7                            | 2.7   | 2.7              | 2.7   | 2.5   | 2.0   | 1.2   |

# Type 930C, Metallized Polypropylene Capacitors for DC Filtering

## Low Dissipation, General Purpose

| Cap.<br>( $\mu$ F) | Catalog<br>Part Number | D<br>mm | L<br>mm | ESR<br>20-100 kHz<br>(m $\Omega$ ) | dV/dt<br>(V/ $\mu$ s) | Max. Ripple Current (A) 20 kHz |       |       |       |       |       |       |
|--------------------|------------------------|---------|---------|------------------------------------|-----------------------|--------------------------------|-------|-------|-------|-------|-------|-------|
|                    |                        |         |         |                                    |                       | Case Temperature               |       |       |       |       |       |       |
|                    |                        |         |         |                                    |                       | 25 °C                          | 35 °C | 45 °C | 55 °C | 65 °C | 75 °C | 85 °C |
| 250 Vdc (175 Vac)  |                        |         |         |                                    |                       |                                |       |       |       |       |       |       |
| .22                | 930C2P22K-F            | 8.5     | 25.4    | ---                                | 21                    | 1.9                            | 1.9   | 1.9   | 1.9   | 1.9   | 1.9   | 1.3   |
| .27                | 930C2P27K-F            | 8.5     | 25.4    | ---                                | 21                    | 2.4                            | 2.4   | 2.4   | 2.4   | 2.4   | 2.2   | 1.4   |
| .33                | 930C2P33K-F            | 9.2     | 25.4    | ---                                | 21                    | 2.9                            | 2.9   | 2.9   | 2.9   | 2.9   | 2.3   | 1.5   |
| .39                | 930C2P39K-F            | 9.9     | 25.4    | ---                                | 21                    | 3.4                            | 3.4   | 3.4   | 3.2   | 2.9   | 2.3   | 1.6   |
| .47                | 930C2P47K-F            | 10.7    | 25.4    | 35                                 | 21                    | 3.8                            | 3.7   | 3.6   | 3.4   | 2.9   | 2.4   | 1.7   |
| .56                | 930C2P56K-F            | 11.8    | 25.4    | 33                                 | 21                    | 3.9                            | 3.8   | 3.7   | 3.5   | 3.1   | 2.5   | 1.8   |
| .68                | 930C2P68K-F            | 12.0    | 31.7    | 32                                 | 15                    | 4.0                            | 3.9   | 3.8   | 3.7   | 3.2   | 2.6   | 1.9   |
| .82                | 930C2P82K-F            | 12.0    | 31.7    | 31                                 | 15                    | 4.2                            | 4.1   | 4.0   | 3.9   | 3.4   | 2.8   | 2.0   |
| 1.00               | 930C2W1K-F             | 13.0    | 32.0    | 28                                 | 15                    | 4.4                            | 4.4   | 4.4   | 4.4   | 4.3   | 3.5   | 3.2   |
| 1.20               | 930C2W1P2K-F           | 14.1    | 32.0    | 27                                 | 15                    | 4.7                            | 4.6   | 4.5   | 5.0   | 4.5   | 3.7   | 3.3   |
| 1.50               | 930C2W1P5K-F           | 15.6    | 32.0    | 26                                 | 15                    | 5.1                            | 5.0   | 4.9   | 4.4   | 4.7   | 3.9   | 3.5   |
| 1.80               | 930C2W1P8K-F           | 16.9    | 31.7    | 25                                 | 15                    | 5.9                            | 5.8   | 5.7   | 5.7   | 5.0   | 4.1   | 3.7   |
| 2.00               | 930C2W2K-F             | 17.8    | 31.7    | 21                                 | 15                    | 7.2                            | 7.2   | 6.8   | 6.0   | 5.2   | 4.3   | 3.9   |
| 2.20               | 930C2W2P2K-F           | 16.5    | 44.4    | 20                                 | 9.0                   | 8.4                            | 7.5   | 7.0   | 6.3   | 5.4   | 4.5   | 4.1   |
| 2.70               | 930C2W2P7K-F           | 17.0    | 44.4    | 19                                 | 9.0                   | 8.6                            | 7.8   | 7.3   | 6.6   | 5.7   | 4.7   | 4.3   |
| 3.00               | 930C2W3K-F             | 17.8    | 44.4    | 18                                 | 9.0                   | 9.0                            | 8.3   | 7.6   | 6.8   | 5.9   | 4.8   | 4.4   |
| 3.30               | 930C2W3P3K-F           | 18.6    | 44.4    | 18                                 | 9.0                   | 9.0                            | 8.4   | 7.8   | 7.0   | 6.0   | 4.9   | 4.5   |
| 3.90               | 930C2W3P9K-F           | 20.2    | 44.4    | 17                                 | 9.0                   | 9.0                            | 8.5   | 8.0   | 7.2   | 6.2   | 5     | 4.6   |
| 4.00               | 930C2W4K-F             | 20.4    | 44.4    | 16                                 | 9.0                   | 9.0                            | 8.5   | 8.2   | 7.4   | 6.3   | 5.1   | 4.7   |
| 4.70               | 930C2W4P7K-F           | 22.0    | 44.4    | 16                                 | 9.0                   | 9.0                            | 8.8   | 8.5   | 7.7   | 6.6   | 5.3   | 4.9   |
| 5.00               | 930C2W5K-F             | 22.6    | 44.4    | 15                                 | 9.0                   | 9.0                            | 9.0   | 8.8   | 7.9   | 6.8   | 5.6   | 5.1   |
| 5.60               | 930C2W5P6K-F           | 23.9    | 44.4    | 15                                 | 9.0                   | 9.0                            | 9.0   | 8.9   | 8.0   | 7.0   | 5.8   | 5.3   |
| 6.00               | 930C2W6K-F             | 24.7    | 44.4    | 15                                 | 9.0                   | 9.0                            | 9.0   | 9.0   | 8.2   | 7.2   | 5.9   | 5.5   |
| 6.80               | 930C2W6P8K-F           | 22.4    | 57.1    | 15                                 | 9.0                   | 9.0                            | 9.0   | 9.0   | 8.4   | 7.4   | 6.0   | 5.6   |
| 8.00               | 930C2W8K-F             | 24.2    | 57.1    | 14                                 | 9.0                   | 9.0                            | 9.0   | 9.0   | 8.7   | 7.8   | 6.3   | 5.8   |
| 8.20               | 930C2W8P2K-F           | 24.5    | 57.1    | 14                                 | 9.0                   | 9.0                            | 9.0   | 9.0   | 8.8   | 7.9   | 6.4   | 5.9   |
| 10.00              | 930C2W10K-F            | 26.9    | 57.1    | 13                                 | 9.0                   | 9.0                            | 9.0   | 9.0   | 9.0   | 8.3   | 6.8   | 6.2   |
| 400 Vdc (250 Vac)  |                        |         |         |                                    |                       |                                |       |       |       |       |       |       |
| .047               | 930C4S47K-F            | 8.0     | 19.0    | ---                                | 49                    | 1.0                            | 1.0   | 1.0   | 1.0   | 1.0   | 1.0   | 0.9   |
| .056               | 930C4S56K-F            | 8.0     | 19.0    | ---                                | 49                    | 1.1                            | 1.1   | 1.1   | 1.1   | 1.1   | 1.1   | 0.9   |
| .068               | 930C4S68K-F            | 8.0     | 19.0    | ---                                | 49                    | 1.4                            | 1.4   | 1.4   | 1.4   | 1.4   | 1.4   | 1.0   |
| .082               | 930C4S82K-F            | 8.1     | 19.0    | ---                                | 49                    | 1.7                            | 1.7   | 1.7   | 1.7   | 1.7   | 1.6   | 1.1   |
| .10                | 930C4P1K-F             | 8.8     | 19.0    | ---                                | 49                    | 2.0                            | 2.0   | 2.0   | 2.0   | 2.0   | 1.9   | 1.3   |
| .12                | 930C4P12K-F            | 7.6     | 25.4    | ---                                | 28                    | 1.4                            | 1.4   | 1.4   | 1.4   | 1.4   | 1.4   | 1.4   |
| .15                | 930C4P15K-F            | 8.5     | 25.4    | ---                                | 28                    | 1.7                            | 1.7   | 1.7   | 1.7   | 1.7   | 1.7   | 1.6   |
| .18                | 930C4P18K-F            | 9.0     | 25.4    | ---                                | 28                    | 2.1                            | 2.1   | 2.1   | 2.1   | 2.1   | 2.1   | 1.7   |
| .22                | 930C4P22K-F            | 9.8     | 25.4    | ---                                | 28                    | 2.6                            | 2.6   | 2.6   | 2.6   | 2.6   | 2.5   | 1.8   |
| .27                | 930C4P27K-F            | 10.7    | 25.4    | ---                                | 28                    | 3.1                            | 3.1   | 3.1   | 3.1   | 3.1   | 2.7   | 1.9   |
| .33                | 930C4P33K-F            | 11.9    | 25.4    | ---                                | 28                    | 3.8                            | 3.8   | 3.8   | 3.8   | 3.5   | 2.9   | 2.0   |
| .39                | 930C4P39K-F            | 12.8    | 25.4    | ---                                | 28                    | 4.1                            | 4.1   | 4.1   | 4.1   | 3.7   | 3.1   | 2.1   |
| .47                | 930C4P47K-F            | 13.8    | 25.4    | 32                                 | 20                    | 5.7                            | 5.5   | 5.0   | 4.4   | 3.8   | 3.2   | 2.2   |
| .56                | 930C4P56K-F            | 12.8    | 32.0    | 31                                 | 20                    | 5.7                            | 5.7   | 5.3   | 4.4   | 4.1   | 3.3   | 2.3   |

# Type 930C, Metallized Polypropylene Capacitors for DC Filtering





## Low Dissipation, General Purpose

| Cap.<br>( $\mu$ F) | Catalog<br>Part Number | D<br>mm | L<br>mm | ESR<br>20-100 kHz<br>(m $\Omega$ ) | dV/dt<br>(V/ $\mu$ s) | Max. Ripple Current (A) 20 kHz |       |       |       |       |       |       |
|--------------------|------------------------|---------|---------|------------------------------------|-----------------------|--------------------------------|-------|-------|-------|-------|-------|-------|
|                    |                        |         |         |                                    |                       | Case Temperature               |       |       |       |       |       |       |
|                    |                        |         |         |                                    |                       | 25 °C                          | 35 °C | 45 °C | 55 °C | 65 °C | 75 °C | 85 °C |
| 400 Vdc (250 Vac)  |                        |         |         |                                    |                       |                                |       |       |       |       |       |       |
| .68                | 930C4P68K-F            | 14.0    | 32.0    | 30                                 | 20                    | 5.7                            | 5.7   | 5.5   | 4.8   | 4.3   | 3.5   | 2.4   |
| .82                | 930C4P82K-F            | 15.2    | 32.0    | 28                                 | 20                    | 5.7                            | 5.7   | 5.6   | 5.3   | 4.5   | 3.7   | 2.6   |
| 1.00               | 930C4W1K-F             | 16.6    | 32.0    | 27                                 | 20                    | 5.7                            | 5.7   | 5.7   | 5.7   | 5.7   | 4.7   | 4.3   |
| 1.20               | 930C4W1P2K-F           | 18.1    | 32.0    | 26                                 | 20                    | 6.3                            | 6.2   | 6.0   | 5.9   | 5.8   | 4.9   | 4.5   |
| 1.50               | 930C4W1P5K-F           | 18.0    | 44.4    | 25                                 | 13                    | 7.0                            | 6.9   | 6.7   | 6.6   | 6.5   | 5.2   | 4.7   |
| 1.80               | 930C4W1P8K-F           | 18.2    | 44.4    | 23                                 | 13                    | 8.0                            | 7.9   | 7.8   | 7.7   | 6.8   | 5.5   | 5.0   |
| 2.00               | 930C4W2K-F             | 19.1    | 44.4    | 21                                 | 13                    | 9.0                            | 9.0   | 9.0   | 8.0   | 7.0   | 5.7   | 5.2   |
| 2.20               | 930C4W2P2K-F           | 21.0    | 44.4    | 20                                 | 13                    | 9.0                            | 9.0   | 9.0   | 8.3   | 7.4   | 5.9   | 5.4   |
| 2.70               | 930C4W2P7K-F           | 22.0    | 44.4    | 19                                 | 13                    | 9.0                            | 9.0   | 9.0   | 8.6   | 7.6   | 6.0   | 5.6   |
| 3.00               | 930C4W3K-F             | 23.1    | 44.4    | 17                                 | 13                    | 9.0                            | 9.0   | 9.0   | 9.0   | 7.9   | 6.4   | 5.9   |
| 3.30               | 930C4W3P3K-F           | 24.1    | 44.4    | 16                                 | 13                    | 9.0                            | 9.0   | 9.0   | 9.0   | 8.1   | 6.6   | 6.3   |
| 3.90               | 930C4W3P9K-F           | 26.2    | 44.4    | 15                                 | 13                    | 9.0                            | 9.0   | 9.0   | 9.0   | 8.3   | 6.8   | 6.5   |
| 630 Vdc (250 Vac)  |                        |         |         |                                    |                       |                                |       |       |       |       |       |       |
| .022               | 930C6S22K-F            | 8.0     | 19.0    | ---                                | 74                    | 0.8                            | 0.8   | 0.8   | 0.8   | 0.8   | 0.8   | 0.8   |
| .027               | 930C6S27K-F            | 8.0     | 19.0    | ---                                | 74                    | 1.0                            | 1.0   | 1.0   | 1.0   | 1.0   | 1.0   | 0.9   |
| .033               | 930C6S33K-F            | 8.5     | 19.0    | ---                                | 74                    | 1.2                            | 1.2   | 1.2   | 1.2   | 1.2   | 1.2   | 1.0   |
| .039               | 930C6S39K-F            | 9.1     | 19.0    | ---                                | 74                    | 1.4                            | 1.4   | 1.4   | 1.4   | 1.4   | 1.4   | 1.0   |
| .047               | 930C6S47K-F            | 9.9     | 19.0    | ---                                | 74                    | 1.7                            | 1.7   | 1.7   | 1.7   | 1.7   | 1.6   | 1.1   |
| .056               | 930C6S56K-F            | 10.6    | 19.0    | ---                                | 74                    | 2.1                            | 2.1   | 2.1   | 2.1   | 2.1   | 1.7   | 1.2   |
| .068               | 930C6S68K-F            | 9.0     | 25.4    | ---                                | 43                    | 1.3                            | 1.3   | 1.3   | 1.3   | 1.3   | 1.3   | 1.3   |
| .082               | 930C6S82K-F            | 9.5     | 25.4    | ---                                | 43                    | 1.6                            | 1.6   | 1.6   | 1.6   | 1.6   | 1.6   | 1.4   |
| .10                | 930C6P1K-F             | 11.0    | 25.4    | ---                                | 43                    | 1.9                            | 1.9   | 1.9   | 1.9   | 1.9   | 1.9   | 1.6   |
| .12                | 930C6P12K-F            | 11.2    | 25.4    | ---                                | 43                    | 2.3                            | 2.3   | 2.3   | 2.3   | 2.3   | 2.3   | 1.8   |
| .15                | 930C6P15K-F            | 13.0    | 32.0    | ---                                | 30                    | 2.9                            | 2.9   | 2.9   | 2.9   | 2.9   | 2.6   | 1.9   |
| .18                | 930C6P18K-F            | 13.7    | 32.0    | ---                                | 30                    | 3.5                            | 3.5   | 3.5   | 3.5   | 3.5   | 2.7   | 1.9   |
| .22                | 930C6P22K-F            | 12.6    | 32.0    | ---                                | 30                    | 2.8                            | 2.8   | 2.8   | 2.8   | 2.8   | 2.8   | 2.3   |
| .27                | 930C6P27K-F            | 13.8    | 32.0    | ---                                | 30                    | 3.5                            | 3.5   | 3.5   | 3.5   | 3.5   | 3.3   | 2.3   |
| .33                | 930C6P33K-F            | 15.1    | 32.0    | ---                                | 30                    | 4.3                            | 4.3   | 4.3   | 4.3   | 4.3   | 3.5   | 2.4   |
| .39                | 930C6P39K-F            | 16.2    | 32.0    | ---                                | 30                    | 5.0                            | 5.0   | 5.0   | 5.0   | 4.6   | 3.7   | 2.5   |
| .47                | 930C6P47K-F            | 17.7    | 37.0    | 28                                 | 20                    | 6.8                            | 6.3   | 5.8   | 5.2   | 4.5   | 3.6   | 2.6   |
| .56                | 930C6P56K-F            | 15.4    | 44.4    | 26                                 | 19                    | 7.4                            | 6.9   | 6.3   | 5.6   | 4.8   | 4.0   | 2.8   |
| .68                | 930C6P68K-F            | 18.0    | 44.4    | 25                                 | 19                    | 7.8                            | 7.2   | 6.6   | 5.9   | 5.1   | 4.2   | 2.9   |
| .82                | 930C6P82K-F            | 18.4    | 44.4    | 22                                 | 19                    | 8.1                            | 7.5   | 6.9   | 6.2   | 5.3   | 4.3   | 3.1   |
| 1.00               | 930C6W1K-F             | 20.2    | 47.0    | 18                                 | 19                    | 8.6                            | 7.9   | 7.3   | 6.5   | 5.6   | 4.6   | 3.6   |

# Type 930C, Metallized Polypropylene Capacitors for DC Filtering

Low Dissipation, General Purpose

## RMS Voltage vs Frequency @ 25 °C



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)