

For more Information  
please call

1-800-Belden1



## General Description:

27 AWG stranded (7x35) .017" bare copper-covered steel conductor, polyethylene insulation, tinned copper braid shield (95% coverage), PVC jacket.

## Physical Characteristics (Overall)

### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	27	7x35	BCCS - Bare Copper Covered Steel	.017

Total Number of Conductors: 1

### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PE - Polyethylene	.100

### Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	TC - Tinned Copper	95.000

### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

### Overall Cable

Overall Nominal Diameter: 0.150 in.

## Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +60°C

UL Temperature Rating: 60°C (UL AWM Style 1354)

Bulk Cable Weight: 14 lbs/1000 ft.

Max. Recommended Pulling Tension: 32 lbs.

Min. Bend Radius/Minor Axis: 1.500 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

AWM Specification: UL Style 1354 (30 V 60°C)

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

### Plenum/Non-Plenum

Plenum (Y/N): No

## Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

**Impedance (Ohm)**

75

**Nom. Inductance:**

**Inductance (µH/ft)**

.115

**Nom. Capacitance Conductor to Shield:**

**Capacitance (pF/ft)**

20.5

**Nominal Velocity of Propagation:**

**VP (%)**

66

**Nominal Delay:**

**Delay (ns/ft)**

1.54

**Nom. Conductor DC Resistance:**

**DCR @ 20°C (Ohm/1000 ft)**

120

**Nominal Outer Shield DC Resistance:**

**DCR @ 20°C (Ohm/1000 ft)**

5.7

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100 ft.)
1	1.2
10	2.4
50	4.2
100	5.7
200	8.3
400	12.1
700	16.5
900	19.0
1000	20.0

**Max. Operating Voltage - UL:**

**Voltage**

30 V RMS (UL AWM Style 1354)

**Max. Operating Voltage - Non-UL:**

**Voltage**

1700 V RMS

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8218 010U1000	1,000 FT	16.000 LB	BLACK		75 OHM COAX
8218 010U500	500 FT	8.500 LB	BLACK		75 OHM COAX
8218 010I1000	1,000 FT	16.000 LB	BLACK	C	75 OHM COAX
8218 010500	500 FT	8.000 LB	BLACK		75 OHM COAX

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 09-25-2012

© 2016 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)