

Weitergabe sowie Verwältigung dieser Unterlage, Verwertung und Mitfeilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.

8												7												6												5												4												3												2												1																																																																																																																																																																																																																																															
																																				<table><tr><td></td><td>14 (14-a)</td><td>C091 11T014 000 2 U</td></tr><tr><td></td><td>12 (12-a)</td><td>C091 11T012 000 2 U</td></tr><tr><td></td><td>8 (08-a)</td><td>C091 11T008 000 2 U</td></tr><tr><td></td><td>7 (07-b)</td><td>C091 11T107 000 2 U</td></tr><tr><td></td><td>7 (07-a)</td><td>C091 11T007 000 2 U</td></tr><tr><td></td><td>6 (06-a)</td><td>C091 11T006 000 2 U</td></tr><tr><td></td><td>5 (05-b)</td><td>C091 11T105 000 2 U</td></tr><tr><td></td><td>5 (05-a)</td><td>C091 11T005 000 2 U</td></tr><tr><td></td><td>4 (04-a)</td><td>C091 11T004 000 2 U</td></tr><tr><td></td><td>3 (03-a)</td><td>C091 11T003 000 2 U</td></tr><tr><td colspan="2">Contact arrangement View on mating side</td><td>Number of contacts (Contact arrangement acc. IEC 61076-2-106)</td><td>Part number</td></tr></table>													14 (14-a)	C091 11T014 000 2 U		12 (12-a)	C091 11T012 000 2 U		8 (08-a)	C091 11T008 000 2 U		7 (07-b)	C091 11T107 000 2 U		7 (07-a)	C091 11T007 000 2 U		6 (06-a)	C091 11T006 000 2 U		5 (05-b)	C091 11T105 000 2 U		5 (05-a)	C091 11T005 000 2 U		4 (04-a)	C091 11T004 000 2 U		3 (03-a)	C091 11T003 000 2 U	Contact arrangement View on mating side		Number of contacts (Contact arrangement acc. IEC 61076-2-106)	Part number																																																																																																																																																																																																																																																		
	14 (14-a)	C091 11T014 000 2 U																																																																																																																																																																																																																																																																																																																																	
	12 (12-a)	C091 11T012 000 2 U																																																																																																																																																																																																																																																																																																																																	
	8 (08-a)	C091 11T008 000 2 U																																																																																																																																																																																																																																																																																																																																	
	7 (07-b)	C091 11T107 000 2 U																																																																																																																																																																																																																																																																																																																																	
	7 (07-a)	C091 11T007 000 2 U																																																																																																																																																																																																																																																																																																																																	
	6 (06-a)	C091 11T006 000 2 U																																																																																																																																																																																																																																																																																																																																	
	5 (05-b)	C091 11T105 000 2 U																																																																																																																																																																																																																																																																																																																																	
	5 (05-a)	C091 11T005 000 2 U																																																																																																																																																																																																																																																																																																																																	
	4 (04-a)	C091 11T004 000 2 U																																																																																																																																																																																																																																																																																																																																	
	3 (03-a)	C091 11T003 000 2 U																																																																																																																																																																																																																																																																																																																																	
Contact arrangement View on mating side		Number of contacts (Contact arrangement acc. IEC 61076-2-106)	Part number																																																																																																																																																																																																																																																																																																																																
<table><tr><td>Number of contacts</td><td>Standard</td><td>3</td><td>4</td><td>5</td><td>5S</td><td>6</td><td>7</td><td>7</td><td>8</td><td>12</td><td>14</td></tr><tr><td>Contact arrangement</td><td>DIN EN 61076-2-106</td><td>03-a</td><td>04-a</td><td>05-a</td><td>05-b</td><td>06-a</td><td>07-a</td><td>07-b</td><td>08-a</td><td>12-a</td><td>14-a</td></tr><tr><td>Contact arrangement</td><td>IEC 60130-9¹⁾</td><td></td><td></td><td>-</td><td></td><td></td><td>-</td><td></td><td></td><td>-</td><td></td></tr><tr><td>Rated voltage²⁾</td><td>IEC 60664-1</td><td>300 V (100 V)</td><td>300 V (63 V)</td><td>100 V (32 V)</td><td>300 V (63 V)</td><td>100 V (32 V)</td><td>150 V (32 V)</td><td>150 V (32 V)</td><td>150 V (32 V)</td><td>150 V (32 V)</td><td>150 V (32 V)</td></tr><tr><td>Rated voltage</td><td>UL 1977</td><td colspan="8">250 V</td><td>60 V</td><td>60 V</td></tr><tr><td>Rated impulse withstand voltage²⁾</td><td>IEC 60664-1</td><td colspan="2">1500 V (840 V)</td><td>1200 V (500 V)</td><td>1500 V (840 V)</td><td colspan="3">1200 V (500 V)</td><td colspan="3">1200 V (500 V)</td></tr><tr><td>Pollution degree²⁾</td><td>IEC 60664-1</td><td colspan="10">1 (3³⁾)</td></tr><tr><td>Installation category</td><td>IEC 60664-1</td><td colspan="10">I</td></tr><tr><td>Insulation group</td><td>IEC 60664-1</td><td colspan="10">II, 400 ≤ CTI < 600</td></tr><tr><td>Current rating</td><td>IEC 60512-5-2 UL 1977</td><td colspan="8">5A/+40°C/+104°F</td><td colspan="2">3A/+40°C/+104°F</td></tr><tr><td>Insulation resistance</td><td>IEC 60512-3-1</td><td colspan="10">>10¹⁰ Ohm⁴⁾</td></tr><tr><td>Contact resistance</td><td>IEC 60512-2-1</td><td colspan="10"><5m Ohm</td></tr><tr><td>Climatic category</td><td>IEC 60668-1</td><td colspan="10">40 / 100 / 56</td></tr><tr><td>Temperatur range</td><td>IEC 60668-1</td><td colspan="10">-40°C...+100°C / -40°F...+212°F</td></tr><tr><td>salt spray resistance</td><td>DIN IEC 60068-2-11</td><td colspan="10">720h</td></tr><tr><td>IP degree</td><td>IEC 60529</td><td colspan="10">IP 67 / IP 65 (in mated condition)</td></tr><tr><td>Insertion and withdrawal force</td><td>IEC 60512-13-2</td><td>25N</td><td>30N</td><td>35N</td><td>50N</td><td>55N</td><td>60N</td><td>50N</td><td colspan="3"></td></tr><tr><td>Mechanical operation</td><td>IEC 60512-9-1</td><td colspan="10">silver ≥500 mating cycles gold ≥1000 mating cycles</td></tr><tr><td>Housing material</td><td></td><td colspan="10">brass and / or zinc die cast, nickel plated</td></tr><tr><td>Dielectric material</td><td></td><td colspan="10">thermoplastic</td></tr><tr><td>Contacts</td><td></td><td colspan="10">silver or gold plated, please order contacts separately acc. to drawing M-N 02 015 00XX X (3-8pol) or M-N 02 010 0157 X U (12-14pol)</td></tr><tr><td>Termination technique</td><td></td><td colspan="10">crimp</td></tr><tr><td>Wire gauge</td><td></td><td colspan="8">2-6 pol (exclusive 5S): 0,09-1,0mm² / 28-18 AWG</td><td colspan="2">0,09-0,25mm² / 28-24 AWG</td></tr><tr><td>Flamability</td><td></td><td colspan="10">UL 94 V0</td></tr><tr><td>locking system</td><td>IEC 60130-9 DIN EN 61076-2-106</td><td colspan="10">metal screw coupling; tightening torque 0,7Nm</td></tr></table>												Number of contacts	Standard	3	4	5	5S	6	7	7	8	12	14	Contact arrangement	DIN EN 61076-2-106	03-a	04-a	05-a	05-b	06-a	07-a	07-b	08-a	12-a	14-a	Contact arrangement	IEC 60130-9 ¹⁾			-			-			-		Rated voltage ²⁾	IEC 60664-1	300 V (100 V)	300 V (63 V)	100 V (32 V)	300 V (63 V)	100 V (32 V)	150 V (32 V)	150 V (32 V)	150 V (32 V)	150 V (32 V)	150 V (32 V)	Rated voltage	UL 1977	250 V								60 V	60 V	Rated impulse withstand voltage ²⁾	IEC 60664-1	1500 V (840 V)		1200 V (500 V)	1500 V (840 V)	1200 V (500 V)			1200 V (500 V)			Pollution degree ²⁾	IEC 60664-1	1 (3 ³⁾)										Installation category	IEC 60664-1	I										Insulation group	IEC 60664-1	II, 400 ≤ CTI < 600										Current rating	IEC 60512-5-2 UL 1977	5A/+40°C/+104°F								3A/+40°C/+104°F		Insulation resistance	IEC 60512-3-1	>10 ¹⁰ Ohm ⁴⁾										Contact resistance	IEC 60512-2-1	<5m Ohm										Climatic category	IEC 60668-1	40 / 100 / 56										Temperatur range	IEC 60668-1	-40°C...+100°C / -40°F...+212°F										salt spray resistance	DIN IEC 60068-2-11	720h										IP degree	IEC 60529	IP 67 / IP 65 (in mated condition)										Insertion and withdrawal force	IEC 60512-13-2	25N	30N	35N	50N	55N	60N	50N				Mechanical operation	IEC 60512-9-1	silver ≥500 mating cycles gold ≥1000 mating cycles										Housing material		brass and / or zinc die cast, nickel plated										Dielectric material		thermoplastic										Contacts		silver or gold plated, please order contacts separately acc. to drawing M-N 02 015 00XX X (3-8pol) or M-N 02 010 0157 X U (12-14pol)										Termination technique		crimp										Wire gauge		2-6 pol (exclusive 5S): 0,09-1,0mm² / 28-18 AWG								0,09-0,25mm² / 28-24 AWG		Flamability		UL 94 V0										locking system	IEC 60130-9 DIN EN 61076-2-106	metal screw coupling; tightening torque 0,7Nm										¹⁾ Edition 2000-05 ²⁾ values in brackets are according to DIN EN 61076-2-106 ³⁾ designed acc. pollution degree 2; can be used under pollution degree 3 when the rules of IEC 60644-1 are fulfilled ⁴⁾ under operating conditions >10⁸ Ohm All technical data have been measured in a laboratory environment and can be different during pratical usage of the product. Any product informtion is for descriptive usage only and not legally binding; particulary the information does not constitute or provide any legal guaranties. Do not connect or disconnect under load. Metal housing parts shall be securely incorporated to protected ground. Parts according to directive 2002/95/EG (RoHS).											
Number of contacts	Standard	3	4	5	5S	6	7	7	8	12	14																																																																																																																																																																																																																																																																																																																								
Contact arrangement	DIN EN 61076-2-106	03-a	04-a	05-a	05-b	06-a	07-a	07-b	08-a	12-a	14-a																																																																																																																																																																																																																																																																																																																								
Contact arrangement	IEC 60130-9 ¹⁾			-			-			-																																																																																																																																																																																																																																																																																																																									
Rated voltage ²⁾	IEC 60664-1	300 V (100 V)	300 V (63 V)	100 V (32 V)	300 V (63 V)	100 V (32 V)	150 V (32 V)	150 V (32 V)	150 V (32 V)	150 V (32 V)	150 V (32 V)																																																																																																																																																																																																																																																																																																																								
Rated voltage	UL 1977	250 V								60 V	60 V																																																																																																																																																																																																																																																																																																																								
Rated impulse withstand voltage ²⁾	IEC 60664-1	1500 V (840 V)		1200 V (500 V)	1500 V (840 V)	1200 V (500 V)			1200 V (500 V)																																																																																																																																																																																																																																																																																																																										
Pollution degree ²⁾	IEC 60664-1	1 (3 ³⁾)																																																																																																																																																																																																																																																																																																																																	
Installation category	IEC 60664-1	I																																																																																																																																																																																																																																																																																																																																	
Insulation group	IEC 60664-1	II, 400 ≤ CTI < 600																																																																																																																																																																																																																																																																																																																																	
Current rating	IEC 60512-5-2 UL 1977	5A/+40°C/+104°F								3A/+40°C/+104°F																																																																																																																																																																																																																																																																																																																									
Insulation resistance	IEC 60512-3-1	>10 ¹⁰ Ohm ⁴⁾																																																																																																																																																																																																																																																																																																																																	
Contact resistance	IEC 60512-2-1	<5m Ohm																																																																																																																																																																																																																																																																																																																																	
Climatic category	IEC 60668-1	40 / 100 / 56																																																																																																																																																																																																																																																																																																																																	
Temperatur range	IEC 60668-1	-40°C...+100°C / -40°F...+212°F																																																																																																																																																																																																																																																																																																																																	
salt spray resistance	DIN IEC 60068-2-11	720h																																																																																																																																																																																																																																																																																																																																	
IP degree	IEC 60529	IP 67 / IP 65 (in mated condition)																																																																																																																																																																																																																																																																																																																																	
Insertion and withdrawal force	IEC 60512-13-2	25N	30N	35N	50N	55N	60N	50N																																																																																																																																																																																																																																																																																																																											
Mechanical operation	IEC 60512-9-1	silver ≥500 mating cycles gold ≥1000 mating cycles																																																																																																																																																																																																																																																																																																																																	
Housing material		brass and / or zinc die cast, nickel plated																																																																																																																																																																																																																																																																																																																																	
Dielectric material		thermoplastic																																																																																																																																																																																																																																																																																																																																	
Contacts		silver or gold plated, please order contacts separately acc. to drawing M-N 02 015 00XX X (3-8pol) or M-N 02 010 0157 X U (12-14pol)																																																																																																																																																																																																																																																																																																																																	
Termination technique		crimp																																																																																																																																																																																																																																																																																																																																	
Wire gauge		2-6 pol (exclusive 5S): 0,09-1,0mm² / 28-18 AWG								0,09-0,25mm² / 28-24 AWG																																																																																																																																																																																																																																																																																																																									
Flamability		UL 94 V0																																																																																																																																																																																																																																																																																																																																	
locking system	IEC 60130-9 DIN EN 61076-2-106	metal screw coupling; tightening torque 0,7Nm																																																																																																																																																																																																																																																																																																																																	
8												7												6												5												4												3												2												1																																																																																																																																																																																																																																															
Gewicht (errechnet) / Calc WT : g												Zul. Abw./Tolerances :												Maßstab / Scale : 2:1												A3																																																																																																																																																																																																																																																																																															
												Prüfmaß / Testdimension												DIN / ISO 13715												CUSTOMER DRAWING																																																																																																																																																																																																																																																																																															
Teileindex												Partindexnumber												2014												Datum/Date												Name																																																																																																																																																																																																																																																																																			
																								Gez.												25.06.												Mohrlang																																																																																																																																																																																																																																																																																			
																								Drawn																																																																																																																																																																																																																																																																																																											
																								Gepr.																																																																																																																																																																																																																																																																																																											
																								Checked																																																																																																																																																																																																																																																																																																											
																								Amphenol-Tuchel Electronics GmbH												M												C091 11TXXX 000 2 U												Blatt/Sheet 1																																																																																																																																																																																																																																																																							
02												201400467												25.06.14												IM																								1 Bl.																																																																																																																																																																																																																																																																							
Index												Änderung/Description												Datum/Date												Name																								Ers. f. / Replacement for : M-C091 11TXXX 000 2 U Rev01																																																																																																																																																																																																																																																																							

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru