PRODUCT DATASHEET
LOST series

Ordering number	**FA11113**		
Description	**FA11113_LOST-W**		
Family	Leila	FWHM	degrees
Type	Assembly	Efficiency	-
LED	Ostar Lighting+	cd/lm	-
Color	Black	Gerber File	Available
Diameter	21.6 mm		
Height	13.2 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	PC		
Fastening	Tape		
Status	Ready		

Ordering number	**FA11463**		
Description	**FA11463_LOST-M2**		
Family	Leila	FWHM	degrees
Type	Assembly	Efficiency	-
LED	Ostar Lighting+	cd/lm	-
Color	Black	Gerber File	Available
Diameter	21.6 mm		
Height	13.2 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	PC		
Fastening	Tape		
Status	Ready		

Ordering number	**FA11110**		
Description	**FA11110_LOST-D**		
Family	Leila	FWHM	25 degrees
Type	Assembly	Efficiency	89 %
LED	Ostar Lighting+	cd/lm	-
Color	Black	Gerber File	Available
Diameter	21.6 mm		
Height	13.2 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	PC		
Fastening	Tape		
Status	Ready		

Ordering number	**FA11112**		
Description	**FA11112_LOST-M**		
Family	Leila	FWHM	30 degrees
Type	Assembly	Efficiency	88 %
LED	Ostar Lighting+	cd/lm	-
Color	Black	Gerber File	Available
Diameter	21.6 mm		
Height	13.2 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	PC		
Fastening	Tape		
Status	Ready		

Ledil Oy
Salorankatu 10
24240 SALO
Finland

http://www.ledil.com
email: ledil@ledil.com
FAX: +358-2-733 8001

PRODUCT DATASHEET
LOST series

Ordering number	**FA11114**		
Description	**FA11114_LOST-O-90**		
Family	Leila	FWHM	36+24 degrees
Type	Assembly	Efficiency	85 %
LED	Ostar Lighting+	cd/lm	-
Color	Black	Gerber File	Available
Diameter	21.6 mm		
Height	13.2 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	PC		
Fastening	Tape		
Status	Ready		

Ordering number	**FA11115**		
Description	**FA11115_LOST-REC**		
Family	Leila	FWHM	36+29 degrees
Type	Assembly	Efficiency	81 %
LED	Ostar Lighting+	cd/lm	-
Color	Black	Gerber File	Available
Diameter	21.6 mm		
Height	13.2 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	PC		
Fastening	Tape		
Status	Ready		

Ordering number	**FA11893**		
Description	**FA11893-LOST-WW**		
Family	Leila	FWHM	degrees
Type	Assembly	Efficiency	-
LED	Ostar Lighting+	cd/lm	-
Color	Black	Gerber File	Available
Diameter	21.6 mm		
Height	13.2 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	PC		
Fastening	Tape		
Status	Ready		

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.

Ledil Oy
Salorankatu 10
24240 SALO
Finland

http://www.ledil.com
email: ledil@ledil.com
FAX: +358-2-733 8001

GENERAL INFORMATION

- Product series especially designed & optimized for Ostar Lighting+ series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Lens material optical grade PMMA with high UV and temperature resistance (105 degrees of Celcius / 220 degrees of Fahrenheit). Allows use of high current and temperature conditions.

Please find more information about used material from below:
http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20UL94_Yellow%20Card.pdf
http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20PLEXIGLAS-Datasheet.pdf
- Optic holder molded by high quality PC material (120 dergees of Celcius / 248 degrees of Fahrenheit).

- Fastening to heat sink with a PU foam adhesive tape of automotive grade. Please find fastening details by clicking link: http://www.ledil.com/datasheets/DataSheet_TAPE.pdf

NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit boar weaken the strength of the tape.

NOTE 2: Assembly to the surface must be made straight, so the tape bonds constant and balanced with fastening surface. Slanted assembly might cause unbalanced bond to the surface. All surfaces where tape is applied must be clean, dry and free from grease and dirt.

If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer - this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.

Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.

Ledil Oy
Salorankatu 10
24240 SALO
Finland

http://www.ledil.com
email: ledil@ledil.com
FAX: +358-2-733 8001

PRODUCT DATASHEET
LOST series

CA11483_LXP2-M & XP-E-HEW



CA11482_LXP2-D



CA11481_LXP2-RS

FA11116_LXP-O-90



FA10832_LXP-W & XPE_HEW

FA10661_LXP-RS



Ledil Oy
Salorankatu 10
24240 SALO
Finland

http://www.ledil.com
email: ledil@ledil.com
FAX: +358-2-733 8001

PRODUCT DATASHEET
LOST series

FA10661_LXP-RS & XP-E-HEW



CA11639_LR2-M



CA11638_LR2-D

CA11637_LR2-RS



Ledil Oy
Salorankatu 10
24240 SALO
Finland

http://www.ledil.com
email: ledil@ledil.com
FAX: +358-2-733 8001


Relative Intensity of CA11637_LR2-RS
100 %
75 %
50 %
25 %
0 %
15
10
5
0
-5
-10
-15


Relative Intensity of CA11638_LR2-D
100 %
75 %
50 %
25 %
0 %
30
25
20
15
10
5
0
-5
-10
-15
-20
-25
-30


Relative intensity of CA11639_LR2-M
100%
75%
50%
25%
0%
70
60
50
40
30
20
10
0
-10
-20
-30
-40
-50
-60
-70

Relative Intensity of FA10661_LXP-RS-HEW




Relative Intensity of FA10661_LXP-RS
100 %
75 %
50 %
25 %
0 %
15
10
5
0
-5
-10
-15


Relative intensity of FA10832_LXP-W-HEW
100%
75%
50%
25%
0%
50
40
30
20
10
0
-10
-20
-30
-40
-50


Relative intensity of FA11116_LXP-O-90-HEW
100%
75%
50%
25%
0%
40
35
30
25
20
15
10
5
0
-5
-10
-15
-20
-25
-30
-35
-40


Relative intensity of CA11631_LXP3-G-RS
100 %
75 %
50 %
25 %
0 %
25
20
15
10
5
0
-5
-10
-15
-20
-25
CA11481_LXP2-G-RS


Relative intensity of CA11481_LXP2-RS
100%
75%
50%
25%
0%
30
25
20
15
10
5
0
-5
-10
-15
-20
-25
-30


Relative intensity of CA11482_LXP2-G-D
100%
75%
50%
25%
0%
30
20
10
0
-10
-20
-30


Relative intensity of CA11482_LXP2-D
100%
75%
50%
25%
0%
40
30
20
10
0
-10
-20
-30
-40


Relative intensity of CA11483_LXP2-G-M
100%
75%
50%
25%
0%
50
40
30
20
10
0
-10
-20
-30
-40
-50


Relative intensity of CA11483_LXP2-M & Cree XP-E-HEW
100%
75%
50%
25%
0%
50
40
30
20
10
0
-10
-20
-30
-40
-50



Isometric view
Scale: 1:1



Bottom view



Front view

MATERIALS
Lens: PMMA
Holder: PC
Tape: PU Foam

Part no.s:
FA11109_LOST-RS
FA11110_LOST-D
FA11112_LOST-M
FA11114_LOST-O-90
FA11115_LOST-REC

This drawing is our property. It can't be reproduced or communicated without our written agreement.

Ledil Oy
Tehdaskatu 13
FIN-24100 SALO
Finland

DRAWN BY pv	DATE 09.03.2010	DRAWING TITLE Datasheet Lost-Series assy			
CHECKED BY hh	DATE 17.09.2009	SIZE A4	DRAWING NUMBER		REV 1
DESIGNED BY pv	DATE 17.09.2009	SCALE 2:1	WEIGHT(g) -		SHEET 1/1

ООО «ЛайфЭлектроникс» “LifeElectronics” LLC

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru