

REFERENCE SPECIFICATIONS

-NFC 93425 (in compliance with HE 507)

PHYSICAL CHARACTERISTICS

- INSULATOR MATERIAL: THERMOPLASTIC ,UL94V0
- ACCESSORIES: BRASS
- SHELLS: STEEL

ELECTRICAL CHARACTERISTICS

- CONTACT/CONTACT : >=1000 V
- CONTACT/GROUND : >=1200 V
- INSULATION RESISTANCE: >=5000 MOhms

ENVIRONMENTAL CHARACTERISTICS



- CLIMATIC CATEGORY: 55/125/21
- TEMPERATURE RANGE -55°C TO +125°C
- DAMP HEAT STEADY STATE 21 DAYS
- SALT SPRAY 24 HOURS

MECHANICAL CHARACTERISTICS


- RETENTION AGAINST TORQUE:
 - Threaded insert: 0.7 N.m minimum
 - Female screw : 0.5 N.m minimum

NOTE ROHS INFORMATION

- The “LF” products meet european union Directives and other country regulations as described in GS-22-008.
- Shell plating :2 to 4µm Cu+ Ni + 3 to 10µmm Sn(pure bright)
- Accessories: Sn pure bright + nickel
- Packaging spec: See GS-14-920



spec ref				dr	Pro Engineer 1	2015/06/16			size	A2	scale	2:1	
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	J Dalibard	2016/09/13			ecn no	ECN-ELX-F-24942-1			
				chr	J Dalibard	2016/09/19			product family - rel level Released				
				appr	Aymeric Soudy	2016/09/20							
surface 	linear	0.X	±0.3	Amphenol FCi	title	SUB FEMALE DW full power without contact			dwg no	C01-8639-2311		rev	E
		0.XX	±0.10										
		0.XXX	±0.05										
	angular	0°	±2°										



FRONT ACCESSORY	Blank without	L insert M3 O insert UNC 4.40	V Female screw UNC 4-40
PCB ACCESSORIES	A without	A without	A without

PART NUMBER	FRONT ACCESSORY	PCB ACCESSORY
D*W xSA00LF	WITHOUT	WITHOUT
D*VxW xSA00LF	Female screw UNC 4-40	WITHOUT
D*LxW xSA00LF	Insert M3	WITHOUT
D*OxW xSA00LF	Insert UNC 4-40	WITHOUT

shell size LAYOUTS

E	2V2
A	3V3
A	3W3
B	5W5
C	8W8

SCALE:4

spec ref				dr	Pro Engineer 1	2015/06/16			size	A2	scale	2:1		
tolerance std				eng	J Dalibard	2016/09/13			ecn no	ECN-ELX-F-24942-1				
				chr	J Dalibard	2016/09/19			rel level					
				appr	Aymeric Soudy	2016/09/20								
product family							-	Released						
surface	✓	linear	0.X	±0.3	Amphenol FCI	title SUB FEMALE DW				dwg no	C01-8639-2311		rev	E
			0.XX	±0.10										
			0.XXX	±0.05										
			angular	0°										
				cat. no.	-	Product - Customer Drw				sheet 2 of 4				

FIRST ANGLE PROJECTION

C

D

E

F

A

B

C

D




E

FIRST ANGLE PROJECTION








2V2


3V3



3W3




SIDE VIEW FOR
LAYOUTS: E A B C



spec ref				dr	Pro Engineer 1		2015/06/16		projection		mm		size	A2		scale	2:1								
tolerance std				TOLERANCES UNLESS OTHERWISE SPECIFIED				eng	J Dalibard		2016/09/13				ecn no		ECN-ELX-F-24942-1								
				chr	J Dalibard		2016/09/19																		
				appr	Aymeric Soudy		2016/09/20																		
surface 				linear		0.X ±0.3 0.XX ±0.10 0.XXX ±0.05		Amphenol FCI		title SUB FEMALE DW full power without contact		dwg no C01-8639-2311		rel level Released		rev E									
																		cat. no.		-		Product - Customer Drw		sheet 3 of 4	



spec ref		dr		Pro Engineer 1	2015/06/16	projection 	mm 	size	A2	scale	2:1	
tolerance std		eng		J Dalibard	2016/09/13			ecn no	ECN-ELX-F-24942-1			
		chr		J Dalibard	2016/09/19				rel level			Released
		appr		Aymeric Soudy	2016/09/20	product family						
surface 	linear	0.X	±0.3	Amphenol FCi	title	SUB FEMALE DW		dwg no	C01-8639-2311		rev	E
		0.XX	±0.10									
		0.XXX	±0.05									
		angular	0°									
					cat. no.	-	Product - Customer Drw			sheet 4 of 4		

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru