


### FEATURES


- Standard 5.0mm x 3.2mm 4-Pad Surface Mount Package
- HCMOS/TTL Compatible Output
- Fundamental and 3<sup>rd</sup> Overtone Crystal Designs
- Frequency Range 1 – 160 MHz
- Frequency Stability  $\pm 50$  ppm Standard,  $\pm 25$  ppm and  $\pm 20$  ppm Available
- Operating Voltages +1.8Vdc, +2.5Vdc, +3.3Vdc or +5.0Vdc
- Operating Temperature to -40°C to +85°C
- Output Enable Standard
- Tape & Reel Packaging Available
- **RoHS/Green Compliant (6/6)**



### APPLICATIONS

Model 636 is ideal for applications; such as digital video, networking equipment, broadband access, Ethernet/Gigabit Ethernet, microprocessors/DSP/FPGA, storage area networks, computers and peripherals, cameras and other portable devices to name a few.

### ORDERING INFORMATION



1] 6I Stability/Temperature combination is not available.

2] Frequency is recorded with three leading significant digits before the 'M' and 5 significant digits after the 'M' (including zeros).


[Ex. XXXXXXXX, (0004M00000 (014M31818) (125M00000)]

**Not all performance combinations and frequencies may be available.  
Contact your local CTS Representative or CTS Customer Service for availability.**

### PACKAGING INFORMATION

Device quantity is 3,000 pieces maximum per reel.

DIMENSIONS IN MILLIMETERS



**ELECTRICAL CHARACTERISTICS**

| ELECTRICAL PARAMETERS | PARAMETER                                                                | SYMBOL         | CONDITIONS                                                                                                                                       | MIN                          | TYP                      | MAX                                | UNIT     |
|-----------------------|--------------------------------------------------------------------------|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|--------------------------|------------------------------------|----------|
|                       | Maximum Supply Voltage                                                   | $V_{CC}$       | -                                                                                                                                                | -0.5                         | -                        | 7.0                                | V        |
|                       | Storage Temperature                                                      | $T_{STG}$      | -                                                                                                                                                | -55                          | -                        | 125                                | °C       |
|                       | Frequency Range                                                          | $f_0$          | -                                                                                                                                                | 1.0                          | -                        | 160                                | MHz      |
|                       | Frequency Stability<br>[See Note 1 and Ordering Information]             | $\Delta f/f_0$ | -                                                                                                                                                | -                            | -                        | 20,25, 50 or 100                   | ± ppm    |
|                       | Aging                                                                    | $\Delta f/f_0$ | -                                                                                                                                                | -                            | -                        | 3                                  | ± ppm/yr |
|                       | Operating Temperature<br>Commercial<br>Industrial                        | $T_A$          | -                                                                                                                                                | -20<br>-40                   | 25                       | 70<br>85                           | °C       |
|                       | Supply Voltage<br>Model 636M<br>Model 636N<br>Model 636L<br>Model 636S   | $V_{CC}$       | ± 10 %                                                                                                                                           | 1.62<br>2.25<br>2.97<br>4.50 | 1.8<br>2.5<br>3.3<br>5.0 | 1.98<br>2.75<br>3.63<br>5.50       | V        |
|                       | Supply Current<br>Model 636M<br>[+1.8V]                                  | $I_{CC}$       | $C_L = 15\text{pF}$<br>1.0 MHz to 34.999 MHz<br>35 MHz to 60 MHz<br>60.001 MHz to 99.999 MHz<br>100 MHz to 106.250 MHz<br>106.251 MHz to 160 MHz | -<br>-<br>-<br>-<br>-        | -<br>-<br>-<br>-<br>-    | 8<br>15<br>25<br>35<br>35          | mA       |
|                       | Model 636N<br>[+2.5V]                                                    |                | 1.0 MHz to 34.999 MHz<br>35 MHz to 60 MHz<br>60.001 MHz to 99.999 MHz<br>100 MHz to 106.250 MHz<br>106.251 MHz to 160 MHz                        | -<br>-<br>-<br>-<br>-        | -<br>-<br>-<br>-<br>-    | 10<br>20<br>30<br>40<br>40         |          |
|                       | Model 636L<br>[+3.3V]                                                    |                | 1.0 MHz to 34.999 MHz<br>35 MHz to 60 MHz<br>60.001 MHz to 99.999 MHz<br>100 MHz to 106.250 MHz<br>106.251 MHz to 160 MHz                        | -<br>-<br>-<br>-<br>-        | -<br>-<br>-<br>-<br>-    | 16<br>25<br>40<br>50<br>50         |          |
|                       | Model 636S<br>[+5.0]                                                     |                | 1.0 MHz to 34.999 MHz<br>35 MHz to 60 MHz<br>60.001 MHz to 99.999 MHz<br>100 MHz to 106.250 MHz                                                  | -<br>-<br>-<br>-             | -<br>-<br>-<br>-         | 25<br>50<br>60<br>80               |          |
|                       | Output Load<br>Model 636M<br>Model 636N & 636L                           |                | 1.0 MHz to 160 MHz<br>1.0 MHz to 50 MHz<br>50.001 MHz to 160 MHz                                                                                 | -<br>-<br>-                  | -<br>-<br>-              | 15<br>30<br>15                     |          |
|                       | Model 636S                                                               |                | 1.0 MHz to 50 MHz<br>50.001 MHz to 80 MHz<br>80.001 MHz to 106.250 MHz                                                                           | -<br>-<br>-                  | -<br>-<br>-              | 50<br>30<br>15                     |          |
|                       | Output Voltage Levels<br>Logic '1' Level<br>Logic '0' Level              |                | $V_{OH}$ CMOS Load<br>$V_{OL}$ CMOS Load                                                                                                         | 90% $V_{CC}$<br>-            | -<br>-                   | -<br>10% $V_{CC}$                  |          |
|                       | Output Current<br>Logic '1' Level (M,N,L,S)<br>Logic '0' Level (M,N,L,S) |                | $I_{OH} V_{OH} = 90\%V_{CC}$<br>$I_{OL} V_{OL} = 10\%V_{CC}$                                                                                     | -<br>-                       | -<br>-                   | -2, -4, -8, -16<br>+2, +4, +8, +16 |          |
|                       | Output Duty Cycle                                                        | SYM            | @ 50% Level                                                                                                                                      | 45                           | -                        | 55                                 | %        |
|                       | Rise and Fall Time<br>Model 636M, 636N & 636L                            | $T_R, T_F$     | @ 10% - 90% Levels, $C_L = 15\text{pF}$<br>1.0 MHz to 50 MHz<br>50.001 MHz to 125 MHz<br>125.001 MHz to 160 MHz                                  | -<br>-<br>-                  | 6<br>3<br>1.5            | 10<br>5<br>2.5                     | ns       |
|                       | Model 636S                                                               |                | 1.0 MHz to 20 MHz<br>20.001 MHz to 50 MHz<br>50.001 MHz to 106.250 MHz                                                                           | -<br>-<br>-                  | 6<br>3<br>1.5            | 8<br>5<br>2                        |          |
|                       | Start Up Time                                                            |                | $T_S$ Application of $V_{CC}$                                                                                                                    | -                            | 5                        | 10                                 |          |
|                       | Period Jitter, Pk-Pk                                                     |                | -                                                                                                                                                | -                            | -                        | 100                                |          |
|                       | Period Jitter, RMS                                                       |                | -                                                                                                                                                | -                            | -                        | 25                                 |          |
|                       | Phase Jitter, RMS                                                        | -              | Bandwidth 12 kHz - 20 MHz                                                                                                                        | -                            | -                        | 1                                  | ps       |


Notes:

1. Inclusive of initial tolerance at time of shipment, changes in supply voltage, load, temperature and aging.


## ELECTRICAL CHARACTERISTICS

|                       | PARAMETER             | SYMBOL    | CONDITIONS                       | MIN  | TYP | MAX | UNIT    |
|-----------------------|-----------------------|-----------|----------------------------------|------|-----|-----|---------|
| ELECTRICAL PARAMETERS | Enable Function       |           |                                  |      |     |     |         |
|                       | Enable Input Voltage  |           |                                  |      |     |     |         |
|                       | Model 636M            | $V_{IH}$  | Pin 1 Logic '1', Output Enabled  | 1.26 | -   | -   | V       |
|                       | Model 636N            |           | Pin 1 Logic '1', Output Enabled  | 1.75 | -   | -   |         |
|                       | Model 636L            |           | Pin 1 Logic '1', Output Enabled  | 2.0  | -   | -   |         |
|                       | Model 636S            |           | Pin 1 Logic '1', Output Enabled  | 4.0  | -   | -   |         |
|                       | Disable Input Voltage |           |                                  |      |     |     |         |
|                       | Model 636M,636N,636L  | $V_{IL}$  | Pin 1 Logic '0', Output Disabled | -    | -   | 0.3 |         |
|                       | Model 636S            |           | Pin 1 Logic '0', Output Disabled | -    | -   | 0.8 |         |
|                       | Enable Time (M,N,L,S) | $T_{PLZ}$ | Pin 1 Logic '1'                  | -    | -   | 10  | ms      |
|                       | Standby Current       | $I_{ST}$  | Pin 1 Logic '0', Output Disabled | -    | -   | 10  | $\mu A$ |

### LVC MOS OUTPUT WAVEFORM



### TEST CIRCUIT, CMOS LOAD




### ENABLE TRUTH TABLE

| PIN 1     | PIN 3     |
|-----------|-----------|
| Logic '1' | Output    |
| Open      | Output    |
| Logic '0' | High Imp. |


## MECHANICAL SPECIFICATIONS

### PACKAGE DRAWING



### SUGGESTED SOLDER PAD GEOMETRY

$C_{BYPASS}$  should be  $\geq 0.01 \mu F$ .



### MARKING INFORMATION

- \*\* - Manufacturing Site Code.
- YWW - Date code, Y - year, WW - week.
- XXMXXXX - Frequency is marked with only leading significant digits before the 'M' and 4 digits after the 'M' (including zeros).  
Ex. XXMXXXX (62M5000)  
XXMXXXX (155M5200)

### NOTES

- Termination pads (e4). Barrier-plating is nickel (Ni) with gold (Au) flash plate.
- Reflow conditions per JEDEC J-STD-020, 260°C maximum.
- Moisture Sensitivity Level 1 per JEDEC J-STD-020.

### D.U.T. PIN ASSIGNMENTS

| PIN | SYMBOL   | DESCRIPTION              |
|-----|----------|--------------------------|
| 1   | EOH      | Enable                   |
| 2   | GND      | Circuit & Package Ground |
| 3   | Output   | RF Output                |
| 4   | $V_{CC}$ | Supply Voltage           |

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)