

标准书名 Classification		产品规格书		Specification	Spec No.	CF.APR-01																																
品 名		碳膜固定电阻器			CF Series	PAGE	10-1																															
Product Name		Fixed Carbon Film Resistors																																				
1. 一般事项 General																																						
适用范围 Scope																																						
本承认书适用于深圳市深中泰电子有限公司制造之[碳素皮膜固定电阻器]。																																						
This specification is available for Fixed Carbon Film Resistors manufactured by ShenZhen ShenZhongTai Electronics CO.,LTD.																																						
品质 Quality																																						
本电阻器的制造系经高品质管理程序，并具有高信赖性的品质保证。																																						
The resistor is manufactured by highly quality-controlled process and guaranteed high reliability.																																						
标准试验状态 Standard measuring conditions																																						
温度 25±2℃、湿度 65±5%。																																						
但在温度 5～35℃、湿度 45～85%之情況下，仍可经予判定。																																						
Temperature 25±2℃, Humidity 65±5%.																																						
Being no doubt about the judgment, measurements can be made within the following Temperature 5～35℃, Humidity 45～85%.																																						
形名（例） Type designation (example)																																						
依使用种类、额定电力、形状、公称电阻值、电阻值容许差而区别，其构造如下：																																						
The type designation shall be in the following form and as specified.																																						
CF 种类 Type 1/4W 额定电力 Rated power <table><tr><td>Normal</td><td>Small</td></tr><tr><td>1/6W(1/8W)</td><td>1/4WS</td></tr><tr><td>1/4W</td><td>1/2WS</td></tr><tr><td>1/2W</td><td>1WS</td></tr><tr><td>1W</td><td>2WS</td></tr><tr><td>2W</td><td>3WS</td></tr><tr><td>3W</td><td>5WS</td></tr></table> T52 形状 Form <table><tr><td>P</td><td>Bulk</td></tr><tr><td>Txx</td><td>Taping XXmm</td></tr><tr><td>M</td><td>M-Form series</td></tr><tr><td>FK</td><td>F-Form series</td></tr></table> J 电阻值容许差 Resistance tolerance <table><tr><td>K</td><td>±10%</td></tr><tr><td>J</td><td>±5%</td></tr><tr><td>G</td><td>±2%</td></tr></table> 10K 公称电阻值 Nominal resistance value <table><tr><td>E-12 Series</td></tr><tr><td>E-24 Series</td></tr><tr><td>E-48 Series</td></tr></table>								Normal	Small	1/6W(1/8W)	1/4WS	1/4W	1/2WS	1/2W	1WS	1W	2WS	2W	3WS	3W	5WS	P	Bulk	Txx	Taping XXmm	M	M-Form series	FK	F-Form series	K	±10%	J	±5%	G	±2%	E-12 Series	E-24 Series	E-48 Series
Normal	Small																																					
1/6W(1/8W)	1/4WS																																					
1/4W	1/2WS																																					
1/2W	1WS																																					
1W	2WS																																					
2W	3WS																																					
3W	5WS																																					
P	Bulk																																					
Txx	Taping XXmm																																					
M	M-Form series																																					
FK	F-Form series																																					
K	±10%																																					
J	±5%																																					
G	±2%																																					
E-12 Series																																						
E-24 Series																																						
E-48 Series																																						
						承 认	作 成																															
						Approved by	Drawn by																															
						周国新	黄根荣																															

标准书名 Classification	产品规格书 Specification	Spec No.	CF.APR-01
品名 Product Name	碳膜固定电阻器 CF Series Fixed Carbon Film Resistors	PAGE	10-2

额定电力 Rated power


额定电力是适应在周围温度 70℃ 可以连续负载的最大电力，如表-1；但周围温度如超过 70℃ 时之额定电力则依图一的电力轻减曲线实施。

Rated power is maximum power which can be continuously loaded at specified ambient temperature 70℃, however when the ambient temperature exceeds 70℃, rated power should be determined from the derating curve of Fig.1.

表-1 Table-1

种类 Type	额定 电力 Rated power	最 高 使用电压 Maximum working voltage	最 高 过负荷电压 Maximum overload voltage	最 高 断续电压 Maximum pulse voltage	耐电压 Dielectric withstanding voltage	电阻值 范围 Resistance range	使用温度范围 Operating temperature range
Normal size	CF1/6W(1/8W)	0.16W	200V	400V	500V	300V	2.2Ω ~ 1MΩ
	CF1/4W	0.25W	300V	500V	750V	500V	2.2Ω ~ 4.7MΩ
	CF1/2W	0.5W	350V	700V	1000V	700V	2.2Ω ~ 5.1MΩ
	CF1W	1W	500V	800V	1500V	800V	2.2Ω ~ 5.1MΩ
	CF2W	2W	500V	1000V	2000V	800V	2.2Ω ~ 5.1MΩ
	CF3W	3W	750V	1000V		800V	2.2Ω ~ 5.1MΩ
Small size	CF1/4WS	0.25W	300V	500V	500V	300V	2.2Ω ~ 1MΩ
	CF1/2WS	0.5W	350V	700V	750V	500V	2.2Ω ~ 4.7MΩ
	CF1WS	1W	500V	800V	1000V	700V	2.2Ω ~ 5.1MΩ
	CF2WS	2W	500V	1000V	1500V	800V	2.2Ω ~ 5.1MΩ
	CF3WS	3W	750V	1000V	2000V	800V	2.2Ω ~ 5.1MΩ
							-55℃ ~ 155℃



图一 电力轻减曲线 Figure 1 Power derating curve



	承 认 Approved by	作 成 Drawn by
	周国新	黄根荣


标准书名 Classification	产品规格书 Specification	Spec No.	CF.APR-01
品名 Product Name	碳膜固定电阻器 CF Series Fixed Carbon Film Resistors	PAGE	10-3

图二 表面温度上升 Figure 2 Surface temperature rise



	承认 Approved by	作成 Drawn by
	周国新	黄根荣

标准书名 Classification	产品规格书 Specification	Spec No.	CF.APR-01										
品 名 Product Name	碳膜固定电阻器 CF Series Fixed Carbon Film Resistors	PAGE	10-4										
额定电压 Rated voltage 额定电压是指对应于额定电力的直流或交流（商用频率之有效值）的电压，由下式求得。 The rated voltage shall be the D.C. or A.C. (R.M.S. at power frequency) voltage which corresponds the rated power and the value of which is calculated from the fomula below. $E = \sqrt{P \cdot R}$ Where E：额定电压 Rated voltage (V) P：额定电力 Rated power (W) R：公称电阻值 Nominal resistance (Ω) 公称电阻值 Nominal resistance values 公称电阻值是按表-2 之数乘以 10ⁿ (n 为整数) 之数值，其单位为欧姆(Ω)。 公称电阻值之范围则按表-1 所示。 The nominal resistance values shall be the numerical values given in Table-2 multiplied by 10ⁿ (n is an integer) in the unit of ohm(Ω). The minimum resistance and maximum resistance shall be as given in Table-1. 表-2 电阻值有效数字的标准 Table-2 Standard nominal resistance values <table><tr><td>系列名 Name of series</td><td>标准公称电阻值（为有效数字，单位省略） Standard nominal resistance values (significant figures with the unit omitted)</td></tr><tr><td>E - 6</td><td>1.0, 1.5, 2.2, 3.3, 4.7, 6.8</td></tr><tr><td>E - 12</td><td>1.0, 1.2, 1.5, 1.8, 2.2, 2.7, 3.3, 3.9, 4.7, 5.6, 6.8, 8.2</td></tr><tr><td>E - 24</td><td>1.0, 1.1, 1.2, 1.3, 1.5, 1.6, 1.8, 2.0, 2.2, 2.4, 2.7, 3.0, 3.3, 3.6, 3.9, 4.3, 4.7, 5.1, 5.6, 6.2, 6.8, 7.5, 8.2, 9.1</td></tr><tr><td>E - 48</td><td>1.00, 1.05, 1.10, 1.15, 1.21, 1.27, 1.33, 1.40, 1.47, 1.54, 1.62, 1.69, 1.78, 1.87, 1.96, 2.05, 2.15, 2.26, 2.37, 2.49, 2.61, 2.74, 2.87, 3.01, 3.16, 3.32, 3.48, 3.65, 3.83, 4.02, 4.22, 4.42, 4.64, 4.87, 5.11, 5.36, 5.62, 5.90, 6.19, 6.49, 6.81, 7.15, 7.50, 7.87, 8.25, 8.66, 9.09, 9.53</td></tr></table>				系列名 Name of series	标准公称电阻值（为有效数字，单位省略） Standard nominal resistance values (significant figures with the unit omitted)	E - 6	1.0, 1.5, 2.2, 3.3, 4.7, 6.8	E - 12	1.0, 1.2, 1.5, 1.8, 2.2, 2.7, 3.3, 3.9, 4.7, 5.6, 6.8, 8.2	E - 24	1.0, 1.1, 1.2, 1.3, 1.5, 1.6, 1.8, 2.0, 2.2, 2.4, 2.7, 3.0, 3.3, 3.6, 3.9, 4.3, 4.7, 5.1, 5.6, 6.2, 6.8, 7.5, 8.2, 9.1	E - 48	1.00, 1.05, 1.10, 1.15, 1.21, 1.27, 1.33, 1.40, 1.47, 1.54, 1.62, 1.69, 1.78, 1.87, 1.96, 2.05, 2.15, 2.26, 2.37, 2.49, 2.61, 2.74, 2.87, 3.01, 3.16, 3.32, 3.48, 3.65, 3.83, 4.02, 4.22, 4.42, 4.64, 4.87, 5.11, 5.36, 5.62, 5.90, 6.19, 6.49, 6.81, 7.15, 7.50, 7.87, 8.25, 8.66, 9.09, 9.53
系列名 Name of series	标准公称电阻值（为有效数字，单位省略） Standard nominal resistance values (significant figures with the unit omitted)												
E - 6	1.0, 1.5, 2.2, 3.3, 4.7, 6.8												
E - 12	1.0, 1.2, 1.5, 1.8, 2.2, 2.7, 3.3, 3.9, 4.7, 5.6, 6.8, 8.2												
E - 24	1.0, 1.1, 1.2, 1.3, 1.5, 1.6, 1.8, 2.0, 2.2, 2.4, 2.7, 3.0, 3.3, 3.6, 3.9, 4.3, 4.7, 5.1, 5.6, 6.2, 6.8, 7.5, 8.2, 9.1												
E - 48	1.00, 1.05, 1.10, 1.15, 1.21, 1.27, 1.33, 1.40, 1.47, 1.54, 1.62, 1.69, 1.78, 1.87, 1.96, 2.05, 2.15, 2.26, 2.37, 2.49, 2.61, 2.74, 2.87, 3.01, 3.16, 3.32, 3.48, 3.65, 3.83, 4.02, 4.22, 4.42, 4.64, 4.87, 5.11, 5.36, 5.62, 5.90, 6.19, 6.49, 6.81, 7.15, 7.50, 7.87, 8.25, 8.66, 9.09, 9.53												
		承 认 Approved by	作 成 Drawn by										
		周国新	黄根荣										

标准书名 Classification		产品规格书	Specification	Spec No.	CF.APR-01
品 名		碳膜固定电阻器	CF Series	PAGE	10-5
Product Name		Fixed Carbon Film Resistors			
构造图 Structure diagram CF 系列之碳素皮膜固定电阻器是按下表的材料而构成： The construction of resistor (CF series) shall be as follows： 					
号码 No.	构造名称 Item	内 容 Material			
1	基体磁器 Ceramic core	使用高含铝量的瓷器棒。 High alumina ceramic is used.			
2	电阻体 Resistance element	电阻体的成份是使用碳素皮膜。 The resistor element shall consist of Carbonl film.			
3	端子 Terminal	铁帽。 Tinned iron cap.			
4	连接 Connection	导线对铁帽须以电气熔接。 The lead wire, which is plated with solder, shall be mounted to the caps by welding process.			
5	导线 Lead wire	焊锡或镀锡铜包钢引线。不含铅 Soldered or tinned annealed copper wire. Lead free			
6	下涂涂装 Undercoat painting	电气绝缘漆。 Electric insulation varnish.			
7	上涂涂装 Finishing painting	使用环氧树脂涂料。 Epoxy resin is used.			
8	表示 Indication	色码。 Color code.			
				承 认 Approved by	作 成 Drawn by
				周国新	黄根荣

标准书名 Classification	产品规格书 Specification	Spec No.	CF.APR-01																			
品 名 Product Name	碳膜固定电阻器 CF Series Fixed Carbon Film Resistors	PAGE	10-6																			
铁帽端子 Terminal caps 的帽端子须确实地连接(电气的及机械的)于电阻体上。 The caps shall be securely connected with the resistor element electrically and mechanically. 涂装 Painting 本体必须依照仕様书之规定以绝缘涂料绝缘之。 Coating in accordance with specification insulates the body. 外装色泽 Resistor body color 表-3 Table-3 <table><tr><th colspan="2">普通型 Normal size</th><th colspan="2">小型化 Small size</th></tr><tr><th>种类 Type</th><th>颜色 Color</th><th>种类 Type</th><th>颜色 Color</th></tr><tr><td>CF1/6W (1/8W)</td><td rowspan="6">淡棕色 Light Brown</td><td>CF1/4WS</td><td>淡棕色 Light Brown</td></tr><tr><td>CF1/4W</td><td rowspan="5">CF1/2WS CF1WS CF2WS CF3WS</td><td rowspan="5">淡棕色 Light Brown</td></tr><tr><td>CF1/2W</td></tr><tr><td>CF1W</td></tr><tr><td>CF2W</td></tr><tr><td>CF3W</td></tr></table> 表示 Indication 参照本仕様书的「3. 表示」。 The indication shall be satisfied with 「3. Indication」.				普通型 Normal size		小型化 Small size		种类 Type	颜色 Color	种类 Type	颜色 Color	CF1/6W (1/8W)	淡棕色 Light Brown	CF1/4WS	淡棕色 Light Brown	CF1/4W	CF1/2WS CF1WS CF2WS CF3WS	淡棕色 Light Brown	CF1/2W	CF1W	CF2W	CF3W
普通型 Normal size		小型化 Small size																				
种类 Type	颜色 Color	种类 Type	颜色 Color																			
CF1/6W (1/8W)	淡棕色 Light Brown	CF1/4WS	淡棕色 Light Brown																			
CF1/4W		CF1/2WS CF1WS CF2WS CF3WS	淡棕色 Light Brown																			
CF1/2W																						
CF1W																						
CF2W																						
CF3W																						
		承 认 Approved by	作 成 Drawn by																			
		周国新	黄根荣																			

标准书名 Classification		产品规格书 Specification				Spec No.	CF.APR-01
品 名 Product Name		碳膜固定电阻器 CF Series Fixed Carbon Film Resistors				PAGE	10-7
2. 特性 Characteristics							
表-4 Table-4							
项目 Item	规格值 Performance					试验方法 (依据 JIS C 5202) Test methods (Conform to JIS C 5202)	
温度系数 Temperature coefficient	T.C.R 种类 Type	±450 PPM/℃	-700 PPM/℃	-1000 PPM/℃	-1300 PPM/℃	5.2 项参照 Comply with 5.2 $\frac{R_1 - R_0}{R_0(T_1 - T_0)} \times 10^6 (\text{PPM}/^\circ\text{C})$ R ₀ : 室温 (T ₀) 所测量之电阻值。 R ₁ : 室温+100℃ (T ₁) 后所测量之电阻值。 R ₀ : Resistance value at room temp. (T ₀). R ₁ : Resistance value at room temp. plus 100℃ (T ₁).	
	CF1/6W (1/8W) & RD1/4WS	Under 47KΩ	51K~ 100KΩ	110K~ 330KΩ	Over 360KΩ		
	CF1/4W & Over	Under 100KΩ	110K~ 1MΩ	1.1M~ 2.2MΩ	Over 2.4MΩ		
短时间过 负荷 Short time overload	±(1%+0.05Ω) 以內。 不得有机械的损伤。 within ±(1%+0.05Ω) No evidence of mechanical damage.					5.5 项参照 Comply with 5.5 额定电压 X 2.5 倍, 5 秒。 不可超过最高过负荷电压 (见表-1) Rated voltage X 2.5 times, 5s But not to exceed maximum overload voltage. (See table-1)	
绝缘抵抗 Insulation resistance	10 ⁴ MΩ 以上。 10 ⁴ MΩ or more					5.6 项参照 Comply with 5.6 置于 V 型槽方法。 施加个别规定之直流电压 60 秒。 V-block method Resistor shall be tested at DC potential respectively for 60 seconds.	
耐电压 Dielectric withstanding voltage	无电弧放电、烧损及绝缘破坏等异状。 No evidence of flashover mechanical damage, arcing or insulation breakdown.					5.7 项参照 Comply with 5.7 常压, 置于 V 型槽方法。 施加个别规定之交流电压 60 秒。(见表-1) Constant pressure, V-block method Resistor shall be tested at AC potential respectively for 60 seconds.(See table-1)	
断续过负 荷 Pulse overload	±(0.75%+0.05Ω) 以內。 within ±(0.75%+0.05Ω)					5.8 项参照 Comply with 5.8 额定电压 X 4 倍, 10000 回 (1 秒 ON, 25 秒 OFF)。 不可超过最高断续电压 (见表-1) Rated voltage X 4 times, 10000 cyc.(1s ON, 25s OFF) But not to exceed maximum pulse voltage.(See table-1)	
端子强度 Terminal strength	端子不得断裂及松弛。 No evidence of mechanical damage.					6.1 项参照 Comply with 6.1 引张强度: 25N(2.5Kgf), 保持 10 秒。 Tensile strength: 25N(2.5kgf), for 10 seconds. 扭转强度: 360° 交互回转 5 回。 Torsional strength: Rotated through 360°, 5 rotations.	
						承 认 Approved by	作 成 Drawn by
						周国新	黄根荣


标准书名 Classification		产品规格书 Specification	Spec No.	CF.APR-01
品 名 Product Name		碳膜固定电阻器 CF Series Fixed Carbon Film Resistors	PAGE	10-8
项目 Item	规格值 Performance	试验方法 (依据 JIS C 5202) Test methods (Conform to JIS C 5202)		
焊锡耐热性 Resistance to soldering heat	±(0.5%+0.05Ω)以內。 不得有机械的损伤。 within ±(0.5%+0.05Ω) No evidence of mechanical damage.	6.4 项参照 Comply with 6.4 350±10℃, 3+0.5/-0 秒, 试验后放置 3 小时。 350±10℃, 3+0.5/-0s After test leave for 3h.		
焊锡附着性 Solderability	导线至少 95%以上新锡覆盖。 Covered with new solder by 95% at least.	6.5 项参照 Comply with 6.5 焊锡温度: 235±5℃。 浸锡时间: 5±0.5 秒。 Test temperature of solder: 235±5℃ Dipping time in solder: 5±0.5s		
耐溶剂性 Resistance to solvent	涂装及色码不得脱落。 No deterioration of protective coating and markings.	6.9 项参照 Comply with 6.9 放入异丙醇溶剂之超音波机内, 保持 3 分钟。 Specimens shall be immersed in a bath of isopropyl alcohol completely for 3 minutes with ultrasonic.		
温度循环 Temperature cycle	±(1%+0.05Ω)以內。 不得有机械的损伤。 within ±(1%+0.05Ω) No evidence of mechanical damage.	7.4 项参照 Comply with 7.4 低温侧: -55℃/30 分, 室温: 10~15 分钟 高温侧: +85℃/30 分, 室温: 10~15 分钟 5 回 Low side : -55℃/30min, Room temp. : 10 to 15min High side : 85℃/30min, Room temp. : 10 to 15min 5 cycles		
耐湿负荷寿命 Load life in humidity	±(1.5%+0.05Ω)以內。 within ±(1.5%+0.05Ω)	7.9 项参照 Comply with 7.9 40±2℃, 湿度 90~95%, 1000 小时 定格电压(90 分钟 ON, 30 分钟 OFF) 40±2℃, 90 to 95%RH, 1000h Rated voltage (90 min ON, 30 min OFF)		
负荷寿命 Load life	±(2%+0.05Ω)以內。 within ±(2%+0.05Ω)	7.10 项参照 Comply with 7.10 70±3℃, 1000 小时 定格电压(90 分钟 ON, 30 分钟 OFF) 70±3℃, 1000h Rated voltage (90 min ON, 30 min OFF)		
			承 认 Approved by	作 成 Drawn by
			周国新	黄根荣

标准书名 Classification	产品规格书 Specification	Spec No.	CF.APR-01
品 名 Product Name	碳膜固定电阻器 CF Series Fixed Carbon Film Resistors	PAGE	10-9

3. 表示 Indication
色码 Color Code



颜色 Color	第 1 数字 1 st figure	第 2 数字 2 nd figure	第 3 数字 3 rd figure	倍 率 Multiplier	误差率 Tolerance
黑 Black	0	0	0	10 ⁰	
棕 Brown	1	1	1	10 ¹	
红 Red	2	2	2	10 ²	±2% (G)
橙 Orange	3	3	3	10 ³	
黄 Yellow	4	4	4	10 ⁴	
绿 Green	5	5	5	10 ⁵	
蓝 Blue	6	6	6	10 ⁶	
紫 Violet	7	7	7	10 ⁷	
灰 Gray	8	8	8		
白 White	9	9	9		
金 Gold				10 ⁻¹	±5% (J)
银 Silver				10 ⁻²	±10% (K)
无 Plain					±20% (M)




	承 认 Approved by	作 成 Drawn by
	周国新	黄根荣

标准书名 Classification	产品规格书 Specification	Spec No.	.APR-01
品 名 Product Name	碳膜固定电阻器 CF Series Fixed Carbon Film Resistors	PAGE	10-10


4. 外形寸法 External dimensions

散装P形与 卧式M形系列
P type & M-Form series (Horizontal Forming)

P Type



M Type



单位：mm
Unit：mm

种 类 Type		尺 寸 Dimensions					
普通型 Normal Size	小型化 Small Size	L	φ D	φ d	H	P	h
1/6W(1/8W)	1/4WS	3.5±0.5	1.7±0.3	0.40±0.05	27±3.0	6.0±1.0	10.0±1.0
1/4W	1/2WS	6.0±0.5	2.3±0.3	0.40±0.05	27±3.0	10.0±1.0	10.0±1.0
1/2W	1WS	9.0±1.0	3.2±0.5	0.50±0.05	27±3.0	12.5±1.0	10.0±1.0
1W	2WS	11.0±1.0	4.0±0.5	0.60±0.05	31±3.0	15.0±1.0	14.0±1.0
2W	3WS	15.0±1.0	5.0±0.5	0.70±0.05	35±3.0	20.0±1.0	20.0±1.0
3W		17.5±1.0	6.5±1.0	0.70±0.05	30±3.0	25.0±1.0	25.0±1.0

	承 认 Approved by	作 成 Drawn by
	周国新	黄根荣

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru