


SPECIFICATION CONTROL DRAWING



Product Revisions		Product Dimensions				"XY"	Cable Dimensions		
Product Names		L max	ϕA min	ϕB min	K min	Wire Gauge (AWG)	D max	F	$M \pm 0.5$ ($M \pm 0.02$)
B-801-50	G	17.50 (0.690)	1.40 (0.055)	2.80 (0.110)	150 (5.900)	30	2.40 (0.095)	0.30 (0.015)	5.00 (0.200)
B-801-56	G					26		to 1.40 (0.055)	
B-801-58	G					28			


MATERIALS

- INSULATION SLEEVE: Heat-shrinkable, transparent blue radiation cross-linked modified polyvinylidene fluoride.
- SOLDER PREFORM WITH FLUX:
SOLDER: TYPE Sn63 per ANSI J-STD-006.
FLUX: TYPE ROL1 per ANSI J-STD-004.
- MELTABLE RING: Thermally stabilized thermoplastic. Color: red.
- CONDUCTOR LEAD: MIL-W-81822/13 AWG "XY" (see table) solid silver plated copper wire. Color: white.

APPLICATION

- These controlled soldering devices are designed to terminate with a solid extension lead:
 - a metallic pin or
 - the primary of a coaxial cable or
 - one or several tin or silver plated wire(s),
 having an insulation rated for at least +125°C.
- Temperature range: -55°C to +150°C.
- Install using Raychem-approved convection or infrared tools in accordance with Raychem Installation Procedure RPIP-825-00.

For best results, prepare the wire(s) as shown:



tyco Electronics 307 Constitution Drive Menlo Park, CA 94025, USA		Raychem		TITLE : SOLDERSLEEVE DEVICE EXTENSION			
Unless otherwise specified dimensions are in millimeters. Inches dimensions are in between brackets.				DOCUMENT NO.: B-801-5X			
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ANGLES: N/A ROUGHNESS IN MICRON	Tyco Electronics reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.		DCR NUMBER: D010114		REPLACES: D981693	
DRAWN BY: M. FORONDA	DATE: 11-Apr.-01	PROD. REV. SEE TABLE	DOC ISSUE: 4	SCALE: None	SIZE: A	SHEET: 1 of 1	

If this document is printed it becomes uncontrolled. Check for the latest revision.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru