

Type 4, 4X Mild Steel and Stainless Steel Base Units *Series 2000*

Modular Console System



Application

- Flexible design provides panel mount or rack mount capabilities for a variety of applications.
- Generally used in combination with other modular console components (ie. another base, terminal, desk and/or turret).
- Available in either single or dual access format.
- Smooth lines and clean edges provide an attractive, contemporary appearance.

Standards

- UL 508 Type 3R, 4, 12
- CSA Type 3R, 4, 12, 13
- EIA RS-310-D
- Complies with
 - NEMA Type 3R, 4, 12
 - IEC 60529, IP66

Construction

- UL 508 Type 3R, 4, 4X, 12
- CSA Type 3R, 4, 4X, 12
- EIA RS-310-D
- Complies with
 - NEMA Type 3R, 4, 4X, 12
 - IEC 60529, IP66

Finish

- Formed 14 gauge steel bodies with 14 gauge steel door.
- Also offered with formed 14 gauge 304 stainless steel bodies with 14 gauge 304 stainless steel door.
- Smooth, continuously welded seams.
- Body stiffeners are provided where required for increased strength and rigidity.
- Offered in 4 widths 24", 36", 48" and 60".
- Single access version has solid sides and back, solid door on front, open top, and closed bottom with removable access panel.
- Dual access version is same as above except has solid door on both front and back.
- 24" and 36" widths have single door on the front (and back for dual access) whereas 48" and 60" widths have two outside hinged doors on the front (and back for dual access).
- Doors can be hinged from either side on 24" and 36" units.
- Door profiles provide increased strength and are pre-punched to provide mounting options.



- Formed lip on enclosure excludes flowing liquids and contaminants.
- Slotted quarter turn oil-tight latches secure the door, with optional tamper resistant and locking latches available.
- Stainless steel models utilize stainless steel hardware.
- Oil resistant gaskets are permanently secured.
- Features several internal stud locations for mounting of various accessories.
- A bonding screw is provided on the door and a grounding stud is provided in the enclosure.

Accessories

- Available in RAL 7035 light gray textured powder coating and natural stainless steel with a smooth, brushed finish.
- Base Covers are available in the same finishes.

Gallery



Accessories

- | | |
|---|---|
| <ul style="list-style-type: none"> • Cooling Products • Filtered Fans • Heaters • Modular Plinth • Data Terminal Extension Ring • Base Cover • Base Panel • "C" Channel Mounting Kit • Combination Rails • DIN Rails • Micro Cell Cable Entry Kit • 24 to 19 Inch Rack Rail Reducer Panel • Four Post Mounting Equipment Slides • Four Post Mounting Fixed Chassis Shelf • Equipment Support Rack Panel • Console Casters | <ul style="list-style-type: none"> • Blowers and Fans • Rack Mount Fan Tray • Pedestal • Footrest • Turret/Terminal Window Door • Base Window Door • Swing Frame • Rail Support Kit • Printer and Paper Stand • DIN Rail Support Kit • Steel Rack Panels • Rack Mount Locking Storage Drawer • Side Support Angles • Two Post Mounting Storage Shelf • Quarter Turn Assemblies |
|---|---|

Single Access



Top View - Single Door
Doors Removed




Top View - Two Door
Doors Removed



**Front View
Single Door**



**Side View
Either**



**Front View
Two Door**

Dual Access



Top View - Single Door
Doors Removed




Top View - Two Door
Doors Removed



**Front View
Single Door**



**Side View
Either**



**Front View
Two Door**

Single Access

| RAL 7035 Light Gray Part No. | Stainless Steel Part No. | B1 | B2 |
|---------------------------------|-----------------------------|-------|-------|
| 2CLB262418 | 2CSB262418 | 24.00 | - |
| 2CLB263618 | 2CSB263618 | 36.00 | - |
| 2CLB264818 | 2CSB264818 | - | 48.00 |
| 2CLB266018 | 2CSB266018 | - | 60.00 |

Dual Access

| RAL 7035 Light Gray Part No. | Stainless Steel Part No. | B1 | B2 |
|---------------------------------|-----------------------------|-------|-------|
| 2CLBX262418 | 2CSBX262418 | 24.00 | - |
| 2CLBX263618 | 2CSBX263618 | 36.00 | - |
| 2CLBX264818 | 2CSBX264818 | - | 48.00 |
| 2CLBX266018 | 2CSBX266018 | - | 60.00 |

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренеспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru