


Arbitrary/Function Generators

AFG3000C Series Datasheet



Unmatched performance, versatility, intuitive operation, and affordability make the AFG3000C Series of Function, Arbitrary Waveform, and Pulse Generators the most useful instruments in the industry.

Key performance specifications

- 10 MHz, 25 MHz, 100 MHz, or 240 MHz sine waveforms
- 14 bits, 250 MS/s, 1 GS/s, or 2 GS/s arbitrary waveforms
- Amplitude up to 20 V_{p-p} into 50 Ω loads

Key features

- 5.6 in. display for full confidence in settings and waveform shape
- Multi-language and intuitive operation saves setup time
- Pulse waveform with variable edge times
- AM, FM, PM, FSK, PWM
- Sweep and burst
- Dual-channel models save cost and bench space
- USB connector on front panel for waveform storage on memory device
- USB, GPIB, and LAN
- LabVIEW and LabWindows/IVI-C drivers

Applications

- Electronic test and design
- Sensor simulation
- Functional test
- Education and training

Superior performance and versatility

Users can choose from 12 different standard waveforms. Arbitrary waveforms can be generated up to 128 K in length at high sampling rates. On pulse waveforms, leading and trailing edge time can be set independently. External signals can be connected and added to the output signal. Dual-channel models can generate two identical or completely different signals. All instruments feature a highly stable time base with only ±1 ppm drift per year.

Intuitive user interface shows more information at a single glance

Color TFT LCD screen on all models shows all relevant waveform parameters and graphical wave shape at a single glance. This gives full confidence in the signal settings and lets you focus on the task at hand. Shortcut keys provide direct access to frequently used functions and parameters. Others can be selected conveniently through clearly structured menus. This reduces the time needed for learning and relearning how to use the instrument. Look and feel are identical to the world's most popular TDS3000 Oscilloscopes.

ArbExpress™ software included for creating waveforms with ease

With this PC software waveforms can be seamlessly imported from any Tektronix oscilloscope, or defined by standard functions, equation editor, and waveform math.

Specifications ¹

All specifications apply to all models unless noted otherwise.

Model overview

	AFG3011C	AFG3021C, AFG3022C	AFG3051C, AFG3052C	AFG3101C, AFG3102C	AFG3251C, AFG3252C
Channels	1	1 / 2	1 / 2	1 / 2	1 / 2
Waveforms	Sine, Square, Pulse, Ramp, Triangle, Sin(x)/x, Exponential Rise and Decay, Gaussian, Lorentz, Haversine, DC, Noise				

General characteristics

Sine waves

	AFG3011C	AFG3021C, AFG3022C	AFG3051C, AFG3052C	AFG3101C, AFG3102C	AFG3251C, AFG3252C
Frequency range	1 μ Hz to 10 MHz	1 μ Hz to 25 MHz	1 μ Hz to 50 MHz	1 μ Hz to 100 MHz	1 μ Hz to 240 MHz
Sine wave in Burst Mode	1 μ Hz to 5 MHz	1 μ Hz to 12.5 MHz	1 μ Hz to 25 MHz	1 μ Hz to 50 MHz	1 μ Hz to 120 MHz
Effective maximum frequency out	10 MHz	25 MHz	50 MHz	100 MHz	240 MHz
Amplitude flatness (1 V_{p-p})	<5 MHz: ± 0.15 dB ≥ 5 MHz to 10 MHz: ± 0.3 dB	<5 MHz: ± 0.15 dB ≥ 5 MHz to 20 MHz: ± 0.3 dB ≥ 20 MHz to 25 MHz: ± 0.5 dB	<5 MHz: ± 0.15 dB ≥ 5 MHz to 45 MHz: ± 0.3 dB ≥ 45 MHz to 50 MHz: ± 0.5 dB	<5 MHz: ± 0.15 dB ≥ 5 MHz to 25 MHz: ± 0.3 dB ≥ 25 MHz to 100 MHz: ± 0.5 dB	<5 MHz: ± 0.15 dB ≥ 5 MHz to 25 MHz: ± 0.3 dB ≥ 25 MHz to 100 MHz: ± 0.5 dB ≥ 100 MHz to 200 MHz: ± 1.0 dB ≥ 200 MHz to 240 MHz: ± 2.0 dB
Amplitude flatness (1 V_{p-p}), typical	<5 MHz: ± 0.11 dB ≥ 5 MHz to 10 MHz: ± 0.2 dB	<5 MHz: ± 0.06 dB ≥ 5 MHz to 25 MHz: ± 0.02 dB	<5 MHz: ± 0.06 dB ≥ 5 MHz to 50 MHz: ± 0.02 dB	<5 MHz: ± 0.03 dB ≥ 5 MHz to 50 MHz: ± 0.02 dB ≥ 50 MHz to 100 MHz: ± 0.03 dB	<5 MHz: ± 0.03 dB ≥ 5 MHz to 50 MHz: ± 0.02 dB ≥ 50 MHz to 100 MHz: ± 0.02 dB ≥ 100 MHz to 200 MHz: ± 0.03 dB ≥ 200 MHz to 240 MHz: ± 0.04 dB
Harmonic distortion (1 V_{p-p})	10 Hz to 20 kHz: < -60 dBc ≥ 20 kHz to 1 MHz: < -55 dBc ≥ 1 MHz to 5 MHz: < -45 dBc ≥ 5 MHz to 10 MHz: < -45 dBc	10 Hz to 20 kHz: < -70 dBc ≥ 20 kHz to 1 MHz: < -60 dBc ≥ 1 MHz to 10 MHz: < -50 dBc ≥ 10 MHz to 25 MHz: < -40 dBc	10 Hz to 20 kHz: < -70 dBc ≥ 20 kHz to 1 MHz: < -60 dBc ≥ 1 MHz to 5 MHz: < -50 dBc ≥ 5 MHz to 50 MHz: < -40 dBc	10 Hz to 1 MHz: < -60 dBc ≥ 1 MHz to 5 MHz: < -50 dBc ≥ 5 MHz to 100 MHz: < -37 dBc	10 Hz to 1 MHz: < -60 dBc ≥ 1 MHz to 5 MHz: < -50 dBc ≥ 5 MHz to 25 MHz: < -37 dBc ≥ 25 MHz to 240 MHz: < -30 dBc
Harmonic distortion (1 V_{p-p}), typical	10 Hz to 20 kHz: < -73 dBc ≥ 20 kHz to 1 MHz: < -72 dBc ≥ 1 MHz to 5 MHz: < -65 dBc ≥ 5 MHz to 10 MHz: < -56 dBc	10 Hz to 20 kHz: < -77 dBc ≥ 20 kHz to 1 MHz: < -72 dBc ≥ 1 MHz to 25 MHz: < -55 dBc	10 Hz to 20 kHz: < -75 dBc ≥ 20 kHz to 1 MHz: < -72 dBc ≥ 1 MHz to 5 MHz: < -65 dBc ≥ 5 MHz to 50 MHz: < -56 dBc	10 Hz to 1 MHz: < -72 dBc ≥ 1 MHz to 5 MHz: < -66 dBc ≥ 5 MHz to 100 MHz: < -43 dBc	10 Hz to 1 MHz: < -67 dBc ≥ 1 MHz to 5 MHz: < -74 dBc ≥ 5 MHz to 25 MHz: < -57 dBc ≥ 25 MHz to 240 MHz: < -43 dBc

¹ The given typical values are not warranted. But 80% or more manufactured units will perform to the level indicated at room temperature (approximately 25 °C).

General characteristics

Spurious(1 V_{p-p})	10 Hz to 1 MHz: < -60 dBc ≥1 MHz to 10 MHz: < -50 dBc	10 Hz to 1 MHz: < -60 dBc ≥1 MHz to 25 MHz: < -50 dBc	10 Hz to 1 MHz: < -60 dBc ≥1 MHz to 50 MHz: < -50 dBc	10 Hz to 1 MHz: < -60 dBc ≥1 MHz to 25 MHz: < -50 dBc ≥25 MHz to 100 MHz: < -50 dBc + 6 dBc/octave	10 Hz to 1 MHz: < -50 dBc ≥1 MHz to 25 MHz: < -47 dBc ≥25 MHz to 240 MHz: < -47 dBc + 6 dBc/octave
Spurious(1 V_{p-p}), typical	10 Hz to 1 MHz: < -61 dBc ≥1 MHz to 10 MHz: < -68 dBc	10 Hz to 1 MHz: < -71 dBc ≥1 MHz to 25 MHz: < -68 dBc	10 Hz to 1 MHz: < -71 dBc ≥1 MHz to 50 MHz: < -69 dBc	10 Hz to 1 MHz: < -71 dBc ≥1 MHz to 25 MHz: < -63 dBc ≥25 MHz to 50 MHz: < -87 dBc ≥50 MHz to 100 MHz: < -52 dBc	10 Hz to 1 MHz: < -63 dBc ≥1 MHz to 25 MHz: < -57 dBc ≥25 MHz to 50 MHz: < -51 dBc ≥50 MHz to 100 MHz: < -69 dBc ≥100 MHz to 240 MHz: < -55 dBc
Phase noise, typical	< -110 dBc/Hz at 10 MHz, 10 kHz offset, 1 V _{p-p}				
Residual clock noise	-63 dBm	-63 dBm	-63 dBm	-57 dBm	-57 dBm

Square waves

	AFG3011C	AFG3021C, AFG3022C	AFG3051C, AFG3052C	AFG3101C, AFG3102C	AFG3251C, AFG3252C
Frequency range	1 μHz to 5 MHz	1 μHz to 25 MHz	1 μHz to 40 MHz	1 μHz to 50 MHz	1 μHz to 120 MHz
Rise/fall time	≤50 ns	≤9 ns	≤7 ns	≤5 ns	≤2.5 ns
Jitter (RMS)	500 ps	500 ps	300 ps	200 ps	100 ps
Jitter (RMS), typical	<210 ps	<60 ps	<60 ps	<35 ps	<35 ps

Ramp waves

	AFG3011C	AFG3021C, AFG3022C	AFG3051C, AFG3052C	AFG3101C, AFG3102C	AFG3251C, AFG3252C
Frequency range	1 μHz to 100 kHz	1 μHz to 500 kHz	1 μHz to 800 kHz	1 μHz to 1 MHz	1 μHz to 2.4 MHz
Linearity, typical	≤0.2% of peak output	≤0.1% of peak output	≤0.1% of peak output	≤0.15% of peak output	≤0.2% of peak output
Symmetry	0% to 100.0%				

Pulse waves

	AFG3011C	AFG3021C, AFG3022C	AFG3051C, AFG3052C	AFG3101C, AFG3102C	AFG3251C, AFG3252C
Frequency range	1 mHz to 5 MHz	1 mHz to 25 MHz	1 mHz to 40 MHz	1 mHz to 50 MHz	1 mHz to 120 MHz
Pulse width	80.00 ns to 999.99 s	16 ns to 999.99 s	12 ns to 999.99 s	8.00 ns to 999.99 s	4.00 ns to 999.99 s
Resolution	10 ps or 5 digits				
Pulse duty	0.001% to 99.999% (Limitations of pulse width apply)				
Edge transition time	50 ns to 625 s	9 ns to 625 s	7 ns to 625 s	5 ns to 625 s	2.5 ns to 625 s
Resolution	10 ps or 4 digits				
Lead delay: range	(Continuous Mode): 0 ps to Period (Triggered/Gated Burst Mode): 0 ps to Period - [Pulse Width + 0.8 * (Leading Edge Time + Trailing Edge Time)]				
Lead delay: resolution	10 ps or 8 digits				

General characteristics

Overshoot, typical	<5%				
Jitter (RMS)	500 ps	500 ps	300 ps	200 ps	100 ps
Jitter (RMS), typical	<210 ps	<60 ps	<60 ps	<35 ps	<35 ps

Other waveforms

	AFG3011C	AFG3021C, AFG3022C	AFG3051C, AFG3052C	AFG3101C, AFG3102C	AFG3251C, AFG3252C
Frequency range	1 μ Hz to 100 kHz	1 μ Hz to 500 kHz	1 μ Hz to 800 kHz	1 μ Hz to 1 MHz	1 μ Hz to 2.4 MHz
Noise bandwidth (-3 dB)	10 MHz	25 MHz	50 MHz	100 MHz	240 MHz
Noise type:	White Gaussian				
Internal noise add	When activated, output signal amplitude is reduced to 50%				
Level	0.0% to 50% of amplitude (V_{p-p}) setting				
Resolution	1%				
DC (into 50 Ω)	-10 V to +10 V	-5 V to +5 V	-5 V to +5 V	-5 V to +5 V	-2.5 V to +2.5 V

Arbitrary waveforms

	AFG3011C	AFG3021C, AFG3022C	AFG3051C, AFG3052C	AFG3101C, AFG3102C	AFG3251C, AFG3252C
Frequency range	1 mHz to 5 MHz	1 mHz to 12.5 MHz	1 mHz to 25 MHz	1 mHz to 50 MHz	1 mHz to 120 MHz
Arbitrary waveforms in Burst Mode	1 mHz to 2.5 MHz	1 mHz to 6.25 MHz	1 mHz to 12.5 MHz	1 mHz to 25 MHz	1 mHz to 60 MHz
Effective analog bandwidth (-3 dB)	8 MHz	70 MHz		100 MHz	225 MHz
Nonvolatile memory	4 waveforms				
Memory: Sample rate (1K=1024 points)	2 to 128 K: 250 MS/s	2 to 128 K: 250 MS/s	2 to 16 K: 1 GS/s >16 K to 128 K: 250 MS/s	2 to 16 K: 1 GS/s >16 K to 128 K: 250 MS/s	2 to 16 K: 2 GS/s >16 K to 128 K: 250 MS/s
Vertical resolution	14 bits				
Rise/fall time	\leq 80 ns	\leq 14 ns	\leq 10 ns	\leq 8 ns	\leq 3 ns
Jitter (RMS)	4 ns	4 ns	1 ns at 1 GS/s 4 ns at 250 MS/s	1 ns at 1 GS/s 4 ns at 250 MS/s	500 ps at 2 GS/s 4 ns at 250 MS/s

Amplitude

	AFG3011C	AFG3021C, AFG3022C	AFG3051C, AFG3052C	AFG3101C, AFG3102C	AFG3251C, AFG3252C
Range, 50 Ω Load	20 mV _{p-p} to 20 V _{p-p}	10 mV _{p-p} to 10 V _{p-p}	10 mV _{p-p} to 10 V _{p-p}	20 mV _{p-p} to 10 V _{p-p}	\leq 200 MHz: 50 mV _{p-p} to 5 V _{p-p} >200 MHz: 50 mV _{p-p} to 4 V _{p-p}
Range (open circuit or High Z)	40 mV _{p-p} to 40 V _{p-p}	20 mV _{p-p} to 20 V _{p-p}	20 mV _{p-p} to 20 V _{p-p}	40 mV _{p-p} to 20 V _{p-p}	\leq 200 MHz: 100 mV _{p-p} to 10 V _{p-p} >200 MHz: 100 mV _{p-p} to 8 V _{p-p}
Accuracy	\pm (2% of setting +2 mV) (1 kHz sine wave, 0 V offset, >20 mV _{p-p} amplitude)	\pm (1% of setting +1 mV) (1 kHz sine wave, 0 V offset, >10 mV _{p-p} amplitude)			

General characteristics

Accuracy, typical	$\pm(1\% \text{ of setting} + 5 \text{ mV})$ (1 kHz sine wave, 0 V offset, $>20 \text{ mV}_{p-p}$ amplitude)	$\pm(0.5\% \text{ of setting} + 0.5 \text{ mV})$ (1 kHz sine wave, 0 V offset, $>10 \text{ mV}_{p-p}$ amplitude)
Resolution	0.1 mV _{p-p} , 0.1 mV _{RMS} , 1 mV, 0.1 dBm or 4 digits	
Units	V _{p-p} , V _{RMS} , dBm (sine wave only) and Volt (high/low setting)	
Output impedance	50 Ω	
Load impedance setting	Selectable: 50 Ω, 1 Ω to 10.0 kΩ, High Z (Adjusts displayed amplitude according to selected load impedance)	
Isolation	42 V _{pk} maximum to earth	
Short-circuit protection	Signal outputs are robust against permanent shorts against floating ground	
External voltage protection	To protect signal outputs against external voltages use fuse adapter 013-0345-xx	

DC offset

	AFG3011C	AFG3021C, AFG3022C	AFG3051C, AFG3052C	AFG3101C, AFG3102C	AFG3251C, AFG3252C
Range (50 Ω load)	$\pm(10 \text{ V}_{pk} - \text{Amplitude}_{p-p} \div 2)$	$\pm(5 \text{ V}_{pk} - \text{Amplitude}_{p-p} \div 2)$	$\pm(5 \text{ V}_{pk} - \text{Amplitude}_{p-p} \div 2)$	$\pm 5 \text{ V}_{pk} \text{ DC}$	$\pm 2.5 \text{ V}_{pk} \text{ DC}$
Range (open circuit or High Z)	$\pm(20 \text{ V}_{pk} - \text{Amplitude}_{p-p} \div 2)$	$\pm(10 \text{ V}_{pk} - \text{Amplitude}_{p-p} \div 2)$	$\pm(10 \text{ V}_{pk} - \text{Amplitude}_{p-p} \div 2)$	$\pm 10 \text{ V}_{pk} \text{ DC}$	$\pm 5 \text{ V}_{pk} \text{ DC}$
Accuracy	$\pm(2\% \text{ of } \text{setting} + 10 \text{ mV} + 1\% \text{ of amplitude } (V_{p-p}))$	$\pm(1\% \text{ of } \text{setting} + 5 \text{ mV} + 0.5\% \text{ of amplitude } (V_{p-p}))$			
Resolution	1 mV				

System characteristics

Frequency resolution	1 μHz or 12 digits
Internal frequency reference	
Stability	All except ARB: $\pm 1 \text{ ppm}$, 0 °C to 50 °C ARB: $\pm 1 \text{ ppm} \pm 1 \mu\text{Hz}$, 0 °C to 50 °C
Aging	$\pm 1 \text{ ppm per year}$
Phase (except DC, noise, pulse)	
Range	-180° to +180°
Resolution	0.01° (sine), 0.1° (other waveforms)
Internal noise add	When activated, output signal amplitude is reduced to 50%
Level	0.0% to 50% of amplitude (V _{p-p}) setting
Resolution	1%
Main output	50 Ω

System characteristics

Remote programming: GPIB, LAN 10BASE-T / 100BASE-TX, USB 1.1
 configuration times, max, typical
 Compatible with SCPI-1999.0 and IEEE 488-2 standards

	USB	LAN	GPIB
Function change	81 ms	81 ms	81 ms
Frequency change (except Pulse)	2.5 ms	6 ms	3.2 ms
Frequency change (Pulse)	40 ms	37 ms	32 ms
Amplitude change	90 ms	97 ms	90 ms
Select user ARB (4k points from USB Memory)	48 ms	50 ms	49 ms
Select user ARB (128k points from USB Memory)	260 ms	266 ms	240 ms

Remote programming: data download time for 4000 point waveform data, typical	USB	LAN	GPIB
	47 ms	78 ms	320 ms

Power source 100-240 V, 47-63 Hz, or 115 V, 360-440 Hz

Power consumption Less than 120 W

Warm up time, typical 20 minutes

Power on self-diagnosis, typical <10 s

Acoustic noise, typical <50 dBA

Display 5.6 in. Color TFT LCD

User interface and Help languages English, French, German, Japanese, Korean, Portuguese, Simplified and Traditional Chinese, Russian (user selectable)

Modulation characteristics

AM, FM, PM

Carrier waveforms All except Pulse, Noise, and DC
Source Internal/external
Internal modulating waveform Sine, square, ramp, noise, ARB
 (AM: maximum waveform length 4,096;
 FM/PM: maximum waveform length 2,048)
Internal modulating frequency 2 mHz to 50.00 kHz
AM modulation depth 0.0% to +120.0%
Min FM peak deviation DC
Max FM peak deviation See following table,
PM phase deviation -360.0° to +360.0°

Pulse width modulation

Carrier waveform Pulse
Source Internal/external

Modulation characteristics

Internal modulating waveform	Sine, square, ramp, noise, ARB (maximum waveform length 2,048)
Internal modulating frequency	2 mHz to 50.00 kHz
Deviation	0% to 50.0% of pulse period

Max FM peak deviation

	AFG3011C	AFG3021C, AFG3022C	AFG3051C, AFG3052C	AFG3101C, AFG3102C	AFG3251C, AFG3252C
Sine	5 MHz	12.5 MHz	25 MHz	50 MHz	120 MHz
Square	2.5 MHz	12.5 MHz	20 MHz	25 MHz	60 MHz
ARB	2.5 MHz	6.25 MHz	12.5 MHz	25 MHz	60 MHz
Others	50 kHz	250 kHz	400 kHz	500 kHz	1.2 MHz

Frequency shift keying

Carrier waveforms	All, except Pulse, Noise, and DC
Source	Internal/external
Internal modulating frequency	2 mHz to 1,000 MHz
Number of keys	2

Sweep

Waveforms	All, except Pulse, Noise, and DC
Type	Linear, logarithmic
Sweep time	1 ms to 300 s
Hold/return time	0 ms to 300 s
Max total sweep time	300 s
Resolution	1 ms or 4 digits
Total sweep time accuracy, typical	≤0.4%
Min start/stop frequency	All except ARB: 1 μHz ARB: 1 mHz
Max start/stop frequency	See chart, below

Sweep: max start/stop frequency

	AFG3011C	AFG3021C, AFG3022C	AFG3051C, AFG3052C	AFG3101C, AFG3102C	AFG3251C, AFG3252C
Sine	10 MHz	25 MHz	50 MHz	100 MHz	240 MHz
Square	5 MHz	25 MHz	40 MHz	50 MHz	120 MHz
ARB	5 MHz	12.5 MHz	25 MHz	50 MHz	120 MHz
Others	100 kHz	500 kHz	800 kHz	1 MHz	2.4 MHz

Burst

Waveforms	All, except Noise and DC
Type	Triggered, gated (1 to 1,000,000 cycles or Infinite)
Internal trigger rate	1 μs to 500.0 s
Gate and trigger sources	Internal, external, remote interface

Auxiliary input characteristics

Modulation inputs	Channel 1, Channel 2
Input range	All except FSK: ± 1 V FSK: 3.3 V logic level
Impedance	10 k Ω
Frequency range	DC to 25 kHz (122 kS/s)

External Triggered/Gated Burst input

Level	TTL compatible
Impedance	10 k Ω
Pulse width	100 ns minimum
Slope	Positive/negative, selectable
Trigger delay	0.0 ns to 85.000 s
Trigger delay resolution	100 ps or 5 digits
Jitter (RMS), typical	Burst: <500 ps (trigger input to signal output)

10 MHz reference input

Impedance	1 k Ω , AC coupled
Required input voltage swing	100 mV _{p-p} to 5 V _{p-p}
Lock range	10 MHz \pm 35 kHz

External channel 1 add input

	AFG3101C, AFG3102C, AFG3251C, AFG3252C only
Impedance	50 Ω
Input range	-1 V to +1 V (DC + peak AC)
Bandwidth	DC to 10 MHz (-3 dB) at 1 V _{p-p}

Auxiliary output characteristics

Trigger output (Channel 1)

Level	Positive TTL level pulse into 1 k Ω
Impedance	50 Ω
Jitter (RMS), typical	AFG3011C/21C/22C: 500 ps AFG3051C/52C: 300 ps AFG3101C/02C: 200 ps AFG3251C/52C: 100 ps
Max frequency	4.9 MHz (4.9 MHz to 50 MHz: A fraction of the frequency is output; >50 MHz: no signal is output)

Clock reference out (10 MHz)

	AFG3101C, AFG3102C, AFG3251C, AFG3252C only
Impedance	50 Ω , AC coupled
Amplitude	1.2 V _{p-p} into 50 Ω load

Physical characteristics

Benchtop configuration

Dimensions

Height	156 mm (6.2 in.)
Width	329.6 mm (13.0 in.)
Depth	168.0 mm (6.6 in.)

Weight

Net	4.5 kg (9.9 lb.)
Shipping	5.9 kg (12.9 lb.)

EMC environmental and safety characteristics

Temperature

Operating	0 °C to +50 °C
Non-operating	-30 °C to +70 °C

Humidity

Operating	≤ +40 °C: ≤80%
	> +40 °C to 50 °C: ≤60%

Altitude

Up to 3,000 m (10,000 ft.)

EMC compliance

European Union	EU Council Directive 2004/108/EC
-----------------------	----------------------------------

Safety

UL 61010-1:2004
CAN/CSA C22.2 No. 61010-1:2004
IEC 61010-1:2001

Ordering information

Arbitrary function generators

AFG3011C	1 µHz to 10 MHz sine wave, 1-channel arbitrary function generator
AFG3021C	1 µHz to 25 MHz sine wave, 1-channel arbitrary function generator
AFG3022C	1 µHz to 25 MHz sine wave, 2-channel arbitrary function generator
AFG3051C	1 µHz to 50 MHz sine wave, 1-channel arbitrary function generator
AFG3052C	1 µHz to 50 MHz sine wave, 2-channel arbitrary function generator
AFG3101C	1 µHz to 100 MHz sine wave, 1-channel arbitrary function generator
AFG3102C	1 µHz to 100 MHz sine wave, 2-channel arbitrary function generator
AFG3251C	1 µHz to 240 MHz sine wave, 1-channel arbitrary function generator
AFG3252C	1 µHz to 240 MHz sine wave, 2-channel arbitrary function generator

Instrument options

Power plug options

Opt. A0	North America power plug (115 V, 60 Hz)
Opt. A1	Universal Euro power plug (220 V, 50 Hz)
Opt. A2	United Kingdom power plug (240 V, 50 Hz)
Opt. A3	Australia power plug (240 V, 50 Hz)
Opt. A5	Switzerland power plug (220 V, 50 Hz)
Opt. A6	Japan power plug (100 V, 50/60 Hz)
Opt. A10	China power plug (50 Hz)
Opt. A11	India power plug (50 Hz)
Opt. A12	Brazil power plug (60 Hz)
Opt. A99	No power cord

Manual options

Opt. L0	English (071-1631-xx)
Opt. L1	French (071-1632-xx)
Opt. L2	Italian (071-1669-xx)
Opt. L3	German (071-1633-xx)
Opt. L4	Spanish (071-1670-xx)
Opt. L5	Japanese (071-1634-xx)
Opt. L6	Portuguese (071-3042-xx)
Opt. L7	Simple Chinese (071-1635-xx)
Opt. L8	Traditional Chinese (071-1636-xx)
Opt. L9	Korean (071-1637-xx)
Opt. L10	Russian (071-1638-xx)
Opt. L99	No manual

Service options

Opt. C3	Calibration Service 3 Years
Opt. C5	Calibration Service 5 Years
Opt. D1	Calibration Data Report
Opt. D3	Calibration Data Report 3 Years (with Opt. C3)
Opt. D5	Calibration Data Report 5 Years (with Opt. C5)
Opt. R5	Repair Service 5 Years (including warranty)
Opt. R5DW	Repair Service Coverage 5 Years (includes product warranty period). 5-year period starts at time of instrument purchase
Opt. SILV400	Standard warranty extended to 5 years

Standard accessories

Accessories

- Quick-start user manual
- Power cord
- USB cable
- CD-ROM with specifications and performance verification manual,
- Programmer manual
- Service manual
- LabView and IVI drivers
- CD-ROM with ArbExpress™ software
- NIST-traceable calibration certificate.
- 3-year warranty on parts and labor


Warranty

Three-year warranty on parts and labor.

Recommended accessories

Accessories

Rackmount kit	RM3100
Fuse adapter, BNC-P to BNC-R	013-0345-xx
Fuse set, 3 pcs, 0.125 A.	159-0454-xx
BNC cable shielded, 3 ft.	012-0482-xx
BNC cable shielded, 9 ft.	012-1256-xx
GPIB cable, double shielded	012-0991-xx
50 Ω BNC terminator	011-0049-02



Datasheet



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.



Product(s) complies with IEEE Standard 488.1-1987, RS-232-C, and with Tektronix Standard Codes and Formats.

ASEAN / Australasia (65) 6356 3900
Belgium 00800 2255 4835*
Central East Europe and the Baltics +41 52 675 3777
Finland +41 52 675 3777
Hong Kong 400 820 5835
Japan 81 (3) 6714 3010
Middle East, Asia, and North Africa +41 52 675 3777
People's Republic of China 400 820 5835
Republic of Korea 001 800 8255 2835
Spain 00800 2255 4835*
Taiwan 886 (2) 2656 6688

Austria 00800 2255 4835*
Brazil +55 (11) 3759 7627
Central Europe & Greece +41 52 675 3777
France 00800 2255 4835*
India 000 800 650 1835
Luxembourg +41 52 675 3777
The Netherlands 00800 2255 4835*
Poland +41 52 675 3777
Russia & CIS +7 (495) 6647564
Sweden 00800 2255 4835*
United Kingdom & Ireland 00800 2255 4835*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
Canada 1 800 833 9200
Denmark +45 80 88 1401
Germany 00800 2255 4835*
Italy 00800 2255 4835*
Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90
Norway 800 16098
Portugal 80 08 12370
South Africa +41 52 675 3777
Switzerland 00800 2255 4835*
USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tektronix.com.

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.



12 May 2015 76W-28281-4

www.tektronix.com

Tektronix[®]



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru