



**MICRO SWITCH™ Watertight  
Miniature Basic Switches  
V15W Series**



# MICRO SWITCH™ V15W Series

## Watertight Miniature Basic Switches

Honeywell MICRO SWITCH™ V15W Series miniature, sealed basic switches feature industrial-grade performance (IP-rated sealing and 10 A electrical rating). These redesigned and upgraded switches are cost-effective solutions for a variety of applications.

The V15W switch with sealed plunger and sealed wire leads conforms to the IP67 environmental seal rating (temporary submersion). The IP67 seal rating is designed for indoor and outdoor applications on commercial appliances, industrial equipment, surface transportation, and agriculture equipment where the switch could be exposed to liquid or particulate contaminants.

In addition, the V15W Series is designed to control logic level/computer based circuits or electrical circuits up to 10 A. Electrical connectivity for the switch is achieved via combination quick connect/solder terminals or sealed wire leads. A wide variety of levers for the V15W Series are available to enhance the application flexibility of the switch package.

The V15W Series is further enhanced with certification from CQC (Asia-Pacific), ENEC (Europe), UL and cUL (Americas) agencies for global applications.

### ***What makes our switches better?***

- Watertight. Dust tight. Leaded versions are sealed to IP67
- High current capacity: this V-sized sealed switch is rated up to 10 A!
- Many different switch characteristics, actuators, and terminations resulting in thousands of potential configurations
- Product performance matched to customer design expectations



VALUE • CUSTOMIZATION • RELIABLE  
ENVIRONMENTAL PROTECTION • FLEXIBLE

## Features and Benefits

### EXCELS IN DUSTY, DIRTY, WET CONDITIONS

**Silicone rubber plunger seal and epoxy resin** assure the V15W Series delivers high sealing capability with an **IP67 rating on all pre-leaded switches** that makes them a great choice for wet, dirty, and/or dusty application settings.

***V-sized sealed switch rated to 10 A!***

### HANDLES LOW VOLTAGE AND POWER-DUTY LOADS WITH EASE

MICRO SWITCH™ V15W Series basic switches are available with a choice of **silver alloy or gold-plated silver alloy contacts** to easily control low-voltage logic level applications. The silver alloy contacts are designed for controlling power-duty ac or dc circuits.

### REDUCES INSTALLATION TIME

Offered with pre-leaded 300 mm wire, the V15W Series can reduce and simplify installation.

### DESIGN FLEXIBILITY

Available with pin plungers, stainless steel levers, three types of terminations, and a variety of switch characteristics to meet an assortment of equipment requirements, MICRO SWITCH™ V15W Series switches also boast electrical ratings from 0.1 A up to 10 A for design flexibility in one package size.

### WORLDWIDE USE

The V15W Series is certified to UL, cUL (North America), CQC (Asia-Pacific), and ENEC (Europe) for world-wide applications.

## Potential Applications



### FOOD PACKAGING PLANTS

Performs a variety of position and counting functions

### ATV AND OFF-ROAD VEHICLES

Often used in brake light assemblies, brake position detection, handle bar controls, run-away prevention, shift lever position, and marine controls

### GARBAGE AND SALT TRUCKS, COMMERCIAL BUSES, VANS

Operates in a variety of functions, including lift position, door ajar/open, salt spreader on/off detection, and wheel chair lifts (sense position of movable platforms)



### VENDING MACHINES

Aids with product selection, liquid dispensing on/off position, and product delivery detection

### GOLF CARTS

Determines foot pedal position and initiates reverse alarm on shift lever



### MEDICAL EQUIPMENT

Often used on hospital bed controls, dental chairs, foot pedals, and pneumatic switches

### FORKLIFT AND RIDING LAWN MOWER SEATS

Senses operator presence or absence and shifter position

# MICRO SWITCH™ Watertight Miniature Basic Switches

## PRODUCT NOMENCLATURE

| Switch Type                                                       | Terminals/Wiring                                                                                                    | Circuitry                                       | Operating Force                                                                                                                                    | Lever Location                                                                         | Lever Type                                                                                                                                                                                                                            | Mounting Holes                               | Contact Material                                           | Electrical Rating (must be included)                                                                                                                               | Special Designator                                                                                                                                                                                                                                                                                                                                    |
|-------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MICRO SWITCH™<br>V-Basic<br>Standard<br>V15W Watertight<br>Switch | <b>D</b> 4,8 mm x 0,8 mm<br><b>E</b> 4,8 mm x 0,5 mm<br><b>W</b> 300 mm long wires <sup>1</sup><br><b>S</b> Special | <b>Z</b> SPDT<br><b>P</b> SPNO<br><b>C</b> SPNC | <b>050</b> 50 g max.<br><b>100</b> 100 g max.<br><b>150</b> 150 g max.<br><b>200</b> 200 g max. <sup>2</sup><br><b>300</b> 300 g max. <sup>2</sup> | No lever<br><b>A</b> Lever pivot far from plunger<br><b>B</b> Lever pivot near plunger | Pin plunger<br><b>01</b> Short straight lever<br><b>02</b> Standard straight lever<br><b>03</b> Long straight lever<br><b>04</b> Simulated roller lever<br><b>05</b> Roller lever<br><b>06</b> Long roller lever<br><b>99</b> Special | Metric (Ø 3,1 mm)<br><b>K</b> USA (Ø 2,9 mm) | Standard silver alloy<br><b>A</b> Gold-plated silver alloy | <b>W1</b> 0,1 A, 125/250 Vac<br>0,1 A, 30 Vdc<br><b>W2</b> 6 A, 125/250 Vac<br>5 A, 30 Vdc<br><b>W3</b> 10 A, 125/250 Vac <sup>2</sup><br>5 A, 30 Vdc <sup>2</sup> | A special designator code is used to indicate some non-standard feature such as a special actuator, wire color, wire length, connector, etc. Review product specification to determine the nature of the non-standard feature. This code will consist of up to three alphanumeric characters. A blank designates no difference from standard listing. |

<sup>1</sup> Electrical rating and wire type (standard)  
W1: 24 AWG (0,20 mm<sup>2</sup>)  
W2: 18 AWG (0,82 mm<sup>2</sup>)  
W3: 16 AWG (1,31 mm<sup>2</sup>)

<sup>2</sup> 200 g and 300 g operate forces are the only forces allowed with the W3 electrical rating.

Not all combinations of model code are available.  
Please contact your Honeywell provider/representative for assistance.

Table 1. Specifications

| Characteristic                                | Parameter                                                                                                                                |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Circuitry                                     | SPDT, SPNO, SPNC                                                                                                                         |
| Operating force                               | 50 gf, 100 gf, 150 gf, 200 gf, 300 gf                                                                                                    |
| Termination                                   | quick connect: 4,8 mm x 0,8 mm<br>quick connect: 4,8 mm x 0,5 mm<br>300 mm lead wire length                                              |
| Actuators (levers 300 series stainless steel) | pin plunger, short straight lever, standard straight lever, long straight lever, simulated roller lever, roller lever, long roller lever |
| Agency certification                          | UL, cUL, ENEC, CQC                                                                                                                       |
| Sealing                                       | IP67 (lead versions)<br>IP00 (quick-connect versions due to exposed terminal)                                                            |
| Plunger sealing                               | silicone                                                                                                                                 |
| Operating temperature                         | -40 °C to 85 °C [-40 °F to 185 °F]                                                                                                       |
| Mechanical life (cycles)                      | 1,000,000 cycles min. @ 180 cycles/minute max.                                                                                           |
| Dielectric strength                           | 500 Vac (RMS) for 1 minute<br>leakage current ≤ 0.5 mA between open contacts                                                             |
| Switch resistance (initial)                   | 300 mΩ max.                                                                                                                              |
| Insulation resistance                         | 100 MΩ min. (500 Vdc for 1 minute)                                                                                                       |
| Contact material                              | silver alloy, gold-plated silver alloy                                                                                                   |
| Housing material                              | PBT thermoplastic polyester                                                                                                              |

Table 2. Electrical Ratings

| Switch option | cUL, UL per 61058-1, File 12252                     | CQC per GB15092-1, ENEC per 61058-1 |
|---------------|-----------------------------------------------------|-------------------------------------|
| W1            | 0.1 RA (Resistive Amp) 125/250 Vac<br>0.1 RA 30 Vdc | 0.1 A 125/250 Vac<br>0.1 A 30 Vdc   |
| W2            | 6 RA (Resistive Amp) 125/250 Vac<br>5 RA 30 Vdc     | 6 A 125/250 Vac<br>5 A 30 Vdc       |
| W3            | 10 RA (Resistive Amp) 125/250 Vac<br>5 RA 30 Vdc    | 10 A 125/250 Vac<br>5 A 30 Vdc      |

Note: cUL, UL, ENEC, and CQC use temperature is 55 °C max. for wired versions, 85 °C max. for terminal versions.

# V15W Series

## PRODUCT SPECIFICATIONS AND LISTINGS

Contact your Honeywell rep or distributor for additional listings

O.F. • Operating force  
R.F. • Release force  
P.T. • Pretravel  
O.T. • Overtravel  
D.T. • Differential travel  
O.P. • Operating position

|                                                                                                                    | Catalog Listing   | Elec. Rating<br>(see page 5) | Termination         | Circuitry/<br>Contacts | O.F. max.<br>newtons<br>[grams] | O.P.<br>nominal       | P.T. max.           | O.T. min.           | D.T. max.            |
|--------------------------------------------------------------------------------------------------------------------|-------------------|------------------------------|---------------------|------------------------|---------------------------------|-----------------------|---------------------|---------------------|----------------------|
|  <b>Pin plunger</b>               | V15W-DZ200-AW1    | W1                           | QC: 4,8 mm x 0,8 mm | SPDT/<br>gold-plated   | 1,96 [200]                      | 14,7 mm<br>[0.578 in] | 1,2 mm<br>[0.05 in] | 1,0 mm<br>[0.04 in] | 0,4 mm<br>[0.015 in] |
|                                                                                                                    | V15W-DZ200-W2     | W2                           | QC: 4,8 mm x 0,8 mm | SPDT/<br>silver alloy  | 1,96 [200]                      | 14,7 mm<br>[0.578 in] | 1,2 mm<br>[0.05 in] | 1,0 mm<br>[0.04 in] | 0,4 mm<br>[0.015 in] |
|                                                                                                                    | V15W-DZ200-W3     | W3                           | QC: 4,8 mm x 0,8 mm | SPDT/<br>silver alloy  | 1,96 [200]                      | 14,7 mm<br>[0.578 in] | 1,2 mm<br>[0.05 in] | 1,0 mm<br>[0.04 in] | 0,4 mm<br>[0.015 in] |
|                                                                                                                    | V15W-EZ200-W3     | W3                           | QC: 4,8 mm x 0,5 mm | SPDT/<br>silver alloy  | 1,96 [200]                      | 14,7 mm<br>[0.578 in] | 1,2 mm<br>[0.05 in] | 1,0 mm<br>[0.04 in] | 0,4 mm<br>[0.015 in] |
|                                                                                                                    | V15W-WC200-AW1    | W1                           | 300 mm wire leads   | SPNC/<br>gold-plated   | 1,96 [200]                      | 14,7 mm<br>[0.578 in] | 1,2 mm<br>[0.05 in] | 1,0 mm<br>[0.04 in] | 0,4 mm<br>[0.015 in] |
|                                                                                                                    | V15W-WP200-W2     | W2                           | 300 mm wire leads   | SPDT/<br>silver alloy  | 1,96 [200]                      | 14,7 mm<br>[0.578 in] | 1,2 mm<br>[0.05 in] | 1,0 mm<br>[0.04 in] | 0,4 mm<br>[0.015 in] |
|                                                                                                                    | V15W-WZ200-W3     | W3                           | 300 mm wire leads   | SPDT/<br>silver alloy  | 1,96 [200]                      | 14,7 mm<br>[0.578 in] | 1,2 mm<br>[0.05 in] | 1,0 mm<br>[0.04 in] | 0,4 mm<br>[0.015 in] |
|  <b>Short straight lever</b>      | V15W-DZ100A01-AW1 | W1                           | QC: 4,8 mm x 0,8 mm | SPDT/<br>gold-plated   | 0,83 [85]                       | 15,1 mm<br>[0.59 in]  | 2,6 mm<br>[0.10 in] | 1,1 mm<br>[0.04 in] | 0,6 mm<br>[0.024 in] |
|  <b>Standard straight lever</b> | V15W-DZ200A02-AW1 | W1                           | QC: 4,8 mm x 0,8 mm | SPDT/<br>gold-plated   | 1,08 [110]                      | 14,8 mm<br>[0.582 in] | 4,0 mm<br>[0.16 in] | 1,5 mm<br>[0.06 in] | 0,9 mm<br>[0.035 in] |
|                                                                                                                    | V15W-DZ200A02-W2  | W2                           | QC: 4,8 mm x 0,8 mm | SPDT/<br>silver alloy  | 1,08 [110]                      | 14,8 mm<br>[0.582 in] | 4,0 mm<br>[0.16 in] | 1,5 mm<br>[0.06 in] | 0,9 mm<br>[0.035 in] |
|                                                                                                                    | V15W-WZ200A02-AW1 | W1                           | 300 mm wire leads   | SPDT/<br>gold-plated   | 1,08 [110]                      | 14,8 mm<br>[0.582 in] | 4,0 mm<br>[0.16 in] | 1,5 mm<br>[0.06 in] | 0,9 mm<br>[0.035 in] |
|                                                                                                                    | V15W-WZ200A02-W2  | W2                           | 300 mm wire leads   | SPDT/<br>silver alloy  | 1,08 [110]                      | 14,8 mm<br>[0.582 in] | 4,0 mm<br>[0.16 in] | 1,5 mm<br>[0.06 in] | 0,9 mm<br>[0.035 in] |
|  <b>Long straight lever</b>     | V15W-WC050A03-W2  | W2                           | 300 mm wire leads   | SPNC/<br>silver alloy  | 0,20 [20]                       | 13,4 mm<br>[0.53 in]  | 7,0 mm<br>[0.28 in] | 2,6 mm<br>[0.10 in] | 2,0 mm<br>[0.08 in]  |
|  <b>Simulated roller lever</b>  | V15W-DZ200A04-W2  | W2                           | QC: 4,8 mm x 0,8 mm | SPDT/<br>silver alloy  | 1,22 [125]                      | 18,1 mm<br>[0.71 in]  | 3,6 mm<br>[0.14 in] | 1,7 mm<br>[0.07 in] | 1,0 mm<br>[0.04 in]  |
|                                                                                                                    | V15W-WZ050B04-W2  | W2                           | 300 mm wire leads   | SPDT/<br>silver alloy  | 0,20 [20]                       | 17,6 mm<br>[0.69 in]  | 7,2 mm<br>[0.28 in] | 2,1 mm<br>[0.08 in] | 1,7 mm<br>[0.07 in]  |
|                                                                                                                    | V15W-WZ200A04-W2  | W2                           | 300 mm wire leads   | SPDT/<br>silver alloy  | 1,22 [125]                      | 18,1 mm<br>[0.71 in]  | 3,6 mm<br>[0.14 in] | 1,7 mm<br>[0.07 in] | 1,0 mm<br>[0.04 in]  |
|                                                                                                                    | V15W-WZ200A04-W3  | W3                           | 300 mm wire leads   | SPDT/<br>silver alloy  | 1,22 [125]                      | 18,1 mm<br>[0.71 in]  | 3,6 mm<br>[0.14 in] | 1,7 mm<br>[0.07 in] | 1,0 mm<br>[0.04 in]  |
|  <b>Roller lever</b>            | V15W-DZ200A05-AW1 | W1                           | QC: 4,8 mm x 0,8 mm | SPDT/<br>gold-plated   | 1,96 [200]                      | 20,6 mm<br>[0.81 in]  | 2,1 mm<br>[0.08 in] | 1,0 mm<br>[0.04 in] | 0,5 mm<br>[0.02 in]  |
|                                                                                                                    | V15W-WZ200A05-AW1 | W1                           | 300 mm wire leads   | SPDT/<br>gold-plated   | 1,96 [200]                      | 20,6 mm<br>[0.81 in]  | 2,1 mm<br>[0.08 in] | 1,0 mm<br>[0.04 in] | 0,5 mm<br>[0.02 in]  |
|                                                                                                                    | V15W-WZ200A05-W2  | W2                           | 300 mm wire leads   | SPDT/<br>silver alloy  | 1,96 [200]                      | 20,6 mm<br>[0.81 in]  | 2,1 mm<br>[0.08 in] | 1,0 mm<br>[0.04 in] | 0,5 mm<br>[0.02 in]  |

# MICRO SWITCH™ Watertight Miniature Basic Switches

O.F. • Operating force  
R.F. • Release force  
P.T. • Pretravel  
O.T. • Overtravel  
D.T. • Differential travel  
O.P. • Operating position

## PRODUCT SPECIFICATIONS AND LISTINGS

Contact your Honeywell rep or distributor for additional listings

|                                                                                                            | Catalog Listing          | Elec. Rating<br>(see page 5) | Termination         | Circuitry/<br>Contacts | O.F. max.<br>newtons<br>[grams] | O.P.<br>nominal      | P.T. max.           | O.T. min.           | D.T. max.           |
|------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------|---------------------|------------------------|---------------------------------|----------------------|---------------------|---------------------|---------------------|
|  <p>Long roller lever</p> | <b>V15W-DZ200A06-AW1</b> | W1                           | QC: 4,8 mm x 0,8 mm | SPDT/<br>gold-plated   | 1,27 [130]                      | 20,4 mm<br>[0.80 in] | 3,3 mm<br>[0.13 in] | 1,3 mm<br>[0.05 in] | 0,7 mm<br>[0.03 in] |
|                                                                                                            | <b>V15W-DZ200A06-W2</b>  | W2                           | QC: 4,8 mm x 0,8 mm | SPDT/<br>silver alloy  | 1,27 [130]                      | 20,4 mm<br>[0.80 in] | 3,3 mm<br>[0.13 in] | 1,3 mm<br>[0.05 in] | 0,7 mm<br>[0.03 in] |
|                                                                                                            | <b>V15W-WP200A06-W2</b>  | W2                           | 300 mm wire leads   | SPNO/<br>silver alloy  | 1,27 [130]                      | 20,4 mm<br>[0.80 in] | 3,3 mm<br>[0.13 in] | 1,3 mm<br>[0.05 in] | 0,7 mm<br>[0.03 in] |
|                                                                                                            | <b>V15W-WZ200A06-AW1</b> | W1                           | 300 mm wire leads   | SPDT/<br>gold-plated   | 1,27 [130]                      | 20,4 mm<br>[0.80 in] | 3,3 mm<br>[0.13 in] | 1,3 mm<br>[0.05 in] | 0,7 mm<br>[0.03 in] |
|                                                                                                            | <b>V15W-WZ200A06-W2</b>  | W2                           | 300 mm wire leads   | SPDT/<br>silver alloy  | 1,27 [130]                      | 20,4 mm<br>[0.80 in] | 3,3 mm<br>[0.13 in] | 1,3 mm<br>[0.05 in] | 0,7 mm<br>[0.03 in] |




# MICRO SWITCH™ Watertight Miniature Basic Switches

## STANDARD LEVER DIMENSIONS


### Lever Type "01"

Short Straight Lever




### Lever Type "02"

Standard Straight Lever




### Lever Type "03"

Long Straight Lever




### Lever Type "04"

Simulated Roller Lever




### Lever Type "05" "06"

ROLLER LEVER DIMENSIONS




### Lever Type "05"

Roller Lever



### Lever Type "06"

Long Roller Lever



This Honeywell datasheet supports the following MICRO SWITCH™ V15W Series Basic Switch Listings

V15W-DZ100A01-AW1  
V15W-DZ200A02-AW1  
V15W-DZ200A02-W2  
V15W-DZ200A04-W2  
V15W-DZ200A05-AW1  
V15W-DZ200A06-AW1  
V15W-DZ200A06-W2

V15W-DZ200-AW1  
V15W-DZ200-W2  
V15W-DZ200-W3  
V15W-EZ200-W3  
V15W-WC050A03-W2  
V15W-WC200-AW1

V15W-WP200A06-W2  
V15W-WP200-W2  
V15W-WZ050B04-W2  
V15W-WZ200A02-AW1  
V15W-WZ200A02-W2  
V15W-WZ200A04-W2

V15W-WZ200A04-W3  
V15W-WZ200A05-AW1  
V15W-WZ200A05-W2  
V15W-WZ200A06-AW1  
V15W-WZ200A06-W2  
V15W-WZ200-W3

## ADDITIONAL INFORMATION

The following associated literature is available on the Honeywell web site at [sensing.honeywell.com](http://sensing.honeywell.com):

- Product installation instructions
- Product range guide
- Product nomenclature tree
- Product application-specific information
  - Application note: Watertight switches in transportation applications
  - Application note: Sensors and switches in oil rig applications
  - Application note: Sensors and switches for potential medical applications
  - Brochure: Sensors and switches for potential medical applications
  - Technical bulletin: Applying precision switches
  - Technical bulletin: Low energy switch guide

### **WARNING**

#### **PERSONAL INJURY**

**DO NOT USE** these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

**Failure to comply with these instructions could result in death or serious injury.**

### **WARNING**

#### **MISUSE OF DOCUMENTATION**

- The information presented in this product sheet is for reference only. Do not use this document as a product installation guide.
- Complete installation, operation, and maintenance information is provided in the instructions supplied with each product.

**Failure to comply with these instructions could result in death or serious injury.**

## WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items it finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While we provide application assistance personally, through our literature and the Honeywell website, it is up to the customer to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

#### **Find out more**

Honeywell serves its customers through a worldwide network of sales offices, representatives and distributors. For application assistance, current specifications, pricing or name of the nearest Authorized Distributor, contact your local sales office.

To learn more about Honeywell's sensing and control products, call **+1-815-235-6847** or **1-800-537-6945**, visit **sensing.honeywell.com**, or e-mail inquiries to **info.sc@honeywell.com**

Sensing and Control  
Honeywell  
1985 Douglas Drive North  
Golden Valley, MN 55422  
**honeywell.com**

The Honeywell logo, consisting of the word "Honeywell" in a bold, red, sans-serif font.

004965-5-EN IL50 GLO  
February 2015  
Copyright © 2015 Honeywell International Inc. All rights reserved.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)