

## Low-Power, High-Speed CMOS Analog Switches

### DESCRIPTION

The DG401, DG403, DG405 monolithic analog switches were designed to provide precision, high performance switching of analog signals. Combining low power (0.35  $\mu$ W, typ.) with high speed ( $t_{ON}$ : 75 ns, typ.), the DG401 series is ideally suited for portable and battery powered industrial and military applications.

Built on the Vishay Siliconix proprietary high-voltage silicon-gate process to achieve high voltage rating and superior switch on/off performance, break-before-make is guaranteed for the SPDT configurations. An epitaxial layer prevents latchup.

Each switch conducts equally well in both directions when on, and blocks up to 30 V peak-to-peak when off. On-resistance is very flat over the full  $\pm 15$  V analog range, rivaling JFET performance without the inherent dynamic range limitations.

The three devices in this series are differentiated by the type of switch action as shown in the functional block diagrams.

### FEATURES

- 44 V supply max. rating
- $\pm 15$  V analog signal range
- On-resistance -  $R_{DS(on)}$ : 30  $\Omega$
- Low leakage -  $I_{D(on)}$ : 40 pA
- Fast switching -  $t_{ON}$ : 75 ns
- Ultra low power requirements -  $P_D$ : 0.35  $\mu$ W
- TTL, CMOS compatible
- Single supply capability
- **Compliant to RoHS directive 2002/95/EC**



**RoHS\***  
COMPLIANT

### BENEFITS

- Wide dynamic range
- Break-before-make switching action
- Simple interfacing

### APPLICATIONS

- Audio and video switching
- Sample-and-hold circuits
- Battery operation
- Test equipment
- Communications systems
- PBX, PABX

### FUNCTIONAL BLOCK DIAGRAM AND PIN CONFIGURATION




Two SPST Switches per Package

| TRUTH TABLE |        |
|-------------|--------|
| Logic       | Switch |
| 0           | OFF    |
| 1           | ON     |

Logic "0"  $\leq 0.8$  V  
Logic "1"  $\geq 2.4$  V

\* Pb containing terminations are not RoHS compliant, exemptions may apply

## FUNCTIONAL BLOCK DIAGRAM AND PIN CONFIGURATION



Two SPDT Switches per Package

| TRUTH TABLE |                                   |                                   |
|-------------|-----------------------------------|-----------------------------------|
| Logic       | SW <sub>1</sub> , SW <sub>2</sub> | SW <sub>3</sub> , SW <sub>4</sub> |
| 0           | OFF                               | ON                                |
| 1           | ON                                | OFF                               |

Logic "0" ≤ 0.8 V  
 Logic "1" ≥ 2.4 V



Two DPST Switches per Package

| TRUTH TABLE |        |
|-------------|--------|
| Logic       | Switch |
| 0           | OFF    |
| 1           | ON     |

Logic "0" ≤ 0.8 V  
 Logic "1" ≥ 2.4 V



| <b>ORDERING INFORMATION</b> |                    |  |
|-----------------------------|--------------------|--|
| Temp. Range                 | Package            | Part Number  |
| <b>DG401</b>                |                    |  |
| - 40 °C to 85 °C            | 16-Pin Plastic DIP | DG401DJ<br>DG401DJ-E3                                |
|                             | 16-Pin Narrow SOIC | DG401DY<br>DG401DY-T1<br>DG401DY-E3<br>DG401DY-T1-E3 |
| <b>DG403</b>                |                    |  |
| - 40 °C to 85 °C            | 16-Pin Plastic DIP | DG403DJ<br>DG403DJ-E3                                |
|                             | 16-Pin Narrow SOIC | DG403DY<br>DG403DY-E3<br>DG403DY-T1<br>DG403DY-T1-E3 |
| <b>DG405</b>                |                    |  |
| - 40 °C to 85 °C            | 16-Pin Plastic DIP | DG405DJ<br>DG405DJ-E3                                |
|                             | 16-Pin Narrow SOIC | DG405DY<br>DG405DY-E3<br>DG405DY-T1<br>DG405DY-T1-E3 |

| <b>ABSOLUTE MAXIMUM RATINGS</b>                               |  |      |    |
|---|--|------|----|
| Parameter   | Limit  | Unit |    |
| V+ to V-  | 44   | V    |    |
| GND to V-   | 25   |      |    |
| V <sub>L</sub>  | (GND - 0.3) to (V+) + 0.3                                |      |    |
| Digital Inputs <sup>a</sup> , V <sub>S</sub> , V <sub>D</sub> | (V-) - 2 to (V+) + 2<br>or 30 mA, whichever occurs first |      |    |
| Current (Any Terminal) Continuous                             | 30   | mA   |    |
| Current, S or D (Pulsed 1 ms, 10 % Duty)                      | 100  |      |    |
| Storage Temperature   | (DJ, DY Suffix)<br>- 65 to 125                           | °C   |    |
| Power Dissipation (Package) <sup>b</sup>                      | 16-Pin Plastic DIP <sup>c</sup>                          | 450  | mW |
|   | 16-Pin SOIC <sup>d</sup>                                 | 600  |    |

**Notes:**

- a. Signals on S<sub>x</sub>, D<sub>x</sub>, or IN<sub>x</sub> exceeding V+ or V- will be clamped by internal diodes. Limit forward diode current to maximum current ratings.
- b. All leads welded or soldered to PC board.
- c. Derate 6 mW/°C above 75 °C.
- d. Derate 7.6 mW/°C above 75 °C.

| SPECIFICATIONS <sup>a</sup>          |                                     |  |                    |                   |                              |                   |      |
|--------------------------------------|-------------------------------------|--|--------------------|-------------------|------------------------------|-------------------|------|
| Parameter                            | Symbol                              | Test Conditions<br>Unless Specified<br>V <sub>+</sub> = 15 V, V <sub>-</sub> = - 15 V<br>V <sub>L</sub> = 5 V, V <sub>IN</sub> = 2.4 V, 0.8 V <sup>f</sup> | Temp. <sup>b</sup> | Typ. <sup>c</sup> | D Suffix<br>- 40 °C to 85 °C |                   | Unit |
|                                      |                                     |  |                    |                   | Min. <sup>d</sup>            | Max. <sup>d</sup> |      |
| <b>Analog Switch</b>                 |                                     |  |                    |                   |                              |                   |      |
| Analog Signal Range <sup>e</sup>     | V <sub>ANALOG</sub>                 |  | Full               |                   | - 15                         | 15                | V    |
| Drain-Source On-Resistance           | R <sub>DS(on)</sub>                 | I <sub>S</sub> = - 10 mA, V <sub>D</sub> = ± 10 V<br>V <sub>+</sub> = 13.5 V, V <sub>-</sub> = - 13.5 V  | Room<br>Full       | 30                |                              | 45<br>55          | Ω    |
| Δ Drain-Source On-Resistance         | ΔR <sub>DS(on)</sub>                | I <sub>S</sub> = - 10 mA, V <sub>D</sub> = ± 5 V, 0 V<br>V <sub>+</sub> = 16.5 V, V <sub>-</sub> = - 16.5 V  | Room<br>Full       | 3                 |                              | 3<br>5            |      |
| Switch Off Leakage Current           | I <sub>S(off)</sub>                 | V <sub>+</sub> = 16.5 V, V <sub>-</sub> = - 16.5 V<br>V <sub>D</sub> = ± 15.5 V, V <sub>S</sub> = ± 15.5 V   | Room<br>Hot        | - 0.01            | - 0.5<br>- 5                 | 0.5<br>5          | nA   |
|                                      | I <sub>D(off)</sub>                 |  | Room<br>Hot        | - 0.01            | - 0.5<br>- 5                 | 0.5<br>5          |      |
| Channel On Leakage Current           | I <sub>D(on)</sub>                  | V <sub>+</sub> = 16.5 V, V <sub>-</sub> = - 16.5 V<br>V <sub>S</sub> = V <sub>D</sub> = ± 15.5 V   | Room<br>Hot        | - 0.04            | - 1<br>- 10                  | 1<br>10           |      |
| <b>Digital Control</b>               |                                     |  |                    |                   |                              |                   |      |
| Input Current V <sub>IN</sub> Low    | I <sub>IL</sub>                     | V <sub>IN</sub> under test = 0.8 V<br>All Other = 2.4 V  | Full               | 0.005             | - 1                          | 1                 | μA   |
| Input Current V <sub>IN</sub> High   | I <sub>IH</sub>                     | V <sub>IN</sub> under test = 2.4 V<br>All Other = 0.8 V  | Full               | 0.005             | - 1                          | 1                 |      |
| <b>Dynamic Characteristics</b>       |                                     |  |                    |                   |                              |                   |      |
| Turn-On Time                         | t <sub>ON</sub>                     | R <sub>L</sub> = 300 Ω, C <sub>L</sub> = 35 pF<br>See Figure 2   | Room               | 75                |                              | 150               | ns   |
| Turn-Off Time                        | t <sub>OFF</sub>                    |  | Room               | 30                |                              | 100               |      |
| Break-Before-Make Time Delay (DG403) | t <sub>D</sub>                      | R <sub>L</sub> = 300 Ω, C <sub>L</sub> = 35 pF   | Room               | 35                | 5                            |                   |      |
| Charge Injection                     | Q                                   | C <sub>L</sub> = 10 nF<br>V <sub>gen</sub> = 0 V, R <sub>gen</sub> = 0 Ω   | Room               | 60                |                              |                   | pC   |
| Off Isolation Reject Ratio           | OIRR                                | R <sub>L</sub> = 100 Ω, C <sub>L</sub> = 5 pF<br>f = 1 MHz   | Room               | 72                |                              |                   | dB   |
| Channel-to-Channel Crosstalk         | X <sub>TALK</sub>                   |  | Room               | 90                |                              |                   |      |
| Source Off Capacitance               | C <sub>S(off)</sub>                 | f = 1 MHz, V <sub>S</sub> = 0 V  | Room               | 12                |                              |                   | pF   |
| Drain Off Capacitance                | C <sub>D(off)</sub>                 |  | Room               | 12                |                              |                   |      |
| Channel On Capacitance               | C <sub>D</sub> , C <sub>S(on)</sub> |  | Room               | 39                |                              |                   |      |
| <b>Power Supplies</b>                |                                     |  |                    |                   |                              |                   |      |
| Positive Supply Current              | I <sub>+</sub>                      | V <sub>+</sub> = 16.5 V, V <sub>-</sub> = - 16.5 V<br>V <sub>IN</sub> = 0 or 5 V   | Room<br>Full       | 0.01              |                              | 1<br>5            | μA   |
| Negative Supply Current              | I <sub>-</sub>                      |  | Room<br>Full       | - 0.01            | - 1<br>- 5                   |                   |      |
| Logic Supply Current                 | I <sub>L</sub>                      |  | Room<br>Full       | 0.01              |                              | 1<br>5            |      |
| Ground Current                       | I <sub>GND</sub>                    |  | Room<br>Full       | - 0.01            | - 1<br>- 5                   |                   |      |

Notes:


- Refer to PROCESS OPTION FLOWCHART.
- Room = 25 °C, Full = as determined by the operating temperature suffix.
- Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing.
- The algebraic convention whereby the most negative value is a minimum and the most positive a maximum, is used in this datasheet.
- Guaranteed by design, not subject to production test.
- V<sub>IN</sub> = input voltage to perform proper function.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

### TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




**Input Switching Threshold vs. Logic Supply Voltage**




**Input Switching Threshold vs. Supply Voltages**




**R<sub>DS(on)</sub> vs. V<sub>D</sub> and Temperature**



**R<sub>DS(on)</sub> vs. V<sub>D</sub> and Power Supply Voltage**



**R<sub>DS(on)</sub> vs. V<sub>D</sub> and Power Supply Voltage (V<sub>-</sub> = 0 V)**



**Charge Injection vs. Analog Voltage**

### TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



**Leakage Current vs. Temperature**



**Leakage Current vs. Analog Voltage**




**Supply Current vs. Temperature**



**Switching Time vs. Temperature\***



**Switching Time vs. Power Supply Voltage\***



**Switching Time vs. Positive Supply Voltage\***

\* Refer to Figure 2 for test conditions.

**TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted



**Supply Current vs. Switching Frequency**

**SCHEMATIC DIAGRAM** Typical Channel



**Figure 1.**


### TEST CIRCUITS

$V_O$  is the steady state output with the switch on. Feedthrough via switch capacitance may result in spikes at the leading and trailing edge of the output waveform.



$C_L$  (includes fixture and stray capacitance)

$$V_O = V_S \frac{R_L}{R_L + r_{DS(on)}}$$



\*  $V_S = 10\text{ V}$  for  $t_{ON}$ ,  $V_S = -10\text{ V}$  for  $t_{OFF}$

Note: Logic input waveform is inverted for switches that have the opposite logic sense control

Figure 2. Switching Time



$C_L$  (includes fixture and stray capacitance)




Figure 3. Break-Before-Make



Figure 4. Charge Injection



**TEST CIRCUITS**



**Figure 5. Off Isolation**



**Figure 7. Crosstalk**



**Figure 6. Insertion Loss**



**Figure 8. Capacitances**

## APPLICATIONS




Figure 9. Stereo Source Selector




Figure 10. Dual Slope Integrator

### Dual Slope Integrators:

The DG403 is well suited to configure a selectable slope integrator. One control signal selects the timing capacitor  $C_1$  or  $C_2$ . Another one selects  $e_{in}$  or discharges the capacitor in preparation for the next integration cycle.

### Band-Pass Switched Capacitor Filter:

Single-pole double-throw switches are a common element for switched capacitor networks and filters. The fast switching times and low leakage of the DG403 allow for higher clock rates and consequently higher filter operating frequencies.



Figure 11. Band-Pass Switched Capacitor Filter

**APPLICATIONS**
**Peak Detector:**

$A_3$  acting as a comparator provides the logic drive for operating  $SW_1$ . The output of  $A_2$  is fed back to  $A_3$  and compared to the analog input  $e_{in}$ . If  $e_{in} > e_{out}$  the output of  $A_3$  is high keeping  $SW_1$  closed. This allows  $C_1$  to charge up to

the analog input voltage. When  $e_{in}$  goes below  $e_{out}$   $A_3$  goes negative, turning  $SW_1$  off. The system will therefore store the most positive analog input experienced.



Figure 12. Positive Peak Detector

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see [www.vishay.com/ppg?70049](http://www.vishay.com/ppg?70049).



**SOIC (NARROW): 16-LEAD**  
JEDEC Part Number: MS-012



| Dim            | MILLIMETERS |       | INCHES    |       |
|----------------|-------------|-------|-----------|-------|
|                | Min         | Max   | Min       | Max   |
| A              | 1.35        | 1.75  | 0.053     | 0.069 |
| A <sub>1</sub> | 0.10        | 0.20  | 0.004     | 0.008 |
| B              | 0.38        | 0.51  | 0.015     | 0.020 |
| C              | 0.18        | 0.23  | 0.007     | 0.009 |
| D              | 9.80        | 10.00 | 0.385     | 0.393 |
| E              | 3.80        | 4.00  | 0.149     | 0.157 |
| e              | 1.27 BSC    |       | 0.050 BSC |       |
| H              | 5.80        | 6.20  | 0.228     | 0.244 |
| L              | 0.50        | 0.93  | 0.020     | 0.037 |
| ∅              | 0°          | 8°    | 0°        | 8°    |

ECN: S-03946—Rev. F, 09-Jul-01  
DWG: 5300



### PDIP: 16-LEAD




| Dim                  | MILLIMETERS |       | INCHES |       |
|----------------------|-------------|-------|--------|-------|
|                      | Min         | Max   | Min    | Max   |
| <b>A</b>             | 3.81        | 5.08  | 0.150  | 0.200 |
| <b>A<sub>1</sub></b> | 0.38        | 1.27  | 0.015  | 0.050 |
| <b>B</b>             | 0.38        | 0.51  | 0.015  | 0.020 |
| <b>B<sub>1</sub></b> | 0.89        | 1.65  | 0.035  | 0.065 |
| <b>C</b>             | 0.20        | 0.30  | 0.008  | 0.012 |
| <b>D</b>             | 18.93       | 21.33 | 0.745  | 0.840 |
| <b>E</b>             | 7.62        | 8.26  | 0.300  | 0.325 |
| <b>E<sub>1</sub></b> | 5.59        | 7.11  | 0.220  | 0.280 |
| <b>e<sub>1</sub></b> | 2.29        | 2.79  | 0.090  | 0.110 |
| <b>e<sub>A</sub></b> | 7.37        | 7.87  | 0.290  | 0.310 |
| <b>L</b>             | 2.79        | 3.81  | 0.110  | 0.150 |
| <b>Q<sub>1</sub></b> | 1.27        | 2.03  | 0.050  | 0.080 |
| <b>S</b>             | 0.38        | 1.52  | .015   | 0.060 |

ECN: S-03946—Rev. D, 09-Jul-01  
DWG: 5482



**CERDIP: 16-LEAD**



| Dim            | MILLIMETERS |       | INCHES    |       |
|----------------|-------------|-------|-----------|-------|
|                | Min         | Max   | Min       | Max   |
| A              | 4.06        | 5.08  | 0.160     | 0.200 |
| A <sub>1</sub> | 0.51        | 1.14  | 0.020     | 0.045 |
| B              | 0.38        | 0.51  | 0.015     | 0.020 |
| B <sub>1</sub> | 1.14        | 1.65  | 0.045     | 0.065 |
| C              | 0.20        | 0.30  | 0.008     | 0.012 |
| D              | 19.05       | 19.56 | 0.750     | 0.770 |
| E              | 7.62        | 8.26  | 0.300     | 0.325 |
| E <sub>1</sub> | 6.60        | 7.62  | 0.260     | 0.300 |
| e <sub>1</sub> | 2.54 BSC    |       | 0.100 BSC |       |
| e <sub>A</sub> | 7.62 BSC    |       | 0.300 BSC |       |
| L              | 3.18        | 3.81  | 0.125     | 0.150 |
| L <sub>1</sub> | 3.81        | 5.08  | 0.150     | 0.200 |
| Q <sub>1</sub> | 1.27        | 2.16  | 0.050     | 0.085 |
| S              | 0.38        | 1.14  | 0.015     | 0.045 |
| ∞              | 0°          | 15°   | 0°        | 15°   |

ECN: S-03946—Rev. G, 09-Jul-01  
DWG: 5403



**20-LEAD LCC**



| Dim                  | MILLIMETERS |      | INCHES    |       |
|----------------------|-------------|------|-----------|-------|
|                      | Min         | Max  | Min       | Max   |
| <b>A</b>             | 1.37        | 2.24 | 0.054     | 0.088 |
| <b>A<sub>1</sub></b> | 1.63        | 2.54 | 0.064     | 0.100 |
| <b>B</b>             | 0.56        | 0.71 | 0.022     | 0.028 |
| <b>D</b>             | 8.69        | 9.09 | 0.342     | 0.358 |
| <b>E</b>             | 8.69        | 9.09 | 0.442     | 0.358 |
| <b>e</b>             | 1.27 BSC    |      | 0.050 BSC |       |
| <b>L</b>             | 1.14        | 1.40 | 0.045     | 0.055 |
| <b>L<sub>1</sub></b> | 1.96        | 2.36 | 0.077     | 0.093 |

ECN: S-03946—Rev. B, 09-Jul-01  
DWG: 5321

## RECOMMENDED MINIMUM PADS FOR SO-16



Recommended Minimum Pads  
Dimensions in Inches/(mm)

[Return to Index](#)





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)